

# Cisco ASR 9000 Series IOS XR 64-Bit

---

# Contents

Product overview	3
Features and benefits	3
Platform support/compatibility	4
System requirements	5
Ordering information	6
Cisco environmental sustainability	7
Cisco Capital	7
Document history	8

The Cisco IOS® XR 64-Bit on ASR 9000 Series operating system is an addition to the current generation of Cisco IOS XR operating systems, delivering the same comprehensive features and system resilience with additional benefits.

## Product overview

The Cisco ASR 9000 Series Aggregation Services Routers have been delivering exceptional scalability, carrier-class reliability, environmentally conscious design, incredible flexibility, and an attractive price-to-performance benchmark to service providers and enterprise customers in edge and core routing.

The Cisco IOS XR 64 Bit on ASR 9000 Series operating system is an addition to the current generation of Cisco IOS XR operating systems, delivering the same comprehensive features and system resilience.

In Cisco IOS XR 64 Bit on ASR 9000, we are evolving the networking operating system specifically to help customers move and innovate faster. While retaining its breadth of protocol spectrum and feature set, Cisco IOS XR Software has now evolved to meet next-generation operational requirements.

As customer organizations have grown over the past decade, they've sought a flexible operating system that can keep up. The new innovations in Cisco IOS XR 64 Bit on ASR 9000 enable incremental builds, agile workflow, and modular delivery of software, while also offering the capability to host third-party applications on Cisco routers.

## Features and benefits

Feature	Benefit
Fully automated initial installation	<ul style="list-style-type: none"> <li>• <b>Bootable ISO:</b> To simplify installation, Cisco IOS XR 64 Bit on ASR 9000 images are in the form of a bootable ISO that's installed on the system. The software also supports iPXE, which allows the administrator to boot from TFTP, HTTP, or FTP.</li> <li>• <b>Auto provisioning:</b> Auto provisioning starts at the end of the software's boot process in a fresh system installation and serves two functions: static configuration application and script execution. It allows administrators to customize settings easily and automatically, without wasting time on manual configuration.</li> </ul>
Visibility for smarter control, simpler monitoring, and faster troubleshooting	<ul style="list-style-type: none"> <li>• <b>Streaming telemetry:</b> Users can take advantage of streaming telemetry to direct data to a configured receiver. Data can be pushed out at intervals determined by the administrator, at a cadence as low as 10 seconds. Using sophisticated algorithms, a back-end server can then analyze data received from Cisco IOS XR 64 Bit on ASR 9000. The data can be encoded in JavaScript Object Notation (JSON) or Google Protocol Buffers (GPB). This analysis enables back-end management systems to measure and even predict control-plane and data-plane trends.</li> <li>• <b>Model-driven interfaces:</b> Prior to Release 6.0, administrators relied on Simple Network Management Protocol (SNMP) and syslog—techniques that are neither scalable nor easily automated. With this latest release of Cisco IOS XR Software, administrators can more easily work together using the internal system database (SysDB) represented by YANG models. SysDB is not a database in a strict sense, but rather a treelike file system that can provide a common mechanism for management clients to modify or access system information. SysDB stores a variety of types of data, including integers of different sizes, character strings, and externally managed data items.</li> </ul>
Flexible design for agile maintenance and updates	<ul style="list-style-type: none"> <li>• <b>Application hosting:</b> The Cisco IOS XR 64 Bit on ASR 9000 architecture supports third-party off-the-shelf applications built with Linux tool chains. Users can run custom applications built with the software development kit that Cisco provides. Application hosting gives administrators a platform for experimenting with their own tools and utilities.</li> <li>• <b>Flexible packaging and provisioning:</b> The Release 6.1.1 architecture facilitates modular software delivery of individual components, which increases operational agility and efficiency. Modular delivery of software also eases difficulties during routine upgrades and maintenance fixes, promoting flexible, asynchronous upgrades.</li> </ul>

Feature	Benefit
<b>Open architecture</b>	<ul style="list-style-type: none"> <li>• <b>Linux-based OS:</b> Release 6.1.1 opens up the architecture of Cisco IOS XR Software using a 64-bit Linux-based operating system. (It uses the Wind River 7 distribution, which is compatible with Yocto 1.5 and approved by the Yocto project.) In contrast to the traditional 32-bit QNX OS, Release 6.1.1 can easily integrate applications, configuration-management tools, and auto provisioning. These attributes make it highly automatable and transparent to monitoring and management tools.</li> </ul>
<b>In-Service Software Upgrade (ISSU)</b>	<ul style="list-style-type: none"> <li>• Cisco IOS XR 64 Bit on ASR 9000 will have a new foundation for ISSU. The virtualized environment running instances of Cisco IOS XR 64 Bit will enable the platform to orchestrate the software upgrade process to minimize the disruption of services in the network without powering down the system to upgrade the operating system.</li> </ul>

## Platform support/compatibility

Product Family	Platforms Supported	Software Release
<b>ASR 9900 Series</b>	ASR 9922	6.1.1
	ASR 9912	
	ASR 9910	6.2.1
	ASR 9906	6.3.1
	ASR 9904	6.1.1
	ASR 9903	7.1.3
	ASR 9902	7.4.1
	ASR 9901	6.4.1
<b>ASR 9000 Series</b>	ASR 9006	6.1.1
	ASR 9010	

## System requirements

For software release to support each of the product IDs below, please refer to the Software Release Notes of each software release from 6.1.1 onward.

Product Family	RSP/RP/FC	Product IDs
<b>ASR 9006</b> <b>ASR 9010</b> <b>ASR 9904</b>	Route switch processor	A9K-RSP5-SE A9K-RSP5-TR A9K-RSP880-LT-SE A9K-RSP880-LT-TR A9K-RSP880-SE A9K-RSP880-TR
<b>ASR 9912</b> <b>ASR 9922</b>	Route processor	A99-RP3-SE A99-RP3-TR A99-RP2-SE A99-RP2-TR
	Fabric card	A99-SFC3 A99-SFC2
<b>ASR 9910</b> <b>ASR-9906</b>	Route processor	A9K-RSP5-SE A9K-RSP5-TR A9K-RSP880-LT-SE A9K-RSP880-LT-TR A99-RSP-SE A99-RSP-TR
	Fabric card	A99-SFC3-S (ASR 9910) A99-SFC-S (ASR 9910) A99-SFC3-T (ASR 9906) A99-SFC-T (ASR 9906)
<b>Line cards</b>	5 <sup>th</sup> Generation Line cards	A99-4T-FC A99-10X400GE-X (-SE, -TR) A99-32HG-FC A99-32X100GE-X (-SE, -TR) A9K-20HG-FLEX (-FC, -SE, -TR) A9K-8HG-FLEX (-FC, -SE, -TR) A99-4HG-FLEX (-FC, -SE, -TR) A9K-4HG-FLEX (-FC, -SE, -TR)

Product Family	RSP/RP/FC	Product IDs
	4 <sup>th</sup> Generation Line Cards	A99-32X100GE (-FC, -TR, -CM) A9K-16X100GE (-FC, -TR, -CM) A99-16X100GE-X (-FC, -SE)
	3 <sup>rd</sup> Generation Line cards	A99-12X100GE (-FC, -CM) A99-12X100GE A99-8X100GE (-FC, -SE, -TR, -CM) A9K-8X100GE (-FC, -SE, -TR, -CM) A9K-8X100G-LB (-SE, -TR) A9K-4X100GE (-FC, -SE, -TR) A9K-400GE-LAN-FC A9K-4X100GE A99-48X100GE-1G (-FC, -SE, -TR) A9K-48X100GE-1G (-FC, -SE, -TR, -CM) A9K-24X100GE-1G (-FC, -SE, -TR, -CM) A9K-MOD400 (-FC, -SE, -TR, -CM) A9K-MOD200 (-FC, -SE, -TR) A9K-400G-DWDM-TR

## Ordering information

Part Number	Product Description
<b>XR-A9K-X64-07.6</b>	Cisco IOS XR 64 Bit IP/MPLS Core Software
<b>XR-A9K-X64K9-07.6</b>	Cisco IOS XR 64 Bit IP/MPLS Core Software 3DES

---

## Cisco environmental sustainability

Information about Cisco’s environmental sustainability policies and initiatives for our products, solutions, operations, and extended operations or supply chain is provided in the “Environment Sustainability” section of Cisco’s [Corporate Social Responsibility](#) (CSR) Report.

Reference links to information about key environmental sustainability topics (mentioned in the “Environment Sustainability” section of the CSR Report) are provided in the following table:

Sustainability topic	Reference
Information on product material content laws and regulations	<a href="#">Materials</a>
Information on electronic waste laws and regulations, including products, batteries, and packaging	<a href="#">WEEE compliance</a>

Cisco makes the packaging data available for informational purposes only. It may not reflect the most current legal developments, and Cisco does not represent, warrant, or guarantee that it is complete, accurate, or up to date. This information is subject to change without notice.

## Cisco Capital

### Flexible payment solutions to help you achieve your objectives

Cisco Capital makes it easier to get the right technology to achieve your objectives, enable business transformation and help you stay competitive. We can help you reduce the total cost of ownership, conserve capital, and accelerate growth. In more than 100 countries, our flexible payment solutions can help you acquire hardware, software, services and complementary third-party equipment in easy, predictable payments. [Learn more](#).

## Document history

New or Revised Topic	Described In	Date
Updated Supported platforms and IOS SW versions	Platform support/compatibility	April 26, 2022
Updated product part numbers of supported line cards	System requirements	April 26, 2022
Updated IOS SW Part numbers	Ordering information	April 26, 2022

**Americas Headquarters**  
Cisco Systems, Inc.  
San Jose, CA

**Asia Pacific Headquarters**  
Cisco Systems (USA) Pte. Ltd.  
Singapore

**Europe Headquarters**  
Cisco Systems International BV Amsterdam,  
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at <https://www.cisco.com/go/offices>.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: <https://www.cisco.com/go/trademarks>. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)