



**Cisco Aggregation Services Routers
ASR 920 Series
Feature Compatibility Matrix**

July 2023

Cisco Systems, Inc.
www.cisco.com

Cisco has more than 200 offices worldwide.
Addresses, phone numbers, and fax numbers
are listed on the Cisco website at
www.cisco.com/go/offices.

THE SPECIFICATIONS AND INFORMATION REGARDING THE PRODUCTS IN THIS MANUAL ARE SUBJECT TO CHANGE WITHOUT NOTICE. ALL STATEMENTS, INFORMATION, AND RECOMMENDATIONS IN THIS MANUAL ARE BELIEVED TO BE ACCURATE BUT ARE PRESENTED WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED. USERS MUST TAKE FULL RESPONSIBILITY FOR THEIR APPLICATION OF ANY PRODUCTS.

THE SOFTWARE LICENSE AND LIMITED WARRANTY FOR THE ACCOMPANYING PRODUCT ARE SET FORTH IN THE INFORMATION PACKET THAT SHIPPED WITH THE PRODUCT AND ARE INCORPORATED HEREIN BY THIS REFERENCE. IF YOU ARE UNABLE TO LOCATE THE SOFTWARE LICENSE OR LIMITED WARRANTY, CONTACT YOUR CISCO REPRESENTATIVE FOR A COPY.

NOTWITHSTANDING ANY OTHER WARRANTY HEREIN, ALL DOCUMENT FILES AND SOFTWARE OF THESE SUPPLIERS ARE PROVIDED "AS IS" WITH ALL FAULTS. CISCO AND THE ABOVE-NAMED SUPPLIERS DISCLAIM ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, WITHOUT LIMITATION, THOSE OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE.


IN NO EVENT SHALL CISCO OR ITS SUPPLIERS BE LIABLE FOR ANY INDIRECT, SPECIAL, CONSEQUENTIAL, OR INCIDENTAL DAMAGES, INCLUDING, WITHOUT LIMITATION, LOST PROFITS OR LOSS OR DAMAGE TO DATA ARISING OUT OF THE USE OR INABILITY TO USE THIS MANUAL, EVEN IF CISCO OR ITS SUPPLIERS HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)

Any Internet Protocol (IP) addresses and phone numbers used in this document are not intended to be actual addresses and phone numbers. Any examples, command display output, network topology diagrams, and other figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses or phone numbers in illustrative content is unintentional and coincidental.

© 2023 Cisco Systems, Inc. All rights reserved.

Feature Compatibility Matrix for the Cisco ASR920 Series Aggregation Services Routers

	Feature Compatibility Matrix for Cisco ASR-920-12CZ-A/Cisco ASR-920-12CZ-AD Cisco ASR-920-4SZ-A/Cisco ASR-920-4SZ-AD Cisco ASR-920-24SZ-IM Cisco ASR-920-24SZ-M Cisco ASR-920-12SZ-IM Cisco ASR-920-12SZ-A/Cisco ASR-920-12SZ-D Cisco ASR-920-20SZ-M Cisco ASR-920-8S4Z-PD					
Feature Name	Cisco ASR-920-12CZ-A/D, Cisco ASR-920-4SZ-A/D	Cisco ASR-920-8S4Z-PD	Cisco ASR-920-24SZ-IM, ASR-920-24SZ-M, ASR-920-24TZ-M	Cisco ASR-920-12SZ-IM	Cisco ASR-920-12SZ-A, Cisco ASR-920-12SZ-D	Cisco ASR-920-20SZ-M
	Supported Release	Supported Release	Supported Release	Supported Release	Supported Release	Supported Release
PPP MRRU Negotiation Configuration	NA	NA	3.15.0S	3.16.0S	NA	NA
MPLS - Multilink PPP support	NA	NA	3.15.0S	3.16.0S	NA	NA
Egress Policing on Non Priority Queues	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Synchronous Ethernet (SyncE): ESMC & SSM	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Provide option to enable/disable USB	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
syslog and trigger support for external alarm	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Support for IEEE 1588-2008 Precision Clock Synchronization Protocol	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
REP Configurable Timers aka REP Fast Hellos	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
QoS Packet Marking	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
1588-2008 Boundary Clock	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Hot Standby Pseudowire Support for Ethernet	NA	NA	3.15.0S	3.16.0S	NA	NA
Hot Standby Pseudowire Support for TDM ACs	NA	NA	3.15.0S	3.16.0S	NA	NA
RMON Full	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Y.1731 Performance Monitoring	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Y.1731 Performance Monitoring (Xconnect & Port-Channel Support)	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Inverse Multiplexing over ATM (IMA)	NA	NA	3.15.0S	3.16.0S	NA	NA
Punt Policing and Monitoring	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Multi-protocol BGP (MP-BGP) - MPLS VPN	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	

Feature Compatibility Matrix for the Cisco ASR920 Series Aggregation Services Routers

Feature Name	Cisco ASR-920-12CZ-A/D, Cisco ASR-920-4SZ-A/D	Cisco ASR-920-8S4Z-PD	Cisco ASR-920-24SZ-IM, ASR-920-24SZ-M, ASR-920-24TZ-M	Cisco ASR-920-12SZ-IM	Cisco ASR-920-12SZ-A, Cisco ASR-920-12SZ-D	Cisco ASR-920-20SZ-M
	Supported Release	Supported Release	Supported Release	Supported Release	Supported Release	Supported Release
Any Transport over MPLS (AToM): ATM AAL5 over MPLS (AAL5oMPLS)	NA	NA	3.15.0S	3.16.0S	NA	NA
Embedded Event Manager (EEM) 4.0	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
ITU-T G.8032 Ethernet Ring Protection Switching	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Circuit Emulation over Packet Switched Network (CESoPSN)	NA	NA	3.15.0S	3.16.0S	NA	NA
Temperature and Voltage Monitoring	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Egress policing and marking	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
1588 PTP Best Master Clock Algorithm (BMCA) a.k.a. PTP Redundancy	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
IPv6 Routing: IS-IS Support for IPv6	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
DHCPv6 - Relay chaining for Prefix Delegation	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
NTPv4 hardening through import of open source version 4.2.6p2 (July 2010)	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
MR-APS integration with hotstandby pseudowire	NA	NA	3.15.0S		NA	NA
L2VPN Componentization	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
N:1 PVC mapping to PWE with non-unique VPI	NA	NA	3.15.0S	3.16.0S	NA	NA
E-OAM - CFM CCM Hardware Offload (802.1ag within ms accuracy)	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
E-OAM - CFM CCM Hardware Offload (802.1ag within ms accuracy) support for Xconnect & BD Up MEP	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
IPv4 unicast routing support	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
SAToP over MPLS	NA	NA	3.15.0S	3.16.0S	NA	NA
Circuit Emulation over IP PSN with UDP PW Demultiplexing	NA	NA	3.16.0S	3.16.0S	NA	NA
Ethernet Local Management Interface (E-LMI)					16.9.1	
QoS EXP matching	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
QoS Support	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Dying Gasp Support for Loss of power supply via SNMP, Syslog and Ethernet OAM	3.13.0S	17.1.1	3.15.0S	3.16.0S	16.9.1	
6PE support	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	

Feature Compatibility Matrix for the Cisco ASR920 Series Aggregation Services Routers

Feature Name	Cisco ASR-920-12CZ-A/D, Cisco ASR-920-4SZ-A/D	Cisco ASR-920-8S4Z-PD	Cisco ASR-920-24SZ-IM, ASR-920-24SZ-M, ASR-920-24TZ-M	Cisco ASR-920-12SZ-IM	Cisco ASR-920-12SZ-A, Cisco ASR-920-12SZ-D	Cisco ASR-920-20SZ-M
	Supported Release	Supported Release	Supported Release	Supported Release	Supported Release	Supported Release
Min Link Support for Port channel	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Port-Shaper and LLQ in the presence of EFPs	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
match any classification	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
IEEE BMCA	3.16.1S	17.1.1	3.16.1S	3.16.1S	16.9.1	
QoS ACLs	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
IGMP Snooping on EFP	3.14.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
IGMP Snooping on Trunk EFP	3.14.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
IGMP Snooping on Port Channel	3.16.0S	17.1.1	3.16.0S	3.16.0S	16.9.1	
IGMP Snooping over PW					NA	
IGMP snooping v1, v2, v3 for aggregated links and LAG					16.9.1	
IGMP State Limit	3.14.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
IPv4 multicast per VRF					16.9.1	
L2VPN Protocol Based CLI	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Storm Control	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Ethernet Data Plane Loopback (with MAC swap)	3.14.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
G.8032 and CFM support for Microwave Adaptive Bandwidth	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Synthetic Frame Loss Measurement (ETH-SLM)	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
IPSLA Support for ETH-SLM (Ethernet Synthetic Loss Measurement in Y1731)	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Switch Port Analyzer (SPAN)	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Hybrid Clocking Support	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Time of Day Selection	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
STM1 support	NA	NA	3.15.0S		NA	NA
Any Transport over MPLS (AToM): Ethernet over MPLS (EoMPLS)	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
EVC & BD MIB support for trunk EFP	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Ethernet Data-Plane Loopback - Route port support & HA	3.14.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Trunk EFP Support on Ether-Channel Interfaces	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	

Feature Compatibility Matrix for the Cisco ASR920 Series Aggregation Services Routers

Feature Name	Cisco ASR-920-12CZ-A/D, Cisco ASR-920-4SZ-A/D	Cisco ASR-920-8S4Z-PD	Cisco ASR-920-24SZ-IM, ASR-920-24SZ-M, ASR-920-24TZ-M	Cisco ASR-920-12SZ-IM	Cisco ASR-920-12SZ-A, Cisco ASR-920-12SZ-D	Cisco ASR-920-20SZ-M
	Supported Release	Supported Release	Supported Release	Supported Release	Supported Release	Supported Release
Egress default queue limit improvement and percent bandwidth support	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
QoS EXP Marking for for Ingress on TDM	NA	NA	3.15.0S	3.16.0S	NA	NA
QoS EXP Marking for for Ingress on ATM	NA	NA	3.15.0S	3.16.0S	NA	NA
1588 BC over MPLS	3.13.0S	17.1.1	3.15.0S	3.16.0S	16.9.1	
SR/MR APS for OC12 port on OC3/OC12 IM	NA	NA	3.15.0S		NA	NA
ITU-T Telecom Profile G.8265.1	3.14.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Control Plane Policing					16.9.1	
IEEE 802.3ad Link Aggregation (LACP)	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
mIppp Egress QoS Support	NA	NA	3.15.0S	3.16.0S	NA	NA
Ingress QoS support for Serial Interface	NA	NA	3.15.0S	3.16.0S	NA	NA
QoS: Global CLI for CoS to EXP table mapping	3.14.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
PTP over Native Ethernet	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
QoS Support for Ether Channels	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
IP FRR/Remote LFA FRR with L2VPN	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
EVC Default Encapsulation for QinQ & xconnect	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
E-OAM: Multi UNI MEP in the same VPN	3.14.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Show Interface Capabilities	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
MPLS-TP: ATM and TDM Pseudowires	NA	NA	3.18.0S	3.18.0S	NA	NA
IPv6 Services: Extended Access Control Lists	3.14.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
IPv6 Switching: Provider Edge Router over MPLS (6PE)	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
BGP GSHUT enhancement	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
BGP Monitoring Protocol	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
VRF aware BGP translate-update	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
BGP - RTC for legacy PE	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
IOS VRF Multicast Multi-Topology Support	3.14.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
End-to-End Transparent Clocking	3.15.0S	17.1.1	3.15.0S	3.17.0S	16.9.1	
Multi-Topology BGP with VRF enhancement	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
POS Concatenation mode on STM1/4 IM	NA	NA	3.15.0S		NA	NA
ISIS local microloop protection	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Autonomic Networking: Certificate Management	3.14.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	

Feature Compatibility Matrix for the Cisco ASR920 Series Aggregation Services Routers

Feature Name	Cisco ASR-920-12CZ-A/D, Cisco ASR-920-4SZ-A/D	Cisco ASR-920-8S4Z-PD	Cisco ASR-920-24SZ-IM, ASR-920-24SZ-M, ASR-920-24TZ-M	Cisco ASR-920-12SZ-IM	Cisco ASR-920-12SZ-A, Cisco ASR-920-12SZ-D	Cisco ASR-920-20SZ-M
	Supported Release	Supported Release	Supported Release	Supported Release	Supported Release	Supported Release
IP tunnel: Antonomic Networking Support	3.14.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
AutoInstall Using DHCP for LAN Interfaces	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
ATM/IMA/PPP/MLPPP Support on OC3 Interface Module	NA	NA	3.17.0S	3.17.0S	NA	NA
IP SLA - Service Performance Testing Infrastructure	3.18.0SP	17.1.1	3.18.0SP	3.18.0SP	16.9.1	
MPLS Traffic Engineering (TE) - Fast Reroute (FRR) Link and Node Protection	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
BGP - Accumulated IGP	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
802.1ad	3.14.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
TWAMP RFC compliance	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Table Map	3.14.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
G.8032 (3.3 ms CCM)	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
MPLS-TP support on SVI Interface						
IEEE 802.1p Support	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
IP FRR over BDI	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
NTP Timestamping	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Audio Media Sense	3.13.0S	17.1.1		3.16.0S	16.9.1	
Smart Licensing with HA Support	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Dual Rate	3.13.0S	17.1.1		3.16.0S	16.9.1	
IPv6 Routing: OSPF for IPv6 (OSPFv3)	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Remote SPAN (RSPAN)	3.14.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
DHCP Snooping	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
BFD over TDM Routed	NA	NA	3.15.0S	3.16.0S	NA	NA
L2PT - Layer 2 Protocol Tunneling	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
ME3600x-24CX OC3 Port Support	NA	NA		NA	NA	NA
ME3600/ME3800: HDLC Support on T1/E1 IM	NA	NA		NA	NA	NA
Secure Shell SSH Version 2 Client Support	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
IPv6 QoS: MQC Packet Classification	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
IPv6 Routing: Static Routing	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
IPv6 Switching: CEF/dCEF Support	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
SNMP over IPv6	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	

Feature Compatibility Matrix for the Cisco ASR920 Series Aggregation Services Routers

Feature Name	Cisco ASR-920-12CZ-A/D, Cisco ASR-920-4SZ-A/D	Cisco ASR-920-8S4Z-PD	Cisco ASR-920-24SZ-IM, ASR-920-24SZ-M, ASR-920-24TZ-M	Cisco ASR-920-12SZ-IM	Cisco ASR-920-12SZ-A, Cisco ASR-920-12SZ-D	Cisco ASR-920-20SZ-M
	Supported Release	Supported Release	Supported Release	Supported Release	Supported Release	Supported Release
Sonet Mode support on OC3 IM	NA	NA	3.15.0S		NA	NA
Channelization support for OC3 IM	NA	NA	3.15.0S		NA	NA
PIM Version 2	3.14.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
BFD Support for Multicast(PIM)	3.14.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Any Transport over MPLS (AToM): ATM Cell Relay over MPLS: Packed Cell Relay	NA	NA	3.15.0S	3.16.0S	NA	NA
Class-based QoS MIB	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
MPLS (Multiprotocol Label Switching)	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
CDP (Cisco Discovery Protocol) Version 2	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
IPv6 VPN over MPLS (6VPE)	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
PTP over Native Ethernet	3.13.0S	17.1.1	3.13.0S	3.16.0S	16.9.1	
EVC Local Connect	3.18.0S	17.1.1	3.18.0S	3.18.0S	16.9.1	
IEEE 802.1Q VLAN Support	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
SNMPv3 (SNMP Version 3)	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Configurable Per VLAN MAC Learning (PVL)	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
MPLS LDP - IGP Synchronization	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Class Based Policing	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Y.1731 DMMv1	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
MPLS over POS Support	NA	NA	3.15.0S		NA	NA
QoS Support on POS on OC3 IM	NA	NA	3.15.0S		NA	NA
RSVP - Resource Reservation Protocol	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Remote Monitoring MIB Update	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Class Based Weighted Fair Queuing (CBWFQ)	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
QoS on serial TDM interface	NA	NA	3.15.0S	3.16.0S	NA	NA
IPv6 ACL	3.13.0S	17.1.1		3.16.0S	16.9.1	
Auto-MDIX	3.13.0S	17.1.1	NA	NA	NA	NA
Port licensing	NA	NA	3.15.0S		NA	NA
PPP	NA	NA	3.15.0S	3.16.0S	NA	NA
HSRP support	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Microwave ACM Signaling and EEM integration	3.16.0S	17.1.1	3.16.0S	3.16.0S	16.9.1	
Microwave ACM Signaling over P2MP Topologies	3.16.0S	17.1.1	3.16.0S	3.16.0S	16.9.1	
SNMPv3 - 3DES and AES Encryption Support	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	

Feature Compatibility Matrix for the Cisco ASR920 Series Aggregation Services Routers

Feature Name	Cisco ASR-920-12CZ-A/D, Cisco ASR-920-4SZ-A/D	Cisco ASR-920-8S4Z-PD	Cisco ASR-920-24SZ-IM, ASR-920-24SZ-M, ASR-920-24TZ-M	Cisco ASR-920-12SZ-IM	Cisco ASR-920-12SZ-A, Cisco ASR-920-12SZ-D	Cisco ASR-920-20SZ-M
	Supported Release	Supported Release	Supported Release	Supported Release	Supported Release	Supported Release
TACACS+	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
MPLS Forwarding Infrastructure Scalability	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
STP Syslog Messages	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
L2PT - Layer 2 Protocol Tunneling on Trunk Ports	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
IPv6 Routing: Unicast Routing	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Diffserv Compliant WRED	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
BGP Support for TCP Path MTU Discovery per Session	3.13.0S	17.1.1	3.13.0S	3.16.0S	16.9.1	
Ethernet Connectivity Fault Management (E-CFM)	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
SNMP (Simple Network Management Protocol)	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Support for dissimilar PHB match at Ingress and Egress for mpls/vpls interface.	3.15.0S	17.1.1	3.15.0S	3.16.0S	16.9.1	
MPLS VPN - Inter-Autonomous System Support	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
OSPF TTL Security Check	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
DS3 support on OC3 port	NA	NA	3.15.0S		NA	NA
Ethernet Operations, Administration, and Maintenance (OAM)	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Service Activation	3.16.0S	17.1.1	3.16.0S		16.9.1	
Etherchannel Min-Links	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
IP 16-way Equal-Cost Multipath	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
RADIUS	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Ethernet Local Management Interface (LMI) at Provider Edge (PE)	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
MLPPP - Multilink PPP	NA	NA	3.15.0S		NA	NA
LMM Support for Smart SFP	3.13.0S	17.1.1			16.9.1	
DHCP Option 82 Configurable Circuit ID and Remote ID	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
MPLS Virtual Private Networks (VPN)	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
DHCP - DHCPv6 Relay Agent notification for Prefix Delegation	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
onePK SS: Policy API for QoS Multi-Action Policer	3.15.0S	17.1.1	3.15.0S			
Interfaces MIB: SNMP context based access	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	

Feature Compatibility Matrix for the Cisco ASR920 Series Aggregation Services Routers

Feature Name	Cisco ASR-920-12CZ-A/D, Cisco ASR-920-4SZ-A/D	Cisco ASR-920-8S4Z-PD	Cisco ASR-920-24SZ-IM, ASR-920-24SZ-M, ASR-920-24TZ-M	Cisco ASR-920-12SZ-IM	Cisco ASR-920-12SZ-A, Cisco ASR-920-12SZ-D	Cisco ASR-920-20SZ-M
	Supported Release	Supported Release	Supported Release	Supported Release	Supported Release	Supported Release
IEEE 802.1ab LLDP (Link Layer Discovery Protocol)	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Network Time Protocol (NTP)	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
EFP aware QoS	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
IEEE 802.1ag (CFM) Support on Port-Channel Interface	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Access Circuit Redundancy	NA	NA	3.15.0S		NA	NA
Secure Copy (SCP)	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
ACFC and PFC support on Multilink interface	NA	NA	3.15.0S	3.16.0S	NA	NA
REP - (Resilient Ethernet Protocol)	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
1 rate 2 color per EVC policer	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
BFD - Static Route Support	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
BFD IPv6 Encaps Support	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
IPv6 - Static Route support for BFD over IPv6	3.14.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
BGP Support for 4-byte ASN	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
EVC 2.0 - Advanced VLAN translations & service mapping based on 802.1ah	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
EVC MIB	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Dual Rate Three Color Ingress Policer on Service Instances	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Clear Channel ATM	NA	NA	3.18.0S	3.18.0S	NA	NA
MST on EVC Bridge-Domain	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
TDM clock recovery	NA	NA	3.15.0S	3.16.0S	NA	NA
SLM Over VPLS	3.17.0S	17.1.1	3.17.0S	3.17.0S	16.9.1	
TSoP Smart SFP -STM1	NA	NA	3.17.0S	3.17.0S	NA	NA
OC3/OC12 CEP SFP				3.18.0SP	NA	NA
X.21 over MPLS	NA	NA		16.6.1	NA	NA
Async RS232 over MPLS	NA	NA		16.6.1	NA	NA
Port Based License - 12/1G Bundle	NA	NA	3.14.0S	NA	NA	NA
ACL- DSCP Matching	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
ACL - Source & Destination Address Matching	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
E&M over MPLS	NA	NA		16.6.1	NA	NA
ACL - IP Protocol	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	

Feature Compatibility Matrix for the Cisco ASR920 Series Aggregation Services Routers

Feature Name	Cisco ASR-920-12CZ-A/D, Cisco ASR-920-4SZ-A/D	Cisco ASR-920-8S4Z-PD	Cisco ASR-920-24SZ-IM, ASR-920-24SZ-M, ASR-920-24TZ-M	Cisco ASR-920-12SZ-IM	Cisco ASR-920-12SZ-A, Cisco ASR-920-12SZ-D	Cisco ASR-920-20SZ-M
	Supported Release	Supported Release	Supported Release	Supported Release	Supported Release	Supported Release
Ingress QoS support for Serial Interface	NA	NA			NA	NA
Static MAC binding to EVCs and Psuedowires	3.14.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
IP SLAs TWAMP Responder v1.0	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
IEEE 802.1W Spanning Tree Rapid Reconfiguration					16.9.1	
Modular QoS CLI (MQC)	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
CFM over EFP interface configured with xconnect	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Resilient Ethernet Protocol-no-edge-neighbour-enhancement	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Jumbo Frames	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
IP FRR	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Synchronous Ethernet Support	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
CEM support on 8 port T1E1 IM	NA	NA	3.14.0S	3.16.0S	NA	NA
PIM Version 2	3.14.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Ordinary Clock Master					16.9.1	
PTP High Jitter Mode					16.9.1	
IPv6 Multicast: Multicast Listener Discovery (MLD) Protocol, Versions 1 and 2	3.15.0S	17.1.1	3.15.0S	3.16.0S	16.9.1	
IPv6 Multicast: PIM Sparse Mode (PIM-SM)	3.15.0S	17.1.1	3.15.0S	3.16.0S	16.9.1	
IPv6 Multicast: PIM Source-Specific Multicast (PIM-SSM)	3.15.0S	17.1.1	3.15.0S	3.16.0S	16.9.1	
IPv6 Multicast: PIM Embedded RP Support	3.15.0S	17.1.1	3.15.0S	3.16.0S	16.9.1	
IPv6 Multicast: PIM Accept Register	3.15.0S	17.1.1	3.15.0S	3.16.0S	16.9.1	
PoE Plus (PoE+, PoEP) support	NA	NA	NA	3.16.0S	16.9.1	
Fp init fails with Qos policies and with huge range of BD on TEFP	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Set and police in the same class-map (Ingress and Egress)	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Egress Port Level Policy with Ingress EFP Level Policy	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	

Feature Compatibility Matrix for the Cisco ASR920 Series Aggregation Services Routers

Feature Name	Cisco ASR-920-12CZ-A/D, Cisco ASR-920-4SZ-A/D	Cisco ASR-920-8S4Z-PD	Cisco ASR-920-24SZ-IM, ASR-920-24SZ-M, ASR-920-24TZ-M	Cisco ASR-920-12SZ-IM	Cisco ASR-920-12SZ-A, Cisco ASR-920-12SZ-D	Cisco ASR-920-20SZ-M
	Supported Release	Supported Release	Supported Release	Supported Release	Supported Release	Supported Release
OSPF doesn't come up when PIM is enabled on VPLS core interface	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
VRRPv3 Protocol Support	3.14.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
BFD Support for HSRP	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
L2VPN Static to Dynamic PW Interconnection & PW Preferred Path for MPLS-TP Tunnels	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
MPLS-TP: PW Redundancy for Static PWs	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
MPLS-TP: MS-PW with Static and Dynamic PW Support	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
L2VPN: PW Status for Static PWs	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Bidirectional MPLS-TP LSP	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
MPLS-TP Path Protection	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
MPLS-TP OAM: GACH	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
MPLS-TP OAM: Continuity Check via BFD	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
MPLS-TP OAM: Ping/Trace	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
MPLS-TP OAM: Fault Management	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
BFD - BFD Hardware Offload Support	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Kerberos V Client Support	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Unicast Reverse Path Forwarding (uRPF)	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
CFM Extension for 1+1 Hot-Standby Support	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
VPLS over MPLS-TP	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
MPLS-TP: LDP signaling over MPLS TP LSPs	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
MPLS-TP: IP addresses for MPLS TP interfaces	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
MPLS TP: IP-less configuration of MPLS TP tunnels	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Callhome V2 enhancements	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Call Home V3	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
BGP - MP-iBGP NSR					16.9.1	
Cisco-BGP-MIBv2	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Trunk EFP support	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
MVPN	3.17.0S	17.1.1	3.17.0S	3.17.0S	16.9.1	
CSL (Cisco Secure Licensing Support)	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	

Feature Compatibility Matrix for the Cisco ASR920 Series Aggregation Services Routers

Feature Name	Cisco ASR-920-12CZ-A/D, Cisco ASR-920-4SZ-A/D	Cisco ASR-920-8S4Z-PD	Cisco ASR-920-24SZ-IM, ASR-920-24SZ-M, ASR-920-24TZ-M	Cisco ASR-920-12SZ-IM	Cisco ASR-920-12SZ-A, Cisco ASR-920-12SZ-D	Cisco ASR-920-20SZ-M
	Supported Release	Supported Release	Supported Release	Supported Release	Supported Release	Supported Release
BFD: BGP multihop client Support (IPv4/IPv6)	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
BGP: Gracefull Shutdown (GSHUT)	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
MFI -Extended LFA	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
MAC Limiting per VFI and BD	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
IEEE 802.3x Flow Control	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
CFM Support on Trunk EFP	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Link Path Through	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Spanning Tree Protocol (STP)	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Static VPLS over MPLS-TP	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
MPLS-TP MIB	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
MPLS -TP: IP Less trace support (NodeId, LinkId)	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
VPLS BGP Signaling	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Y.1731 enhancements (On-demand & Concurrent support)	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
MFI - VPLS BGP sig	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Unicast Reverse Path Forwarding (uRPF) Loose mode	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
uRPF for IPv6 (Strict and Loose mode)	3.16.0S	17.1.1	3.16.0S	3.16.0S	16.9.1	
IS-IS Support for BFD over IPv6	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
BGP PIC (edge & core) - for RFC-3107 labeled iBGP	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
QoS Classification based on EFP	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
BD and CFM Protocol Based New CLI Model	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Offloading IPv4 Async BFD sessions with 3.3ms timers	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
QoS: Global CLI for CoS to EXP table mapping	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
L2VPN Protocol Base CLIs	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
MPLS -TP: Linear Protection/PSC support	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
QoS support for dataplane loopback for EFP	3.15.0S	17.1.1	3.15.0S	3.16.0S	16.9.1	
BFD Debug Enhancement	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
BFD Deterministic Hardware Offload	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Remote LFA FRR and labeled BGP FRR integration	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	

Feature Compatibility Matrix for the Cisco ASR920 Series Aggregation Services Routers

Feature Name	Cisco ASR-920-12CZ-A/D, Cisco ASR-920-4SZ-A/D	Cisco ASR-920-8S4Z-PD	Cisco ASR-920-24SZ-IM, ASR-920-24SZ-M, ASR-920-24TZ-M	Cisco ASR-920-12SZ-IM	Cisco ASR-920-12SZ-A, Cisco ASR-920-12SZ-D	Cisco ASR-920-20SZ-M
	Supported Release	Supported Release	Supported Release	Supported Release	Supported Release	Supported Release
Pseudowire Group Switchover	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Auto-IP	3.14.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
TCAM threshold based alarms	3.14.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Onboard Failure Logging					16.9.1	
Secure Boot Support	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
VPLS over remote LFA	3.13.0S	17.1.1			16.9.1	
Autoroute announce and forwarding adjacencies for OSPFv3 over IPv4 TE tunnels	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
onePK SS: Policy	3.14.0S	17.1.1	3.14.0S		16.9.1	
OnePK	3.14.0S	17.1.1	3.14.0S		16.9.1	
Flexlink	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Control Plane Security (CoPP)	3.14.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
REP-AG Enhancements	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Prefix Independent Convergence with Fast Re-Route Over Bridge Domain Interface	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
BGP Per Neighbor Graceful Restart Configuration					16.9.1	
Routed Pseudo-Wire and Routed VPLS	3.15.0S	17.1.1	3.15.0S	3.16.0S	16.9.1	
WAN mode support	NA	NA	3.14.0S	3.16.0S	16.9.1	
CFM Support for Cylon ASIC with integrated OAM HW offload	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
PIM DR Loadbalancing	3.14.0S	17.1.1		3.16.0S	16.9.1	
PTP-SYNCE on 10G interface in WANPHY mode	NA	NA	3.15.0S	3.16.0S	16.9.1	
eCPU & FPGA stats	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
VRRP and LLDP MED support for ZTP (vLAN 127 Support)	3.14.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
EVC 2.0 - 802.1ad Provider Bridges Support	3.15.0S	17.1.1	3.15.0S	3.16.0S	16.9.1	
nV Access for ME1200	3.14.0S	17.1.1	3.14.0S		16.9.1	
EFP policers without Ingress TCAM consumption	3.14.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Enhanced Tracking Support / Enhanced Object Tracking / EOT	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Source Specific Multicast (SSM) Mapping	3.14.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	

Feature Compatibility Matrix for the Cisco ASR920 Series Aggregation Services Routers

Feature Name	Cisco ASR-920-12CZ-A/D, Cisco ASR-920-4SZ-A/D	Cisco ASR-920-8S4Z-PD	Cisco ASR-920-24SZ-IM, ASR-920-24SZ-M, ASR-920-24TZ-M	Cisco ASR-920-12SZ-IM	Cisco ASR-920-12SZ-A, Cisco ASR-920-12SZ-D	Cisco ASR-920-20SZ-M
	Supported Release	Supported Release	Supported Release	Supported Release	Supported Release	Supported Release
DAI (Dynamic ARP Inspection)	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Secure Shell SSH Version 2 Server Support	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Field Programmable Device Upgrade Tool	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Virtual Private LAN Services (VPLS)	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
IS-IS Support for BFD over IPv4	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
OSPF Support for BFD over IPv4	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
IPv6 SDM Template	3.14.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Access Switch Device Manager (SDM) Template - Default	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Access Switch Device Manager (SDM) Template - IP & Video	3.16.0S	17.1.1	3.16.0S	3.16.0S	16.9.1	
MQC - Multi-Level Priority Queue	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
BFD Echo Mode	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
IS-IS - MPLS LDP Autoconfiguration	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
VPLS Autodiscovery, BGP based	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
LACP 1-1 redundancy with fast switchover	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Multichassis LACP (mLACP)	3.15.0S	17.1.1	3.15.0S	3.16.0S	16.9.1	
BGP Support for BFD	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
CISL - SNMP Support	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
4293 IP-MIB (IPv6 only) and RFC 4292 IP-FORWARD-MIB (IPv6 only)	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
H-VPLS N-PE Redundancy for MPLS Access	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Label Switched Multicast (LSM) Multicast Label Distribution Protocol (mLDP) based Multicast VPN (mVPN) support	3.15.0S	17.1.1	3.15.0S	3.16.0S	16.9.1	
VPLS MAC Address Withdrawal	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Enhanced Ingress Hierarchical Policing	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
MPLS TE - Bundled Interface Support (EtherChannel and MLP)	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
MAC Address Limiting on Service Instance / Bridge Domain	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
L2 ACL on Service Instance on Port-channel	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	

Feature Compatibility Matrix for the Cisco ASR920 Series Aggregation Services Routers

Feature Name	Cisco ASR-920-12CZ-A/D, Cisco ASR-920-4SZ-A/D	Cisco ASR-920-8S4Z-PD	Cisco ASR-920-24SZ-IM, ASR-920-24SZ-M, ASR-920-24TZ-M	Cisco ASR-920-12SZ-IM	Cisco ASR-920-12SZ-A, Cisco ASR-920-12SZ-D	Cisco ASR-920-20SZ-M
	Supported Release	Supported Release	Supported Release	Supported Release	Supported Release	Supported Release
MAC Address Security for EVC Bridge-Domain	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
PPPoE Client on BDI	3.15.0S	17.1.1	3.15.0S	3.16.0S	16.9.1	
Qos EVC Push Rewrite	3.15.0S	17.1.1	3.15.0S	3.16.0S	16.9.1	
Label Switched Multicast Point-to-Multipoint Traffic Engineering	3.15.0S	17.1.1	3.15.0S	3.16.0S	16.9.1	
NSR - LDP Support	NA	NA	NA	NA	16.9.1	
Hop-by-Hop BC in a ring with master/slave role reversal	3.15.0S	17.1.1	3.15.0S	3.16.0S	16.9.1	
BGP PIC Edge/Core VPNv6	3.15.0S	17.1.1	3.15.0S	3.16.0S	16.9.1	
ACL - ICMP Code	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
DHCP Server v6	3.15.0S	17.1.1	3.15.0S	3.16.0S	16.9.1	
IPv6 DHCP Client	3.15.0S	17.1.1	3.15.0S	3.16.0S	16.9.1	
IEEE 1588v2 (PTP) Asymmetric Phase Correction					16.9.1	
BCP Support over MLPPP	16.5.1	17.1.1	16.5.1	16.5.1	NA	NA
IKE Security Protocol				3.18.0S	NS	NS
IPSec Triple DES Encryption (3DES)				3.18.0S	NS	NS
Encrypted Pre-shared Key				3.18.0S	NS	NS
Advanced Encryption Standard (AES)				3.18.0S	NS	NS
IKE Mode Configuration				3.18.0S	NS	NS
Multicast Source Discovery Protocol (MSDP)	3.14.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
MPLS OAM Support for Multisegment Pseudowires	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Static MAC binding to EVCs and Psuedowires	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
BGP PIC Edge for IP/MPLS	3.13.0S	17.1.1			16.9.1	
GNSS reciever support	NA	NA	NA	3.17.0S	16.9.1	
UniDirectional Link Detection (UDLD)	3.13.0S	17.1.1	3.14.0S	3.16.0S	16.9.1	
Policy-Based Routing (PBR)	NA	NA	3.16.0S	3.16.0S	16.9.1	
PTP Hybrid BMCA	3.15.0S	17.1.1	3.15.0S		16.9.1	
QoS Priority Propagation in Multi-level Scheduler	3.15.0S	17.1.1	3.15.0S	3.16.0S	16.9.1	
3G/4G USB Dongle Support	3.15.0S	17.1.1	3.15.0S		16.9.1	
IEEE 802.1Q Custom Ethertype	3.15.0S	17.1.1	3.15.0S	3.16.0S	16.9.1	

Feature Compatibility Matrix for the Cisco ASR920 Series Aggregation Services Routers

Feature Name	Cisco ASR-920-12CZ-A/D, Cisco ASR-920-4SZ-A/D	Cisco ASR-920-8S4Z-PD	Cisco ASR-920-24SZ-IM, ASR-920-24SZ-M, ASR-920-24TZ-M	Cisco ASR-920-12SZ-IM	Cisco ASR-920-12SZ-A, Cisco ASR-920-12SZ-D	Cisco ASR-920-20SZ-M
	Supported Release	Supported Release	Supported Release	Supported Release	Supported Release	Supported Release
Hierarchical Color-Aware Policing	3.15.0S	17.1.1	3.15.0S	3.16.0S	16.9.1	
8 path ECMP	3.16.0S	17.1.1	3.16.0S	3.16.0S	16.9.1	
Support sending PW Grouping ID TLV	3.16.0S	17.1.1	3.16.0S	3.16.0S	16.9.1	
Image Signing	3.16.0S	17.1.1	3.16.0S	3.16.0S	16.9.1	
Priority Queuing - Shaper support	3.16.0S	17.1.1	3.16.0S	3.16.0S	16.9.1	
Segment Routing - ISIS v4 node SID	3.16.0S	17.1.1	3.16.0S	3.16.0S	16.9.1	
Option to disable volume-based IPsec lifetime rekey	NA	NA	NA	3.18.0S	NS	NA
IPSec Dead Peer Detection (DPD) Periodic Message Option	NA	NA	NA	3.18.0S	NS	NA
IPSec Anti-Replay Window: Expanding and Disabling	NA	NA	NA	3.18.0S	NS	NA
IKE - PKCS12 Support	NA	NA	NA	3.18.0S	NS	NA
Certification Authority Interoperability (CA)	NA	NA	NA	3.18.0S	NS	NA
Wildcard Pre-Shared Key	NA	NA	NA	3.18.0S	NS	NA
PKI Integration with AAA Server	NA	NA	NA	3.18.0S	NS	NA
Phase profile G8275.1	3.18.0S	17.1.1	3.18.0S	3.18.0S	16.9.1	
Phase profile G8273.2	3.18.0SP	17.1.1	3.18.0SP	3.18.0SP	16.9.1	
FlexLSP base functionality	3.18.0SP	17.1.1	3.18.0SP	3.18.0SP	16.9.1	
PKI - CLI to Control Certificate Revocation List (CRL) Cache	NA	NA	NA	3.18.0S	NS	NA
CRL pre-fetch with tunable timers	NA	NA	NA	3.18.0S	NS	NA
Delete crypto session(s) or revoked peer cert(s) on CRL download	NA	NA	NA	3.18.0S	NS	NA
OCSP (Online Certificate Status Protocol)	NA	NA	NA	3.18.0S	NS	NA
VLAN Scale Convergence	3.17.0S	17.1.1	3.17.0S	3.17.0S	16.9.1	
Ethernet Fault Detection	3.17.0S	17.1.1	3.17.0S	3.17.0S	16.9.1	
Qos Support for VLAN Translation	3.17.0S	17.1.1	3.17.0S	3.17.0S	16.9.1	
CFM over CVLAN	3.17.0S	17.1.1	3.17.0S	3.17.0S	16.9.1	
MLDP Extranet	3.17.0S	17.1.1	3.17.0S	3.17.0S	16.9.1	
MPLS-TE over BDI	3.17.0S	17.1.1	3.17.0S	3.17.0S	16.9.1	
L3 Security ACL for EVC support	3.17.0S	17.1.1	3.17.0S	3.17.0S	16.9.1	

Feature Compatibility Matrix for the Cisco ASR920 Series Aggregation Services Routers

Feature Name	Cisco ASR-920-12CZ-A/D, Cisco ASR-920-4SZ-A/D	Cisco ASR-920-8S4Z-PD	Cisco ASR-920-24SZ-IM, ASR-920-24SZ-M, ASR-920-24TZ-M	Cisco ASR-920-12SZ-IM	Cisco ASR-920-12SZ-A, Cisco ASR-920-12SZ-D	Cisco ASR-920-20SZ-M
	Supported Release	Supported Release	Supported Release	Supported Release	Supported Release	Supported Release
Flexi License	3.18.0S	17.1.1	3.18.0S	3.18.0S	16.9.1	
IPv6 MVPN with MLDP	3.18.0S	17.1.1	3.18.0S	3.18.0S	16.9.1	
Circuit Emulation over UDP on A900-IMA32D on ASR900 RSP2 and ASR920	NA	NA	3.18.0S	3.18.0S	NA	NA
Netflow with EFP support	3.18.0SP	17.1.1	3.18.0SP	3.18.0SP	NS	NA
PPPoE Intermediate Agent	3.18.0S	17.1.1	3.18.0S	3.18.0S	16.9.1	
Asymmetric EFP	3.18.0S	17.1.1	3.18.0S	3.18.0S	16.9.1	
EVPN VPWS	3.18.0S	17.1.1	3.18.0S	3.18.0S	16.9.1	
Ethernet loopback for untagged/default	3.18.0S	17.1.1	3.18.0S	3.18.0S	16.9.1	
Larger String for EVC VLAN Encapsulation	3.18.0S	17.1.1	3.18.0S	3.18.0S	16.9.1	
8K EFP per box (rsp3) + 4K EFP per port					16.9.1	
ASR 900 4 port C37.94 Interface Module				16.6.1	NA	NA
OTN Wrapper on Ethernet cards: 2x10GE, 1x10G+8x1G					16.9.1	
Differential clock recovery on 9xOCn IM interfaces					16.9.1	
Differential clock recovery on DSx interfaces					16.9.1	
STM-4 TSoP	NA	NA	3.18.0S	3.18.0S	NA	NA
G.8275.2	16.5.1	17.1.1	16.5.1	16.5.1	16.9.1	
VRF Aware IPsec	NA	NA	NA	NA	NA	NA
PVST/RPVST	16.5.1	17.1.1	16.5.1	16.5.1	16.9.1	
Egress Shaping on MLPPP Bundle	16.5.1	17.1.1	16.5.1	16.5.1	16.9.1	
Egress QoS Support on MLPPP Bundle (Strict Priority Queuing)	16.5.1	17.1.1	16.5.1	16.5.1	16.9.1	
1G on 8x10G IM					16.9.1	
100G IM OTN					16.9.1	
Flex LSP Phase-2	16.5.1	17.1.1	16.5.1	16.5.1	16.9.1	
UPSR					NA	NA
5G XFI					NA	NA
Adaptive Clock Recovery (ACR) for 8 T1/E1 - only for CEM over MPLS	16.5.1	17.1.1	16.5.1	16.5.1	NA	NA
10G SADT	16.5.1	17.1.1	16.5.1	16.5.1	16.9.1	
VPLS Over BDI/PC	16.5.1	17.1.1	16.5.1	16.5.1	16.9.1	

Feature Compatibility Matrix for the Cisco ASR920 Series Aggregation Services Routers

Feature Name	Cisco ASR-920-12CZ-A/D, Cisco ASR-920-4SZ-A/D	Cisco ASR-920-8S4Z-PD	Cisco ASR-920-24SZ-IM, ASR-920-24SZ-M, ASR-920-24TZ-M	Cisco ASR-920-12SZ-IM	Cisco ASR-920-12SZ-A, Cisco ASR-920-12SZ-D	Cisco ASR-920-20SZ-M
	Supported Release	Supported Release	Supported Release	Supported Release	Supported Release	Supported Release
Static PW with OAM enabling Remote Port Shutdown	16.5.1	17.1.1	16.5.1	16.5.1	16.9.1	
System clock at 1.4MHz					16.9.1	
TWAMP with VRF support	16.5.1	17.1.1	16.5.1	16.5.1	16.9.1	
1mHz Bandwidth settings with GNSS Enabled					16.9.1	
mVPN-GRE over Physical Interface & BDI					16.9.1	
Active / Active QoS					16.9.1	
FMEA	16.11.1	17.1.1	16.11.1	16.11.1	16.9.1	
RSP2 Rebranding					16.9.1	
IP Source Guard	16.6.1	17.1.1			16.9.1	
MEF OpNID/Latching Loopback	16.7.1	17.1.1	16.7.1	16.7.1	16.9.1	
L2CP protocol for forward/discard at EVC (MRP, MMRP, MVRP)	16.7.1	17.1.1	16.7.1	16.7.1	16.9.1	
VLAN on Trunk EFP	16.7.1	17.1.1	16.7.1	16.7.1	16.9.1	
1-port OC481/ STM-16 or 4-port OC-12/OC-3 / STM-1/STM-4 + 12-Port T1/E1 + 4-Port T3/E3 CEM Interface Module 3G card				16.7.1	16.9.1	
AIS support on IMS8D, IMA16D	16.7.1	17.1.1	16.7.1	16.7.1	NA	NA
SADT - FPGA Support					16.9.1	
BFD suport on IPv6					16.9.1	
Backup PW on VPLS	16.8.1	17.1.1	16.8.1	16.8.1	16.9.1	
Support for multi-priority level queue	16.8.1	17.1.1	16.8.1	16.8.1	16.9.1	
SDM Template for IPv6 L3 Classification	16.8.1	17.1.1	16.8.1	16.8.1	16.9.1	16.9.1
Generic Routing Encapsulation (GRE) - RFC 2784	16.11.1	17.1.1	16.11.1	16.11.1	16.11.1	16.11.1
COPP	16.11.1	17.1.1	16.11.1	16.11.1	16.11.1	16.11.1
Runtime Defenses: ASLR, BOSC, X-Space	16.11.1	17.1.1	16.11.1	16.11.1	16.11.1	16.11.1
ASR920 Video Template - IPv4 QoS classifications Scalability Increase	16.11.1	17.1.1	16.11.1	16.11.1	16.11.1	16.11.1
Enhancement - Micro BFD	16.11.1	17.1.1	16.11.1	16.11.1	16.11.1	16.11.1
GigE UNI does not provide full throughput when VLAN tag is applied	16.11.1	17.1.1	16.11.1	16.11.1	16.11.1	16.11.1
CoS marking for locally originated packets	16.11.1	17.1.1	16.11.1	16.11.1	16.11.1	

Feature Compatibility Matrix for the Cisco ASR920 Series Aggregation Services Routers

Feature Name	Cisco ASR-920-12CZ-A/D, Cisco ASR-920-4SZ-A/D	Cisco ASR-920-8S4Z-PD	Cisco ASR-920-24SZ-IM, ASR-920-24SZ-M, ASR-920-24TZ-M	Cisco ASR-920-12SZ-IM	Cisco ASR-920-12SZ-A, Cisco ASR-920-12SZ-D	Cisco ASR-920-20SZ-M
	Supported Release	Supported Release	Supported Release	Supported Release	Supported Release	Supported Release
SR-TE: Affinity constraints for ODN	16.11.1	17.1.1	16.11.1	16.11.1	16.11.1	16.11.1
SR-TE ODN Color Extended Community (L3VPN)	17.1.1	17.1.1	17.1.1	17.1.1	17.1.1	17.1.1
IP SLA for Pseudowire	16.11.1	17.1.1	16.11.1	16.11.1		
Kernel migration to 4.9 (from 3.9) for RSP3				16.11.1	16.11.1	16.11.1
NETCONF/RESTCONF service level ACLs	16.11.1	17.1.1	16.11.1	16.11.1	16.11.1	16.11.1
BITS Frammer Software Support for ASR920, ASR900, NCS 4200	16.12.1	17.1.1	16.12.1	16.12.1	16.12.1	16.12.1
SR - uLoop Avoidance - ASR 920	16.12.1	17.1.1	16.12.1	16.12.1	16.12.1	16.12.1
NCS 4201/4202: Y.1564 10G internal mode	16.12.1	17.1.1	16.12.1	16.12.1	16.12.1	16.12.1
DS3/OCn Smart VCOP support on ASR-920-4SZ Variant	16.12.1	17.1.1				
DS1 Smart VCOP support on ASR920/NCS 4200	16.12.1	17.1.1	16.12.1	16.12.1	16.12.1	16.12.1
Truncating delay stats in SNMP MIB for Y.1731	16.12.1	17.1.1	16.12.1	16.12.1	16.12.1	16.12.1
LDP-BGP Tracking	17.1.1	17.1.1	17.1.1	17.1.1	17.1.1	17.1.1
Configurable OH Accounting for 4201/4202/RSP2	17.1.1	17.1.1	17.1.1	17.1.1	17.1.1	17.1.1
gRPC Network Management Interface (gNMI)	17.1.1	17.1.1	17.1.1	17.1.1	17.1.1	17.1.1
Model Driven Telemetry - gNMI Dial-In	17.1.1	17.1.1	17.1.1	17.1.1	17.1.1	17.1.1
ONS 10G I-temp support	17.1.1	17.1.1	17.1.1	17.1.1	17.1.1	17.1.1
PTP Multi-Profile Support On ASR903 and ASR920	17.1.1	17.1.1	17.1.1	17.1.1	17.1.1	17.1.1
Configurable Link Delay Value + Flooding in ISIS / BGP-LS - ASR 900 / RSP2	17.1.1	17.1.1	17.1.1	17.1.1	17.1.1	17.1.1
SR-Services: L2VPN (VPWS+VPLS) and EVPN VPWS (Single-Homing) over SR - ASR 900 / RSP2	17.1.1	17.1.1	17.1.1	17.1.1	17.1.1	17.1.1
4X10G (ASR-920-8S4Z-PD)	17.1.1	17.1.1				
Traps and Performance MIBs for GNSS				17.1.1	17.1.1	
ASR 900 / RSP2	17.1.1	17.1.1	17.1.1	17.1.1	17.1.1	17.1.1
MPLS TE: Newer SR-TE Policy CLI	17.1.1	17.1.1	17.1.1	17.1.1	17.1.1	17.1.1
SyncE yang module Telemetry integration	17.3.1	17.3.1	17.3.1	17.3.1	17.3.1	17.3.1
Native Multicast SLA Measurement	17.3.1	17.3.1	17.3.1	17.3.1	17.3.1	17.3.1

Feature Compatibility Matrix for the Cisco ASR920 Series Aggregation Services Routers

Feature Name	Cisco ASR-920-12CZ-A/D, Cisco ASR-920-4SZ-A/D	Cisco ASR-920-8S4Z-PD	Cisco ASR-920-24SZ-IM, ASR-920-24SZ-M, ASR-920-24TZ-M	Cisco ASR-920-12SZ-IM	Cisco ASR-920-12SZ-A, Cisco ASR-920-12SZ-D	Cisco ASR-920-20SZ-M
	Supported Release	Supported Release	Supported Release	Supported Release	Supported Release	Supported Release
Aggregated Interface Stats on Bundle	17.3.1	17.3.1	17.3.1	17.3.1	17.3.1	17.3.1
SRTE: PM: Sampled One-way End to End Delay (SR-Policy) Measurement - ASR 900 / RSP2	17.3.1	17.3.1	17.3.1	17.3.1	17.3.1	17.3.1
SR: PM: Delay measurement using RFC5357 (TWAMP Light) encoding (SW punt path timestamp) - ASR 900 / RSP2	17.3.1	17.3.1	17.3.1	17.3.1	17.3.1	17.3.1
SR-Services: EVPN (ELAN) L2 Gateway - RFC 7432 (Single-Homing) - ASR900 / RSP2	17.3.1	17.3.1	17.3.1	17.3.1	17.3.1	17.3.1
SRTE: Static route traffic steering using SRTE Policy	17.3.1	17.3.1	17.3.1	17.3.1	17.3.1	17.3.1
SRTE: Per-Flow (Class) ODN and Automated Steering (IPv4 GRT + L3VPN-VPNv4/v6 Services Steering)	17.3.1	17.3.1	17.3.1	17.3.1	17.3.1	17.3.1
SRTE: ISIS Flex Algo (Ph1): Metric minimization, avoidance, multi-plane, delay metric w/ rounding, Inter-Area	17.3.1	17.3.1	17.3.1	17.3.1	17.3.1	17.3.1
KGV E2E Solution - IOS XE Platforms	17.3.1	17.3.1	17.3.1	17.3.1	17.3.1	17.3.1
Static PW over P2MP	17.3.1	17.3.1	17.3.1	17.3.1	17.3.1	17.3.1
ASR920 IMA3G 1+1 OC3/12 single card APS support			17.3.1	17.3.1		
TWS - 17.3.1 PSB compliance testing and Automation (SP Access)	17.3.1	17.3.1	17.3.1	17.3.1	17.3.1	17.3.1
BFD Dampening	17.3.1	17.3.1	17.3.1	17.3.1	17.3.1	17.3.1
On-change notifications for IS-IS state - Configured/Adjacency	17.4.1	17.4.1	17.4.1	17.4.1	17.4.1	17.4.1
SRTE: ISIS Flex-Algo (Ph2): TI LFA + uLoop Avoidance + SID Leaking + ODN w/ Auto-Steering - ASR 920	17.4.1	17.4.1	17.4.1	17.4.1	17.4.1	17.4.1
STS1E Framed SAToP Support on IMA3G			17.4.1	17.4.1		

Feature Compatibility Matrix for the Cisco ASR920 Series Aggregation Services Routers

Feature Name	Cisco ASR-920-12CZ-A/D, Cisco ASR-920-4SZ-A/D	Cisco ASR-920-8S4Z-PD	Cisco ASR-920-24SZ-IM, ASR-920-24SZ-M, ASR-920-24TZ-M	Cisco ASR-920-12SZ-IM	Cisco ASR-920-12SZ-A, Cisco ASR-920-12SZ-D	Cisco ASR-920-20SZ-M
	Supported Release	Supported Release	Supported Release	Supported Release	Supported Release	Supported Release
SR-PCE: PCE Initiated SR Policy + OSPF Autoroute - ASR 920 SR-PCE: PCE Initiated SR Policy + OSPF Autoroute - ASR 920 - OSPF SR-PCE: PCE Initiated SR Policy + OSPF Autoroute - ASR 920 - SR Infra	17.4.1	17.4.1	17.4.1	17.4.1	17.4.1	17.4.1
SR: PM: Telemetry MDT and EDT support for Performance Monitoring KPI (Yang Oper) SR: PM: Telemetry MDT and EDT support for Performance Monitoring KPI (Yang Oper) - SR infra	17.4.1	17.4.1	17.4.1	17.4.1	17.4.1	17.4.1
SRTE-Services: L2VPN (VPWS+VPLS) over SR-TE preferred-path - ASR 920 SRTE-Services: L2VPN (VPWS+VPLS) over SR-TE preferred-path - ASR 920 : SRTE SRTE-Services: L2VPN (VPWS+VPLS) over SR-TE preferred-path - ASR 920 - PD	17.4.1	17.4.1	17.4.1	17.4.1	17.4.1	17.4.1
Complete YANG Model for CFM Configuration	17.4.1	17.4.1	17.4.1	17.4.1	17.4.1	17.4.1
Complete YANG Model for Ethernet EVC Configuration	17.4.1	17.4.1	17.4.1	17.4.1	17.4.1	17.4.1
Multicast SLA Measurement with MLDP on ASR920	17.4.1	17.4.1	17.4.1	17.4.1	17.4.1	17.4.1
On-change notifications for L2 VPN Psuedo Wire - Configured/Established	17.5.1	17.5.1	17.5.1	17.5.1	17.5.1	
SR: EVPN IRB (L2+L3 Anycast GW) + DCI/BL (Single-Homing) - ASR920 RSP2	17.5.1	17.5.1	17.5.1	17.5.1	17.5.1	
SRTE: PM: Liveness of SR Policy endpoint + SR-PM Delay deduction (loopback Mode) + SR-Policy w/ PM Liveness on all candidate-paths - RSP2/RSP3	17.5.1	17.5.1	17.5.1	17.5.1	17.5.1	

Feature Compatibility Matrix for the Cisco ASR920 Series Aggregation Services Routers

Feature Name	Cisco ASR-920-12CZ-A/D, Cisco ASR-920-4SZ-A/D	Cisco ASR-920-8S4Z-PD	Cisco ASR-920-24SZ-IM, ASR-920-24SZ-M, ASR-920-24TZ-M	Cisco ASR-920-12SZ-IM	Cisco ASR-920-12SZ-A, Cisco ASR-920-12SZ-D	Cisco ASR-920-20SZ-M
	Supported Release	Supported Release	Supported Release	Supported Release	Supported Release	Supported Release
Support for BFD, sub-second fast hello for VRRPv3 convergence and re-convergence on ASR920	17.5.1	17.5.1	17.5.1	17.5.1	17.5.1	
Complete YANG Model for L2VPN Xconnect	17.5.1	17.5.1	17.5.1	17.5.1	17.5.1	
Complete YANG Model for Pseudowire Interface Configuration	17.5.1	17.5.1	17.5.1	17.5.1	17.5.1	
SRTE: OSPF Flex Algo (Ph1): : Metric minimization + avoidance + multi-plane + delay metric w/ rounding + Inter-Area + ODN w/ Auto-Steering - ASR 900 / RSP3/ RSP2	17.5.1	17.5.1	17.5.1	17.5.1	17.5.1	
GR-820-CORE Performance Monitoring			17.5.1	17.5.1		
TWAMP Light	17.5.1	17.5.1	17.5.1	17.5.1	17.5.1	
IP Address Range-Based Filtering Support for CoPP ACL	17.5.1	17.5.1	17.5.1	17.5.1	17.5.1	
CFM sessions Hardware Offload	17.5.1	17.5.1	17.5.1	17.5.1	17.5.1	
Increase QoS Service-Policy Scale	17.5.1	17.5.1	17.5.1	17.5.1	17.5.1	
SRTE: SR Policy Counters	17.5.1	17.5.1	17.5.1	17.5.1	17.5.1	
Unframed Framing Support on E1 and Channel STM links			17.5.1	17.5.1		
MLPPP IP Termination on Serial Physical and Logical Interfaces			17.5.1	17.5.1		
ISIS Flexible Algorithm Include Affinity support	17.6.1	17.6.1	17.6.1	17.6.1		
T1 Framed SAToP support for Smart TPoP pluggables	17.6.1	17.6.1	17.6.1	17.6.1	17.6.1	
Support for BFD, sub-second fast hello for VRRPv3 convergence and re-convergen	17.6.1	17.6.1	17.6.1	17.6.1	17.6.1	
Remote LFA for MLDP	17.6.1	17.6.1	17.6.1	17.6.1	17.6.1	
Support for E1 Smart optics which supports Circuit emulation PW on uni-directional LSP & Bi-directional Flex LSP	17.6.1		17.6.1	17.6.1		
SRTE: OSPF Flex-Algo (Ph2): TI LFA	17.6.1	17.6.1	17.6.1	17.6.1	17.6.1	

Feature Compatibility Matrix for the Cisco ASR920 Series Aggregation Services Routers

Feature Name	Cisco ASR-920-12CZ-A/D, Cisco ASR-920-4SZ-A/D	Cisco ASR-920-8S4Z-PD	Cisco ASR-920-24SZ-IM, ASR-920-24SZ-M, ASR-920-24TZ-M	Cisco ASR-920-12SZ-IM	Cisco ASR-920-12SZ-A, Cisco ASR-920-12SZ-D	Cisco ASR-920-20SZ-M
	Supported Release	Supported Release	Supported Release	Supported Release	Supported Release	Supported Release
Ingress + Egress Flexible NetFlow	17.6.1	17.6.1	17.6.1	17.6.1	17.6.1	
YANG Model support for show mpls tr tunnel command	17.6.1	17.6.1	17.6.1	17.6.1	17.6.1	
YANG Model Support for RSVP Commands	17.6.1	17.6.1	17.6.1	17.6.1	17.6.1	
YANG Model Support for IPSLA Operating Model for Y1731	17.6.1	17.6.1	17.6.1	17.6.1	17.6.1	
Yang: Native: Oper model support for "sh mpls ldp neighbor"	17.6.1	17.6.1	17.6.1	17.6.1	17.6.1	
YANG Model support for QoS Overhead Accounting	17.6.1	17.6.1	17.6.1	17.6.1	17.6.1	
YANG Model support for alarm profile configurations	17.6.1	17.6.1	17.6.1	17.6.1	17.6.1	
YANG Model Support for Shared Risk Link Groups (SRLG) Group Identification (GID) configurations	17.6.1	17.6.1	17.6.1	17.6.1	17.6.1	
DHCP relay v4/v6 (in same VRF)SR: EVPN IRB (L2+L3 Anycast GW) + DCI/BL (Single-Homing)	17.6.1	17.6.1	17.6.1	17.6.1	17.6.1	
Stitching of subnet route from EVPN to L3VPN	17.6.1	17.6.1	17.6.1	17.6.1	17.6.1	
SR-PCE: Enabling SR-PM delay/liveness for PCE-Initiated policies	17.6.1	17.6.1	17.6.1	17.6.1	17.6.1	
SR-PCE: PCE Initiated SR Policy + ISIS Autoroute - ASR 900 / RSP 2 and RSP3	17.7.1	17.7.1	17.7.1	17.7.1	17.7.1	
Framed SAToP support for DS3 Smart pluggable (LAB-147)			17.7.1	17.7.1		
YANG - Oper Model - complete Y1564 Service Performance probe statistics	17.7.1	17.7.1	17.7.1	17.7.1	17.7.1	
SR with OSPF P2MP NB mode	17.7.1	17.7.1	17.7.1	17.7.1	17.7.1	
Customer requires number format for MA name rather than a string format on RSP2	17.7.1	17.7.1	17.7.1	17.7.1	17.7.1	
Default Smart Licensing enablement - ASR90x/ASR920/NCS520	17.7.1	17.7.1	17.7.1	17.7.1	17.7.1	17.7.1
Multicast SLA Measurement with Telemetry on ASR920	17.7.1	17.7.1	17.7.1	17.7.1	17.7.1	

Feature Compatibility Matrix for the Cisco ASR920 Series Aggregation Services Routers

Feature Name	Cisco ASR-920-12CZ-A/D, Cisco ASR-920-4SZ-A/D	Cisco ASR-920-8S4Z-PD	Cisco ASR-920-24SZ-IM, ASR-920-24SZ-M, ASR-920-24TZ-M	Cisco ASR-920-12SZ-IM	Cisco ASR-920-12SZ-A, Cisco ASR-920-12SZ-D	Cisco ASR-920-20SZ-M
	Supported Release	Supported Release	Supported Release	Supported Release	Supported Release	Supported Release
FR Support for IP Interworking on Eomer/Elboron IM				17.8.1		
EDPL on Bundle Interface	17.8.1	17.8.1	17.8.1	17.8.1	17.8.1	
Long Service name	17.8.1	17.8.1	17.8.1	17.8.1	17.8.1	
48T1E1-CE support				17.8.1		
Default Smart Licensing enablement Phase 2	17.8.1	17.8.1	17.8.1	17.8.1	17.8.1	
YANG - dot1ad is not supported in "rewrite ingress tag push"	17.8.1	17.8.1	17.8.1	17.8.1	17.8.1	
Increase Maximum MTU Size (>9600 bytes)	17.8.1	17.8.1	17.8.1	17.8.1	17.8.1	
L2CP feature needs to be enhanced to include more addresses/protocols	17.9.1	17.9.1	17.9.1	17.9.1	17.9.1	
[SVSP-247] Y1731 packets bypassing software QoS queues on NNI link	17.9.1	17.9.1	17.9.1	17.9.1	17.9.1	
Flex-LSP co-routed tunnel inter-area support	17.9.1	17.9.1	17.9.1	17.9.1	17.9.1	
PSB baseline testing (SP Access)	17.9.1	17.9.1	17.9.1	17.9.1	17.9.1	
Nodes should clear all user files from bootflash during factory reset (No Service password-recovery feature)	17.9.1	17.9.1	17.9.1	17.9.1		
SNMP DG with MPLS-TE	17.9.1	17.9.1	17.9.1	17.9.1	17.9.1	
Smart Pluggable firmware upgrade delivery mechanism	17.9.1		17.9.1	17.9.1		
Smart Pluggable Clock Status	17.9.1		17.9.1	17.9.1		
Custom Idle Pattern/Trunk Conditioning			17.9.1	17.9.1		
ADM upgrade		17.9.1	17.9.1			
Validation of IPV6 support as per " new RFC8200 Spec"	17.10.1	17.10.1	17.10.1	17.10.1	17.10.1	17.10.1
YANG - Support for L2VPN Oper models	17.10.1	17.10.1	17.10.1	17.10.1	17.10.1	17.10.1
Command Needed to Force PW up when AC is Down			17.10.1	17.10.1	17.10.1	
Need support for disabling/enabling gratuitous ARP	17.10.1	17.10.1	17.10.1	17.10.1	17.10.1	17.10.1



**Cisco Aggregation Services Routers
ASR 920 Series
Feature Compatibility Matrix**

July 2023

Cisco Systems, Inc.
www.cisco.com

Cisco has more than 200 offices worldwide.
Addresses, phone numbers, and fax numbers
are listed on the Cisco website at
www.cisco.com/go/offices.

THE SPECIFICATIONS AND INFORMATION REGARDING THE PRODUCTS IN THIS MANUAL ARE SUBJECT TO CHANGE WITHOUT NOTICE. ALL STATEMENTS, INFORMATION, AND RECOMMENDATIONS IN THIS MANUAL ARE BELIEVED TO BE ACCURATE BUT ARE PRESENTED WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED. USERS MUST TAKE FULL RESPONSIBILITY FOR THEIR APPLICATION OF ANY PRODUCTS.

THE SOFTWARE LICENSE AND LIMITED WARRANTY FOR THE ACCOMPANYING PRODUCT ARE SET FORTH IN THE INFORMATION PACKET THAT SHIPPED WITH THE PRODUCT AND ARE INCORPORATED HEREIN BY THIS REFERENCE. IF YOU ARE UNABLE TO LOCATE THE SOFTWARE LICENSE OR LIMITED WARRANTY, CONTACT YOUR CISCO REPRESENTATIVE FOR A COPY.

NOTWITHSTANDING ANY OTHER WARRANTY HEREIN, ALL DOCUMENT FILES AND SOFTWARE OF THESE SUPPLIERS ARE PROVIDED "AS IS" WITH ALL FAULTS. CISCO AND THE ABOVE-NAMED SUPPLIERS DISCLAIM ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, WITHOUT LIMITATION, THOSE OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE.

IN NO EVENT SHALL CISCO OR ITS SUPPLIERS BE LIABLE FOR ANY INDIRECT, SPECIAL, CONSEQUENTIAL, OR INCIDENTAL DAMAGES, INCLUDING, WITHOUT LIMITATION, LOST PROFITS OR LOSS OR DAMAGE TO DATA ARISING OUT OF THE USE OR INABILITY TO USE THIS MANUAL, EVEN IF CISCO OR ITS SUPPLIERS HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)

Any Internet Protocol (IP) addresses and phone numbers used in this document are not intended to be actual addresses and phone numbers. Any examples, command display output, network topology diagrams, and other figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses or phone numbers in illustrative content is unintentional and coincidental.

© 2023 Cisco Systems, Inc. All rights reserved.

Feature Compatibility Matrix for the Cisco ASR920 Series Aggregation Services Routers

Feature Name	Cisco ASR-920-12CZ-A/D, Cisco ASR-920-4SZ-A/D	Cisco ASR-920-8S4Z-PD	Cisco ASR-920-24SZ-IM, ASR-920-24SZ-M, ASR-920-24TZ-M	Cisco ASR-920-12SZ-IM	Cisco ASR-920-12SZ-A, Cisco ASR-920-12SZ-D	Cisco ASR-920-20SZ-M
	Supported Release	Supported Release	Supported Release	Supported Release	Supported Release	Supported Release
Support for Tagged LLDP Packets	17.10.1	17.10.1	17.10.1	17.10.1	17.10.1	17.10.1
ASR920 12CZ 4SZ TSoP	17.10.1					
Nodes should clear all user files from bootflash during factory reset (No Service password-recovery feature)	17.10.1	17.10.1	17.10.1	17.10.1	17.10.1	17.10.1
To enable telemetry based collection	17.10.1	17.10.1	17.10.1	17.10.1	17.10.1	17.10.1
BGP aggregate-address not showing in advertised routes when BGP LU is configured	17.10.1	17.10.1	17.10.1	17.10.1	17.10.1	17.10.1
Y1564 - SADT: Enhancement to resolve loss in observed throughput	17.10.1	17.10.1	17.10.1	17.10.1	17.10.1	17.10.1
System CESoP NxDSO BERT			17.11.1	17.11.1		
Frame Relay Port Mode			17.11.1	17.11.1		
Support for 3-in-24 BERT Patterns			17.11.1	17.11.1		
QoS for Y.1564 SADT External Sessions	17.11.1	17.11.1	17.11.1	17.11.1	17.11.1	
gNMI Dial-Out Using gRPC Tunnel Service	17.11.1	17.11.1	17.11.1	17.11.1	17.11.1	
YANG Support for show l2vpn atom vc detail Command	17.11.1	17.11.1	17.11.1	17.11.1	17.11.1	
Layer 3 Termination on Frame Relay Serial Interfaces					17.11.1	
NTP Support for IPv6 Networks	17.11.1	17.11.1	17.11.1	17.11.1	17.11.1	
No License Snapshot Support	17.11.1	17.11.1	17.11.1	17.11.1	17.11.1	
Track with EFP for convergence optimization - ASR 920/903	17.12.1	17.12.1	17.12.1	17.12.1	17.12.1	

Legend:

Blank Cells indicate the feature is not supported in a release yet.
NA indicates that the feature will not be supported on that platform.