



Release Notes for the Cisco Catalyst ESS9300 Embedded Series Switch – Release 17.5.1

The following release notes support the ESS9300. These release notes are updated to describe new features, limitations, troubleshooting, recommended configurations, caveats, and provide information on how to obtain support and documentation.

Revised April 16, 2021

Note: The documentation set for this product strives to use bias-free language. For purposes of this documentation set, bias-free is defined as language that does not imply discrimination based on age, disability, gender, racial identity, ethnic identity, sexual orientation, socioeconomic status, and intersectionality. Exceptions may be present in the documentation due to language that is hardcoded in the user interfaces of the product software, language used based on RFP documentation, or language that is used by a referenced third-party product.

Contents

This publication consists of the following sections:

- [Product Overview, page 1](#)
- [Image Information, page 2](#)
- [Software Downloads, page 2](#)
- [Related Documentation, page 2](#)
- [Feature Support, page 2](#)
- [Caveats, page 2](#)
- [Communications, Services, and Additional Information, page 3](#)

Product Overview

The ESS9300 is a Small Form Factor (SFF) Ruggedized GigE Embedded platform for tactical, outdoor and mobile environments. The compact design simplifies integration and offers the system integrator the ability to use the ESS9300 in a wide variety of applications. The Cisco ESS 9300 consists of one switch card. There are no cooling plates sold with it. It is up to the system integrator to design a thermal solution. The ESS-9300-10X-E board supports up to 10 ports of 10 GE fiber. Thermal power is 35 Watts.

Image Information

Note: You must have a Cisco.com account to download the software.

Cisco ESS9300 operates on the following Cisco IOS images:

- ie9k_iosxe.17.05.01.SPA.bin

Software Downloads

The latest image file for the ESS9300 is:

<https://software.cisco.com/download/home/286327314>

Related Documentation

The following documentation is available:

- All of the Cisco ESS9300 documentation can be found here:

<https://www.cisco.com/c/en/us/support/switches/catalyst-ess9300-embedded-series/series.html>

Feature Support

Support for RFC4884 ICMPv6 was added to the ESS3300, and also validated on ESS9300 Switches from Release 17.5.1.

RFC 4884 redefines selected ICMP error messages to support multi-part operation.

Caveats

Caveats describe unexpected behavior in Cisco IOS releases. Caveats listed as open in a prior release are carried forward to the next release as either open or resolved.

Note: You must have a Cisco.com account to log in and access the Cisco Bug Search Tool. If you do not have one, you can [register for an account](#).

For more information about the Cisco Bug Search Tool, see the [Bug Search Tool Help & FAQ](#).

Open Caveats

- **CSCvw59860**

Port is going ERR-Disabled state with specific SFP variants.

Symptoms: Occasionally, when connecting some specific SFPs (SFP-H10GB-CU1M/CU3M/CU5M) in ESS9300 where the peer box is also ESS9300, it is observed that link goes in err-disable state where these SFPs are connected and does not recover.

Conditions: SFP connected should be on of the following:

SFP-H10GB-CU1M

SFP-H10GB-CU3M

SFP-H10GB-CU5M

Workaround: None.

Resolved Caveats

■ CSCvw13680

Alarm Output LED is set based on severity of input/facility Alarm.

Summary: When alarm is asserted/triggered, Alarm Output LED color is set based on the severity of the Input/Facility Alarm.

Alarm Output LED Color Settings:

GREEN: No Alarm detected or Input Alarm detected with severity NONE

RED: Input/Facility Alarm detected with severity Minor

Flashing RED: Input/Facility Alarm detected with severity Major

Communications, Services, and Additional Information

- To receive timely, relevant information from Cisco, sign up at [Cisco Profile Manager](#).
- To get the business impact you're looking for with the technologies that matter, visit [Cisco Services](#).
- To submit a service request, visit [Cisco Support](#).
- To discover and browse secure, validated enterprise-class apps, products, solutions and services, visit [Cisco Marketplace](#).
- To obtain general networking, training, and certification titles, visit [Cisco Press](#).
- To find warranty information for a specific product or product family, access [Cisco Warranty Finder](#).

Modifications to this product not authorized by Cisco could void the FCC approval and negate your authority to operate the product.

The Cisco implementation of TCP header compression is an adaptation of a program developed by the University of California, Berkeley (UCB) as part of UCB's public domain version of the UNIX operating system. All rights reserved. Copyright © 1981, Regents of the University of California.

NOTWITHSTANDING ANY OTHER WARRANTY HEREIN, ALL DOCUMENT FILES AND SOFTWARE OF THESE SUPPLIERS ARE PROVIDED "AS IS" WITH ALL FAULTS. CISCO AND THE ABOVE-NAMED SUPPLIERS DISCLAIM ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, WITHOUT LIMITATION, THOSE OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE.

IN NO EVENT SHALL CISCO OR ITS SUPPLIERS BE LIABLE FOR ANY INDIRECT, SPECIAL, CONSEQUENTIAL, OR INCIDENTAL DAMAGES, INCLUDING, WITHOUT LIMITATION, LOST PROFITS OR LOSS OR DAMAGE TO DATA ARISING OUT OF THE USE OR INABILITY TO USE THIS MANUAL, EVEN IF CISCO OR ITS SUPPLIERS HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

Any Internet Protocol (IP) addresses and phone numbers used in this document are not intended to be actual addresses and phone numbers. Any examples, command display output, network topology diagrams, and other figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses or phone numbers in illustrative content is unintentional and coincidental.

Communications, Services, and Additional Information

All printed copies and duplicate soft copies of this document are considered uncontrolled. See the current online version for the latest version.

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco website at www.cisco.com/go/offices.

© 2021 Cisco Systems, Inc. All rights reserved.