

VG930m

19" DIGITAL MEDIA GRAPHIC SERIES LCD

WITH SWIVEL AND HEIGHT ADJUST

Stylish, multimedia performance.

The ViewSonic® 19" VG930m delivers multimedia performance to your desktop in a stylish, slim design. It's an ideal choice for business applications that include mixed data, audio, graphics and video content. Graphics professionals and gamers will love the FAST 8MS VIDEO RESPONSE that delivers blur-free, full motion video and crystal-clear graphics rendering. OPTISYNC® ANALOG AND DIGITAL INPUTS ensure seamless compatibility with VGA and digital DVI sources. VESA® wall mount-compliance and the INTEGRATED AMP AND STEREO SPEAKERS reduce desktop clutter while accenting your office décor. The Kensington® security port offers theft deterrence and the OSD/Power lock ensures your optimal screen settings remain in place.



FAST VIDEO RESPONSE FOR INTENSE GRAPHICS

- > **ClearMotiv® 8ms video response time**
Fast 8ms video response delivers broadcast-quality video.
- > **Dynamic Structure™ technology**
Innovative liquid crystal composition and pixel matrix accelerate video response for seamless video and intense graphics.
- > **OptiSync® digital/analog inputs expand your connectivity**
Multi-mode input technology supports both digital (DVI) and analog (VGA) signals for ultimate compatibility and configuration flexibility.
- > **Ergonomic base adds ease and comfort**
Ultimate ergonomic flexibility comes built-in with the convenient 3.2" height adjustment and 360° swivel.
- > **Multimedia enhanced**
Save workspace and enjoy rich, stereo sound with two built-in stereo speakers.
- > **Stylish slim-bezel design**
The full 19" viewable screen in an ultra-thin bezel lets you see more without taking up valuable desktop real estate.
- > **High 300 nit brightness (typ) and 700:1 contrast ratio (typ)**
- > **VESA® 100mm wall mount interface and Kensington® security port**
- > **Windows Vista approved**
- > **PC and Mac® compatible**
- > **TCO'03 and ENERGY STAR® qualified**



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic®
See the difference® 

VG930m

19" DIGITAL MEDIA GRAPHIC SERIES LCD WITH SWIVEL AND HEIGHT ADJUST



360° SWIVEL



HEIGHT ADJUST



TILT



ISO 9001:2000
FM 40187



ISO 14001:1996
FM 40968

ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Customer Service and Technical Support: (800) 688-6688 • Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

*Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Windows Vista and the Windows logo are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2007 ViewSonic Corporation. All rights reserved. [13348-01B-06/07] VG930m-3

LCD	Type	19" color TFT active matrix SXGA LCD
	Display Area	14.8" horizontal x 11.9" vertical; 19.0" diagonal
	Optimum Resolution	1280x1024
	Contrast Ratio	700:1 (typ)
	Viewing Angles	160° horizontal, 155° vertical @ contrast ratio > 5:1
	Response Time	8ms (typ)
	Light Source	Long life, 50,000 hrs. (typ)
VIDEO INPUT	Brightness	300 cd/m2 (typ)
	Panel Surface	Anti-glare
	Analog/Digital	RGB analog (75 ohms, 0.7 Vp-p)/DVI-D
COMPATIBILITY	Frequency	F _H : 30~82kHz, F _V : 50~75Hz
	Sync	H/V separated (TTL)
CONNECTOR	PC	VGA up to 1280x1024 non-interlaced
	Mac®*	Power Mac™ G3/G4/G5 up to 1280x1024
POWER	Analog/Digital	15-pin mini D-sub/DVI-D
	Audio In	Stereo mini audio line in
	Power	3-pin AC plug
AUDIO	Voltage	AC 100~240V (universal), 50~60Hz (auto switch)
	Consumption	35W (typ)
CONTROLS	Speakers	2x1.5-watt
	Amplifier	1.5-watt
ERGONOMICS	Basic	Power, 1, down, up, 2
	OnView®	Auto image adjust, brightness, contrast, input selection, ViewMatch® color adjust (sRGB, 9300K, 6800K, 6500K), information (mode, model number, serial number), audio (volume, mute), manual image adjust (H. position, V. position, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), memory recall
OPERATING CONDITIONS	Temperature	41~95°F (5~35°C)
DIMENSIONS (W x H x D)	Humidity	20~80% (non-condensing)
WEIGHT	Physical with stand	16.8" x 18.9" x 9.1" (428mm x 479mm x 230mm)
	Physical without stand	16.8" x 15.5" x 2.6" (428mm x 399mm x 68mm)
REGULATIONS	Net with stand	13.3 lb. (6.0 kg)
	Net without stand	9.9 lb. (4.5 kg)
	Gross with stand	16.0 lb. (7.2 kg)
RECYCLE/DISPOSAL	UL, cUL, FCC-B, CB, CE, ENERGY STAR®, NOM, TUV/GS, TUV-S, TUV/ERGO (covers ISO13406-2 & MPR II), TCO'03, GOST-R + 20 original copies hygienic, SASO, PCBC, VCCI, BSMI, CCC, PSB, C-TICK, RoHS	The lamp in this product contains mercury. Please dispose of in accordance with local, state and federal laws.
POWER MANAGEMENT	Meets TCO'03 and ENERGY STAR® standards	
PACKAGE CONTENTS	LCD display, VGA cable, power cable, audio cable, Quick Start Guide, ViewSonic Wizard CD	
WARRANTY	Three-year limited warranty	

ViewSonic®
See the difference®

For more product information, visit us on the web at ViewSonic.com