

VA926g

19" VALUE SERIES LCD
WITH ENERGY STAR® 5.0

Lean and Green.

The ViewSonic® 19" viewable VA926g LCD monitor delivers reliability, performance and simplicity for users who prefer a standard aspect ratio display and a native resolution of 1280x1024. The VA926g features DVI and analog dual inputs to ensure seamless compatibility with traditional VGA output sources as well as pure digital DVI connectivity. It also incorporates 100,000:1 dynamic contrast ratio and ENERGY STAR® 5.0 certification for crystal clear images and reduced power consumption. Packed with essential features such as ViewSonic's OnView® control interface with Power / OSD lock, sRGB color management and VESA wall mount capability, the VA926g offers solid dependability and elegant design within reach to a wide range of users.



ALL YOU NEED FOR A PRODUCTIVE DAY

- > **Full 19" viewable screen**
Displays a full, flat 19" viewable screen area with crisp detail and fully saturated color.
- > **1280x1024 native resolution**
Incredible image detail for sharp text and graphics.
- > **100,000:1 dynamic contrast ratio**
Darker black levels and better overall front-of-screen performance.
- > **OptiSync® digital/analog inputs expand your connectivity**
Multi-mode input technology supports both digital (DVI) and analog (VGA) signals for ultimate compatibility and configuration flexibility.
- > **Power / OSD lock secures your settings**
Prevents changes to monitor settings and maintains an optimized image.
- > **OnView® controls for superior screen adjustability**
Screen adjustments are precisely made via an easy-to-use on-screen menu.
- > **VESA wall mount compliant**
- > **PC and MAC® compatible**
- > **ENERGY STAR® 5.0 certified**



ViewSonic®
See the difference® 

VA926g

19" VALUE SERIES LCD WITH ENERGY STAR® 5.0



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by TUV NORD.

LCD	Type	19" Color TFT Active Matrix SXGA LCD
	Display Area	14.8" horizontal x 11.9" vertical; 19" diagonal
	Optimum Resolution	1280x1024
	Contrast Ratio	1000:1 static (typ); 100,000:1 dynamic
	Viewing Angles	170° horizontal, 160° vertical @ contrast ratio > 10:1
	Response Time	5ms (typ)
	Light Source	Long life, 40,000 hrs. (typ)
	Brightness	250 cd/m ² (typ)
VIDEO INPUT	Panel Surface	Anti-glare, hard coating (3H)
	Analog	RGB analog (75 ohms, 0.7/1.0 Vp-p)
	Digital	DVI-D (TMDS, 100 ohms)
COMPATIBILITY	Frequency	F _H : 30~82kHz, F _V : 56~75Hz
	PC	VGA up to 1280x1024 non-interlaced
CONNECTOR	Mac®*	Power Mac™ up to 1280x1024
	Analog	15-pin mini D-sub (VGA)
POWER	Digital	DVI-D
	Power	3-pin plug (CEE22)
	Voltage	AC 100~240V (universal), 50/60Hz
CONTROLS	Consumption	25W (typ)
	Basic	1, 2, power, down, up
ERGONOMICS	OSD	Auto Image Adjust, Contrast/Brightness, Input Select (D-sub, DVI), Color Adjust (sRGB, 9300K, 6500K, 5400K, User Color [R, G, B]), Information, Manual Image Adjust (Horizontal Size, H/V Position, Fine Tune, Sharpness, Eco-mode), Setup Menu (Language Select, Resolution Notice, OSD Position, OSD Time Out, OSD Background), Memory Recall
	Tilt	Down 5°, Up 20°
OPERATING CONDITIONS	Temperature	32~104° F (0~40° C)
	Humidity	10~90% (non-condensing)
DIMENSIONS (W x H x D)	Physical with stand	16.2" x 17.1" x 7.7" (412.2mm x 434.9mm x 195mm)
	Physical without stand	16.2" x 14.0" x 2.5" (412.2mm x 354.9mm x 63.8mm)
	Packaging	18.5" x 20.1" x 5.5" (470mm x 510mm x 140mm)
WEIGHT	Net with stand	9.04 lb. (4.1 kg)
	Net without stand	8.14 lb. (3.7 kg)
	Gross	12.13 lb. (5.5 kg)
WALL MOUNT REGULATIONS	VESA 100mm x 100mm	
RECYCLE/DISPOSAL	UL, CUL, FCC-B (ICES-003B), CB, CE, TCO'5.0, ICES-003B, GOST-R (4 copies), HYGIENIC, ENERGY STAR®, CCC, CEL, BSMI, PSB, C-TICK, WEEE, RoHS, UKraine	
PACKAGE CONTENTS	The lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws.	
WARRANTY	LCD display, power cable, VGA cable, Quick Start Guide, ViewSonic Wizard CD (User Guide & drivers).	
	Three-year limited warranty on parts, labor and backlight.	

Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

*Adapter may be required. Analog adapter available from ViewSonic. Specifications and availability are subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Windows and Windows Vista are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. MAC is a trademark of Apple, Inc., registered in the United States and other countries. All other corporate names and trademarks stated herein are the property of their respective companies. Copyright © 2010 ViewSonic Corporation. All rights reserved. [15161-00B-08/10] VA926g-1

ViewSonic®
See the difference® 

For more product information, visit us on the web at ViewSonic.com