DisplayPort to VGA Converter Cable

DisplayPort Male to HD15 Female, 15 cm (6 in.), Active, Black
Part No.: 325325

Easily connect a DisplayPort source with a VGA display.
The Manhattan DisplayPort to VGA Converter helps establish a fast, simple and convenient link between newer DisplayPort-equipped desktop and notebook computers and other media sources with existing VGA monitors. The Manhattan DisplayPort to VGA Converter is easy and quick to install and requires no complicated configuration or setup to help extend the service life and fully realize the investment and value of legacy VGA displays, projectors and other equipment. This low power, cost-effective and reliable solution allows PC users to transition to DisplayPort bandwidths, resolutions, Deep Color and more without the expense of upgrading to newer and costly monitors and projectors. Its integrated, all-in-one design helps achieve a compact, integrated solution that eliminates unnecessary cables, tangles and clutter to keep installations and workspaces neat and orderly.

Features:

- Easily connects DisplayPort-equipped computers with VGA monitors, projectors and more
- Delivers a high-quality digital video signal – ideal for extending service of legacy VGA equipment
- Supports Deep Color, high-bandwidth 10.8 Gbps applications and resolutions up to 1080p on 1920 x 1200 (WUXGA) displays
- Integrated design simplifies connections and eliminates cable tangles and clutter
- Plug and play; Windows and Mac compatible
- Lifetime Warranty

Specifications:

Standards and Certifications
• UL 20276

Connectors
• DisplayPort 20-pin male
• HD 15-pin female

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.
All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Gold-plated contacts
- Molded PVC
- Built-in strain relief

Cable
- Length: 15 cm (6 in.)
- 28-AWG conductors
- Withstanding voltage: 300 VDC
- Thermal plastic casing
- Shielded

General
- Maximum single link range: 1920 x 1200, 1080P
- VGA resolution: up to 1920 x 1200
- Frequency: 154 MHz / 144 MHz
- Active

Package Contents
- DisplayPort to VGA Converter Cable