Planar PXL2270MW
22" LCD Monitor

ThePlanar® PXL2270MW is a 22" widescreen backlit-LED LCD monitor featuring wide viewing angles, and VGA, DisplayPort and HDMI video inputs. It fits seamlessly into home, office, healthcare and digital signage applications.

SPECIFICATION	DETAIL
Product Name	PXL2270MW
Planar Part Number	997-8001-00
Viewable Size	21.5" diagonal (18.77" horizontal x 10.56" vertical)
Aspect Ratio	16:9
Contrast Ratio (typ)	1000:1
Viewing Angle (typ)	178° Horizontal and 178° Vertical (Specified at CR>10:1)
Response Time (typ)	5 ms (GTG)
Brightness (Typical)	250 cd/m²
Display Type	ADS (Advanced super Dimension Switch) Edge-Lit LED LCD Active Matrix Flat Panel Display (TFT)
Display Resolution	1920 x 1080, full HD
Tilt Range	-5° to +20°
Palette	16.7 million colors
Pixel Pitch	0.24825 mm
Refresh Rate	55~76 Hz (60 Hz recommended)
Dimensions (W x H x D)	20.20" x 14.36" x 6.89"
Dimensions without Stand	20.20" x 12.00" x 1.9"
Panel Depth	1.9"
Display Weight	7.3 lbs. (6.6 lbs. without base and stand)
Shipping weight	9.5 lbs.
Video Inputs	HDMI, DisplayPort, VGA

Audio Output	1W x 2
External Connections	HDMI 19-pin, DisplayPort 20-pin, VGA 15-pin, 3.5 mm audio in, 3.5mm headphone out
Compatibility	PC and Mac® (adapter may be required for Mac)
Power Supply	Internal
Power Consumption (max)	23 Watt typical (0.5 Watt standby)
Power Requirements	AC 100/240 VAC
VESA Compatible/Location	Built-in 100mm VESA, monitor back
Product Approvals	FCC-B, CE, UL/cUL, RoHS
Service and Support	3-Year Customer First™ Warranty featuring FREE 2-Day Advance Replacement (US only)
Options / Features	Wide color consistent viewing angle, Uniform bezel, Discreet branding, Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot
In the Box	PXL2270MW 21.5" LED LCD Monitor, Power cord, VGA cable, DP cable, audio cable, and User's guide
UPC	8 10689 00220 8

For more information, please visit www.planar.com

Specifications are subject to change without notice.

Specification Report Date: 5/18/2015