

SANSUI Accu D-LED LCD Series – **SLED6516**



BASIC FEATURES

- Ultra High Definition Digital TV (Native 4k2k/60Hz bypass, upscaling FHD 120Hz to 4k1k/120Hz)
- Integrated Digital Tuner (ATSC, QAM)
- Receives Over-the-Air DTV Broadcast Signals
- 65" (16:9) UHD LED (3840 x 2160)
- Brightness 300cd/m²
- Contrast ratio 1,000,000:1 (w/DBC)
- Response time 6.5ms
- 3D Comb Filter
- Wall Mount Vesa (400 x 400)
- Energy Star Ver. 6.1
- Hotel Mode
- HDMI2.0/HDCP2.2 (1 port)
- MHL (1 port)

JACK CONFIGURATION

- HDMI Input x 4 (HDMI2.0(4K@60Hz) x 1, HDMI1.4 x 2, MHL x 1)
- Component Input x 1
- A/V Input x 1
- PC Monitor Input
- Digital Audio Out (Optical)
- Analog Audio Out (Mini Jack)
- Headphone Jack

DIMENSIONS

- | | |
|------------------------------|----------------------|
| • Unit w/stand (W x D x H) | 57.56"x12.17"x35.51" |
| • Unit w/o stand (W x D x H) | 57.56"x2.31"x33.40" |
| • Carton (W x D x H) | 62.83"x7.01"x38.58" |
| • Unit Weight | 47.4 lbs |
| • Carton Weight | 63.49 lbs |
| • On Mode Power Consumption | 180W |
| • Unit Color | Black |
| • Container Quantity | 165/40HQ |
| • Country of Origin | China |
| • UPC# | 859 087 005 084 |

ACCESSORIES

- Remote Control
- Battery 3A x 2

* All trademark's are the property of their respected owners. Information for reference purposes only. Subject to change without notice. Not responsible for typographical errors.