



# JUNCEUS

## VIRTUAL 7.1 CHANNEL GAMING HEADSET



GX gaming now releases its new generation 7.1 channel gaming headset - Junceus. With a 7.1 channel surround sound system, you can hear incoming enemy footsteps and avoid being killed. This headset is the almighty weapon you should have for any battlefield.

The 40mm neodymium driver offers you stereo-grade sound effects. The cushioned ear cups allow you to wear it all day long, without feeling any discomfort. You can adjust the flexible microphone to any voice position. The inner headband of the Junceus makes a perfect fit for your head. In addition, the LED Lighting creates a more exciting gaming experience. All the Junceus features intensify your gaming sensation and totally absorb you in the gaming world.



### Cushioned ear cups

Cushioned ear cups allow you to wear it all day long, without feeling any discomfort



### Flexible Microphone

Adjust the microphone to any voice position



### In-line function control

Adjust volume, switch LED lighting, and turn microphone on/off



### Adjustable headband

The inner headband of Junceus makes a perfect fit for your head comfort



### Shiny LED Lighting

LED Lighting enhances your experience in the gaming world

# JUNCEUS

## VIRTUAL 7.1 CHANNEL GAMING HEADSET



### System Requirements

- Supports Windows® 8/7/Vista/XP

### Product Specifications

#### Headset

- Sensitivity: 111±3dB (at 1KHz)
- Frequency response: 20Hz ~20kHz
- Driver unit: 40 mm
- Impedance: 32 ohm
- Driver unit material: Neodymium magnet
- Cable length: 2.2M

#### Microphone

- Type: Omni-directional microphone
- Sensitivity: -47+/-3dB (at 1KHz)
- Impedance: ≤2.2k ohm

### Package Contents

- Junceus Gaming Headset
- Driver Disk
- Multi-language quick guide



Model Name		HS-G650 Junceus	HS-G700V Cavimanus	HS-G850 Zabius
Package				
Interface support		USB	USB	USB /3.5mm
Sensitivity		111dB	95 dB	117dB
Frequency response		20 HZ ~20KHz	20 HZ ~20KHz	20 HZ ~20KHz
Driver Unit		40 mm	40 mm	40mm
Virtual 7.1 Channel		Yes	Yes	No
Impedance		32 ohm	32 ohm	32 ohm
Microphone sensitivity		-47dB	-39dB	-42dB
WEEE data	Dimension (W x H x D) mm	215 x 83.5 x 205	220 x 75 x 190	220 x 90 x 200
	Body Weight	403g	405g	374g
	Package Size (W x H x D)mm	230 x 105 x 250	212 x 97 x 222	240 x 104 x 215
Shipping Information	PCs/CTN	20	20	10
	CUFT/CTN	5.78	5.16	2.5
	PCs/20'container	3200	3860	4000
Bar code	EAN (Black)	4710268 248637	4710268 239086	4710268 244035
	UPC (Black)	091163 248637	091163 239086	091163 244035
Part #	Black	3171-0062-101	3171-0043-101	3171-0057-101

