2-Port DisplayPort to VGA Hub, DP1.2, TAA

MODEL NUMBER: **B157-002-VGA**

Converts and splits a DisplayPort video signal for display on two VGA monitors, projectors or televisions at the same time. Ideal for offices, conference rooms, retail settings, trade shows and classrooms.

Description

The B157-002-VGA 2-Port DisplayPort to VGA Splitter converts and splits a DisplayPort video signal for display on two VGA-enabled monitors, projectors or televisions at the same time. Ideal for offices, conference rooms, retail settings, trade shows and classrooms, this compact splitter features a built-in DisplayPort cable that connects to the source. It lets you use your existing VGA displays instead of buying new DisplayPort monitors or docking stations.

The B157-002-VGA supports video resolutions up to 1080p @ 60 Hz (1920 x 1080), as well as HDCP, EDID and DDC. Orange LEDs next to each output port indicate whether the splitter is powered on and transmitting a signal to the connected displays. The splitter works with all operating systems and is small enough to carry in your backpack or computer bag. Plug-and-play convenience means no software or drivers are needed. An included USB Micro-B cable connects between the source and the splitter to provide power, so no external power supply is required.

Features

Converts and Splits DisplayPort Signal to 2 VGA Displays Simultaneously Ideal for offices, conference rooms, trade shows and classroomsBuilt-in DisplayPort cable connects to sourceIncluded USB Micro-B cable supplies power to splitterSave money on new DisplayPort displays or docking stations
Top-Shelf Performance Supports video resolutions up to 1080p @ 60 Hz (1920 x 1080)Complies with HDCP, EDID and DDCLEDs indicate whether splitter is powered on and transmitting signal to connected displays
Easy to Use Almost Anywhere Works with all operating systemsPlug and play—no software, drivers or external power supply requiredCompact unit fits easily in backpack or computer bag

Highlights

- Supports video resolutions up to 1080p @ 60 Hz (1920 x 1080)
- Included USB Micro-B cable supplies power to unit
- Works with all operating systems
- Compact enough for easy carrying in backpack or laptop bag
- Plug and play—no software or drivers required

Package Includes

- B157-002-VGA 2-Port DisplayPort to VGA Splitter
- USB Micro-B cable, 3 ft.
- Owner's manual

Specifications

OVERVIEW	
UPC Code	037332191496
Technology	VGA/SVGA; DisplayPort

VIDEO	
Max Supported Video Resolution	1080p @ 60 Hz (1920 x 1080)
Max Supported Color Depth	24-bit True Color
3D Video Supported	Yes

AUDIO	
Audio Specification	2.0-channel surround sound audio

USER INTERFACE, ALERTS & CONTROLS	
LED Indicators	(x2) Orange (Monitor Signal)

PHYSICAL	
Color	Black
Wire Gauge (AWG)	28
Material of Construction	Metal
Shipping Dimensions (hwd / cm)	4.32 x 20.07 x 14.22
Shipping Dimensions (hwd / in.)	1.70 x 7.90 x 5.60
Shipping Weight (kg)	0.27
Shipping Weight (lbs.)	0.60
Unit Dimensions (hwd / cm)	2.55 x 6.15 x 7.6
Unit Dimensions (hwd / in.)	1.03 x 2.42 x 2.99
Unit Dimensions (hwd / mm)	25.5 x 61.5 x 76
Unit Weight (kg)	0.07
Unit Weight (lbs.)	0.154

COMMUNICATIONS	
EDID Compatible	Yes

CONNECTIONS	
Ports	2
Side A - Connector 1	DISPLAYPORT (MALE)
Side A - Connector 2	MICRO-USB B (FEMALE)
Side B - Connector 1	(2) HD15 (FEMALE)
Connector Plating	Nickel

FEATURES & SPECIFICATIONS	
Displayport Specification	1.2

HDCP Specification	1.3
SPECIAL FEATURES	
MST Support	No
STANDARDS & COMPLIANCE	
Certifications	CE, FCC, RoHS, REACH
WARRANTY	
Product Warranty Period (Worldwide)	3-year limited warranty