ThinkCentre M600 Tiny Platform Specifications

Processor	Intel® Celeron® Processor N3000 Series or Intel Pentium® Processor N3000 Series	Keyboard	Some: PS/2 Keyboard (PS/2 connector), Lenovo logo
	Processor Cores / Frequency (Base/Max) Cache Memory Types Integrated Graphics		Some: Preferred Pro USB Keyboard (USB connector), Lenovo logo Some: Lenovo USB Fingerprint Keyboard (USB connector)
	Celeron N3000 2 / 2 1.04 / 2.08 GHz 2MB DDR3L-1600 Intel HD		Some: Ultraslim Plus Wireless Keyboard (2.4GHz via USB receiver), black Some: PS/2 Optical Wheel Mouse, black, Lenovo logo
	Celeron N3050 2 / 2 1.6 / 2.16 GHz 2MB DDR3L-1600 Intel HD		Some: Enhanced Optical USB Mouse, black, Lenovo logo
	Pentium N3700 4 / 4 1.6 / 2.4 GHz 2MB DDR3L-1600 Intel HD		Some: Ultraslim Plus Wireless Mouse (2.4GHz via USB receiver), black
Chipset	Intel Architecture (IA) SoC that integrates Intel processor core, graphics, memory controller, and I/O interfaces into a single system-on-chip solution	Mechanical	Tiny (1L or 2L), black color; metal case
Graphics	Intel HD Graphics in processor, uses main memory, DirectX® 11.1,		Dimensions (WxDxH) Max weight (lb / kg)
	twoDisplayPort™, one optional 3rd DP or VGA, supports triple independent display; Maximum resolution: 3840x2160(DP)@30Hz; 1920x1200(optional VGA)@60Hz;		M600 Tiny only (1L) 7.05" X 7.20" X 1.36" 2.9 lb (1.3 kg) 179mm X 182.9mm X 34.5mm
Monitor cable	1920x1080(DP to VGA dongle)@60Hz; 1920x1080(DP to DVI dongle)@60Hz; 3840x2160(DP to HDMI dongle)@30Hz Optional DP to VGA, DP to DVI-D (single link), or DP to HDMI 1.4 dongle		M600 Tiny only (2L) 7.05" X 7.20" X 3.15" 4.2 lb (1.9 kg) 179mm X 182.9mm X 80mm
Memory	8GB max / DDR3 Low Voltage, DDR3L-1600, non-parity, one 204-pin SO-DIMM socket		M600 Tiny (1L) with 7.42" X 7.30" X 2.48" 4.12 lb (1.87 kg) VESA mount & ODD box 188.4mm X 185.38mm X 63mm
Storage	Some: M.2 Solid State Drive (SSD), SATA interface Some: hard disk, 5400 or 7200 rpm, SATA 6.0Gb/s, 2.5" Wide		M600 Tiny (1L) with 7.42" X 7.30" X 2.62" 3.53 lb (1.6 kg) VESA mount & I/O box 188.4mm X 185.38mm X 66.6mm
	Some: 500GB (5400 rpm) Solid State Hybrid Drive (SSHD) / with 8GB MLC NAND flash memory, SATA 6.0Gb/s, 2.5" wide	VESA mount Floor Stand	Optional VESA mount bracket kit, supports VESA 75mm and 100mm Optional system floor stand for vertical orientation
Optical	Some: Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Wide Some: external ODD box with DVD-ROM, 9.5mm high, via USB Some: external ODD box with DVD±RW, 9.5mm high, via USB	Power supply	65 watts AC/DC adapter, autosensing, 88% PSU (not included for TIO models) 90 watts AC/DC adapter, autosensing, 88% PSU (only for models with I/O box)
Onboard SATA Media reader	Some: external ODD box (for TIO) with DVD-ROM, 9.5mm high, via USB Some: external ODD box (for TIO) with DVD±RW, 9.5mm high, via USB SATA 6.0Gb/s controller, one connectors on planar None	Limited warranty ³	Some: 1-year or 3-year, depot service / service upgrades available some: 1-year or 3-year, limited onsite service / service upgrades available some: 3-year, limited onsite service, OID (Onsite International Delivery) / service upgrades available
Front ports	Two USB 3.0 (one is Always On and fast charge), one microphone (stereo, 3.5mm),		For Lenovo service upgrade options, please go to S-TC sheet
Rear ports	one headphone / microphone combo jack (stereo, 3.5mm) Two USB 2.0, two USB 3.0 (optional external optical box or I/O box occupies one or two specific USB on some models), ethernet (RJ-45), two DisplayPort, one optional port (VGA, 3rd DP, or serial on some models), one headphone; additional four serial (9-pin), one parallel (25-pin), and two PS/2 ports on 2L models	Preload	Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 10 Pro 64-bit Some: Windows 7 Professional 64 Some: Windows 7 Professional 64 Some: Windows® 10 Pro 64-bit Preloaded applications (only some listed)
I/O box	Optional external I/O box, extends two USB 2.0, two USB 3.0, and one serial on rear, two USB 2.0 on front, via USB (occupy two specific USB 3.0 of M600 Tiny)		Some: Windows 10 Home 64-bit - WES 7 only: Preloaded applications (only some listed) ■ RDP Client (RDP 8.1 support)
Audio support	High Definition (HD) Audio, Realtek ALC223 / optional internal speaker (1 watt)		Desktop Power Manager Citrix Client
WLAN¹³ Bluetooth™ Ethornot	Some: 11ac wireless, M.2 Card, Realtek RTL8821AE (dual band), Wi-Fi + Bluetooth 4.0 combo adapter, 1x1 Some: 11ac wireless, M.2 Card, Qualcomm Atheros QCA9377 (dual band), Wi-Fi + Bluetooth 4.1 combo adapter, 1x1 Some: 11ac wireless, M.2 Card, Qualcomm Atheros QCA6174 (dual band), Wi-Fi + Bluetooth 4.1 combo adapter, 2x2 Some: 11ac wireless, M.2 Card, Intel Dual Band Wireless-AC 3165, Wi-Fi + Bluetooth 4.0 combo adapter, 1x1 Some: 11ac wireless, M.2 Card, Intel Dual Band Wireless-AC 8260, Wi-Fi + Bluetooth 4.1 combo adapter, 2x2 Some: Bluetooth 4.0 or 4.1 wireless, integrated in Wi-Fi + BT combo adapter		Lenovo REACHit Lenovo SHAREit Lenovo Bluetooth Lock McAfee® LiveSafe™ (30-day trial) Microsoft Office preloaded; purchase a product key to activate PowerDVD Create (DVD±RW) Lenovo ThinkVantage Tools Only for Window 10 Lenovo Companion (Win10) Cyberlink PowerDVD (DVD, DVD±RW) Internet Explorer 11 Java Flash Microsoft® Silverlight Echo Agent (client for LTM, Lenovo Thin Client Manager) Adobe Reader UltraVNC LeTOS only: xFreeRDP
Ethernet Modem	One gigabit ethernet port, Realtek RTL8111GN, Wake on LAN® None		 Lenovo QuickOptimizer Only for Window 7 Citrix ICA Client VMware View Client
Manageability Security chip Security features	None Trusted Platform Module, TCG 1.2-compliant • Security slot (in rear for optional Kensington® MicroSaver® cable) • Padlock loop • Padlock loop • Boot sequence control		 Rescue and Recovery Password Manager ThinkVantage System Update Lenovo Message Center Plus Adobe® Reader® Java Mozilla Firefox
	 Smart USB protection, allows keyboard/ Boot without keyboard and mouse mouse only, blocks all storage devices Individual USB port disablement 	Environment	ENERGY STAR® 6.0*, EPEAT™ Gold rating* (*for Windows models only); GREENGUARD®; RoHS-compliant; Cisco EnergyWise compatible; ErP Lot 3
	 Power-on password Chassis intrusion switch 	Accessories	For compatible accessories, please go to TC-AQP sheet

Model	10G90014US
Product	M600 Tiny
Region	US
Machine Type	10G9
TopSeller	TopSeller
Case 1L/2L	1L
Processor	Pentium N3700
Memory	4GBx1
Graphics	Intel HD
Storage	500GB 7200
External Optical / I/O box	None
WLAN	Intel 3165 ac
Optional Port	None
Monitor Cable	None
Chassis Intrusion Switch	Switch
Floor Stand	Stand
VESA Mount	None
Keyboard/Mouse	USB
Internal Speaker	Speaker
Power Supply	65W
Kensington Cable Lock	None
Preload	Win7 P64 DG Win10
Base Warranty (year)	1-onsite
Global	No
Ann Date (mm/yy)	05/16























