Technical Specifications

TL-C-HDCP

Features at a Glance

- HDMI input supports HDMI2.0& HDCP2.2
- HDMI output supports HDMI1.4& HDCP1.4
- EDID bypass
- Auto input resolution detection

The TL-C-HDCP is a 1x1 HDMI Convertor that features high-definition HDMI transmission and HDCP conversion. The HDMI input supports HDCP2.2and HDMI output supports HDCP1.4. It maximally transmits 4k*2k@60Hz signal up to 15m. Meanwhile, it converts HDCP2.2 signal to HDCP1.4 signal. The EDID bypass function ensures the source device will give the best resolution to fit the display.

Specifications

I/O Connections	
HDMI	1 HDMI type A connector
Power	1 micro USB connector
Supported Audio and Video	
Maximum Video Compatibility	4096*2160 @ 60Hz
Video Compliance	HDMI 1.4, HDCP 2.2
Input Video Signal	0.5-1.0 Vpp
Chassis and Environmental	
Enclosure	Painted aluminum
Dimensions	45.5*12*75 mm
Shipping Weight	49g
Operating Temperature (Environment)	0~50℃
Operating Humidity (Environment)	10%-90%
Power, ESD, and Regulatory	
Maximum Power Consumption	0.5W
Power Supply	DC 5V
Regulatory	CE, FCC
Other	
Standard Warranty	1Year
Diagnostic Indicators	Power
Included Items	Mounting ears, Screws, Plastic feet, Power Adapter, User manual

Dimensional Drawings

12.00 mm
(0.47 in)

12.00 mm
(0.47 in)

45.50 mm
(1.79 in)

DC 5V

OUT

TechLogix
N e t w o r x

75.00 mm
(2.95 in)

75.00 mm
(2.95 in)

TL-C-HDCP

☼

IN

45.50 mm
(1.79 in)

12.00 mm
(0.47 in)

12.00 mm
(0.47 in)