



## Specification

Update Date: 19/May/15 Version: 1

<b>Model Number:</b>	SE32HYT	<b>Features</b>
UPC Code	819456011931	Built in 3D PAL/NTSC Comb Filter
<b>Display Features</b>		
Diagonal Panel Size	31.5 inch	Built in 3D Video Noise Reduction
Active Area	697.685mm(H) x 392.256mm(V)	Built in BTSC/SAP
Aspect Ratio	16:9	Over-The-Air ATSC/NTSC RF Input Support
Panel Resolution	1366 x 768	Support V-CHIP/CCD/Favorite Channel Edition
Panel Refresh Rate	60Hz	Digital/Analog Channel auto tuning
Brightness	180~200 cd/m2	Component &HDMI support :480I,576I,480P,576P,720P,1080I,1080P
DynamicContrast ratio	800~1400:1	USB Support File Format: JPEG, MP3
Viewing Angle	178°(H) x 178°(V)(CR≥10)	Built in WiFi:stream your favorite music, movies and TV shows and access apps like Netflix,Vudu,Toongoggles,YouTube,Accuweather,Pandora
Dot Pitch	0.51075mm (H) x 0.51075mm (V)	OSD Language: English/French/Spanish
Maximum Color	16.7 M	<b>Accessories Included</b>
Response time Gray-Gray	14ms	Remote Control / Battery Included
<b>Electronics</b>		
Scaler Solution	MSD6308	User Manual / Quick Start Guide
DNR	3D	<b>Power Requirements</b>
Digital Comb Filter / Type	3D	Power Source AC100-240V 50/60Hz
<b>TV System &amp; Video Standards Supported</b>		
TV System	ATSC/NTSC M	Power ON consumption <60W
Channel CATV - UHF/VHF (ATV)	AIR: 2-69;Cable: 1~135	Standby consumption <0.5W
Composite / S-Video input	PAL/NTSC	Operating Temperature 5°C-35°C
<b>Video Connections</b>		
Analog&Digital TV Tuner	x1	Operating Humidity 20%-80%
Composite Video Input	x1(Y terminal will be the same )	<b>Dimension (WxHxD)</b>
S-Video Input (4pin DIN)	NO	VESA Dimension(WxH) 200mmx100mm
Component Input (Y,Cb,Cr/Y,Pb,Pr)	x1	Unit w/ Stand (Inch) 28.74" x 19.13" x 8.19"
VGA Input (15 pin D-Sub)	x1	Unit w/o Stand (Inch) 28.74" x 17.36" x 3.11"
RJ45	x1	Carton (Inch) 32.09" x 20.87" x 5.94"
HDMI Input	x3	<b>Weight ( lbs )</b>
USB	x1	Net Weight w/Stand 9.92Lbs
<b>Audio</b>		Net Weight w/o Stand 9.75 Lbs
Maximum Audio Output	2x8W	Gross Weight 14.33Lbs
Number of speakers	x2	<b>Warranty &amp; Support</b>
Audio Surround	Yes	One Year Manufacture Warranty
<b>Audio Connections</b>		
Stereo Mini Phono Jack Input (3.5mm)	x1(VGA Audio)	Toll Free Customer Support
RCA Input	x1(R/L)	On-Line Manual / Firmware Access
Headphone: Stereo Mini (3.5mm)	x1	<b>Logistic</b>
RCA Output	NO	Standard Pallet Unit Load
Optical Output	x1	20' GP Container Unit Load w/o Pallet 420
<b>VGA Resolutions Supported</b>		
640x480		40' GP Container Unit Load w/o Pallet 840
800x600		40' HQ Container Unit Load w/o Pallet 1050
1024x768		
1360x768		
This spec may change from time to time,we are not liable for any misrepresentation if we post the wrong specs on the sheet		

