USB-C Docking Station, 4K @ 30 Hz, HDMI, Thunderbolt 3, PD Charging, Micro SD – Silver

MODEL NUMBER: **U442-DOCK10-S**

Features

Highlights

- Transmits HDMI audio/video signals from sources supporting USB DisplayPort Alt Mode
- Delivers UHD picture quality at resolutions up to 3840 x 2160 (4K x 2K) @ 30 Hz
- 2 USB-A ports transfer data from thumb drives or printers at speeds up to 5 Gbps
- Powers and charges PD Charging-compliant devices, such as MacBooks and Chromebooks
- Easy installation with plug-and-play operation—no software required

Applications

- Play video from your laptop or PC on an HDMI display, such as an HDTV or projector
- Transfer data to and from a USB flash drive or Micro SD memory card
- Charge your notebook or laptop by connecting its wall charger to the USB-C PD Charging port
- Write a report using a USB keyboard with your tablet or Android smartphone

System Requirements

- Source device with USB-C or Thunderbolt 3 port that supports USB DisplayPort Alternate Mode
- Display device with DVI* or

HDMI input

- Not for use with Thunderbolt
  monitors

Package Includes

- U442-DOCK10-S USB-C
  Docking Station, 4K, HDMI,
  Thunderbolt 3, PD, MicroSD –
  30 Hz, Silver
- Owner's manual

Specifications

MODEL TEXT	
What Does This Product Do?	
OVERVIEW	
Over Current Protection	
INPUT	
Cable Length (ft.)	
Cable Length (m)	
Cable Length (in.)	
Built-In Cable Length (ft.)	
Built-In Cable Length (m)	
Built-In Cable Length (in.)	
Built-In Cable Length (cm)	
External Power Supply Input Specs (V / Hz / A)	
External Power Supply Output Specs (V / A)	
External Power Supply Cord Length (ft.)	
External Power Supply Cord Length (m.)	
Cable Length (cm)	
Product Length (in.)	

Product Length (cm.)	
Product Length (ft.)	
Product Length (m.)	

USER INTERFACE, ALERTS & CONTROLS

LED Indicators	

PHYSICAL

Unit Dimensions (hwd / in.)	
Unit Dimensions (hwd / cm)	
Unit Weight (lbs.)	
Material of Construction	
Color	Silver
Transmitter Unit Dimensions (hwd / in.)	
Transmitter Unit Dimensions (hwd / cm.)	
Receiver Unit Dimensions (hwd / in.)	
Receiver Unit Dimensions (hwd / cm.)	
Transmitter Unit Weight (lbs.)	
Transmitter Unit Weight (kg)	
Receiver Unit Weight (lbs.)	
Receiver Unit Weight (kg)	

ENVIRONMENTAL

Operating Temperature Range	
Storage Temperature Range	
Relative Humidity	
Operating Elevation (ft.)	
Storage Elevation (ft.)	
BTUs	
Power Consumption (Watts)	
Operating Humidity Range	
Storage Humidity Range	
Power Provided to Connected Device(s)	

COMMUNICATIONS

Signal Range (ft.)	
CONNECTIONS	
Ports	
PORT EXPANSION	
Max Distance (Between any 2 Units)	
FEATURES & SPECIFICATIONS	
Max Supported Video Resolution	
Audio Specification	
Recommended Category Cable	
CERTIFICATIONS	
Certifications	