



Mini DisplayPort to 2-Port DisplayPort Splitter Hub with MST

4K@30Hz, USB Power, Video Wall Function

Part No.: **207775**

Easily distribute a single Ultra-High-Definition (UHD) signal to multiple displays. The Manhattan Mini DisplayPort to 2-Port DisplayPort Splitter Hub with Multi-Stream Transport (MST) streams a 4K DisplayPort (DP) signal from a single UHD source to up to two UHD displays.

Flexible Solution for Many A/V Applications

Ideal for trade shows, classrooms, video conferencing, presentations and retail applications, the Manhattan Mini DisplayPort to 2-Port DisplayPort Splitter Hub with MST features a built-in booster for added signal strength. It's a great choice for splitting and distributing a synchronous signal, in either mirrored or extended modes, to multiple 4K DP displays. MST mode creates a video wall from two displays to give the user a more immersive experience when gaming, in a conference setting or in a home office.

Quality Construction and Easy Installation

Full compliance with DisplayPort, HDCP 2.2 and DVI 1.0 ensures that the Manhattan Mini DisplayPort to 2-Port DisplayPort Splitter Hub with MST can provide long service and reliable performance. Quickly connect DP cables (not included) and the included USB power cable, and this affordable, Ultra-High-Definition 4K DisplayPort solution is complete — no software/hardware configuration or complicated settings required.

Features:

- Duplicates an Ultra-High-Definition (UHD) Mini DisplayPort signal for up to two UHD DisplayPort displays
- 4K@30Hz resolution, full 3D video and Deep Color
- Supports compressed DTS Master Audio as well as 7.1 surround sound audio up to 192 kHz
- Supports Mirror, Extended and Multi-Stream Transport (MST) modes to maximize work or gaming capabilities
- Mirror mode duplicates the computer screen onto two displays with resolutions up to 4K@30Hz
- Extended mode expands the desktop workspace to up to two additional screens with resolutions up to 4K@30Hz

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- MST mode creates a video wall for a more immersive experience, using two screens — with resolutions up to 3840x2160 at 30 Hz — as one; requires a graphics card that supports video-wall function
- USB powered with Plug and Play installation; no special setup or remote required
- Integrated Mini DisplayPort cable
- Ideal for enhancing display capabilities or creating a video wall in locations such as schools, churches, conference rooms, trade shows and retail outlets; perfect for digital signage and AMD Eyefinity Technology in gaming
- HDCP 2.2 compliant
- Gold-plated contacts for corrosion-free connections
- Three-Year Warranty

Specifications:

Standards and Certifications

- DP 1.2
- HDCP 2.2
- DVI 1.0
- CTS 1.4a
- CE
- FCC
- RoHS2

Connections

- One Mini DisplayPort (Mini DP) male (input)
- Two DisplayPort (DP) female (output)
- One 5 V / 1 A USB Micro-B power female (input)

Signal Input/Output

- Input video signal: 0.5 – 1.0 V p-p
- Input DDC signal: 5 V p-p (TTL)
- Maximum single-link range: 5.4 Gbps, 3840x2160 at 30 Hz resolution
- Output video: HDCP 2.2, DVI 1.0

Video Resolutions

- DTV/HDTV: 480i/480p/576i/576p/720p/1080i/1080p/4K@30Hz

Physical

- Dimensions: 255 x 50 x 11 mm (9.8 x 2.0 x 0.4 in.)
- USB Micro-B power cable, 1 m (3 ft.)
- Weight: 50 g (1.8 oz.)
- Housing: plastic

Operating Environment

- Operation Temperature: 0 – 40°C (32 – 104°F)
- Storage Temperature: -20 – 60°C (-4 – 140°F)
- Humidity (noncondensing): 0 – 96%

System Requirements

- Windows XP/Vista/7/8.1/10
- DP 1.2 graphics card

Package Contents

- Mini DisplayPort to 2-Port DisplayPort Splitter Hub with MST
- USB power cable
- Quick Instruction Guide



