

RS-422/RS-485 USB to Serial FTDI Adapter with COM Retention (USB-B to DB9 F/M), 1 Port

MODEL NUMBER: U208-001-IND



USB to serial converter lets you connect a 9-pin serial device to your computer or laptop's USB-A port.

Features

Connects a Modem or Other 9-Pin Serial Device to Your Computer's USB-A Port

This USB to serial converter turns your computer's USB port into a DB9 port capable of connecting RS-422 and RS-485 serial devices, such as modems, handheld scanners and GPS systems. No external power source is needed. Just connect the included USB cable between the U208-001-IND and your computer, and insert the included CD into your computer's CD drive in order to launch the driver. You'll be able to configure and share data among point-of-sale equipment and other serial devices. LEDs indicate when serial data is being sent or received.

Independent DIP Switch for Easy Port Configuration

The U208-001-IND's sole serial port can be set to automatically detect an RS-422 or RS-485 device by adjusting its DIP switch setting. The port can also be set specifically for use in 4-wire mode.

COM Retention Feature for Convenient Reassigning of COM Values to Ports

This USB to RS-485 adapter with built-in FTDI chipset offers COM retention. It automatically reassigns the same COM port values to each port, so when the cable is disconnected or the system is rebooted, no additional configuration is needed. The cable auto-detects and auto-switches RS-422 and RS-485 devices. It also supports RS-485 auto-transceiver turn around with unique featured ATTA hardware.

Rugged All-Metal Housing Designed to Last in Harsh Industrial Applications

The wall-mountable USB to serial converter with an industrial-grade steel enclosure offers electrostatic discharge (ESD) protection to $\pm 15\text{kV}$. It supports serial communications speeds up to one Mbps and USB 2.0 specifications, though it is backward compatible with USB 1.1 devices.

2-Year Warranty

The U208-001-IND is backed by a 2-year warranty, ensuring reliability and performance.

Highlights

- Auto-detects and -switches RS-422 and RS-485 serial devices
- Independent DIP switch controls provide easy port configuration
- Automatically reassigns COM values to each port to avoid additional configuration
- USB-powered, so no bulky or obtrusive external power supply is required
- Compatible with Windows, Mac and Linux—works with most computers

Applications

- Connect and control 9-pin point-of-sale devices, including barcode scanners and credit card readers
- Activate surveillance cameras, access panels and other security equipment
- Operate serial-based medical and scientific instruments, such as bedside monitors and nursing call stations

System Requirements

- Windows XP or later
- Mac OS X 10.4 or later
- Linux 2.6.31 or later
- Computer with an available USB port

Package Includes

- U208-001-IND RS422/485 USB to Serial FTDI Adapter
- USB-A to USB-B cable (M/M), 3 ft.



- (2) 2-pin jumpers
- Driver CD
- Owner's manual

Specifications

OVERVIEW	
UPC Code	037332206008
Technology	Serial (RS422); Serial (RS485); USB (all versions)
INPUT	
Bus Powered	Yes
USER INTERFACE, ALERTS & CONTROLS	
LED Indicators	Green (Serial Data Received), Yellow (Serial Data Sent)
PHYSICAL	
Unit Packaging Type	Box
Unit Dimensions (hwd / in.)	0.9 x 2.8 x 3.0
Unit Dimensions (hwd / cm)	2.31 x 7.19 x 7.49
Unit Weight (lbs.)	0.30
Unit Weight (kg)	0.14
Material of Construction	Steel (SGCC)
Color	Black
ENVIRONMENTAL	
Operating Temperature Range	32 to 104 F (0 to 40 C)
Storage Temperature Range	14 to 131 F (-10 to 55 C)
Relative Humidity	5% to 90% RH, Non-Condensing
BTUs	15.4 BTU/Hr
Power Consumption (Watts)	4.5
CONNECTIONS	
Ports	1
Side A - Connector 1	USB B (FEMALE)
Side B - Connector 1	DB9 (MALE)



Connector Plating	Nickel
Contact Plating	Gold
FEATURES & SPECIFICATIONS	
USB Specification	USB 2.0 (up to 480 Mbps)
Driver Required	Yes
CERTIFICATIONS	
Certifications	Tested to CE, FCC, RoHS, REACH
WARRANTY	
Product Warranty Period (Worldwide)	2-year limited warranty

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>