## ThinkStation P340 Tower 30DH00JCUS

Product

ThinkStation P340 Tower

**Region** NA

Country/Region

Machine Type 30DH

TopSeller TopSeller

**Processor** Intel Core i7-10700 (8C / 16T, 2.9 / 4.8GHz, 16MB)

Integrated Graphics Intel UHD Graphics 630

Discrete Graphics None

Chipset Intel W480

HDD Controller Onboard Intel RST SATA RAID

*M.2 SSD RAID Controller* Onboard Intel RSTe PCIe

Memory 1x 32GB UDIMM DDR4-2933 non-ECC

Internal Disk Drive None

M.2 SSD Drive 1x 1TB SSD M.2 PCIe NVMe Opal

**Optane Memory** None

**Optical** 9.0mm DVD±RW

*Media Reader* SD Reader

**Onboard Ethernet** 1x GbE RJ-45

Additional Ethernet None WLAN + Bluetooth None

**Optional Rear Ports** 1x Video port, DP

Chassis Intrusion Switch None

Cover Lock None

Cable Lock None

Keyboard USB Traditional Keyboard, Black, English

Mouse USB Calliope Mouse

**Power Supply** 500W 92%

System Management Intel vPro with AMT 14

**Operating System** Windows 10 Pro 64, English

Bundled Software

Base Warranty 3-year, Onsite

Bundled Service 3Y Premier Support Upgrade from 3Y Onsite (5WS0U26646)

EAN / UPC / JAN 195348323673

End of Support 2028-07-30 Announce Date

2020-09-02

### Notes:

### California Electronic Waste Recycling Fee

In California, per state law, Lenovo charges an electronic waste recycling fee on this covered device at the time of sale of the product. For more information, go to: https://www.calrecycle.ca.gov/Electronics/Consumer

## L WWW.LENOVO.COM

Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area.

Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. Lenovo provides this publication "as is" without warranty of any kind, either express or implied, including the implied warranties of merchantability or fitness for a particular purpose.

### https://psref.lenovo.com





### ThinkStation P340 Tower Platform Specifications

Lenovo

Components	Specification						Components	Specification	
Form factor	17L Tower							Disk Type Interface RPM Offering Max Qty	
Dimensions	Height: 376 mm (14.8 in). Width: 170 mm (6.7 in). Depth: 315.35 mm (12.4 in)							3.5" SATA HDD SATA 6Gb/s 7.2K 1TB/2TB/4TB/6TB 2	
	Maximum configuration: 20.68 lb (9.38 kg)						Storage Support	2.5" SATA HDD SATA 6Gb/s 7.2K 1TB FIPS 4	
	5 1x FCLGA1200							2.5" SATA SSD SATA 6Gb/s - 512GB/1TB 4	
	rt Up to one Xeon, Core i9, i7, i5, or i3 processor							M.2 PCIe SSD PCIe NVMe - 256GB/512GB/1TB/2TB 4	
							1	Optane Memory  PCIe NVMe - 16GB 1	
Processor	Processor Number         Cores         Threads         Base Frequency         Cache         TDP         Memory Types         ECC         Processor Graphics         vPro							Bay 1 First 3.5" disk bay	
	Xeon W-1290P         10         20         3.7GHz         20MB         125W         DDR4-2933         Yes         UHD P630         Yes						_	Bay 2 First 2.5" SATA bay	
	Xeon W-1290         10         20         3.2GHz         20MB         80W         DDR4-2933         Yes         UHD P630         Yes           Xeon W-1270P         8         16         3.8GHz         16MB         125W         DDR4-2933         Yes         UHD P630         Yes           Xeon W-1270P         8         16         3.4GHz         16MB         80W         DDR4-2933         Yes         UHD P630         Yes           Xeon W-1270         8         16         3.4GHz         16MB         80W         DDR4-2933         Yes         UHD P630         Yes           Xeon W-1250P         6         12         4.1GHz         12MB         125W         DDR4-2666         Yes         UHD P630         Yes           Xeon W-1250         6         12         3.3GHz         12MB         80W         DDR4-2666         Yes         UHD P630         Yes					Yes		Bay 3 Secondary 3.5" disk bay	
								Bay 4 Secondary 2.5" disk bay	
								Bay 5 9mm Slim ODD bay	
								Bay 6 Media reader	
	Core i9-10900K 10	20 3.7GHz		V DDR4-2933 No		Yes		M.2 4x M.2 SSD (2 onboard. 2 via PCIe to M.2 adapter)	
	Core i9-10900 10	20 2.8GHz		DDR4-2933 No	UHD 630	Yes	Media reader	Optional SD reader on most models	
	Core i7-10700K         8         16         3.8GHz         16MB         125W         DDR4-2933         No         UHD 630         Yes           Core i7-10700         8         16         2.9GHz         16MB         65W         DDR4-2933         No         UHD 630         Yes					Yes Yes	Network	One onboard GbE port via integrated gigabit ethernet Intel i219LM, supports	
						interfaces	Wake-on-LAN. Optional PCIe ethernet adapters are available		
	Core i5-10600 6	12 3.3GHz		DDR4-2666 No	UHD 630	Yes	WLAN +	Optional Intel Wi-Fi 6 AX201, 2x2, 2.4GHz/5GHz (160MHz channels), WiFi 6,	
	Core i5-10500 6	12 3.1GHz	12MB 65W	DDR4-2666 No	UHD 630	Yes	Bluetooth	Bluetooth 5	
	Core i5-10400 6	12 2.9GHz		/ DDR4-2666 No		No		Power-on and admin password. Trusted Platform Module, TCG 2.0 compliant.	
	Core i3-10320 4	8 3.8GHz		DDR4-2666 No	UHD 630	No	Security reatures	Optional chassis intrusion switch, E-lock, cable lock, Kensington lock, and pad lock	
	Core i3-10300 4 Core i3-10100 4	8 3.7GHz 8 3.6GHz		/ DDR4-2666 No / DDR4-2666 No		No No	-	Supports Intel vPro on Xeon and selected Core i7 or i5 models.	
Chipset	Intel W480 Chipset	0 3.00HZ		DDR4-2000 NO		INU	Intel vPro	vPro also requires AX201 if Wi-Fi function is needed	
	4 DIMM sockets with 2 channels							Intel Active Management Technology 14 on vPro models,	
	4 DIMM Sockets with 2 channels 8GB/16GB/32GB DDR4-2933 UDIMM ECC.						Intel AMT	Intel Standard Manageability on other models	
	or 4GB/8GB/16GB/32GB DDR4-2933 UDIMM non-ECC						Base warranty	Most models comes with 3-year limited onsite service with 9x5/NBD.	
								Other models may have 1 or 2-year limited onsite service	
Memory Protection	lemory Protection ECC. ECC memory and ECC-enable CPU are needed						HD Audio	Intel HD Audio interface with Realtek ALC623 Codec	
	Three PCIe 3.0 slots as following:						Front ports	2x USB-A 3.2 Gen 1, 2x USB-A 3.2 Gen 2, 1x USB-C 3.2 Gen 1, 1x Mic-in, 1x Combo iack	
Expansion slots	Slot 1 PCIe 3.0 x16, full height, full length, links to CPU							2x USB-A 3.2 Gen 1, 2x USB-A 2.0, 1x RJ-45, 1x COM, 2x DP,	
	Slot 2 PCIe 3.0 x1, full height, full length, links to PCH						· ·	1x Audio line-out	
	Slot 3 PCIe 3.0 x16 (negotiable link width x4), full height, full length, links to PCH					СН		Supports the following via cable:	
Processor graphics	Integrated Intel UHD Graphics P630 in Xeon processors, or Intel UHD Graphics 630						Optional rear ports	1x COM, 1x Parallel, 2x PS/2, 1x video (DP, HDMI, or USB-C), 2x USB 2.0, Supports the following via PCIe adapter:	
	in Core processors.							4x COM*, 1x USB-C 3.2 Gen 2, 2x USB-A 3.2 Gen 1*, 1x Thunderbolt	
	Works along with discrete graphics to support multi-display, enables three rear							Notes: 4x COM and 2x USB-A 3.2 Gen 1 are special bids only.	
	display connectors (2 DP standard, 1 video port optional (Video port can be DP,							Operating: 50 ° F to 95 ° F (10 ° C to 35 ° C)	
	HDMI, or USB-C )						Temperature	Non operating (no package): 14 ° F to 140 ° F (-10 ° C to 60 ° C)	
Discrete Graphics Offering	Graphics	Memory	Power	Connector		Max		Non operating (with package): -40 °F to 140 °F (-40 °C to 60 °C)	
	Quadro P400	2GB GDDR5	30W	3x miniDP		Qty 2	Altitude	Operating: -15.2 m (-50 ft) to 3048 m (10 000 ft).	
	Quadro P620	2GB GDDR5	40W	4x miniDP		2		Storage: -15.2 m (-50 ft) to 10, 668 m (35 000 ft)	
	Quadro P1000	4GB GDDR5	50W	4x miniDP		2	Humidity	Operating: 30%~90%, non-condensing Storage (with package): 20%~90%, non-condensing	
	Quadro P2200	o P2200         5GB GDDR5X         75W         4x DP         2           o RTX 4000         8GB GDDR6         160W         3x DP, 1x VirtualLink         1					Environmental certification	RoHS-compliant, EPEAT Silver rating, and ENERGY STAR 8 qualified	
	Quadro RTX 4000					1			
	Quadro RTX 5000 16GB GDDR6 265W 4x DP, 1x VirtualLink 1					1		Supports one of the following:	
	Notes: RTX 4000/RTX 5000/2x P2200 needs 500W PSU.						Power supply	<ul> <li>300W, 90% PSU, 100V - 240V, 80 PLUS Gold qualified</li> </ul>	
	Storage Controller Type Interface Disk Type RAID							<ul> <li>500W, 92% PSU, 100V - 240V, 80 PLUS Platinum qualified</li> </ul>	
Storage	Onboard Intel RST SATA RAID Std SATA 6Gb/s HDD or SSD 0/1/10/5						ISV certifications	Please visit www.thinkworkstations.com/isv-certifications/	
Controller	Onboard Intel RST PCIe RAID   Std   PCIe NVMe   M.2 PCIe SSD   0/1						Note: 1 Depending on many factors, actual data transfer speed mentioned on this page may be lower than theoretical speed		
	Notes: RAID 5 and 10 are available on 2.5" HDD/SSD.						<ol> <li>Depending on many factors, actual data transfer speed mentioned on this page may be lower than theoretical speed.</li> <li>Any questions or advice on ThinkStation PSREF, please contact Lenovo workstation PSREF developer</li> </ol>		

# ThinkStation P340 Tower











