AC Power Supply for Tripp Lite N785-CH12 Media Converter Chassis, 75W

MODEL NUMBER: **N785-CH75W-AC**

Highlights

- Supplies AC power to a media converter installation using Tripp Lite's N785-CH12
- Multiple power supplies provide primary and redundant power to prevent downtime

System Requirements

Tripp Lite N785-CH12 Media Converter Chassis

Package Includes

N785-CH75W-AC 75W AC Power Supply

75W AC power supply provides primary or redundant power to your media converter installation.

Features

Powers Your Tripp Lite N785-CH12 12-Port Media Converter Chassis

This 75-watt AC power supply works with the Tripp Lite N785-CH12 media converter chassis to provide redundant power that helps prevent unwanted and expensive downtime. One N785-CH75W-AC comes pre-installed with the N785-CH12 to provide primary power. An additional power supply is also recommended as a replacement part.

Specifications

OVERVIEW	
UPC Code	037332267061
Accessory Type	Power Supply
Accessory Class	Networking Accessories

DISPLAY	
Accessories (Included)	Fuse Glass Tube (x2)

POWER	
External Power Supply Input Specs (V / Hz / A)	90-240V / 50/60 Hz / 2A
External Power Supply Output Specs (V / A)	12V/6.5A
External Power Supply Cord Length (ft.)	6

External Power Supply Cord Length (m.)	1.83
External Power Supply Plug(s)	NEMA 5-15P North America

PHYSICAL	
Power Cord Color	Black
Unit Dimensions (hwd / in.)	5.24 x 2.32 x 9.06
Unit Dimensions (hwd / cm)	13.3 x 5.9 x 23.0
Unit Packaging Type	Box

ENVIRONMENTAL	
Operating Temperature Range	32 to 122F (0 to 50C)
Storage Temperature Range	-4 to 185F (-20 to 85C)
Operating Humidity Range	20% to 90%
Storage Humidity Range	20% to 90%

FEATURES & SPECIFICATIONS	
Auto MDIX Support	No

STANDARDS & COMPLIANCE	
Certifications	CE, FCC, RoHS, REACH
External Power Supply Certifications	CE; FCC; RoHS

WARRANTY	
Product Warranty Period (Worldwide)	3-year limited warranty