

Clamp-On Storage Drawer

Part Number: K52175WW | UPC Code: 085896521754

Keep supplies out of the way, yet easily with reach. Declutter your desk and keep office supplies out of the way, yet easily within reach, with the Clamp-On Storage Drawer. Solid, stable, non-permanent C-clamp design installs in minutes with no tools or modifications to the desk or table — just clamp and go. Smooth-moving rail with two level adjustments provides ample tray clearance to accommodate everything from slim and mechanical gaming keyboards; to standard and vertical mice; to trackballs; to pens, markers, pads, and notebooks. Fits desks and tables up to 1.97" (5 cm) and has a 26.5 pound (12 kg) weight capacity. TAA-compliant.

Features include:

- Easy installation, no tools required
- Non-permanent, won't damage desk or table
- · Smooth-moving rail with ample clearance
- Fits desks and tables up to 1.97" (5 cm) thick
- · Two levels of height adjustment
- 26.5 pound (12 kg) weight capacity
- TAA-compliant

Kensington

Clamp-On Storage Drawer

Part Number: K52175WW | UPC Code: 085896521754



Sturdy, Easy-to-Install Clamps

Solid, stable, non-permanent C-clamp design installs in minutes with no tools, modifications, or damage to the desk or table — just clamp and go. Fits desks and tables up to 1.97" (5 cm) and has a 26.5 pound (12 kg) weight capacity.



Helps Keep Desktop Neat and Organized

Conveniently stores keyboards, mice, trackballs, pens, markers, pads, notebooks, and more, keeping them out of the way, but easily within reach.



Smooth-Moving Rail and Adjustable Height

Easily accessible drawer offers two levels of height adjustment to provide ample clearance for storage items.



TAA-Compliant

Ready for use in U.S. Federal Government institutions and organizations.

Clamp-On Storage Drawer

Part Number: K52175WW | UPC Code: 085896521754

Matarial	Specifications
ivialtilai	DUCCIIICALIUIIS

Extension under the desk Slides under a total of 12.20 inches from the desk edge Product Dimensions Unit Dimension (Including c-clamps) 620 x 310 x 105 ~ 120mm (24.4 x 12.2 x 4.1 in ~ 4.7 in) Unit Dimension (Drawer only) 510 x 300 x 50mm (20.1 x 11.8 x 2.0 in) Drawer Dimension (Inner) 480 x 250 x 38mm (18.9 x 9.8 x 1.5 in) Enclosure Color & Material C-clamp Brackets: Black / Iron, Knob: Black / HIPS, Drawer: Black / HIPS Packaging Dimensions Packaging Style B2B Brown Box; Non-FSC Packaging Dimensions 645 x 340 x 105mm (25.4 x 13.4 x 4.1 in) Packaging Weight 447.5g (15.8oz) Master Carton 4 pcs Packaging Content Drawer Body, C-Clamp (Left), C-Clamp (Right), Component Bag (Contains 5x M4*101 screws),	Material Specifications		
Weight Capacity 12kg (26.5 lbs) SmartFit Enabled HIPS (Drawer Body), POM (Rails & Slides) Maximum Desttop Thickness supported 10 - 50mm (0.4 - 1.97") Maximum Extension slides out a total of 8.27 inches from the desk edge Extension under the desk Slides under a total of 12.20 inches from the desk edge Unit Dimensions Product Dimensions Unit Dimension (Including c-clamps) 620 x 310 x 105 ~ 120mm (24.4 x 12.2 x 4.1in ~ 4.7in) Unit Dimension (Drawer only) 510 x 300 x 50mm (20.1 x 11.8 x 2.0in) Drawer Dimension (Inner) 480 x 250 x 38mm (18.9 x 9.8 x 1.5in) Enclosure Color & Material C-clamp Brackets: Black / Iron, Knob: Black / HIPS, Drawer: Black / HIPS Packaging Dimensions Packaging Style 82B Brown Box; Non-FSC 645 x 340 x 105mm (25.4 x 13.4 x 4.1in) Packaging Weight 447.5g (15.802) Master Carton 4 pcs Packaging Content Drawer Body, C-Clamp (Left), C-Clamp (Right), Component Bag (Contains 5x M4*101 screws), Kensington IG, Kensington 2 Year Warranty Bookle Power and environmental Operating Temperature -18 to 60°C (-0.4 to 140°F) Storage Temperature -18 to 60°C (-0.4 to 140°F) Relative Humidity 0% to 85% RH Country of Origin, Regulatory, and Warranty Certifications & Compliance RoHS, REACH and CA Prop. 65		C-clamp Brackets	Coated Iron (Clamp), HIPS (Knob)
SmartFit Enabled HIPS (Drawer Body), POM (Rails & Slides)		The Drawer	HIPS (Drawer Body), POM (Rails & Slides)
Maximum Desttop Thickness supported 10 - 50mm (0.4 - 1.97") Maximum Extension slides out a total of 8.27 inches from the desk edge Product Dimensions Unit Dimension (Including c-clamps) 620 x 310 x 105 ~ 120mm (2.44 x 12.2 x 4.1in ~ 4.7in) Unit Dimension (Drawer only) 510 x 300 x 50mm (20.1 x 11.8 x 2.0in) Drawer Dimension (Inner) 480 x 250 x 38mm (18.9 x 9.8 x 1.5in) Enclosure Color & Material C-clamp Brackets: Black / Iron, Knob: Black / HIPS, Drawer: Black / HIPS Packaging Dimensions Packaging Style B2B Brown Box; Non-FSC Packaging Weight 447.5g (15.802) Master Carton 4 pcs Packaging Content Drawer Bag (Contains Sx M4*101 screws), Kensington IG, Kensington 2 Year Warranty Bookle Power and environmental Operating Temperature -18 to 60°C (-0.4 to 140°F) Storage Temperature -18 to 60°C (-0.4 to 140°F) Relative Humidity 0% to 85% RH Country of Origin, Regulatory, and Warranty Country of Origin, Regulatory, and Warranty Certifications & Compliance RoHS, REACH and CA Prop. 65		Weight Capacity	12Kg (26.5 lbs)
Maximum Extension slides out a total of 8.27 inches from the desk edge Product Dimensions		SmartFit Enabled	HIPS (Drawer Body), POM (Rails & Slides)
Product Dimensions Unit Dimension (Including c-clamps) 620 x 310 x 105 ~ 120mm (24.4 x 12.2 x 4.1in ~ 4.7in)		Maximum Desttop Thickness supported	10 - 50mm (0.4 - 1.97")
Product Dimensions Unit Dimension (Including c-clamps) 620 x 310 x 105 ~ 120mm (24.4 x 12.2 x 4.1in ~ 4.7in)		Maximum Extension	slides out a total of 8.27 inches from the desk edge
Unit Dimension (Including c-clamps) Country of Origin, Regulatory Country of Origin Country of Country of Origin Country of Origin Country of Origin Country of Country of Origin C		Extension under the desk	
(24.4 x 12.2 x 4.1 in ~ 4.7 in) Unit Dimension (Drawer only) 510 x 300 x 50mm (20.1 x 11.8 x 2.0 in) Drawer Dimension (Inner) 480 x 250 x 38mm (18.9 x 9.8 x 1.5 in) Enclosure Color & Material C-clamp Brackets: Black / Iron, Knob: Black / HIPS, Drawer: Black / HIPS Packaging Dimensions B2B Brown Box; Non-FSC Packaging Dimensions 645 x 340 x 105mm (25.4 x 13.4 x 4.1 in) Packaging Weight 447.5g (15.8oz) Master Carton 4 pcs Packaging Content Drawer Body, C-Clamp (Left), C-Clamp (Right), Component Bag (Contains 5x M4*101 screws), Kensington IG, Kensington 2 Year Warranty Bookle Power and environmental Operating Temperature -18 to 60°C (-0.4 to 140°F) Storage Temperature -18 to 60°C (-0.4 to 140°F) Relative Humidity 0% to 85% RH Country of Origin, Regulatory, and Warranty Country of Origin Taiwan Certifications & Compliance RoHS, REACH and CA Prop. 65	Product Dimensions		
Drawer Dimension (Inner) Enclosure Color & Material C-clamp Brackets: Black / Iron, Knob: Black / HIPS, Drawer: Black / HIPS Packaging Dimensions Packaging Style Packaging Dimensions Packaging Dimensions Packaging Dimensions B2B Brown Box; Non-FSC Packaging Dimensions 645 x 340 x 105mm (25.4 x 13.4 x 4.1in) Packaging Weight 447.5g (15.8oz) Master Carton Packaging Content Drawer Body, C-Clamp (Left), C-Clamp (Right), Component Bag (Contains 5x MA*10L screws), Kensington IG, Kensington 2 Year Warranty Bookle Power and environmental Operating Temperature -18 to 60°C (-0.4 to 140°F) Storage Temperature -18 to 60°C (-0.4 to 140°F) Relative Humidity 0% to 85% RH Country of Origin, Regulatory, and Warranty Country of Origin Taiwan Certifications & Compliance RoHS, REACH and CA Prop. 65		Unit Dimension (Including c-clamps)	
Packaging Dimensions Packaging Style B2B Brown Box; Non-FSC Packaging Dimensions 645 x 340 x 105mm (25.4 x 13.4 x 4.1in) Packaging Weight 447.5g (15.8oz) Master Carton 4 pcs Packaging Content Drawer Body, C-Clamp (Left), C-Clamp (Right), Component Bag (Contains 5x M4*10L screws), Kensington IG, Kensington 2 Year Warranty Bookle Power and environmental Operating Temperature -18 to 60°C (-0.4 to 140°F) Storage Temperature -18 to 60°C (-0.4 to 140°F) Relative Humidity 0% to 85% RH Country of Origin, Regulatory, and Warranty Country of Origin Taiwan Certifications & Compliance RoHS, REACH and CA Prop. 65		Unit Dimension (Drawer only)	510 x 300 x 50mm (20.1 x 11.8 x 2.0in)
Packaging Dimensions Packaging Style Packaging Dimensions Packaging Dimensions Packaging Dimensions Packaging Weight Packaging Weight Packaging Content Packaging Uisana Sanda X 4.1in) Packaging (15.8oz) Pa		Drawer Dimension (Inner)	480 x 250 x 38mm (18.9 x 9.8 x 1.5in)
Packaging Style Packaging Dimensions 645 x 340 x 105mm (25.4 x 13.4 x 4.1in) Packaging Weight 447.5g (15.8oz) Master Carton 4 pcs Packaging Content Drawer Body, C-Clamp (Left), C-Clamp (Right), Component Bag (Contains 5x M4*10L screws), Kensington IG, Kensington 2 Year Warranty Bookle Power and environmental Operating Temperature -18 to 60°C (-0.4 to 140°F) Storage Temperature -18 to 60°C (-0.4 to 140°F) Relative Humidity 0% to 85% RH Country of Origin, Regulatory, and Warranty Country of Origin Taiwan Certifications & Compliance RoHS, REACH and CA Prop. 65		Enclosure Color & Material	
Packaging Dimensions 645 x 340 x 105mm (25.4 x 13.4 x 4.1in) Packaging Weight 447.5g (15.8oz) Master Carton 4 pcs Packaging Content Drawer Body, C-Clamp (Left), C-Clamp (Right), Component Bag (Contains 5x M4*10L screws), Kensington IG, Kensington 2 Year Warranty Bookle Power and environmental Operating Temperature -18 to 60°C (-0.4 to 140°F) Storage Temperature -18 to 60°C (-0.4 to 140°F) Relative Humidity 0% to 85% RH Country of Origin, Regulatory, and Warranty Country of Origin Taiwan Certifications & Compliance RoHS, REACH and CA Prop. 65	Packaging Dimensions		
Packaging Weight Master Carton Packaging Content Packaging Content Drawer Body, C-Clamp (Left), C-Clamp (Right), Component Bag (Contains 5x M4*10L screws), Kensington IG, Kensington 2 Year Warranty Bookle Power and environmental Operating Temperature Operating Temperature -18 to 60°C (-0.4 to 140°F) Storage Temperature -18 to 60°C (-0.4 to 140°F) Relative Humidity O% to 85% RH Country of Origin, Regulatory, and Warranty Country of Origin Taiwan Certifications & Compliance RoHS, REACH and CA Prop. 65		Packaging Style	B2B Brown Box; Non-FSC
Master Carton Packaging Content Drawer Body, C-Clamp (Left), C-Clamp (Right), Component Bag (Contains 5x M4*10L screws), Kensington IG, Kensington 2 Year Warranty Bookle Power and environmental Operating Temperature -18 to 60°C (-0.4 to 140°F) Storage Temperature -18 to 60°C (-0.4 to 140°F) Relative Humidity O% to 85% RH Country of Origin, Regulatory, and Warranty Country of Origin Taiwan Certifications & Compliance RoHS, REACH and CA Prop. 65		Packaging Dimensions	645 x 340 x 105mm (25.4 x 13.4 x 4.1in)
Packaging Content Drawer Body, C-Clamp (Left), C-Clamp (Right), Component Bag (Contains 5x M4*10L screws), Kensington IG, Kensington 2 Year Warranty Bookle Power and environmental Operating Temperature -18 to 60°C (-0.4 to 140°F) Storage Temperature -18 to 60°C (-0.4 to 140°F) Relative Humidity O% to 85% RH Country of Origin, Regulatory, and Warranty Country of Origin Taiwan Certifications & Compliance RoHS, REACH and CA Prop. 65		Packaging Weight	447.5g (15.8oz)
Component Bag (Contains 5x M4*10L screws), Kensington IG, Kensington 2 Year Warranty Bookle Power and environmental Operating Temperature -18 to 60°C (-0.4 to 140°F) Storage Temperature -18 to 60°C (-0.4 to 140°F) Relative Humidity 0% to 85% RH Country of Origin, Regulatory, and Warranty Country of Origin Taiwan Certifications & Compliance RoHS, REACH and CA Prop. 65		Master Carton	4 pcs
Operating Temperature -18 to 60°C (-0.4 to 140°F) Storage Temperature -18 to 60°C (-0.4 to 140°F) Relative Humidity 0% to 85% RH Country of Origin, Regulatory, and Warranty Country of Origin Taiwan Certifications & Compliance RoHS, REACH and CA Prop. 65		Packaging Content	
Storage Temperature Relative Humidity O% to 85% RH Country of Origin, Regulatory, and Warranty Country of Origin Taiwan Certifications & Compliance RoHS, REACH and CA Prop. 65	Power and environmenta	al	
Relative Humidity 0% to 85% RH Country of Origin, Regulatory, and Warranty Country of Origin Taiwan Certifications & Compliance RoHS, REACH and CA Prop. 65		Operating Temperature	-18 to 60°C (-0.4 to 140°F)
Country of Origin, Regulatory, and Warranty Country of Origin Taiwan Certifications & Compliance RoHS, REACH and CA Prop. 65		Storage Temperature	-18 to 60°C (-0.4 to 140°F)
Country of Origin Taiwan Certifications & Compliance RoHS, REACH and CA Prop. 65		Relative Humidity	0% to 85% RH
Certifications & Compliance RoHS, REACH and CA Prop. 65	Country of Origin, Regula	atory, and Warranty	
		Country of Origin	Taiwan
Warranty 2-Years Warranty		Certifications & Compliance	RoHS, REACH and CA Prop. 65
		Warranty	2-Years Warranty



