

USB-C Docking Station, Multi Monitor HDMI/DP/USB-C Video Output, USB-C Dock, Triple Monitor 4K30/Dual 4K60 - 7-Port USB Hub, 60W Power Delivery, GbE, 3.5mm Audio - Works With Chromebook certified

Product ID: DK31C3MNCR



Connect a USB Type-C/Thunderbolt 4 enabled Chromebook and a combination of DisplayPort and HDMI monitors to this USB-C Docking Station. This dock supports Chromebooks and Ultra HD 4K monitors. The 3.3ft (1m) USB-C Screw Lock to USB-C Cable ensures a secure connection to the dock and host device.

This USB-C Docking Station is tested and certified to meet Google's compatibility standards. The certification ensures seamless operation with Chromebook devices. This is the ideal dock to deploy in business and education environments. Automatic firmware updates are available through ChromeOS for maximum security, compatibility, and performance.

Connect a combination of one USB-C DP Alt Mode, one HDMI, and/or up to two DisplayPort monitors to the Video 1 and Video 2 Ports and connect one HDMI monitor to the Video 3 Port for a triple-monitor setup at 4K 30Hz, and features up to 4K 60Hz. High-resolution video performance is vital for applications involving detailed graphics, enhancing workplace productivity by expanding the display capabilities of Chromebook devices.

Connect the docking station to a Chromebook's USB Type-C/Thunderbolt 4 port to enable a variety of connectivity options and features.

- 3x USB-A ports with support for USB 10Gbps one 1.5A charging port
- 2x USB-A ports with support for High-Speed 2.0 (480 Mbps) ports for USB-peripheral devices
- 2x USB-C ports with support for USB 10Gbps and Type-C data and 1.5A charging port, Video 1 Port (DP Alt Mode)
- 1x Gigabit Ethernet port
- 1x 3.5mm Audio Jack 4-pole TRRS for a 3.5mm headset
- 2x Kensington Security Lock Slots



The USB-C Docking Station supports 60W USB Power Delivery, using the universal power adapter.

This product is backed for 3-years by StarTech.com, including free lifetime 24/5 multi-lingual technical assistance.

## Certifications, Reports and Compatibility



## Applications

• Works With Chromebook (WWCB) certified and features guaranteed compatibility with ChromeOS devices like USB-C or Thunderbolt 4 Chromebooks

• Seamless operation with Chromebooks and automatic firmware updates through ChromeOS makes it ideal for IT setup and deployments

• Connect up to three external 4K 30Hz monitors for a triple-monitor setup

## Features

• WORKS WITH CHROMEBOOK CERTIFIED: WWCB certified, for guaranteed compatibility with USB-C, Thunderbolt 4 Chromebooks; Features auto-updates to firmware through ChromeOS for max performance, compatibility, and security

• FLEXIBLE MULTI-MONITOR OUTPUTS: MST based video supports extended dual-4K 60Hz monitors with HDMI 2.0b, DisplayPort 1.4, and USB-C video outputs, triple 4K 30Hz, or single 5K 60Hz (DP 1.4 HBR3); Ideal for use with USB-C monitors (portable or desktop)

• FULL-FEATURED: 7-Port USB Hub (2x USB-A 10Gbps, 1x USB-A 10Gbps w/BC 1.2 charging, 1x USB-C 10Gbps, 2x USB-A 480Mbps, 1x USB-C shared 10Gbps & DP Alt Mode video), 60W Power Delivery, Gigabit Ethernet, 3.5mm headset/audio port

• SECURE & EASY SETUP: Ideal for all Chromebooks incl. ChromeOS Enterprise Devices; 3.3ft locking USB-C cable; Front facing host port (screw-locking) & Power/Mode button; Automatic driver install; K-Slot/Nano-Slot for anti-theft security anchor; Mount Holes

• OPTIMIZED FOR VIDEO PERFORMANCE: Port Replicator enables switching between two and four lane modes; Default four lane mode features 4K video with USB 2.0 480Mbps, while two lane mode features USB 3.2 Gen2 10Gbps throughput with 1080p video

Hardware



Warranty	3 Years
4K Support	Yes
Fast-Charge Port(s)	No
Displays Supported	3
Ports	8
Interface	USB 3.2 Gen 2 - 10 Gbit/s
Bus Type	USB-C
Compatible Lock Slot	Kensington Standard Slot (K-Slot)
	Kensington Nano Slot
Industry Standards	DisplayPort 1.4
	HDMI 2.0b
	USB 3.2 Gen 2 (10 Gbps)
	USB-C Power Delivery 3.0 Specification
Chipset ID	Synaptics - VMM5320
	Realtek -RTS5420
	Parade - PS8469
	Parade - PS8468
	Parade - PS8805
	Parade - PS8803
	VIA/VLI - VL822
	Realtek - ALC5686
	VIA/VLI - VL211
	Realtek - RTL8153B

## Performance

Maximum Data Transfer Rate	10 Gbps
Maximum Digital Resolutions	DisplayPort: Up to 4K (4096 x 2160) 60Hz
	HDMI: Up to 4K (4096 x 2160) 60Hz

STARTECH.COM



		USB-C DP Alt Mode: Up to 4K (4096 x 2160) 60Hz
		Supports Single 5K 60Hz, Dual 4K 60Hz, or Triple 4K 30Hz displays
	Type and Rate	USB 3.2 Gen 2 - 10 Gbit/s
		USB 2.0 - 480 Mbit/s
	Compatible Networks	10/100/1000 Mbps
	PXE	Yes
	General Specifications	Video 1 USB-C port can perform charging and data transfer while paired DP output is displaying video
		4 Video Lanes (4K): 480 Mbps
		2 Video Lanes (1080p): 10 Gbps
Connector(s)		
	External Ports	3 - USB 3.2 Type-A (9 pin, Gen 2, 10Gbps)
		2 - USB 2.0 Type-A (4 pin, 480Mbps)
		1 - USB 3.2 Type-C (24 pin, Gen 2, 10Gbps)
		1 - USB 3.2 Type-C (24 pin, Gen 2, 10Gbps, 7.5W Power, DP Alt-Mode Video)
		2 - DisplayPort
		2 - HDMI
		1 - RJ-45
		1 - 3.5 mm Stereo Audio
	Host Connectors	1 - USB 3.2 Gen 2 USB Type-C (Power Delivery + Data, 24 Pin, 10 Gbps)
Software		
	OS Compatibility	ChromeOS
Special Notes / Requirements		
	System and Cable Requirements	Compatible with Chromebooks running ChromeOS and equipped with USB-C, TB3/TB4 (to ensure full adapter functionality, the host device's USB-C port must support USB Power Delivery and DP alt mode).



Type-C standard. Ensure your host device's USB-C port supports USB Power Delivery and DP alt mode. A 4K-capable display is required to achieve 4096 x 2160p/ 2160p resolution. A 4K-capable computer is required to achieve 3840 x 2160			
Type-C standard. Ensure your host device's USB-C port supports USB Power Delivery and DP alt mode. A 4K-capable display is required to achieve 4096 x 2160p 2160p resolution. A 4K-capable display is required to achieve 3840 x 2160 resolution (4K is also known as 4K x 2K) on the DP Alt-Mo USB-C port. USB 3.2 Gen 2 (10 Gbps) is also known as USB 3.1, and SuperSpeed USB 10Gbps. Indicators LED Indicators 1 - Power - Solid Green: ON in 4-Lane Mode (480 Mbps) 1 - Power - Solid Orange: ON in 2-Lane Mode (10 Gbps) 1 - Network Port - Yellow On: Link Detected 1 - Network Port - Yellow On: Link Detected 1 - Network Port - Yellow Flashing: Activity 1 - Network Port - Yellow On: 100Mbps Power Power Source AC Adapter Included Power Delivery 60W Input Voltage 100 - 240 AC Input Voltage 100 - 240 AC Input Current 2.37A Output Voltage 20V DC Output Voltage 20V DC Output Current 6.75A Plug Type CP (OD:7.4/ID:5.1/CPD:0.6) Power Consumption (In 135W		Note	Compatible with Chromebooks only.
2160p resolution.         A 4K-capable computer is required to achieve 3840 x 2160         resolution (4K is also known as 4K x 2K) on the DP Alt-Mo         USB 3.2 Gen 2 (10 Gbps) is also known as USB 3.1, and         SuperSpeed USB 10Gbps.         Indicators         LED Indicators         1 - Power - Solid Green: ON in 4-Lane Mode (480 Mbps)         1 - Power - Solid Orange: ON in 2-Lane Mode (10 Gbps)         1 - Network Port - Yellow On: Link Detected         1 - Network Port - Yellow Con: 100Mbps         Power         Power Source         AC Adapter Included         Power Delivery       60W         Input Current       2.37A         Output Voltage       20V DC         Output Voltage       20V DC         Output Voltage       CP (OD:7.4/ID:5.1/CPD:0.6)         Power Consumption (In       135W			
resolution (4K is also known as 4K x 2K) on the DP Alt-Mo USB-C port. USB 3.2 Gen 2 (10 Gbps) is also known as USB 3.1, and SuperSpeed USB 10Gbps. Indicators LED Indicators 1 - Power - Solid Green: ON in 4-Lane Mode (480 Mbps) 1 - Power - Solid Orange: ON in 2-Lane Mode (10 Gbps) 1 - Network Port - Yellow On: Link Detected 1 - Network Port - Yellow On: Link Detected 1 - Network Port - Yellow On: 1Gbps 1 - Network Port - Green On: 1Gbps 1 - Network Port - Yellow On: 100Mbps Power Power Source AC Adapter Included Power Delivery 60W Input Voltage 100 - 240 AC Input Current 2.37A Output Voltage 20V DC Output Voltage 20V DC Output Voltage CP (OD:7.4/ID:5.1/CPD:0.6) Power Consumption (In 135W			A 4K-capable display is required to achieve 4096 x 2160p/3840 x 2160p resolution.
Indicators LED Indicators LED Indicators LED Indicators 1 - Power - Solid Green: ON in 4-Lane Mode (480 Mbps) 1 - Power - Solid Orange: ON in 2-Lane Mode (10 Gbps) 1 - Network Port - Yellow On: Link Detected 1 - Network Port - Yellow Con: Link Detected 1 - Network Port - Yellow Flashing: Activity 1 - Network Port - Green On: 1Gbps 1 - Network Port - Yellow On: 100Mbps Power Power Source Power Source AC Adapter Included Power Delivery 60W Input Voltage 100 - 240 AC Input Current 2.37A Output Voltage 20V DC Output Voltage CP (OD:7.4/ID:5.1/CPD:0.6) Power Consumption (In 135W			A 4K-capable computer is required to achieve 3840 x 2160p resolution (4K is also known as 4K x 2K) on the DP Alt-Mode USB-C port.
LED Indicators 1 - Power - Solid Green: ON in 4-Lane Mode (480 Mbps) 1 - Power - Solid Orange: ON in 2-Lane Mode (10 Gbps) 1 - Network Port - Yellow On: Link Detected 1 - Network Port - Yellow Flashing: Activity 1 - Network Port - Yellow On: 100Mbps Power Power Source AC Adapter Included Power Delivery 60W Input Voltage 100 - 240 AC Input Current 2.37A Output Voltage 20V DC Output Voltage 20V DC Output Current 6.75A Plug Type CP (OD:7.4/ID:5.1/CPD:0.6) Power Consumption (In 135W			
1 - Power - Solid Orange: ON in 2-Lane Mode (10 Gbps)         1 - Network Port - Yellow On: Link Detected         1 - Network Port - Yellow Flashing: Activity         1 - Network Port - Yellow Flashing: Activity         1 - Network Port - Green On: 1Gbps         1 - Network Port - Yellow On: 100Mbps         Power         Power Source         AC Adapter Included         Power Delivery         60W         Input Voltage         100 - 240 AC         Input Current         2.37A         Output Voltage         20V DC         Output Current         6.75A         Plug Type       CP (OD:7.4/ID:5.1/CPD:0.6)         Power Consumption (In       135W	dicators		
1 - Network Port - Yellow On: Link Detected         1 - Network Port - Yellow Flashing: Activity         1 - Network Port - Green On: 1Gbps         1 - Network Port - Yellow On: 100Mbps         Power         Power Source         AC Adapter Included         Power Delivery       60W         Input Voltage       100 - 240 AC         Input Current       2.37A         Output Voltage       20V DC         Output Current       6.75A         Plug Type       CP (OD:7.4/ID:5.1/CPD:0.6)         Power Consumption (In       135W		LED Indicators	1 - Power - Solid Green: ON in 4-Lane Mode (480 Mbps)
1 - Network Port - Yellow Flashing: Activity         1 - Network Port - Green On: 1Gbps         1 - Network Port - Yellow On: 100Mbps         Power         Power Source       AC Adapter Included         Power Delivery       60W         Input Voltage       100 - 240 AC         Input Current       2.37A         Output Voltage       20V DC         Output Current       6.75A         Plug Type       CP (OD:7.4/ID:5.1/CPD:0.6)         Power Consumption (In       135W			1 - Power - Solid Orange: ON in 2-Lane Mode (10 Gbps)
1 - Network Port - Green On: 1Gbps         1 - Network Port - Yellow On: 100Mbps         Power         Power Source       AC Adapter Included         Power Delivery       60W         Input Voltage       100 - 240 AC         Input Current       2.37A         Output Voltage       20V DC         Output Current       6.75A         Plug Type       CP (OD:7.4/ID:5.1/CPD:0.6)         Power Consumption (In       135W			1 - Network Port - Yellow On: Link Detected
Power       Power Source       AC Adapter Included         Power Delivery       60W         Input Voltage       100 - 240 AC         Input Current       2.37A         Output Voltage       20V DC         Output Current       6.75A         Plug Type       CP (OD:7.4/ID:5.1/CPD:0.6)         Power Consumption (In       135W			1 - Network Port - Yellow Flashing: Activity
PowerPower SourceAC Adapter IncludedPower Delivery60WInput Voltage100 - 240 ACInput Current2.37AOutput Voltage20V DCOutput Current6.75APlug TypeCP (OD:7.4/ID:5.1/CPD:0.6)Power Consumption (In135W			1 - Network Port - Green On: 1Gbps
Power SourceAC Adapter IncludedPower Delivery60WInput Voltage100 - 240 ACInput Current2.37AOutput Voltage20V DCOutput Current6.75APlug TypeCP (OD:7.4/ID:5.1/CPD:0.6)Power Consumption (In135W			1 - Network Port - Yellow On: 100Mbps
Power Delivery60WInput Voltage100 - 240 ACInput Current2.37AOutput Voltage20V DCOutput Current6.75APlug TypeCP (OD:7.4/ID:5.1/CPD:0.6)Power Consumption (In135W	ower		
Input Voltage 100 - 240 AC Input Current 2.37A Output Voltage 20V DC Output Current 6.75A Plug Type CP (OD:7.4/ID:5.1/CPD:0.6) Power Consumption (In 135W		Power Source	AC Adapter Included
Input Current 2.37A Output Voltage 20V DC Output Current 6.75A Plug Type CP (OD:7.4/ID:5.1/CPD:0.6) Power Consumption (In 135W		Power Delivery	60W
Output Voltage20V DCOutput Current6.75APlug TypeCP (OD:7.4/ID:5.1/CPD:0.6)Power Consumption (In135W		Input Voltage	100 - 240 AC
Output Current6.75APlug TypeCP (OD:7.4/ID:5.1/CPD:0.6)Power Consumption (In135W		Input Current	2.37A
Plug Type CP (OD:7.4/ID:5.1/CPD:0.6) Power Consumption (In 135W		Output Voltage	20V DC
Power Consumption (In 135W		Output Current	6.75A
		Plug Type	CP (OD:7.4/ID:5.1/CPD:0.6)
			135W
Environmental Operating Temperature 0 to 40C (32 to 104F)	nvironmental	Operating Temperature	0 to 40C (32 to 104F)



	Storage Temperature	-20 to 70C (-4 to 158F)
	Humidity	0% to 95%
Physical Characteristics		
	Product Length	8.3 in [21.0 cm]
	Product Width	3.1 in [8.0 cm]
	Product Height	1.3 in [3.2 cm]
	Weight of Product	0.0 oz [0.0 g]
Packaging Information		
	Package Length	0.0 in [0.0 mm]
	Package Width	0.0 in [0.0 mm]
	Package Height	0.0 in [0.0 mm]
	Shipping (Package) Weight	8.9 oz [253.0 g]
What's in the Box		
	Included in Package	1 - USB-C Docking Station
		1 - 3 ft (1m) USB-C Screw Lock to USB-C Cable
		1 - Power Adapter (NA/JP)
		1 - Quick-Start Guide

\*Product appearance and specifications are subject to change without notice.

