

DisplayPort Extension Cable with Active Repeater and Latching Connector (M/F), 8K 60 Hz, HDR, 4:4:4, HDCP 2.2, 9 ft. (2.7 m), TAA

MODEL NUMBER: P579-009-8K6











Extends your existing 8K DisplayPort connection by 9 ft. Latching male connector helps prevent accidental disconnections.

Features

Extends Your Existing DisplayPort Cable Run by 9-ft.

The dependable P579-009-4K6 (M/F) connects to your existing DisplayPort cable to extend the run by nine-feet (2.7 meters). This allows you more flexibility in placing, for instance, a cable box or media server connected to a DisplayPort-enabled television, monitor or projector. The male connector latches securely to help prevent the cable from becoming accidentally disconnected and disrupting a continuous audio/video signal.

Enjoy the Clarity of 4K/8K Video with Multi-Channel Audio and 4:4:4 Color

This extension cable supports 8K Ultra HD resolutions up to 7680 x 4320 at 60 Hz with multi-channel sound. It's compatible with DisplayPort 1.4 standards for HDR, providing a wide range of vibrant colors with richer contrast, brighter whites and deeper blacks. HDCP 2.2 compliance allows you to stream 4K content with no complications. This cable also supports 4:4:4 chroma subsampling for top-level PC gaming or using your HDTV as a PC monitor.

Invest in Quality Construction for Reliable Performance

You're expecting this 8K cable to last a long time, which is why it has been constructed with high-quality materials, such as a rugged PVC jacket. Contacts and connectors are gold-plated to resist corrosion. Double shielding reduces line noise (EMI/RFI) that can disrupt signals traveling through the DisplayPort cord. The source device provides power, so no external power adapter is needed.

TAA-Compliant for GSA Schedule Purchases

The P579-009-8K6 is compliant with the Federal Trade Agreements Act (TAA), which makes it eligible for GSA (General Services Administration) Schedule and other federal procurement contracts.

Specifications

OVERVIEW

Highlights

- Supports UHD resolutions up to 8K @ 60 Hz (4:4:4) for state-ofthe-art video quality
- Carries High Dynamic Range (HDR) signals for rich contrast and expanded color accuracy
- Complies with HDCP 2.2 standards to display up-to-date 8K video content
- Active repeater allows clean transmission without expense of an external booster
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Package Includes

P579-009-8K6 DisplayPort 1.4 Extension Cable (M/F), 8K 60 Hz, 9 ft. (2.7 m)



| UPC Code | 037332279590 |
|---------------------------------|------------------------------|
| Product Type | Passive |
| Technology | DisplayPort |
| Cable Type | Passive |
| | |
| VIDEO | |
| Max Supported Video Resolution | 7680 X 4320 (8K) 60HZ |
| Max Supported Color Depth | 24-bit True Color |
| HDR Support | Yes |
| 3D Video Supported | No |
| Chroma Sub Sampling | 4:4:4 |
| DisplayPort Alt Mode | No |
| PHYSICAL | |
| Color | Black |
| Material of Construction | PVC |
| Cable Jacket Color | Black |
| Connector Color | Blue |
| Cable Jacket Material | PVC |
| Cable Jacket Rating | VW-1 |
| Cable Outer Diameter (OD) | 7.3MM |
| Wire Gauge (AWG) | 28 |
| Cable Length (ft.) | 9 |
| Cable Length (m) | 2.74 |
| Cable Length (in.) | 108 |
| Shipping Dimensions (hwd / in.) | 9.00 x 7.00 x 0.50 |
| Shipping Weight (lbs.) | 0.41 |
| Shipping Weight (kg) | 0.19 |
| Unit Dimensions (hwd / in.) | 9.000 x 7.000 x 0.500 |
| Unit Packaging Type | Polybag |
| | |
| ENVIRONMENTAL | |
| Operating Temperature Range | 32° to 104°F (0° to 40°C) |
| Storage Temperature Range | 5° to 122°F (-15° to 50°C) |
| Operating Humidity Range | 0% TO 85% RH, NON-CONDENSING |
| Storage Humidity Range | 0% TO 85% RH, NON-CONDENSING |



| COMMUNICATIONS | | |
|---|--|--|
| EDID Compatible | No | |
| Consumer Electronics Control (CEC) Supported | No | |
| CONNECTIONS | | |
| Side A - Connector 1 | DISPLAYPORT (MALE) | |
| Side B - Connector 1 | DISPLAYPORT (FEMALE) | |
| Connector Plating | Gold | |
| Contact Plating | Gold | |
| Connector Style | Straight | |
| Latching or Gripping Connector | Yes | |
| FEATURES & SPECIFICATIONS | | |
| EMI/RFI Line Noise Protection | No | |
| Integrated/Removable Cable | No | |
| MST Support | No | |
| IP68 Rated | No | |
| Fully Molded Connector Ends | No | |
| Ohms | No | |
| Integral Strain Relief | No | |
| Impedance-Matched Twisted-Pair Construction | No | |
| Scaler Function | No | |
| IP67 Rated | No | |
| Displayport Specification | 1.4 | |
| HDCP Specification | 2.2 | |
| Driver Required | No | |
| STANDARDS & COMPLIANCE | | |
| Product Compliance | CE (Europe); FCC (USA); RoHS; Trade Agreements Act (TAA); UKCA | |
| WARRANTY & SUPPORT | | |
| Product Warranty Period (Worldwide) | 3-year limited warranty | |







© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.