





EPDU2116SMBO

Overview

Lead Time Usually in Stock

Main

Colour	Black
Product Or Component Type	PDU
Pdu Type	Metered outlet
Cord Length	3 m
Number Of Cables	1
Provided Equipment	Installation guide

Complementary

Input Voltage	200 V
Height	1800 mm
Width	55 mm
Output Voltage	230 V
Depth	56 mm
Net Weight	6.67 kg
Mounting Location	Side
Mounting Preference	No preference
Input Plug Type	IEC 60309 16 A 2P + E
Mounting Mode	Not rack-mountable
Rack Units	0U
Usb Compatible	No
Mounting Position	Vertical
Communication Port Protocol	SNMP
[In] Rated Current	16 A
Permissible Voltage	200240 V
Max Line Current	16 A
Input Current Limits	16 A
Load Capacity	3680 VA
Network Frequency	50/60 Hz

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Plug Standard	IEC 60309
Total Number Of Outlets	20 IEC 60320 C13
Communication Network Type	10/100BASF-T

Environment

Product Certifications	CE
Ambient Air Temperature For Operation	-550 °C
Relative Humidity	595 %
Operating Altitude	03000 m
Ambient Air Temperature For Storage	-2565 °C
Storage Relative Humidity	595 %
Storage Altitude	015000 mm

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	203 cm
Package 1 Width	19.5 cm
Package 1 Length	13 cm
Package 1 Weight	7.84 kg

Contractual warranty

Warranty 2 Years repair and Replace



Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



RoHS/REACh

Well-being performance



Rohs Exemption Information

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions