

Ez One Shot[®]

BARCODE SCANNER USER'S MANUAL



CONTENTS

GENERAL

Table of contents.....	1
Preface, Ez Troubleshooting.....	2-3
Cloning Mode.....	4-5
How to fix the scanner to the terminal.....	6-7
How to change a cable.....	7
How to set up the parameter.....	8

SETTING GROUP(GROUP1~14)

1 Interfaces selection, Computer type, Default, Setup Code ON/OFF.....	9
2 Reading Mode	10
Bi-color Setting	11
Advanced Autosensing Setting	12
Advanced Autosensing and Idle Mode Setting.....	13
Wireless Scanner Setting.....	14-26
3 Check Version, Beep tone, Terminator.....	27
4 Send Data Length, Preamble, Postamble.....	28
5 Accuracy adjustment.....	29
6 Code ID, Label Type Positive/Negative.....	30
7 Symbologies Code Identifier.....	31
8~9 Set Code ID, Customer Configuration.....	32-33
10 Delay between block and character.....	34
11 Keyboard layout, Caplock Mode, Numeric Key.....	35
12 RS232: Baud rate, Data bits, Parity.....	36
13 RS232: Stop bit, Handshaking, ACK/NAK, Flow Control, BCC.....	37
14 Wand Emulation parameter setting.....	38

SYMBOLY FORMATTING(GROUP15~32)

15~17 Enable/Disable Barcode Symbology.....	39-41
17 China postcode(Toshiba code).....	41
18 MSI code, UK Plessey code.....	43
19 Code 93, Telepen, IATA.....	45
20 Interleaved 2 of 5, Code 11.....	47
21 Industrial 2 of 5, Matrix 2 of 5.....	49
22 Codabar.....	51
23 ABC Codabar, CX Codabar.....	53
24 Codabar Coupling.....	54
25 Code 39 (Full ASCII/Standard), Code 32.....	55
26 UPC-E.....	57
27 UPC-E(0)&(1), UPC-E EXPAND.....	58
28 UPC-A.....	59
29 EAN-8.....	60
30 EAN-13, ISSN, ISBN, ISMN.....	61
31 EAN/UCC 128, Code 128, PDF417.....	62
32 DataBar(RSS) Stacked, Limited, Expanded.....	63

FULL ASCII(CODE39)TABLE, FUNCTION KEY TABLE(GROUP33~47)

33~41 Full ASCII table(Code 39).....	64-72
42~44 Function Key table(Code 39) for PC-AT.....	73-75
45~47 Trouble Shooting.....	76-78

APPENDIX

Appendix 1 Default table.....	79-82
Appendix 2 Cable Pin Assignment.....	83-84
Appendix 3 Barcode test chart.....	85-86

No	Kind of Troubles	Symptoms	Solutions
1	Computer Type (Group 1)	Scanner seems to be performing as usual, but no data is being output.	<ol style="list-style-type: none"> 1. Unplug the cable from the host computer. 2. Plug the cable back into the host computer. 3. Set the scanner to the exact computer type immediately.
2	Interfaces Selection (Group 1)	The scanner does not scan when the trigger is depressed.	<ol style="list-style-type: none"> 1. Unplug the cable from the host computer. 2. Plug the cable back into the host computer. 3. Set the scanner to the correct interface. The cable needs to match the interface.
3	Setting Procedure have not completed (Setting Need Triple Shot scanning) ----- Group - 4, 5, 8, 9, 17, 18, 19, 20, 22, 23, 25, 31	The scanner does not output data and beeps three times at every scan. This symptom indicates that a three-scan setting is not yet completed. Some settings take three scans to complete, they are: <ol style="list-style-type: none"> 1. Preamble, Postamble (Group4) 2. Accuracy Adjustment (Group5) 3. Customer ID Configuration (Group 8 & 9) 4. Min/Max Length (Group 17, 18, 19, 20, 21, 22, 25) 5. ABC Codabar (Group 22 & 23) 6. CX-Codabar (Group 22 & 23) 7. Coupling Codabar (Group 22 & 23) 8. EAN 128 (Group 31) 	<ol style="list-style-type: none"> 1. Follow the procedures for these settings at the appropriate pages. 2. The scanner will beep three times for an incomplete setting. 3. Scan RESET to try a setting again.
4	Limitation of length of the bar code	The scanner is reading correctly, except for certain bar codes of a certain length.	Reset the Min/Max setting for the bar code symbology affected.
5	Setup Code Disabled	When scanning the Default barcode, the scanner is not reset to Default but output data ".A001\$".	Scan SETUP CODE ON(Group 1) to enable all setup codes.
6	RS232 Protocol Communication setting problem	The scanner appears to be working in the RS-232 interface, but no data is output.	Ensure the correct RS-232 communication parameters have been set: Baud Rate, Handshaking, Stop Bits, Data Bits, and Parity. These settings must be the same for both the scanner and the host.


CLONING MODE

WHAT IS CLONING MODE?

CLONING duplicates a scanners settings in other scanners. It can save time when a number of scanners must be programmed to the same settings.

HOW SHOULD CLONING WORK?

1. Using this guide, make all the necessary settings for one wand.
2. Scan the CLONING MODE bar code shown below.
3. When CLONING MODE is scanned, all setup parameters will be converted to alphanumeric characters and shown on the monitor.
4. Using a bar code printer, print out all the setup parameters as Code 39 bar code labels.
5. Scan the printed labels sequentially with each wand to be programmed.



.A018\$(Cloning Mode on PC/AT) - you can clone the settings to a PC/AT regardless of the kind of device chosen on the scanner.

NOTES:

1. All cloning strings are upper case.
2. All cloning strings printed on labels should be the same as those on the monitor sequentially from first to last.
3. Cloning mode works in Word Note Pad only.
4. Never edit the data on the first row (.A017\$). It is an entry command for cloning.
5. The cloning string's length can be adjusted by combining multiple strings into one, or by breaking one string into multiple strings starting from the second row after "...". Length must be in sequences of four, such as 4, 8, 12, 16, 20 (MAX).
6. Be sure to print the dots exactly where they are shown on the monitor.

FORMAT OF CLONING

* Format of Cloning:

1st row >>> ".A017\$" (never edit any data of the first row)

2nd row >>> "...XXXX" you can adjust the String's Length starting from the dots "..." forward. The length of the string should be in 4, 8, 12, 16 or 20 (MAX)digits.

3rd row ~ so on >>> XXXX

End row - A dot "." Is the ending of cloning.

XXXX Stands for any string

EXAMPLE :

1. PROJECT ASSIGNMENTS:

- 1.1. Beep tone: **BEEP LOW -- HIGH.**
- 1.2. Capslock Mode: **CAPSLOCK ON.**
- 1.3. Reading Mode: **CONTINUOUS AUTO OFF.**


2. SETTING PROCEDURE:

- 2.1. Scan **BEEP LOW -- HIGH (GROUP 3).**
- 2.2. Scan **CAPSLOCK ON (GROUP 11).**
- 2.3. Scan **CONTINUOUS AUTO OFF (GROUP 2).**

3. All parameters will be converted to alphanumeric characters and shown on the monitor.



4. Print the results shown on the monitor as bar codes with a bar code printer. The bar codes should be in the Code 39 symbology.



5. Scan these labels with any of the wands that must be programmed with the same settings as the first wand. Be sure to scan from the first row to the second and so on sequentially, top to bottom.

CORRECT SETTING

.A017\$ 0604 5A02 5F04 .	4 4 4 4 . (Dot)	.A017\$06045A02 5F04.	12 4+.(Dot)
--	-----------------------------	----------------------------------	----------------


WRONG SETTING

.A017\$0604 5A02 5F04 .	←	Wrong Setting: The string "..." consists of 4 Dots, located at the beginning of second row; do not break the "..." into multiple strings.
.A017\$06045 A025F04 .	✓ 9 x } 7 x } ←	Wrong Setting: The string lengths of the second and third row do not match the length requirements, because rows should be in length of four digits.
.A017\$.... 0604 5A02 5F04.	X ←	Wrong Setting because you add "..." after .A017\$: The .A017\$ is a FIXED parameter to enter setup procedure. It is an unchangeable parameter. Never add, delete or rearrange data from the FIRST row.

HOW TO CONNECT THE SCANNER TO THE HOST TERMINAL: Handheld Barcode Scanner

KEYBOARD WEDGE INTERFACE

1. Power down the host computer.
2. Disconnect the keyboard cable from the computer.
3. Connect the "Y" cable between the keyboard and the scanner and computer.
4. Restart the computer.
5. The scanner will beep.
6. Set the scanner to KEYBOARD interface by referring to GROUP 1 (Interfaces Selection)
7. Scanner will beep to confirm the setting.
8. Scan a bar code to confirm that data shows on the monitor.




RS-232 INTERFACE

1. Power down the host computer.
2. Disconnect the RS-232 cable between the scanner and computer.
3. Connect the power adaptor to the cable.
4. Restart the computer,
5. Plug the power adaptor into a power outlet.
6. The scanner will beep.
7. Set the scanner to RS-232 interface by referring to GROUP 1 (Interfaces Selection).
8. Set RS-232 protocol: Baud Rate, Stop Bits, Handshaking, Data Bits and Parity.
9. Scan a bar code to confirm that data shows on the monitor.

NOTES:

1. Before plugging the power adaptor into the scanner, be sure the voltage, power consumption, and inner and outer DC characteristics are correct to avoid serious damage to the scanner and/or the computer.
2. Make sure the protocol communication settings of the scanner (such as baud rate, data bits, etc.) match those of the host computer. Otherwise, no data will be transmitted.



Check the power adaptor to ensure:


1. Input of AC current 110V/ 220V matches the power supply standard of the country in which the scanner is being used.
2. Adaptor output is +5V DC
3. The jack input is +5V DC



USB INTERFACE

The USB Interface supported is compatible with Apple MAC series, later PCs and Windows 98, 2000, Me and XP, Vista.

1. Connect the USB cable between the scanner and the computer.
2. The scanner will beep.
3. The scanner will detect the USB driver automatically. (The first time the scanner is connected via the USB port, follow the appropriate instructions for the host computer.)
4. Set the scanner to KEYBOARD/USB interface by referring to GROUP-1 (Interfaces Selection)
5. Scanner will beep to confirm the setting.
6. Scan a bar code to confirm that data shows on the monitor.




HOW TO CHANGE A CABLE

The scanners are designed to switch easily between interface options. To switch from one interface to another, the appropriate cable must be installed. To change a cabl, simply follow these steps:

1. To release the cable, insert a pin or straightened paper clip into the hole at the base of the scanner where the cable is connected.
2. Remove the cable from the scanner.
3. Plug in the new cable.

After changing to a new cable, be sure to reset the interface setting as appropriate (including parameter settings for the RS-232 interface).




HOW TO SET PARAMETERS

How do you program a scanner with this user's guide?

1. Use the scanner to scan at the bar code representing the function/parameter you want to set.
2. When you hear two beeps, the new settings have been defined or updated into the memory processor.

Default parameters are indicated in bold type and underlined characters. The character font is ARIAL BLACK. CD = Check Digit. CDV = Check Digit Verification.

Most settings require only a single bar code, but a few need several different bar codes to be scanned in order to completely define a setting. They are:



SETTING BAR CODE

Preamble / Postamble (maximum 16 digits)

Step 1: Scan CLR PRE/POSTAMBLE.

Step 2: Scan PREAMBLE or POSTAMBLE.

Step 3: Scan any alphanumeric from Full ASCII Table in Group 33-44

Step 4: Scan PREAMBLE or POSTAMBLE.

Min Length / Max Length

Step 1: Scan MIN LENGTH or MAX LENGTH.

Step 2: Scan two digits from Group 41 or Full ASCII numeric table in Appendix

Step 3: Scan MIN LENGTH or MAX LENGTH.

Accuracy Adjustment

Step 1: Scan ACCURACY ADJUSTMENT.

Step 2: Scan one digit from GROUP 5

Step 3: Scan ACCURACY ADJUSTMENT.

Set Code ID (Example: Code 39)

Step 1: Scan CODE 39 SET ID from Group 8

Step 2: Scan either one or two alphanumerics (maximum 2 digits) from Full ASCII table in Group 35-41

Step 3: Scan CODE 39 SET ID from Group 8

Set A Data - (CX-Codabar, ABC Codabar, Codabar Coupling).

Step 1: Scan SET INSERT DATA.

Step 2: Scan one alphanumeric character from Full ASCII Table in Group 35-41

Step 3: Scan SET INSERT DATA.

NOTES:

1. The scanner will beep three times as a reminder that a setting is not yet complete.
2. If you make a mistake, forget a step, etc., scan RESET to start again.

RESET



GROUP-1

INTERFACES SELECTION, COMPUTER TYPE, DEFAULT, SETUP CODE

DEFAULT

.A001\$



COMPUTER TYPE

.C004\$



PC-AT

.C007\$



NOTEBOOK*

SYMPTOMS	SOLUTION
Scanner seems to be performing as usual, but no data is being output.	<ol style="list-style-type: none">1. Unplug the cable from the host computer.2. Plug the cable back into the host computer.3. Set the scanner to the exact computer type immediately.

Caution: Please ensure the correct computer type is set when the scanner is attached to a new host computer. If set to Notebook, the scanner will operate with no external keyboard.

.C005\$




USB KB



.C008\$



USB KB



INTERFACES SELECTION

.C001\$



PS2

.C002\$



RS232

SYMPTOMS	SOLUTION
The wand does not scan/ The scanner does not scan when the trigger is depressed.	<ol style="list-style-type: none">1. Unplug the cable from the host computer.2. Plug the cable back into the host computer.3. Set the wand to the correct interface. The cable needs to match the interface.

Caution: This scanner is designed to switch easily between interface options. To switch from one interface to another, the appropriate cable must be installed. After changing to a new cable, be sure to reset the interface setting as appropriate.

SETUP CODE READ

.B015\$



SETUP CODE ON

.B016\$



SETUP CODE OFF

Caution: Scanning SETUP CODE OFF will turn the scanner into unprogrammable state and the scanner will not react to any setup code.

GROUP-2

READING MODE SETTING

. F005\$



CONTINUOUS MODE

- * LED is always on.
- * The trigger does not function in Continuous Mode.

. F001\$



FLASH MODE

- * The LED is on steady if a bar code is close to the scanner, but starts flashing if no bar code is detected after 60 seconds.
- * The trigger does not function in Flash Mode.

. F002\$



TRIGGER MODE

- * The LED will light when the trigger is pressed.
- * The LED will go off when the trigger is released.

. F006\$



CONTINUOUS AUTO OFF

- * The LED is always on when the trigger is pressed.
- * The LED will go off if no bar code has been detected after 60 seconds.

. F003\$



TOGGLE MODE

- * This function works like Trigger Mode, but the scanner beeps to indicate a good read.

. F007\$



*AUTO SENSING MODE(CCD)

- * If Auto-Sensing Mode(CCD) is on, the LED will go off if no bar code is detected after Deactivation Time elapses.(The default is 3 sec.)
- * The LED lights automatically when a BAR CODE is detected.
- * If Auto-Sensing Mode(CCD) is on, the Magnetic Switch and Blue LED will be activated at the same time.

. F010\$



*AUTO SENSING MODE(Laser)

- * If Auto-Sensing Mode(Laser) is on, the LED will go off if no barcode is detected after Deactivation Time elapses.(The default is 3 sec.)
- * The laser emits automatically when an OBJECT is detected.
- * If Auto-Sensing Mode(Laser) is on, the Magnetic Switch will be activated.

NOTES:

1. To extend the scanner's life, keep the scanner set to Trigger Mode or Continuous Auto Off Mode.
2. The LED indicator will glow for GOOD READ.
3. For advanced settings of Auto-Sensing Mode(such as Deactivation Time, Magnetic Switch and Blue LED) please refer to the next pages.

GROUP-2.2

BI-COLOR LIGHT SOURCE SETTINGS

(The following settings are supported by Bi-Color models)

CYCLE MODE

. D027\$



GREEN > RED

. D028\$



RED > GREEN

. D029\$



GREEN > BI-COLOR

. D030\$



RED > BI-COLOR

NOTES:

1. Illumination color will switch back and forth from one to another when good read does not occur.
 2. Illumination color will remain as the one used at the last good read.
-

SINGLE MODE

. D031\$



BI-COLOR

. D032\$



GREEN

. D033\$



RED

NOTES:

1. Illumination color will remain single.

GROUP-2.3

ADVANCED AUTO-SENSING MODE SETTINGS

(The following settings are available after the activation of Auto-Sensing Mode)

MAGNETIC SWITCH (CCD & LASER SCANNERS)

. F034\$



MAGNETIC SWITCH ON

. F035\$



MAGNETIC SWITCH OFF

NOTES:

1. The Magnetic Switch is automatically activated when Auto-Sensing Mode is on.
 2. To enable Magnetic Switch, the scanner should be paired with an Autosense Stand to perform Auto-Sensing function.
 3. When Magnetic Switch is disabled, the scanner will perform Auto-Sensing function without Autosense Stand.
-

GREEN LED/ SUPPLEMENT LIGHT (CCD SCANNER ONLY)

. F032\$



GREEN LED ON

. F033\$



GREEN LED OFF

NOTES:

1. The green LED is automatically activated when Auto-Sensing Mode is on.
2. Green LED serves as Supplement Light for a CCD scanner in order to enhance the sensitivity of scanner in Auto-Sensing Mode.

GROUP-2.4

ADVANCED AUTO-SENSING MODE SETTINGS

(The following settings are available after the activation of Auto-Sensing Mode)

. F030\$



DEACTIVATION TIME

**DEACTIVATION TIME
(CCD & LASER SCANNERS)**

NOTES:

1. The default of Deactivation Time is 3 Sec.
2. Deactivation Time is the time interval between the last scan and the automatic deactivation of LED or Laser light in Auto-Sensing Mode.
3. You can set the Deactivation Time value by the following three steps:

Step 1: scan Deactivation Time

Step 2: scan two digits(Limit Range: 01 ~ 30sec.) from the Full ASCII numeric table.

Step 3: scan Deactivation Time

. F031\$



SAME CODE INTERVAL

**SAME CODE INTERVAL
(LASER SCANNER ONLY)**

NOTES:

1. The default of Same Code Interval is 30 Sec.
2. Same Code Interval is the time interval between two consecutive scans on the SAME bar code in Auto-Sensing Mode.
3. You can set the value of Same Code Interval by the following three steps:

Step 1: scan Same Code Interval

Step 2: scan two digits(Limit Range: 03 ~ 60sec.)from the Full ASCII numeric table.

Step 3: scan Same Code Interval

IDLE MODE SETTING

IDLE MODE

.B028\$



Pre-Idle Time

.B026\$



Idle Mode On

.B027\$



Idle Mode Off

NOTES:

1. Idle Mode is only supported by certain models.
2. When Idle Mode is on, the scanner will enter idle state to save power after a period of inactivity, or Pre-Idle Time(the default is 1 min).
3. You can set the value of Pre-Idle Time by the following four steps:

Step 1: scan Idle Mode On

Step 2: scan Pre-Idle Time

Step 3: scan one digits(Limit Range: 1~9 Min.)from the Full ASCII numeric table.

Step 4: scan Pre-Idle Time

GROUP-2.5

WIRELESS SCANNER SETTINGS

LED & BEEPER INDICATION

Scanner	Status	Blue/Green LED	Red LED	Beeper	Remark
	Initializing/ Power-up		Solid for 2 sec	1 long beep	
	Successful Barcode Scan	1 Flash		1 beep	
	Successful Connection	2 Flashes		2 beeps	
	Reads Configuration Barcode			2 short beeps	
	Data Temporarily Stored	1 Flash		High-Low beeps	See Batch Mode
	Data Permanently Stored	1 Flash		Low-High beeps	See Memory Mode
	Wireless Disconnection	Solid for 2 sec		3 beeps	
	Unsuccessful Pincode Setup	Flashing		3 short beeps	Scan Pincode Stop and retry
	Barcode Scan w/o Connection	Flashing		3 short beeps	
	Low Power		Flashing	5 beeps	
	Barcode Scan w/o Connection	Flashing		Several short beeps	
	Power Off or Standby				See Power Off Timeout
	Cradle	Status	Blue LED	Red LED	Green LED
Successful Connection		Solid			
Charging			Solid	Flashing	Power adaptor needed
Full Charge				Flashing	4 hours to fully charge

GROUP-2.6

WIRELESS SCANNER SETTINGS

CONNECTION OPTIONS

. E041\$



BT mode - HID plug & play

1. Connect the cradle to the host PC.
2. Scan **[DISCONNECT]**
3. Scan **[BT mode - HID plug & play]**, and the scanner will emit 8 beeps.
4. Scan the Host Address barcode on the cradle's bottom.
5. The scanner will beep twice and cradle's blue indicator LED will stay on to verify a successful connection.

*Note: Only supported by model with charging cradle.

. E040\$



BT mode - HID non-pincode

1. Press the trigger for 1 second to activate the scanner.
2. Scan **[DISCONNECT]**
3. Scan **[BT mode - HID non-pincode]**; the scanner will emit 8 beeps.
4. Select "Wireless Scanner" from discovered device list.
5. For PC, please click "Pair without using a code"
6. The scanner will beep twice to verify the connection.

*Note: In this mode, the scanner is recognized by the host as a mouse (pointing device). If your host fails to find it, please try **[BT mode - HID]** instead.

. E042\$



BT mode - SPP

1. Press the trigger for 1 second to activate the scanner.
 2. Scan **[DISCONNECT]**
 3. Scan **[BT mode - SPP]**; the scanner will emit 8 beeps.
 4. Select "Wireless Scanner" from discovered device list.
 5. For PC, please click "Enter the device's pairing code".
 6. Enter "1234" from the host.
 7. Open serial communication software with com port (see Device Manager) properly set up.
 8. The scanner will beep twice to verify the connection.
-

. E043\$



BT mode - HID

1. Press the trigger for 1 second to activate the scanner.
 2. Scan **[DISCONNECT]**
 3. Scan **[BT mode - HID]**; the scanner will emit 8 beeps.
 4. Select "Wireless Scanner" from discovered device list.
 5. For PC, please click "Create a pairing code for me"
 6. The Bluetooth application may prompt you to scan a pincode.
 7. Follow the steps in **PINCODE SETUP** section the on next page.
 8. The scanner will beep twice to verify the connection.
-

. E031\$



Disconnect

GROUP-2.7

WIRELESS SCANNER SETTINGS

PINCODE SETUP

STEP 1

Pincode Start

.E032\$



STEP 2

Scan numeric barcodes (see **NUMERIC BARCODES** below) based on the pincode generated by the Bluetooth application.

NUMERIC BARCODES



1

6



2

7



3

8



4

9



5

0



STEP 3

Enter

\$TX



STEP 4

Pincode Stop

.E033\$



GROUP-2.8

WIRELESS SCANNER SETTINGS

SET BLUETOOTH DEVICE ID

To customize your own Bluetooth device name for the wireless scanner, please follow below steps:

STEP 1

Default Wireless ID



STEP 2

Set Wireless ID



STEP 3

Scan 7 alphanumeric characters from Full ASCII Table (GROUP 35-41)

STEP 4

Set Wireless ID



STEP 5

Scan a desired BT mode in **Connection Option** (GROUP 2.6) to complete the configuration.

*Note:

1. If you have connected the scanner with the host BEFORE customizing your Bluetooth device name, please remove the device and create a new connection to make sure device name is refreshed. For PC, it is recommended to restart the Bluetooth adaptor in order to refresh device name.
2. At Step 3, the scanner will beep three times as an alert that more than 7 characters are entered.
3. To reset the Bluetooth device name to default ("Wireless Scanner"), please simply do Step 1 & Step 5, skipping Step 2 to Step 4.

GROUP-2.9

WIRELESS SCANNER SETTINGS

POWER OFF TIMEOUT

The timeout before automatic power-off to save battery power.

. B017\$



1 MIN

. B018\$



3 MIN

. B019\$



5 MIN

. B020\$



10 MIN

. B021\$



DIABLE
(NO POWER-OFF)

. B029\$



User Define (sec)

* Note:

1. Scan [User Define]
2. Scan 2 numeric barcodes below (Range: 10 to 99)
3. Scan [User Define]



1

6



2

7



3

8



4

9



5

0



GROUP-2.10

WIRELESS SCANNER SETTINGS

iOS (Apple)

Getting Connected

Please pair with the scanner via [BT mode - HID]. (GROUP 2.6)

Getting Connected without Pincode

. E049\$



ENABLE SSP

Secure Simple Pairing (SSP), supported by Bluetooth 2.1 or above, allows you to pair with iOS without pincode.

Please scan [Enable SSP] above before entering the pairing procedure of [BT mode - HID]. (GROUP 2.6)

Touch Keyboard

. E047\$



ENABLE iOS HOTKEY

. E048\$



DISABLE iOS HOTKEY

After enabling iOS Hotkey(disabled by default), you may simply double-click the trigger to toggle the iPhone/iPad Touch Keyboard.

Android


Getting Connected

To get connected to Android, please follow the instruction in [BT mode - HID]. (GROUP 2.6)

Touch Keyboard

While connected with the scanner, the Touch Keyboard on the Android smartphone or tablet might disappear. To resolve this issue, please change settings on Android device with below steps:

1. Enter "Settings"
2. Enter "Language & input"
3. In Keyboard & input window, tap "Default" to continue.
4. Turn off "Hardware - Physical keyboard", and the Touch Keyboard will function properly again.



GROUP-2.11

WIRELESS SCANNER SETTINGS

LINK QUALITY

ENABLE



DISABLE



When enabled, Link Quality ensures a more secure data transmission from the scanner to the cradle/host. However the distance of data transmission will decrease.

BATCH MODE

ENABLE



DISABLE



When out of range, the scanner will temporarily keep scanned data in its memory buffer(2K RAM) until the buffer is full. The scanner will send all stored data back to the host after getting in range.

*Note:

1. Batch Mode will not function when Memory Mode is enabled, or no connection is made beforehand.
2. It is recommended to turn **[LINK QUALITY] OFF** in order to let Batch Mode function properly.

GROUP-2.12

WIRELESS SCANNER SETTINGS

SPP MASTER MODE

First, please generate one configuration barcode for the target SPP slave device in below methods:

1. The barcode must be Code 39
2. Barcode data format: LTB + Target MAC address

For example, the target SPP slave device's MAC address is 001583522C3B.

Please encode:

LTB001583522C3B in Code39 barcode.

Then, follow below steps to create connection:

STEP 1

SPP - Master

. E042\$



STEP 2

ENABLE SSP (NON-PINCODE)

. E049\$



*Note: Please skip this step if the target SPP slave device does not support non-pincode connection.

STEP 3

LTB001583522C3B



(Your Target SPP Slave Device Barcode)

GROUP-2.13

WIRELESS SCANNER SETTINGS

SET SPP PINCODE

By default, the SPP pincode for the scanner is "1234".
You may customize this pincode with below steps:

STEP 1

Set SPP Pincode

. B024\$



STEP 2

Scan numeric barcodes (see **NUMERIC BARCODES** below)
Up to 8 numbers can be set as SPP pincode.

NUMERIC BARCODES



1

6



2

7



3

8



4

9



5

0



STEP 3

Set SPP Pincode

. B024\$



STEP 4

Scan a desired BT mode in **Connection Option** (GROUP 2.6)
to complete the configuration.

GROUP-2.14

WIRELESS SCANNER SETTINGS

SPP REMOTE CONTROL

There are two ways for the scanner to reply to the host whether it is well connected:

Command Response

Host sends: CR,LF,{A,L},CR,LF (8 bytes)
Scanner replies: O,K,CR,LF (4 bytes)

Beeper Response

Host sends: CR,LF,{M,1},CR,LF (8 bytes)
Scanner reacts: a short beep

SHUT DOWN

This configuration barcode will shut down the scanner immediately and reserve the pairing record.

. E255\$



SHUT DOWN

DISCONNECTION

. E031\$



DISCONNECT
(CLEAR PAIRING RECORD)

. E046\$



DISCONNECT
(KEEP PAIRING RECORD)

GROUP-2.15

WIRELESS SCANNER SETTINGS

MEMORY MODE

For memory version only

. R001\$



ENABLE MEMORY

. R002\$



DISABLE MEMORY

Once enabled, the scanner will stop sending data via Bluetooth and start storing data into the internal flash disk (2MB)

Delete Last Record/ Clear All Record

. R005\$



DELETE LAST RECORD


. R004\$



CLEAR ALL RECORD

OUTPUT DATA

For memory version only



You may output data ONLY when memory is enabled (GROUP 2.15)

Data Output Method

WIRELESS

. R014\$



USB-VCP

. R013\$



To output stored data via Wireless, please do the following:

1. Scan **[WIRELESS]**
2. Scan **[OUTPUT DATA]**

To output stored data via USB-VCP, please do the following:

1. Install VCP driver (available on CD)
2. Connect the scanner & host with USB cable
3. Scan **[USB-VCP]**
4. Save data as *.csv by "Covert to CSV.exe" (available on CD)

GROUP-2.16

WIRELESS SCANNER SETTINGS

DATA FORMAT

For memory version only

. R011\$



DATA FORMAT

The default Data Format is <Item No.>, <Date>, <Time>, <Barcode Data> below are items and their setup codes:

Code	Item	Code	Item
1	Item No.	3	Time
2	Date	4	Barcode Data

Example:

To change Data Format to <Item No.>, <Barcode Data>, <Date>, <Time>

1. Scan [Data Format]
2. Scan [1], [4], [2], [3] from Group 41.
3. Scan [Data Format]

. R010\$



FIELD SEPARATOR

Default is comma (,) . You may replace it with any alphanumeric characters from the full ASCII table in User's Manual (on CD).

Example: To change Field Separator to Semicolon (;)

1. Scan [Field Separator]
2. Scan [;] from the full ASCII table(Group 33-41)
3. Scan [Field Separator]

DATE & TIME SETUP

For memory version only

SET DATE

. R006\$



Example: To set Date to 2012-08-01 (Year-Month-Day):

1. Scan [Set Date]
2. Scan [1], [2], [0], [8], [0], [1] from Group 41.
3. Scan [Set Date]

SET TIME

. R007\$



Example: To set Time to 08:10:30 am (Hr:Min:Sec)

1. Scan [Set Time]
2. Scan [0], [8], [1], [0], [3], [0] from Group 41.
3. Scan [Set Time]

* To avoid Time and Date being reset to factory default due to running out of battery, please fully charge the scanner for at least 3 hours before use.

GROUP-2.17

WIRELESS SCANNER SETTINGS

DATE FORMAT

For memory version only

. R008\$



DATE FORMAT

The default Date Format is DD/MM/YYYY (Code = 09), below is full list of available formats and their setup codes:

Code	Format	Code	Format
01	DD-MM-YYYY	09	DD/MM/YYYY
02	MM-DD-YYYY	10	MM/DD/YYYY
03	DD-MM-YY	11	DD/MM/YY
04	MM-DD-YY	12	MM/DD/YY
05	YYYY-MM-DD	13	YYYY/MM/DD
06	YY-MM-DD	14	YY/MM/DD
07	DD-MM	15	DD/MM
08	MM-DD	16	MM/DD

Example:

To set Date Format to MM/DD/YY (Code = 12)

1. Scan [Date Format]
2. Scan [1], [2] from Group 41.
3. Scan [Date Format]

TIME FORMAT

For memory version only

. R009\$



TIME FORMAT

The default Time Format is HH:MM:SS (Code = 01), below are available formats and their setup codes:

Code	Format	Code	Format
01	HH:MM:SS	02	HH:MM

Example:

To set Time Format to HH:MM (Code = 02)

1. Scan [Time Format]
2. Scan [0], [2] from Group 41.
3. Scan [TimeFormat]

GROUP-3

CHECK VERSION, BEEP TONE, TERMINATOR

BEEP TONE MODE



CHECK VERSION



TERMINATOR



NOTES:

1. For the Keyboard Wedge interface the default terminator is CR.
2. For the USB interface the default terminator is CR.
3. For the RS232 interface the default terminator is CR+LF.

GROUP-4

SEND DATA LENGTH, PREAMBLE & POSTAMBLE.

SEND DATA LENGTH

.D019\$



SEND DATA LENGTH ON

.D020\$



SEND DATA LENGTH OFF

PREAMBLE & POSTAMBLE (PREFIX AND SUFFIX)

.A011\$



CLEAR PRE/ POSTAMBLE

.A012\$



PREAMBLE (16)

.A013\$



POSTAMBLE (16)

EXAMPLE:

Set PREAMBLE String as “##”
POSTAMBLE String as “\$\$”

SETTING PROCEDURE:

- STEP 1 : Scan : CLEAR PRE/ POSTAMBLE.
- STEP 2 : Scan : PREAMBLE.
- STEP 3 : Scan : “#” twice from FULL ASCII Table.
- STEP 4 : Scan : PREAMBLE.
- STEP 5 : Scan : POSTAMBLE.
- STEP 6 : Scan : “\$” twice from FULL ASCII Table.
- STEP 7 : Scan : POSTAMBLE.

FORMAT:

{Preamble}{Code ID}{Bar Code}{Postamble}

NOTES:

1. A PREAMBLE is a string of up to 16 characters added to the beginning of a scanned barcode.
2. A POSTAMBLE is a string of up to 16 characters added to the end of a scanned barcode.
3. Default value for both: None.

GROUP-5

ACCURACY ADJUSTMENT



ACCURACY ADJUSTMENT



Accuracy Adjustment assures a more reliable decoded output. Enabling the feature and setting a number from 1 to 9 subjects the decoded output a higher standard of accuracy. The higher the number, the greater the accuracy.

SETTING PROCEDURE:

1. Scan **ACCURACY ADJUSTMENT**.
2. Scan one digit (1-9) from barcode menu above.
3. Scan **ACCURACY ADJUSTMENT**.

RESET



NOTES:

1. The scanner will beep three times as reminder that a setting is not yet complete.
2. If you make a mistake, forget a step, etc., scan **RESET** to start again.

GROUP-6

LABEL TYPE POSITIVE / NEGATIVE, ENABLE AND DISABLE CODE ID

LABEL TYPE POSITIVE / NEGATIVE

.D021\$



DISABLE NEGATIVE LABEL
(POSITIVE LABEL ENABLE)

.D022\$



ENABLE NEGATIVE LABEL
(POSITIVE & NEGATIVE ENABLE)

ENABLE CODE ID

.A008\$



FACTORY ID ON

.A014\$



AIM ID ON

.A015\$



SET ID ON

DISABLE CODE ID

.A009\$



NOTES:

1. Only ONE code ID will be sent.
2. The code ID is located at the position before the bar code data and after the preamble.

EXAMPLE :

- 1.Preamble 145287,
- 2.Code ID: enable AIM ID,
- 3.Bar code symbologies : EAN 13+5

145287	JE0	4563987123453	12411
Preamble 145287	CODE ID AIM ID : JE0	BARCODE / DATA EAN 13 +5	
OUTPUT : 145287JE0456398712345312411			

GROUP-7

SYMBOLOGIES CODE ID IDENTIFIER, SET ID

SYMBOLOGIES CODE ID IDENTIFIER						
Symbologies	Factory ID	AIM ID (new)	Symbologies	Factory ID	AIM ID (new)	
EAN 128	T]C1	MSI	O]M0	
Code 128	K]C0	MSI(MOD 10 / CDV & not send CD)]M1	
EAN8(+2/+5 OFF)	S]E4	Code 32	B]X0	
EAN8(+2 ON)]E4	Codabar	N]F0	
EAN8(+5 ON)]E4]F1	
UPC-E(+2/+5 OFF)	E]E0	Codabar(CDV & Send CD)]F2	
UPC-E(+2 ON)]E3	Codabar(CDV & not send CD)]F4		
UPC-E(+5 ON)]E3	UK Plessey	P]P0	
UPC-A(+2/+5 OFF)	A]E0	Matrix 2 of 5	Y]X0	
UPC-A(+2 ON)]E3	Full ASCII Code 39(disable CDV)	D]A4	
UPC-A(+5 ON)]E3	Full ASCII Code 39(CDV & send CD)]A5	
EAN-13(+2/+5 OFF)	F]E0	Full ASCII Code 39(CDV & not send CD)]A7	
EAN-13(+2 ON)]E3	Standard Code 39(disable CDV)	M]A0	
EAN-13(+5 ON)]E3	Standard Code 39(CDV & send CD)]A1	
Code 93	L]G0	Standard Code 39(CDV & not send CD)]A3	
Code 11(disable CDV)	J]H0	Interleaved 2 of 5(CDV & send CD)	I]I1	
Code 11(send one CD)]H0	Interleaved 2 of 5(CDV & not send CD)]I3	
Code 11(send two CD)]H1	Interleaved 2 of 5(disable CDV)]I0	
Code 11(not send CD)]H3	Databar]e0	
Telepen(ASCII)	U]B0	Databar Stacked	G		
Telepen(Numeric)]B1	Databar Stacked Omnidirectional			
IATA 2 of 5	R]R0	Databar Truncated			C
Industrial 2 of 5	V]S0	Databar Limited			
China Post Code	H]X0	Databar Expanded			
PDF417	Z]E0	Databar Expanded Stacked		Q	

SET ID - SETTING PROCEDURES

Setting steps:

1. Scan the SET ID bar code for a particular symbology.
2. Scan one or two alphanumeric characters from the Full ASCII Table.
3. Scan the SET ID bar code again.

Example: Define the MSI Code ID = A, Code 93 = G9
MSI :

Step1: Scan MSI Set ID (Group 9).

Step2: "A" from (Group 37).

Step3: Scan MSI Set ID (Group 9).

Code 93:

Step1: Scan Code 93 Set ID (Group8).

Step2: "G" from(Group37), Scan "9" from(Group41).

Step3: Scan Code 93 Set ID (Group8).

NOTES:

1. The length of a Code ID is either one or two characters. If one character is set, the Code ID output will be one character. If two characters are set, the Code ID output will be two characters.
2. Only one type of Code ID will be sent.

GROUP-8

CODE ID CONFIGURATION: SET ID

. P001\$



EAN 13 Set ID

. P002\$



EAN 8 Set ID

. P003\$



UPC E Set ID

. P004\$



UPC A Set ID

. P005\$



Code 39 Set ID

. P013\$



Code 93 Set ID

. P007\$



Codabar Set ID

. P021\$



IATA Set ID

. P010\$



Code 128 Set ID

. P016\$



EAN 128 Set ID

. P022\$



Telepen Set ID

. P009\$



Code 11 Set ID

. P011\$



Code 32 Set ID

. P012\$



China Post Code
(TOSHIBA Code) Set ID

GROUP-9

CODE ID CONFIGURATION: SET ID

MSI Code Set ID  . P014\$

UK Plessey Set ID  . P015\$

Matrix 2 of 5 Set ID  . P017\$

Interleaved 2 of 5 Set ID  . P006\$

Industrial 2 of 5 Set ID  . P018\$

Full ASCII Code39 Set ID  . P008\$

GS1 Databar (RSS) Limited Set ID  . P019\$

GS1 Databar (RSS) Expanded Set ID  . P020\$

GS1 Databar (RSS) Set ID  . P024\$

LABEL Code Set ID (Reserved)  . P020\$

RESET  . P023\$

1. The scanner will beep three times as a reminder that a setting is not yet complete.
2. If you make a mistake, forget a step, etc., scan RESET to start again.

GROUP-10

DELAY BETWEEN BLOCKS AND CHARACTERS

INTERBLOCK DELAY

. B001\$ 	<u>0mS</u>
. B002\$ 	10mS
. B003\$ 	50mS
. B004\$ 	100mS
. B005\$ 	200mS
. B006\$ 	500mS

INTERCHARACTER DELAY

. B010\$ 	<u>140uS</u>
. B011\$ 	500uS
. B012\$ 	1mS
. B013\$ 	4mS
. B014\$ 	16mS

GROUP-11

KEYBOARD LAYOUT/ CAPLOCK MODE/ NUMERIC KEY

KEYBOARD LAYOUT



CAPITAL LOCK MODE



NOTE:

1. When barcode scanner is set to Caplock Free mode, no matter keyboard Capslock LED indicator is ON or OFF, output will be always the same as the Original barcode. In other words, what you see is what output is. (CODABAR is the exception)
2. If ABCD/ ABCD, abcd/ abcd, ABCD/T*E, abcd/tn*e are on, they work independently according to their rules.

NUMERIC KEY



GROUP-12

RS232: BAUD RATE, DATA BITS & PARITY

BAUD RATE



DATA BITS & PARITY



GROUP-13

RS232: STOP BIT, HANDSHAKING, ACK/NAK, FLOW CONTROL, BCC

STOP BITS

.E016\$



1 STOP BIT

.E017\$



2 STOP BITS

HANDSHAKING

.E018\$



NONE

.E019\$



RTS enable at Power on

.E020\$



RTS enable with Communication

ACK / NAK

.E023\$



ON

.E024\$



OFF

FLOW CONTROL: TIME OUT

.E025\$



1 Sec

.E026\$



3 Sec

.E027\$



10 Sec

.E028\$



Unlimited

BCC

.E029\$



RS232 BCC Char On

.E030\$



RS232 BCC Char Off

GROUP-14

WAND EMULATION PARAMETER SETTING



**LEVEL DURATION OF
MINI WIDTH**



**POLARITY OF
IDLE CONDITION**



**OUTPUT OF WAND
EMULATION**



WAVE FORM



GROUP-15

ENABLE/ DISABLE SYMBOLOGIES

ENABLE




ENABLE ALL CODE



CODE 32



CHINA POSTAL CODE



UK PLESSEY CODE



INDUSTRIAL 2 OF 5



MATRIX 2 OF 5



INTERLEAVED 2 OF 5



CODE 128



CODABAR



TELEPEN

DISABLE



DISABLE ALL CODE



CODE 32



CHINA POSTAL CODE



UK PLESSEY CODE



INDUSTRIAL 2 OF 5



MATRIX 2 OF 5



INTERLEAVED 2 OF 5



CODE 128



CODABAR



TELEPEN

GROUP-16

ENABLE/ DISABLE SYMBOLOGIES

ENABLE



DISABLE



GROUP-17

ENABLE/DISABLE SYMBOLOGIES, CHINA POSTAL CODE

ENABLE

. N032\$



GS1 Databar ENABLE

. N038\$



GS1 Databar STACKED ENABLE

. N010\$



GS1 Databar LIMITED ENABLE

. N026\$



GS1 Databar EXPANDED ENABLE

. N028\$



GS1 Databar EXPANDED STACKED ENABLE

. G021\$



PDF 417 ENABLE

DISABLE

. N033\$



GS1 Databar DISABLE

. N039\$



GS1 Databar STACKED DISABLE

. N011\$



GS1 Databar LIMITED DISABLE

. N027\$



GS1 Databar EXPANDED DISABLE

. N029\$



GS1 Databar EXPANDED STACKED DISABLE

. G022\$



PDF417 DISABLE

CHINA POSTAL CODE

[TOSHIBA CODE]

. K001\$



ENABLE

. K002\$



DISABLE

. K003\$



DISABLE CDV

. K004\$



CDV & SEND CD

. K005\$



CDV & NOT SEND CD

. K006\$



MIN LENGTH (11)

. K007\$



MAX LENGTH (48)

APPENDIX

FULL ASCII (Code 39) NUMERIC TABLE



SETTING PROCEDURE

MIN / MAX LENGTH

STEP 1 - Scan: MIN LENGTH/ MAX LENGTH

STEP 2 - Scan: Two digits from Appendix.

STEP 3 - Scan: MIN LENGTH/ MAX LENGTH

Please note that when Min Length and / or Max Length are enabled, the scanner will only read bar codes that fall into those length parameters. Bar codes shorter or longer than specified will not be read. The default lengths for these are indicated in parentheses under the Min and Max bar codes for each symbology.

NOTES:

1. The scanner will beep three times as a reminder that a setting is not yet complete.
2. If you make a mistake, forget a step, etc., Scan RESET to start again.

RESET ➔



GROUP-18

SYMBOLOLOGIES: MSI CODE, UK PLESSEY CODE



MSI






UK PLESSEY CODE



APPENDIX

FULL ASCII (Code 39) NUMERIC TABLE

0		1	
2		3	
4		5	
6		7	
8		9	

SETTING PROCEDURE

MIN / MAX LENGTH

STEP 1 - Scan: MIN LENGTH/ MAX LENGTH

STEP 2 - Scan: Two digits from Appendix.

STEP 3 - Scan: MIN LENGTH/ MAX LENGTH

Please note that when Min Length and / or Max Length are enabled, the scanner will only read bar codes that fall into those length parameters. Bar codes shorter or longer than specified will not be read. The default lengths for these are indicated in parentheses under the Min and Max bar codes for each symbology.

NOTES:

1. The scanner will beep three times as a reminder that a setting is not yet complete.
2. If you make a mistake, forget a step, etc., Scan RESET to start again.

RESET ➔



GROUP-19

SYMBOLOLOGIES: CODE 93, TELEPEN, IATA

. G010\$



ENABLE

. G011\$



DISABLE

CODE 93

. G012\$



MIN LENGTH (6)

. G013\$



MAX LENGTH (48)

. L014\$



ENABLE TELEPEN

. L015\$



DISABLE TELEPEN

TELEPEN

. L020\$



TELEPEN ASCII

. L021\$



TELEPEN NUMBER

. N017\$



ENABLE

. N018\$



DISABLE

. N019\$



DISABLE CDV

. N020\$



CDV & SEND CD

IATA

. N021\$



CDV & NOT SEND CDV

. N022\$



MIN LENGTH (6)

. N023\$



MAX LENGTH (48)

APPENDIX

FULL ASCII (Code 39) NUMERIC TABLE



SETTING PROCEDURE

MIN / MAX LENGTH

STEP 1 - Scan: MIN LENGTH/ MAX LENGTH

STEP 2 - Scan: Two digits from Appendix.

STEP 3 - Scan: MIN LENGTH/ MAX LENGTH

Please note that when Min Length and / or Max Length are enabled, the scanner will only read bar codes that fall into those length parameters. Bar codes shorter or longer than specified will not be read. The default lengths for these are indicated in parentheses under the Min and Max bar codes for each symbology.

NOTES:

1. The scanner will beep three times as a reminder that a setting is not yet complete.
2. If you make a mistake, forget a step, etc., Scan RESET to start again.

RESET ➔



GROUP-20

SYBBOLOGIES: INTERLEAVED 2 OF 5, CODE 11



INTERLEAVED 2 OF 5








CODE 11



APPENDIX

FULL ASCII (Code 39) NUMERIC TABLE

0		1	
2		3	
4		5	
6		7	
8		9	

SETTING PROCEDURE

MIN / MAX LENGTH

STEP 1 - Scan: MIN LENGTH/ MAX LENGTH

STEP 2 - Scan: Two digits from Appendix.

STEP 3 - Scan: MIN LENGTH/ MAX LENGTH

Please note that when Min Length and / or Max Length are enabled, the scanner will only read bar codes that fall into those length parameters. Bar codes shorter or longer than specified will not be read. The default lengths for these are indicated in parentheses under the Min and Max bar codes for each symbology.

NOTES:

1. The scanner will beep three times as a reminder that a setting is not yet complete.
2. If you make a mistake, forget a step, etc., Scan RESET to start again.

RESET ➔



GROUP-21

SYMBOLOLOGIES: INDUSTRIAL 2 OF 5, MATRIX 2 OF 5



INDUSTRIAL 2 OF 5






MATRIX 2 OF 5



APPENDIX

FULL ASCII (Code 39) NUMERIC TABLE

0		1	
2		3	
4		5	
6		7	
8		9	

SETTING PROCEDURE

MIN / MAX LENGTH

STEP 1 - Scan: MIN LENGTH/ MAX LENGTH

STEP 2 - Scan: Two digits from Appendix.

STEP 3 - Scan: MIN LENGTH/ MAX LENGTH

Please note that when Min Length and / or Max Length are enabled, the scanner will only read bar codes that fall into those length parameters. Bar codes shorter or longer than specified will not be read. The default lengths for these are indicated in parentheses under the Min and Max bar codes for each symbology.

NOTES:

1. The scanner will beep three times as a reminder that a setting is not yet complete.
2. If you make a mistake, forget a step, etc., Scan RESET to start again.

RESET ➔



GROUP-22

SYMBOLOLOGIES: CODABAR



CODABAR



START / STOP



Example of ST (Start) / SP (Stop)

123456	Not Transmit ST/SP
A123456B	ST/SP: ABCD/ABCD
a123456b	ST/SP: abcd/abcd
A123456N	ST/SP: ABCD/TN*E
a123456n	ST/SP: abcd/tn*e



CLSI FORMAT

CLSI- Enable library space insertion. If you enable the CLSI format, this option inserts spaces in position 2, 7, 13 of the data string for use in library systems.

APPENDIX

FULL ASCII (Code 39) NUMERIC TABLE



SETTING PROCEDURE

MIN / MAX LENGTH

STEP 1 - Scan: MIN LENGTH/ MAX LENGTH

STEP 2 - Scan: Two digits from Appendix.

STEP 3 - Scan: MIN LENGTH/ MAX LENGTH

Please note that when Min Length and / or Max Length are enabled, the scanner will only read bar codes that fall into those length parameters. Bar codes shorter or longer than specified will not be read. The default lengths for these are indicated in parentheses under the Min and Max bar codes for each symbology.

NOTES:

1. The scanner will beep three times as a reminder that a setting is not yet complete.
2. If you make a mistake, forget a step, etc., Scan RESET to start again.

RESET ➔



GROUP-23

SYMBOLOLOGIES: ABC- CODABAR, CX- CODABAR



ON



OFF



SET INSERT DATA*

ABC- CODABAR



INSERT DATA- ON



INSERT DATA- OFF

* The data can be any alphanumerics of FULL ASCII Table (GROUP 33-41)

REMARK:

ABC-CODABAR (American Blood Commission). The ABC Code is an acronym for American Blood Commission. This bar code is a variant of the CODABAR Code developed for the use in the blood bank. This Code consists of two bar codes which are decoded in one read cycle. The code is concatenated when the stop character of the first bar code and the start character of the second bar code is a "D", these two "D" are not transmitted.



ON



OFF



SET INSERT DATA*

CX CODE- CODABAR



INSERT DATA- ON



INSERT DATA- OFF

* The data can be any alphanumerics of FULL ASCII Table (GROUP 33-41)

REMARK:

The CX-Code consists of two bar codes which are decoded in one read cycle, the code is concatenated when the stop character of the first bar code is a C, and the start character of the second bar code is a B. The B and C characters are not transmitted.

GROUP-24

SYMBOLOGIES: CODABAR COUPLING, ADJACENT REQUIRED



CODABAR COUPLING



ABC-Codabar and CX-Codabar have certain rules regarding the Stop Character of first bar code and the stop character of second bar code while in conjunction, while Codabar-Coupling is enabled, the data from any two Codabar bar codes can be coupled into one set of data without any limitations between the Stop character of first bar code and the Start character of second bar code. The Start and Stop characters associated with each bar code will be sent.

* The data can be any alphanumerics of FULL ASCII Table (GROUP 33-41)

ADJACENT REQUIRED

If CODABAR ADJACENT is enabled, the scanner will only read two adjacent Codabar bar codes; a single bar code will not be read.

NOTES:

1. Both ABC-Codabar and CX-Codabar can be enabled together, except when Codabar-Coupling is also enabled.
2. If ABC-Codabar, CX-Codabar, and Codabar-Coupling are all enabled at the same time, the scanner will read only Codabar-Coupling, that is, ABC-Codabar, CX-Codabar will be considered coupling formats.



SETTING PROCEDURE - SET INSERT DATA

Step 1- Scan SET INSERT DATA.

Step 2- Scan any combination of alphanumeric characters from FULL ASCII Table.

Step 3- Scan SET INSERT DATA.

RESET



NOTES:

1. The scanner will beep three times as a reminder that a setting is not yet complete.
2. If you make a mistake, forget a step, etc., Scan RESET to start again.

GROUP-25

SYMBOLOGIES: STANDARD & FULL ASCII CODE 39, CODE 32

STANDARD CODE 39 & FULL ASCII 39



NOTE:

The default for Code 39 is Standard Code 39. If Full ASCII Code 39 is enabled, Standard Code 39 will be automatically disabled.



CODE 32



APPENDIX

FULL ASCII (Code 39) NUMERIC TABLE



SETTING PROCEDURE

MIN / MAX LENGTH

STEP 1 - Scan: MIN LENGTH/ MAX LENGTH

STEP 2 - Scan: Two digits from Appendix.

STEP 3 - Scan: MIN LENGTH/ MAX LENGTH

Please note that when Min Length and / or Max Length are enabled, the scanner will only read bar codes that fall into those length parameters. Bar codes shorter or longer than specified will not be read. The default lengths for these are indicated in parentheses under the Min and Max bar codes for each symbology.

NOTES:

1. The scanner will beep three times as a reminder that a setting is not yet complete.
2. If you make a mistake, forget a step, etc., Scan RESET to start again.

RESET ➔



GROUP-26

SYBBOLOGIES FORMATTING: UPC-E



ADD ON SUPPLEMENT



NOTE:

If ADDENDA REQUIRED is set to ON, the scanner will only read an UPC-E bar code that has an addenda. At the same time please also scan +5 ON or +2 ON so the scanner will output a 5-digit or 2-digit addendum.

GROUP-27

SYMBOLOLOGIES: UPC-E SYSTEM NUMBER

UPC-E0



UPC-E1



NOTE:

Most UPC bar codes lead with 0 number systems, for these bar codes use UPC E(0) selection. For the bar codes that lead with the 1 number, use UPC E(1) selection.

UPC-E EXPAND TO UPC-A



NOTE:

1. If UPC-E EXPAND TO UPC A FORMAT is enabled, the output of UPC-A will be 12 digits.
2. The default output of UPC-A is 12 digits, if UPC-A EXPAND TO EAN13 is enabled, a zero will be added to in front of the bar code.

GROUP-28

SYMBOLOGIES FORMATTING: UPC- A



UPC-A EXPAND TO EAN-13



ADD ON SUPPLEMENT



NOTE:

If ADDENDA REQUIRED is set to ON, the scanner will only read an UPC-E bar code that has an addenda. At the same time please also scan +5 ON or +2 ON so the scanner will output a 5-digit or 2-digit addendum.

GROUP-29

SYMBOLOGIES FORMATTING: EAN 8



EAN-8



ADD ON SUPPLEMENT



NOTE:

If ADDENDA REQUIRED is set to ON, the scanner will only read an UPC-E bar code that has an addenda. At the same time please also scan +5 ON or +2 ON so the scanner will output a 5-digit or 2-digit addendum.

GROUP-30

SYMBOLOGIES FORMATTING: EAN13, ISBN, ISSN, ISMN



ADD ON SUPPLEMENT



NOTES:

1. If ADDENDA REQUIRED is set to ON, the scanner will only read an EAN-13 bar code that has an addenda.
2. Either ISSN or ISBN will be considered as an extension of EAN-13. If ISSN or ISBN needs to be read, EAN-13 must be enabled. If ISSN and ISBN need to be read with addenda, EAN-13 must be enabled with ADDENDA REQUIRED set to ON, and +2 ON or +5 ON must be enabled as well.



NOTE:

Both ISSN and ISBN are the extension codes of EAN-13. If scanner is required to read either ISSN or ISBN, EAN-13 must be enabled. Otherwise the scanner will not be able to read ISSN or ISBN.



GROUP-31

SYMBOLOLOGIES: EAN/UCC-128, CODE 128



ENABLE



DISABLE



CODE ID ENABLE



CODE ID DISABLE

EAN/ UCC-128



FUNC 1 CHAR SEND



FUNC 1 CHAR NOT SEND



DEFINE EAN 128

NOTES: DEFINE EAN 128

The first FNC1 character is translated to Jc1, and the second FNC1 character is translated to an ASCII <GS> character (scan from Group 41)

String format:

Jc1	DATA CHARACTERS	<GS>	DATA CHARACTERS
-----	-----------------	------	-----------------

Setting Procedure:

- 1: Scan DEFINE EAN128.
 - 2: Scan ASCII Code (Group 41)
 - 3: Scan DEFINE EAN128.
-

CODE 128



ENABLE



DISABLE



MIN LENGTH (5)



MAX LENGTH (48)

PDF417



ENABLE



DISABLE

GROUP-32

GS1 DataBar, LIMITED, EXPANDED

GS1 DataBar (RSS) - OMNI & STACKED

. N032\$



GS1 DataBar ENABLE

. N034\$



GS1 DataBar CHECK DIGIT SEND

. N036\$



GS1 DataBar PREFIX SEND

. N038\$



GS1 DataBar STACKED ENABLE

. P024\$



GS1 DataBar SET ID

. N033\$



GS1 DataBar DISABLE

. N035\$



GS1 DataBar CHECK DIGIT NOT SEND

. N037\$



GS1 DataBar PREFIX NOT SEND

. N039\$



GS1 DataBar STACKED DISABLE

GS1 DataBar (RSS) - LIMITED

. N010\$



GS1 DataBar LIMITED ENABLE

. N012\$



GS1 DataBar LIMITED CHECK DIGIT SEND

. N024\$



GS1 DataBar LIMITED PREFIX SEND

. P019\$



GS1 DataBar LIMITED SET ID

. N011\$



GS1 DataBar LIMITED DISABLE

. N013\$



GS1 DataBar LIMITED CHECK DIGIT NOT SEND

. N025\$



GS1 DataBar LIMITED PREFIX NOT SEND

GS1 DataBar (RSS) - EXPANDED

. N026\$



GS1 DataBar EXPANDED ENABLE

. N028\$



GS1 DataBar EXPANDED STACKED ENABLE

. N030\$



GS1 DataBar EXPANDED MIN LENGTH

. P020\$



GS1 DataBar EXPANDED SET ID

. N027\$



GS1 DataBar EXPANDED DISABLE

. N029\$



GS1 DataBar EXPANDED STACKED DISABLE

. N031\$



GS1 DataBar EXPANDED MAX LENGTH

GROUP-33

FULL ASCII TABLE (CODE 39) CONTROL CODES

%L		NUL
\$A		SOH
\$B		STX
\$C		ETX
\$D		EOT
\$E		ENQ
\$F		ACK
\$G		BEL
\$H		BS
\$I		HT
\$J		LF
\$K		VT
\$L		FF
\$M		CR
\$N		SO
\$O		SI

GROUP-34

FULL ASCII TABLE (CODE 39) CONTROL CODES

DLE	\$P 
DC1	\$Q 
DC2	\$R 
DC3	\$S 
DC4	\$T 
NAK	\$U 
SYN	\$V 
ETB	\$W 
CAN	\$X 
EM	\$Y 
SUB	\$Z 
ESC	%A 
FS	%B 
GS	%C 
RS	%D 
US	%E 
SP	

GROUP-35

FULL ASCII TABLE (CODE 39) SYMBOLS

+		+
-		-
.		.
\$		\$
%		%
/		/
%L		\
/ A		!
%V		@
/ C		#
%N		^
%S		~
/ F		&
/ J		*
%□		-
%H		=
%Q		

GROUP-36

FULL ASCII TABLE (CODE 39)
SYMBOLS

{	%P	
}	%R	
[%K	
]	%M	
(/ H	
)	/ I	
<	%G	
>	%I	
,	%W	
"	/ B	
'	/ G	
,	/ L	
;	%F	
:	/ Z	
?	%J	
DEL	%T	

GROUP-37

FULL ASCII TABLE (CODE 39)
UPPER CASE ALPHABETS

A  A

B  B

C  C

D  D

E  E

F  F

G  G

H  H

I  I

J  J

K  K

L  L

M  M


GROUP-38

FULL ASCII TABLE (CODE 39)
UPPER CASE ALPHABETS


N 

O 

P 

Q 

R 

S 

T 

U 

V 

W 

X 

Y 

Z 

GROUP-39

FULL ASCII TABLE (CODE 39)
LOWER CASE ALPHABETS

+A  a

+B  b

+C  c

+D  d

+E  e

+F  f

+G  g

+H  h

+I  i

+J  j

+K  k

+L  l

+M  m

GROUP-40

FULL ASCII TABLE (CODE 39)
LOWER CASE ALPHABETS

n 

o 

p 

q 

r 

s 

t 

u 

v 

w 

x 

y 

z 

GROUP-41

FULL ASCII TABLE (CODE 39) NUMBERS



0



1



2



3



4



5



6



7



















8



9

GROUP-42

FULL ASCII TABLE (CODE 39) FUNCTION KEYS

F1	\$TA	
F2	\$TB	
F3	\$TC	
F4	\$TD	
F5	\$TE	
F6	\$TF	
F7	\$TG	
F8	\$TH	
F9	\$TI	
F10	\$TJ	
F11	\$TK	
F12	\$TL	
Home	\$TM	
End	\$TN	
Enter (Numeric Key)	\$T+D	
App	\$T+□	

GROUP-43

FULL ASCII TABLE (CODE 39)
NAVIGATION KEYS

\$T0



Cursor Right

\$TP



Cursor Left

\$TQ



Cursor Up

\$TR



Cursor Down

\$TS



Page Up

\$TT



Page Down

\$TU



Tab

\$TV



Back Tab

\$TW



Esc

\$TX



Enter

\$TY



BS

\$TZ



Ins

\$T%K



Del

GROUP-44

FULL ASCII TABLE (CODE 39) MODIFIER KEYS



For UK Keyboard Special Character



Note:

- *1: When "Alt(Left)Make" is programmed, please scan "Alt(Left)Break" to resume barcode setting.
- *2: When "Shift(Left)Make" is programmed, please scan "Shift(Left)Break" to resume barcode setting.
- *3: When "Ctrl(Left)Make" is programmed, please scan "Ctrl(Left)Break" to resume barcode setting.



GROUP-45 TROUBLE SHOOTING

Our Barcode Scanners are simple to install and use.
Most operational issues can be attributed to:



INCORRECT INTERFACE CONNECTION
INCORRECT CONFIGURATION SETUP
POOR BARCODE QUALITY

GENERAL PROCEDURES

1. First, make sure the scanner is firmly connected to the host computer, when attached correctly, the scanner will emit one long beep. When the trigger is pressed, LED will flash.
2. Once the power is on, try scanning some sample bar codes from this user's guide. The scanner should beep and the LED should flash to indicate a good read in the default configuration. If reading the bar code does not result in a good read, there may have been a problem with the scanning technique or the interface configuration setting. Reset the scanner to default.
3. If the scanner indicates a good read, but there is no output of data to the monitor, please check the cabling connection.

KEYBOARD INTERFACES PROBLEMS

In general, the Keyboard Wedge interface is trouble free, but there is still something to check in the event of a problem:

Do you have the correct cable?

Most computers use an XT/AT-compatible keyboard. Be sure you have the proper cable for your computer.

Does the keyboard work?

Since the keyed-in data from keyboard must pass through the decoder, the cabling connections are correct if the keyboard is functioning.

Can your computer accept the data fast enough?

Your computer's BIOS has a feature related to keyboard typing speed. Try to set the Intercharacter Delay feature to stimulate the keystroke entry speed.

Does keyboard port supply enough power?

Most notebook computers do not supply enough power to the scanner. The symptom of insufficient power is a lower "good read" rate (since there is not enough power to properly support the scanning operation).



GROUP-47 TROUBLE SHOOTING

Is the proper symbology enabled?

Each bar code symbology can be individually enabled or disabled. It is suggested that you enable only those that you will be scanning, thereby eliminating the possibility of misreads from the scanning of other symbologies.

Does the selected bar code symbology configuration match the bar code(s) being read?

Scanned data from each bar code symbology can be restricted to eliminate the scanning of unused symbologies. The restrictions are individually set for each symbology.

POOR BAR CODE QUALITY

The third problem area has nothing to do with the scanner, but rather the printed quality of the bar code and/or the scanning technique employed.

TOLERANCE OF BAR CODE

A bar code may have a tolerance. Normally, the tolerances are caused by bar code font software or a printer. Software with a proven reputation should be chosen to generate bar codes. If the printed bar codes are distorted, the scanner might not recognize them.

It is very difficult to get a good read from a poor quality bar code unless it is scanned many times. As the quality of the symbology drops, the chances for undetected error increase. A bar code Check Digit Verification (CDV) should be used to check the quality of the suspect bar codes.

LABELS (PAPER & COLOR & PRINTER)

The light source of a bar code scanner is generally red, so there are some restrictions for the printing of labels. Care should be taken when choosing materials, especially color inks and papers. Sometimes the combination of the label color and the color of the ink can, in effect, blind the scanner. Media with a shiny surface will also cause reading difficulties for scanners.

Moreover, poor printing quality can also result in reading difficulties for the scanner. Bad printing may be caused by the type of printer used; dot matrix and inkjet printers will not procedure high quality bar codes. Also check to make sure the ink, ribbon, or toner in good supply.



GROUP-47 TROUBLE SHOOTING

Is the proper symbology enabled?

Each bar code symbology can be individually enabled or disabled. It is suggested that you enable only those that you will be scanning, thereby eliminating the possibility of misreads from the scanning of other symbologies.

Does the selected bar code symbology configuration match the bar code(s) being read?

Scanned data from each bar code symbology can be restricted to eliminate the scanning of unused symbologies. The restrictions are individually set for each symbology.

POOR BAR CODE QUALITY

The third problem area has nothing to do with the scanner, but rather the printed quality of the bar code and/or the scanning technique employed.

TOLERANCE OF BAR CODE

A bar code may have a tolerance. Normally, the tolerances are caused by bar code font software or a printer. Software with a proven reputation should be chosen to generate bar codes. If the printed bar codes are distorted, the scanner might not recognize them.

It is very difficult to get a good read from a poor quality bar code unless it is scanned many times. As the quality of the symbology drops, the chances for undetected error increase. A bar code Check Digit Verification (CDV) should be used to check the quality of the suspect bar codes.

LABELS (PAPER & COLOR & PRINTER)

The light source of a bar code scanner is generally red, so there are some restrictions for the printing of labels. Care should be taken when choosing materials, especially color inks and papers. Sometimes the combination of the label color and the color of the ink can, in effect, blind the scanner. Media with a shiny surface will also cause reading difficulties for scanners.

Moreover, poor printing quality can also result in reading difficulties for the scanner. Bad printing may be caused by the type of printer used; dot matrix and inkjet printers will not procedure high quality bar codes. Also check to make sure the ink, ribbon, or toner in good supply.

APPENDIX 1

DEFAULT TABLE 1

GROUP	PARAMETER	DEFAULT
1	Computer Type	PC-AT
	Interface	(depends on customer order)
	Setup Code	On
2	Reading Mode	Trigger
2.2	Bi-color Light Source	Green > Red
2.3	Magnetic Switch	On
	Green LED/ Supplement Light (CCD Scanner)	On
2.4	Deactivation Time (CCD & Laser Scanner)	3 Sec
	Same Code Interval (Laser Scanner)	30 Sec
	Idle Mode	Off
	Pre-Idle Time	1 Min
2.6	Connection Options	BT HID
2.8	Wireless ID	Wireless Scanner
2.9	Power Off Timeout	3 Min
2.10	SSP (Secure Simple Pairing)	Disable
	iOS Hotkey	Disable
2.11	Link Quality	Disable
	Batch Mode	Disable
2.13	SPP Pincode	1234
2.15	Memory Mode	Disable
	Data Output Method	Wireless
2.16	Data Format	<Item No.><Date><Time><Barcode Data>
	Field Separator	,
2.17	Date Format	DD/MM/YYYY
	Time Format	HH:MM:SS
3	Beep Tone Mode 2.1k	Beep Medium
	Beep Tone Mode 2.7k	Beep Medium
	Terminator	CR(KB, USB); CR+LF(RS232)
4	Send Data Length	Off
	Preamble & Postamble	None
5	Accuracy Adjustment	0
6	Label Type Positive/ Negative	Disable
6~9	Enable & Disable Code ID	Off
10	Interblock Delay	0ms
	Intercharacter Delay	140us
11	Keyboard Layout	English(USA)
	Caplock	Off
	Numeric Key	Alphanumeric Key
12	Baud Rate	9600
	Data Bits & Parity	8 Bits None
13	Stop Bits	1 stop bit
	Handshaking	None
	ACK/NAK	Off
	Flow Control Timeout	1 Sec
	BCC	Off
14	Level duration of Mini Width	200us
	Polarity of Idle Condition	High
	Output of Wand Emulation	Bar High/ Space Low
	Wave Form	Full ASCII 39
	Idle Mode	Off
	Pre-Idle Time	1 Min
15	Enable and Disable Symbologies	
	Code 32	Disable
	China Postal Code	Enable
	UK Plessey Code	Disable
	Industrial 2 of 5	Disable
	Matrix 2 of 5	Disable
	Interleaved 2 of 5	Enable
	Code 128	Enable
	Codabar	Enable
Telepen	Disable	

APPENDIX 1

DEFAULT TABLE 2

GROUP	PARAMETER	DEFAULT	
16	UPC-A	Enable	
	UPC-E	Enable	
	EAN-8	Enable	
	EAN-13	Enable	
	MSI	Disable	
	Code 39	Enable	
	Code 11	Disable	
	Code 93	Disable	
	EAN-128	Enable	
IATA	Disable		
17	1	GS1 Databar	Disable
		GS1 Databar Stacked	Enable
		GS1 Databar Limited	Disable
		GS1 Databar Expanded	Disable
		GS1 Databar Expanded Stacked	Enable
	PDF417	Disable	
	2	China Post Code	
		Enable/Disable	Enable
		Check Digits	Disable CDV
		Min Length	11 digits
Max Length		48 digits	
18	1	MSI	
		Enable/Disable	Disable
		Check Digits	CDV & send CD
		Check Digits Mode	Single MOD 10
	2	UK Plessey	
		Enable/Disable	Disable
19	1	Code 93	
		Enable/Disable	Disable
		Min Length	6 digits
		Max Length	48 digits
	2	Telepen	
		Enable/Disable	Disable
		Telepen ASCII/ Number	Number
	3	IATA	
		Enable/Disable	Disable
		Check Digits	Disable CDV
		Min Length	6 digits
		Max Length	48 digits
20	1	Interleaved 2 of 5	
		Enable/Disable	Enable
		Check Digits	Disable CDV
		First/ last digit suppressed	No suppressed
		Min Length	6 digits
	Max Length	48 digits	
	2	Code II	
		Enable/Disable	Disable
		Check Digits	Disable CDV
		Min Length	6 digits
Max Length		32 digits	
21	1	Industrial 2 of 5	
		Enable/Disable	Disable
		Check Digits	Disable CDV
		Min Length	6 digits
	Max Length	48 digits	
	2	Matrix 2 of 5	
		Enable/Disable	Disable
		Check Digits	Disable CDV
		Min Length	6 digits
		Max Length	48 digits

APPENDIX 1

DEFAULT TABLE 3

GROUP	PARAMETER	DEFAULT	
22	Codabar		
	Enable/Disable	Enable	
	Check Digits	Disable CDV	
	Min Length	6 digits	
	Max Length	48 digits	
	ST/SP; Abcd/abcd, abcd/tn*c, ABCD/ABCD,ABCD/TN*C	ABCD/ABCD	
	Start(ST)/Stop(SP)	Send	
	CLSI Format	On	
23	1	ABC-Codabar	
		ON/OFF	Off
		Insert Data	Off
	2	CX-Codabar	
		ON/OFF	Off
	Insert Data	Off	
24	Codabar-Coupling		
	ON/OFF	Off	
	Insert Data	Off	
	Adjacent Required	Off	
25	1	Code 39	
		Full ASCII 39 Enable/Disable	Enable
		Check Digits	Disable CDV
		Start/Stop	Not Send
		Min Length	1 digit
		Max Length	48 digits
	2	Code 32	
		Enable/Disable	Disable
		Leading	send
	Tailing	send	
26	UPC-E		
	Enable/Disable	Enable	
	Check Digits	Send	
	Lead Digits	Send	
	Add a space	Off	
	Addenda required	Off	
	+5 On/Off	Off	
	+2 On/Off	Off	
27	UPC-E systems number		
	UPC E(0) On/Off	On	
	UPC E(1) On/Off	Off	
	UPC-E expand to UPC-A	Disable	
	UPC-A expand to EAN-13	Disable	
28	UPC-A		
	Enable/Disable	Enable	
	Check Digits	Send	
	Lead Digits	Send	
	Add a space	Off	
	Addenda required	Off	
	+5 On/Off	Off	
	+2 On/Off	Off	
29	EAN-8		
	Enable/Disable	Enable	
	Check Digits	Send	
	Lead Digits	Send	
	Add a space	Off	
	Addenda required	Off	
	+5 On/Off	Off	
	+2 On/Off	Off	

APPENDIX 1

DEFAULT TABLE 4

GROUP	PARAMETER	DEFAULT	
30	EAN-13		
	Enable/Disable	Enable	
	Check Digits	Send	
	Lead Digits	Send	
	Add a space	Off	
	Addenda required	Off	
	+5 On/Off	Off	
	+2 On/Off	Off	
	ISSN On/Off	Off	
	ISBN	Off	
31	1	EAN/UCC128	
		Enable/Disable	Enable
		Code ID	Disable
		Func 1 Char Send	Not Send
	2	Code 128	
		Enable/Disable	Enable
		Check Digits	Disable CDV
		Min Length	5 digits
		Max Length	48 digits
	3	PDF417	
		Enable/Disable	Disable
	32	GS1 Databar	
GS1 Databar Check Digit			
GS1 Databar Prefix			
GS1 Databar Stacked			
GS1 Databar Limited			
GS1 Databar Limited Check Digit			
GS1 Databar Limited Prefix			
GS1 Databar Expanded			
GS1 Databar Expanded Stacked			


APPENDIX 2

Cable Pin Assignment INTERFACES:

1. TTL, Wand Emulation


1.1) AMP (D-Sub 9Pin):

Pin	Signal
2	Data
7	GND
9	+5VCC



1.2) Din 5 male (240 degree):

Pin	Signal
1	+ 5VCC
2	Data
3	GND
4	N/A
5	N/A




2. Keyboard Interface:

Type of connector:


2.1) PS/2 Mini Din6 Female:

Pin	Signal
1	PC Data
2	NC
3	GND
4	+5VCC
5	PC-Clk
6	NC



2.2) PS/2 Mini Din6 Male:


Pin	Signal
1	KB- Data
2	NC
3	GND
4	+5VCC
5	KB-Clk
6	NC



Type of connector:


2.3) PC-AT: Din 5 Male:

Pin	Signal
1	KB-Clk
2	KB-Data
3	NC
4	GND
5	+5VCC



2.4) PC-AT: Din 5 Female:


Pin	Signal
1	PC-Clk
2	PC-Data
3	NC
4	GND
5	+5VCC



3.RS232 Interfaces:


3.1) DB9F

Pin	Signal
2	TXD(Out)
3	RXD(In)
5	GND
7	CTS(In)
8	RTS(Out)
9	+5VCC



3.2) DB25F

Pin	Signal
2	RXD(In)
3	TXD(Out)
4	CTS(In)
5	RTS(Out)
7	GND
16	+5VCC
25	+5VCC



APPENDIX 3

BAR CODE TEST CHART

DENSITY	NARROW mm(mil)	WIDE mm(mil)	CHAR.GAP mm(mil)	N/W RATIO
MEDIUM DENSITY	0.25(10)	0.625(25)	0.25(10)	1/2.5

MEDIUM DENSITY

NW-7
(CODABAR)



b\$:/.+00123B

CODE-39



CODE-39 TEST

Interleaved
2of5



9876543210

UPC



EAN



APPENDIX 3

BAR CODE TEST CHART

DENSITY	NARROW mm(mil)	WIDE mm(mil)	CHAR.GAP mm(mil)	N/W RATIO
LOW DENSITY	0.33(13)	0.825(32.5)	0.33(13)	1/2.5

LOW DENSITY



C9876543210D



CODE-39 TEST



0012345690

