

C2G 1ft (0.3m) Cat6 Non-Booted Unshielded (UTP) Ethernet Network Patch Cable - Gray Part No. CG-04064



For fast Ethernet and Gigabit computer networks that require bandwidth-intensive voice, data, or video distribution applications. Meets all Cat6 TIA/EIA standards, and drastically reduces both impedance and structural return loss (SRL). Each of the individual pairs is bonded together to help maintain the twist-spacing throughout the line right up to the termination point. Constructed from high quality copper cable, this design minimizes Near-End Crosstalk (NEXT) levels. Available in a variety of colors to easily color-code your network installation.

Features & Benefits

Designed for network adapters, hubs, switches, routers, HDBaseT applications and more

Meets all Cat6 TIA/EIA requirements for supporting a wide variety of applications

Available in a variety of colors to color-code a network

Supports 10 Gigabit networks up to 180ft for fast data transmission and maximum performance and supports 1 Gigabit up to 328ft

Constructed with unshielded twisted pair (UTP) wires, designed to counter EMI, RFI, and crosstalk

Specifications

General Info				
Product Line	C2G	Color	Gray	
UPC Number	757120040644	Country Of Origin	Vietnam	
Features	PoE (Power Over Ethernet)	Application Sector	Residential, Commercial, Industrial	
Warranty Type	Lifetime	Туре	Cable	
Dimensions				
Product Length US	1.0 FT	Cable Length	1 ft	
Technical Information				
Jacket Material	PVC (Polyvinyl Chloride)	Wire Gauge	24 AWG	

Cable Type	Ethernet Patch Cable, Unbooted, Unshielded (UTP)	Jacket Rating	Standard / Non-Rated
Adapter Rear	RJ-45 Male	Adapter Front	RJ-45 Male