

1m (3ft) Certified SuperSpeed USB 3.0 A to B Cable - M/M

Product ID: USB3CAB1M



The USB3CAB1M 1-meter USB 3.0 A-to-B cable provides a high quality connection between peripheral devices that feature a USB 3.0 type-B port, such as hard drive enclosures, card readers, docking stations and video capture devices and a USB-capable computer.

This cable is USB-IF certified to USB 3.0 specifications, guaranteeing a dependable, long-lasting connection to your USB 'B' devices and is backed by StarTech.com's Lifetime Warranty.

Certifications, Reports and Compatibility

Applications

• Connect a SuperSpeed USB 3.0 Type B peripheral (hard drive enclosure, card reader, docking station, video capture device, etc.) to a USB 3.0 capable desktop, laptop, or server

Features

- 1x USB 'A' male connector
- 1x USB 'B' male connector
- USB-IF Certified SuperSpeed USB 3.0
- Data transfer rates up to 5Gbps
- Aluminum-Mylar Foil with Braided Shielding
- Molded connectors with strain relief



• Backward compatible with USB 2.0

Hardware

Warranty Lifetime

Connector Plating Nickel

Cable Jacket Material PVC - Polyvinyl Chloride

Cable Shield Material Aluminum-Mylar Foil with Braid

Performance

Type and Rate USB 3.0 - 5 Gbit/s

Connector(s)

Connector A USB Type-A (9 pin) USB 3.0 (5 Gbps)

Connector B USB Type-B (9 pin) USB 3.0

Environmental

Operating Temperature -20C to 80C (-4F to 176F)

Storage Temperature -20C to 80C (-4F to 176F)

Physical Characteristics

Color Black

Connector Style Straight

Wire Gauge 24/28 AWG

Cable Length 39.4 in [100 cm]

Product Length 39.4 in [100.0 cm]

Product Width 0.0 in [0.0 mm]

Product Height 0.0 in [0.0 mm]

Weight of Product 1.7 oz [49.0 g]

Packaging Information

Package Quantity 1



Package Length 8.7 in [22.0 cm]

Package Width 7.9 in [20.0 cm]

Package Height 0.6 in [16.0 mm]

Shipping (Package)

Weight

2.0 oz [58.0 g]

What's in the

Box

Included in Package 1m USB 3.0 Certified A to B Cable - M/M

^{*}Product appearance and specifications are subject to change without notice.