

Thunderbolt 3 PCIe Expansion Chassis with DisplayPort - PCIe x16

Product ID: TB31PCIEX16



This Thunderbolt3 PCIe expansion chassis lets you add a PCI Express card to your laptop or desktop computer, through an external Thunderbolt 3 connection. The chassis also features a DisplayPort video output, so you can connect an additional monitor to your laptop, and supports Thunderbolt 3 daisy chaining, so you can expand your workstation even further.

The Thunderbolt 3 PCIe chassis makes it easy to expand your system with the capabilities you need to work at peak productivity. You can add many types of PCI Express cards, such as a PCIe USB 3.1/3.0/2.0 and USB-C, SSD, network, eSATA, FireWire or video capture cards. And, with the speed and bandwidth support of Thunderbolt 3 and PCIe 3.0, you can enjoy many of the same port additions you would from the PCI Express expansion slots of a desktop system.

The external PCIe enclosure features a dedicated DisplayPort output that lets you add an additional display to your laptop or desktop computer. The enclosure features a second Thunderbolt 3 (USB-C) port, that you can use to connect a secondary display (a USB-C video adapter may be required). With multiple extended displays, you can work more efficiently by multitasking faster, and avoid the hassle of continually repositioning several open windows or programs.

You can also use the second Thunderbolt 3 port to connect additional Thunderbolt, USB and DisplayPort devices to your system. You can daisy chain up to six Thunderbolt 3 devices and expand your workstation to suit your specific requirements.

Thunderbolt 3 is the fastest connection available, which means you don't have to deal with the performance bottlenecks of a slower connection, and can accomplish more in the same amount of time.

At up to 40Gbps this Thunderbolt 3 expansion chassis gives you the throughput to add displays to your laptop, access files quickly, and work without disruptions. It's easy to access and edit large uncompressed files such as videos and images on the fly, making it ideal for dynamic on-site production.

The TB31PCIEX16 is backed by a StarTech.com 2-year warranty and free lifetime technical support.



Certifications, Reports and Compatibility

Applications

- Add many types of PCIe cards, such as a PCIe USB 3.1/3.0/2.0 and USB-C, SSD, network, eSATA, FireWire or video capture cards to your Thunderbolt 3 laptop
- Add an external PCIe card to your Thunderbolt 3 equipped desktop computer

Features

- TAA Compliant
- Increased productivity with Thunderbolt 3 and up to 40Gbps bandwidth twice the speed of Thunderbolt 2 (20Gbps) and eight times faster than USB 3.0 (5Gbps)
- Supports one 4K DisplayPort monitor, and a second extended monitor display through the Thunderbolt 3 (USB-C) port
- Daisy chain up to six Thunderbolt 3 devices
- Supports 5K Thunderbolt displays
- · Supports half-length and dual-slot PCIe card standards at all heights, with standard profile slot brackets
- Provides a x16 4 lane PCIe 3.0 slot or interface
- Durable aluminum construction
- Works on Mac and Windows computers
- Internal 60 mm cooling fan

Hardware		
	Warranty	2 Years
	Fan(s)	Yes
	Fans	60 mm
	Ports	3
	Air Flow Rate	14.06 CFM
	Noise Level	24.55 dB
	Interface	Thunderbolt



Bus Type Thunderbolt 3

Card Type Standard Profile

Industry Standards Thunderbolt 3

Fan Bearing Type Sleeve Bearing

Chipset ID Intel - Alpine Ridge DSL6540

Performance

Maximum Data Transfer

Rate

40 Gbps (Thunderbolt 3)

Bandwidth 3.94 GB/s (x4 PCIe 3.0)

Type and Rate Thunderbolt 3 - 40 Gbit/s

Connector(s)

Internal Ports PCI Express x16

External Ports Thunderbolt 3 USB-C (24-pin) (40Gbps)

DisplayPort (20 pin)

Software

OS Compatibility Windows 7, 8, 8.1, 10
br / >macOS 10.12 - 10.15, 11.0

Special Notes / Requirements

System and Cable Requirements

Thunderbolt 3 equipped computer with a Thunderbolt 3 port.

Note The expansion chassis does not support video cards.

This expansion chassis does not provide full power delivery but will provide 15W of power, resulting in a slow charge to some laptops, such as MacBook Pro. When the dock is connected to your host laptop, a charging icon may appear on your laptop's screen. This is only sufficient enough to charge your laptop in sleep state, and charging will require an extended time period.

5K support can only be achieved using a Thunderbolt 3 5K monitor.

DisplayPort 5K monitors will not work with this expansion chassis.

A 4K-capable display is required to achieve 4K x 2K resolution (4K is also known as 4K x 2K).

Certain monitors may be limited to 4K at 30Hz when connecting through DisplayPort. These monitors include the following models: Dell P2715Q, Viewsonic VX2475Smhl-4K, Philips 288P6LJEB, LG



31MU97C-B, Asus PB287Q (these models will need to be set to 4K at 30Hz).

When connecting a display to one of the Thunderbolt 3 USB-C ports, a USB-C video adapter might be required depending on the input of your display.

Secondary Thunderbolt 3 port can also be used to connect USB 3.1 (10Gbps) USB-Type C devices, such as USB 3.1 Hubs. Backwards compatible with USB 3.0 (USB 3.1 Gen 1), and USB 2.0.

		tn	

LED Indicators

Power(Blue)

Power

Power Source AC Adapter Included

Input Voltage 100 - 240 AC

Input Current 2A

Output Voltage 12V DC

Output Current 5.417A

Center Tip Polarity Positive

Plug Type N

Power Consumption (In

Watts)

Environmental

Operating Temperature 5C to 35C (41F to 95F)

Storage Temperature -20C to 50C (-4F to 122F)

Humidity 20-80%RH

Physical Characteristics

Color Black

Material Aluminum and Steel

Cable Length 19.7 in [50 cm]

Product Length 11.0 in [28 cm]

Product Width 5.6 in [14.2 cm]



	Product Height	3.2 in [82 mm]	
	Weight of Product	3.6 lb [1.6 kg]	
Packaging Information			
	Package Length	14.2 in [36 cm]	
	Package Width	11.4 in [29 cm]	
	Package Height	5.7 in [14.5 cm]	
	Shipping (Package) Weight	6.9 lb [3.1 kg]	
What's in the Box			
	Included in Package	Thunderbolt 3 PCIe expansion box	
		Thunderbolt 3 cable	
		rubber feet	
		universal power adapter (NA/JP, UK, EU, ANZ)	
		quick-start guide	

^{*}Product appearance and specifications are subject to change without notice.