

## ThinkSystem PM893 Read Intensive SATA 6Gb SSDs Product Guide

The ThinkSystem PM893 Read Intensive SATA SSDs are general-purpose SSDs based on the Samsung PM893 platform and are available in capacities ranging from 480GB to 7.86TB. They are engineered for greater performance and endurance in a cost-effective design, and to support a broader set of workloads.



Figure 1. Lenovo ThinkSystem 2.5" PM893 Read Intensive SATA 6Gb Hot Swap SSD

### Did you know?

Lenovo Read Intensive SSDs are suitable for read-intensive and general-purpose data center workloads. Overall, these SSDs provide outstanding IOPS/watt and cost/IOPS for enterprise solutions and are an excellent choice for applications such as web serving, hyperscale cloud, content delivery, caching, databases, and analytics.

## Part number information

The following table lists the part numbers and feature codes.

Table 1. Ordering part numbers and feature codes

Part number	Feature code	Description
2.5-inch hot-swap drives for ThinkSystem		
4XB7A72438	BM8B	ThinkSystem 2.5" PM893 480GB Read Intensive SATA 6Gb HS SSD
4XB7A72439	BM8A	ThinkSystem 2.5" PM893 960GB Read Intensive SATA 6Gb HS SSD
4XB7A72440	BM89	ThinkSystem 2.5" PM893 1.92TB Read Intensive SATA 6Gb HS SSD
4XB7A72441	BM88	ThinkSystem 2.5" PM893 3.84TB Read Intensive SATA 6Gb HS SSD
4XB7A72442	BM87	ThinkSystem 2.5" PM893 7.68TB Read Intensive SATA 6Gb HS SSD

The part numbers include the following items:

- One 2.5-inch solid-state drive in a ThinkSystem hot-swap tray
- Documentation flyer

## Features

The PM893 SSDs have the following features:

- Low cost, read-intensive SSD from Samsung
- 2.5-inch industry standard form factor with hot-swap tray
- 6 Gbps SATA interface
- Advanced ECC Engine and End-to-End Data Protection
- Samsung V6 (128-layer) TLC V-NAND stacks the vertical NAND layers in three dimensions, solving the cell-to-cell interference that causes data corruption in planar NAND.
- Protect data integrity from unexpected power loss with Samsung's advanced power-loss protection (PLP) architecture
- Supports Self-Monitoring, Analysis and Reporting Technology (S.M.A.R.T).
- Dynamic Thermal Guard Protection protects the SSD from overheating by automatically controlling the speed of the CPU relative to its core temperature

Read-Intensive (Entry) SSDs and Write-Intensive (Performance) SSDs have similar read and write IOPS performance, but the key difference between them is their endurance (or lifetime) (that is, how long they can perform write operations because SSDs have a finite number of program/erase (P/E) cycles). Read-Intensive SSDs have a better cost/IOPS ratio but lower endurance compared to Write-Intensive SSDs. SSD write endurance is typically measured by the number of program/erase (P/E) cycles that the drive incurs over its lifetime, listed as the total bytes of written data (TBW) in the device specification.

The TBW value assigned to a solid-state device is the total bytes of written data (based on the number of P/E cycles) that a drive can be guaranteed to complete (% of remaining P/E cycles = % of remaining TBW). Reaching this limit does not cause the drive to immediately fail. It simply denotes the maximum number of writes that can be guaranteed. A solid-state device will not fail upon reaching the specified TBW. At some point based on manufacturing variance margin, after surpassing the TBW value, the drive will reach the end-of-life point, at which the drive will go into a read-only mode.

Because of such behavior by Read-Intensive solid-state drives, careful planning must be done to use them only in read-intensive or mix-use up to 70% read/30% write environments to ensure that the TBW of the drive will not be exceeded before the required life expectancy.

For example, the 3.84TB PM893 drive has an endurance of 7,008 TB of total bytes written (TBW). This means that for full operation over five years, write workload must be limited to no more than 3,840 GB of writes per day, which is equivalent to 1.0 full drive writes per day (DWPD). For the device to last three years, the drive write workload must be limited to no more than 6,400 GB of writes per day, which is equivalent to 1.7 full drive writes per day.

## Technical specifications

The following table lists the technical specifications of the PM893 SSDs.

Table 2. Technical specifications

Feature	480 GB drive	960 GB drive	1.92 TB drive	3.84 TB drive	7.68 TB drive
Interface	6 Gbps SATA	6 Gbps SATA	6 Gbps SATA	6 Gbps SATA	6 Gbps SATA
Capacity	480 GB	960 GB	1.92 TB	3.84 TB	7.68 TB
SED encryption	None	None	None	None	None
Endurance (total bytes written)	876 TB	1752 TB	3504 TB	7008 TB	14,016 TB
Endurance (drive writes per day for 5 years)	1 DWPD	1 DWPD	1 DWPD	1 DWPD	1 DWPD
Data reliability (UBER)	< 1 in 10 <sup>17</sup> bits read	< 1 in 10 <sup>17</sup> bits read	< 1 in 10 <sup>17</sup> bits read	< 1 in 10 <sup>17</sup> bits read	< 1 in 10 <sup>17</sup> bits read
MTBF	2,000,000 hours	2,000,000 hours	2,000,000 hours	2,000,000 hours	2,000,000 hours
IOPS reads (4 KB blocks)	98,000	98,000	98,000	98,000	98,000
IOPS writes (4 KB blocks)	29,000	31,000	31,000	31,000	31,000
Sequential read rate (128 KB blocks)	560 MBps	560 MBps	560 MBps	560 MBps	560 MBps
Sequential write rate (128 KB blocks)	530 MBps	530 MBps	530 MBps	530 MBps	530 MBps
Read latency (random)	120 µs	120 µs	120 µs	120 µs	120 µs
Write latency (random)	40 µs	40 µs	40 µs	40 µs	40 µs
Shock, non-operating	1,500 G (Max) at 0.5 ms	1,500 G (Max) at 0.5 ms	1,500 G (Max) at 0.5 ms	1,500 G (Max) at 0.5 ms	1,500 G (Max) at 0.5 ms
Vibration, non-operating	20 G (20-2000 Hz)	20 G (20-2000 Hz)	20 G (20-2000 Hz)	20 G (20-2000 Hz)	20 G (20-2000 Hz)
Typical power (R/W)	2.1 W / 3.2 W	2.2 W / 3.2 W	2.2 W / 3.2 W	2.2 W / 3.2 W	2.2 W / 3.2 W

## Server support

The following tables list the ThinkSystem servers that are compatible.

Table 3. Server support (Part 1 of 2)

Part Number	Description	Edge		1S Intel V2			2S Intel V2				AMD			Dense V2			4S V2	8S			
		SE350 (7Z46 / 7D1X)	SE450 (7D8T)	ST150 V2 (7D8K / 7D8J)	ST250 V2 (7D8G / 7D8F)	SR250 V2 (7D7R / 7D7Q)	ST650 V2 (7Z75 / 7Z74)	SR630 V2 (7Z70 / 7Z71)	SR650 V2 (7Z72 / 7Z73)	SR670 V2 (7Z22 / 7Z23)	SR635 (7Y98 / 7Y99)	SR655 (7Y00 / 7Z01)	SR645 (7D2Y / 7D2X)	SR665 (7D2W / 7D2V)	SD630 V2 (7D1K)	SD650 V2 (7D1M)	SD650-N V2 (7D1N)	SN550 V2 (7Z69)	SR850 V2 (7D31 / 7D32)	SR860 V2 (7Z59 / 7Z60)	SR950 (7X11 / 7X12)
4XB7A72438	ThinkSystem 2.5" PM893 480GB Read Intensive SATA 6Gb HS SSD	N	N	N	N	N	Y	Y	Y	Y	Y	Y	Y	N	N	N	Y	Y	Y	Y	Y
4XB7A72439	ThinkSystem 2.5" PM893 960GB Read Intensive SATA 6Gb HS SSD	N	N	N	N	N	Y	Y	Y	Y	Y	Y	Y	N	N	N	Y	Y	Y	Y	Y
4XB7A72440	ThinkSystem 2.5" PM893 1.92TB Read Intensive SATA 6Gb HS SSD	N	N	N	N	N	Y	Y	Y	Y	Y	Y	Y	N	N	N	Y	Y	Y	Y	Y
4XB7A72441	ThinkSystem 2.5" PM893 3.84TB Read Intensive SATA 6Gb HS SSD	N	N	N	N	N	Y	Y	Y	Y	Y	Y	Y	N	N	N	Y	Y	Y	Y	Y
4XB7A72442	ThinkSystem 2.5" PM893 7.68TB Read Intensive SATA 6Gb HS SSD	N	N	N	N	N	Y	Y	Y	Y	Y	Y	Y	N	N	N	Y	Y	Y	Y	Y

Table 4. Server support (Part 2 of 2)

Part Number	Description	1S Intel V1			2S Intel V1								Dense V1			4S V1			
		ST50 (7Y48 / 7Y50)	ST250 (7Y45 / 7Y46)	SR150 (7Y54)	SR250 (7Y52 / 7Y51)	ST550 (7X09 / 7X10)	SR530 (7X07 / 7X08)	SR550 (7X03 / 7X04)	SR570 (7Y02 / 7Y03)	SR590 (7X98 / 7X99)	SR630 (7X01 / 7X02)	SR650 (7X05 / 7X06)	SR670 (7Y36 / 7Y37)	SD530 (7X21)	SD650 (7X58)	SN550 (7X16)	SN850 (7X15)	SR850 (7X18 / 7X19)	SR850P (7D2F / 2D2G)
4XB7A72438	ThinkSystem 2.5" PM893 480GB Read Intensive SATA 6Gb HS SSD	N	Y	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	Y	Y	Y	Y	Y
4XB7A72439	ThinkSystem 2.5" PM893 960GB Read Intensive SATA 6Gb HS SSD	N	Y	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	Y	Y	Y	Y	Y
4XB7A72440	ThinkSystem 2.5" PM893 1.92TB Read Intensive SATA 6Gb HS SSD	N	Y	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	Y	Y	Y	Y	Y
4XB7A72441	ThinkSystem 2.5" PM893 3.84TB Read Intensive SATA 6Gb HS SSD	N	Y	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	Y	Y	Y	Y	Y
4XB7A72442	ThinkSystem 2.5" PM893 7.68TB Read Intensive SATA 6Gb HS SSD	N	Y	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	Y	Y	Y	Y	Y

## Operating system support

SSDs operate transparently to users, storage systems, applications, databases, and operating systems.

Operating system support is based on the controller used to connect to the drives. Consult the controller product guide for more information:

- RAID controllers: <https://lenovopress.com/servers/options/raid>
- SAS HBAs: <https://lenovopress.com/servers/options/hba>

## Warranty

The ThinkSystem PM893 Read Intensive SATA SSDs carry a one-year, customer-replaceable unit (CRU) limited warranty. When the SSDs are installed in a supported server, these drives assume the system's base warranty and any warranty upgrades.

Solid State Memory cells have an intrinsic, finite number of program/erase cycles that each cell can incur. As a result, each solid state device has a maximum amount of program/erase cycles to which it can be subjected. The warranty for Lenovo solid state drives (SSDs) is limited to drives that have not reached the maximum guaranteed number of program/erase cycles, as documented in the Official Published Specifications for the SSD product. A drive that reaches this limit may fail to operate according to its Specifications.

## Physical specifications

The PM893 SSDs have the following physical specifications:

Dimensions and weight (approximate, without the hot-swap tray):

- Height: 7 mm (0.3 in.)
- Width: 70 mm (2.8 in.)
- Depth: 100 mm (4.0 in.)
- Weight: 58 g (2.1 oz)

Shipping dimensions and weight for the 2.5-inch drives (approximate):

- Height: 63 mm (2.5 in.)
- Width: 133 mm (5.2 in.)
- Depth: 174 mm (6.9 in.)
- Weight (hot-swap): 433 g (1.0 lb)

## Operating environment

The PM893 SSDs are supported in the following environment:

- Temperature: 0 - 70 °C (32 - 158 °F)
- Relative humidity: 5 - 95% (noncondensing)
- Maximum altitude: 3,050 m (10,000 ft)

## Agency approvals

The PM893 SSDs conform to the following regulations:

- UL
- TUV
- FCC
- CE Mark
- C-Tick Mark
- BSMI (Taiwan)
- KCC (Korea EMI)

## Related publications and links

For more information, see the following documents:

- Samsung Data Center SSDs product page:  
<https://www.samsung.com/semiconductor/ssd/datacenter-ssd/>
- Lenovo ThinkSystem storage options product web page  
<https://lenovopress.com/lp0761-storage-options-for-thinksystem-servers>
- Lenovo ThinkSystem SSD Portfolio comparison:  
<https://lenovopress.com/lp1261-lenovo-thinksystem-ssd-portfolio>
- Lenovo server options product page  
<https://www.lenovo.com/us/en/data-center/options/>
- Lenovo RAID Introduction  
<https://lenovopress.com/lp0578-lenovo-raid-introduction>
- Lenovo RAID Management Tools and Resources  
<https://lenovopress.com/lp0579-lenovo-raid-management-tools-and-resources>

## Related product families

Product families related to this document are the following:

- [Drives](#)

## Notices

Lenovo may not offer the products, services, or features discussed in this document in all countries. Consult your local Lenovo representative for information on the products and services currently available in your area. Any reference to a Lenovo product, program, or service is not intended to state or imply that only that Lenovo product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any Lenovo intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any other product, program, or service. Lenovo may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to:

Lenovo (United States), Inc.  
8001 Development Drive  
Morrisville, NC 27560  
U.S.A.  
Attention: Lenovo Director of Licensing

LENOVO PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. Lenovo may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

The products described in this document are not intended for use in implantation or other life support applications where malfunction may result in injury or death to persons. The information contained in this document does not affect or change Lenovo product specifications or warranties. Nothing in this document shall operate as an express or implied license or indemnity under the intellectual property rights of Lenovo or third parties. All information contained in this document was obtained in specific environments and is presented as an illustration. The result obtained in other operating environments may vary. Lenovo may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Any references in this publication to non-Lenovo Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this Lenovo product, and use of those Web sites is at your own risk. Any performance data contained herein was determined in a controlled environment. Therefore, the result obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurements may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

© Copyright Lenovo 2022. All rights reserved.

This document, LP1542, was created or updated on January 17, 2022.

Send us your comments in one of the following ways:

- Use the online Contact us review form found at:  
<https://lenovopress.lenovo.com/LP1542>
- Send your comments in an e-mail to:  
[comments@lenovopress.com](mailto:comments@lenovopress.com)

This document is available online at <https://lenovopress.lenovo.com/LP1542>.



## Trademarks

Lenovo and the Lenovo logo are trademarks or registered trademarks of Lenovo in the United States, other countries, or both. A current list of Lenovo trademarks is available on the Web at <https://www.lenovo.com/us/en/legal/copytrade/>.

The following terms are trademarks of Lenovo in the United States, other countries, or both:

Lenovo®

ThinkSystem

The following terms are trademarks of other companies:

Intel® is a trademark of Intel Corporation or its subsidiaries.

Other company, product, or service names may be trademarks or service marks of others.