

Overview

Lasting durability meets streamlined design

Deliver exceptional experiences to customers and value to your business with the sleek, functional HP Engage One Essential. This elegant system offers rugged durability with the performance you need, and a range of deployment and accessory options so you can tailor it for your specific operations.

Resiliently crafted, defined by design

Conduct business confidently with a fanless, fully sealed design to protect from dust and liquid intrusion (IP54 certified[1]). And with its sleek look, this device complements any environment.

Design your ideal system

Configure a system for your unique business with integrated accessory options[3] that help keep counters clutter free—magnetic stripe reader, barcode scanner, fingerprint reader and more—and a choice of stands, VESA® mounts and customer facing displays. [4]

Essential everyday performance

Get all the performance you need, without unnecessary frills. Blaze through shifts with an Intel® processor[5], a range of ports to connect everyday devices, and fast, reliable network connectivity through wired ethernet or Wi-Fi. 5[6].

- [1] HP Engage One Essential All-in-One System is IP54 Certified. Test results are not a guarantee of future performance under these test conditions. Accidental damage requires an optional HP Accidental Damage Protection Care Pack.
- [3] Embedded peripherals excluding the barcode scanner and 6.6 inch customer facing display must be configured at purchase.
- [4] Stands and VESA® Hubs must be configured at purchase.
- [5] Multi-core is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. Performance and clock frequency will vary depending on application workload and your hardware and software configurations. Intel's numbering, branding and/or naming is not a measurement of higher performance.
- [6] Wireless access point and internet service required and sold separately. Availability of public wireless access points limited. Wi-Fi 5 (802.11 ac) is backwards compatible with prior 802.11 specs.

Specifications

Form factor	All-in-one
Operating system	Windows 10 IoT Enterprise
Processor family	Intel® Celeron® processor
Processor	Intel® Celeron® N6211 (1.2 GHz base frequency, up to 3.0 GHz with Intel® Turbo Boost Technology, 1.5 MB L2 cache, 2 cores 2 threads) ^[6,7]
Memory	4 GB DDR4-3200 MHz RAM (1 x 4 GB)
Memory Slots	1 SODIMM
Internal Storage	128 GB PCIe® TLC SSD
Graphics	Integrated
Graphics (integrated)	Intel® UHD Graphics
Display	35.6 cm (14") diagonal, FHD (1920 x 1080), touch, IPS, anti-glare, 250 nits, 45% NTSC
Display	14" diagonal, FHD (1920 x 1080), touch, IPS, anti-glare, 250 nits, 45% $\rm NTSC^{[12]}$
Audio	Integrated HD audio with Realtek ALC3247 codec with standards internal speakers, digital mic and 1W mono speaker
Minimum dimensions (W x D x H)	$35.40 \times 22.00 \times 26.67$ cm (head unit and essential stand); $35.40 \times 22.00 \times 28.38$ cm (head unit and advanced stand); $35.40 \times 22.00 \times 28.38$ cm (head unit and advanced swivel stand); $35.40 \times 4.84 \times 21.50$ cm (head unit and pro VESA hub); $35.40 \times 5.55 \times 21.50$ cm (head unit and essential VESA hub)
Minimum dimensions (W x D x H)	$13.94 \times 8.66 \times 10.5$ in (head unit and essential stand); $13.94 \times 8.66 \times 11.17$ in (head unit and advanced stand); $13.94 \times 8.66 \times 11.17$ in (head unit and advanced swivel stand); $13.94 \times 2.19 \times 8.47$ in (head unit and essential VESA hub); $13.94 \times 1.9 \times 8.47$ in (head unit and pro VESA hub)
Weight	4.35 kg (head unit and essential stand); 4.80 kg (head unit and advanced stand); 5.40 kg (head unit and advanced swivel stand); 3.00 kg (head unit and pro VESA hub); 2.8 kg (head unit and essential VESA hub)
Weight	9.59 lb (head unit and essential stand); 10.58 lb (head unit and advanced stand); 11.91 lb (head unit and advanced swivel stand); 6.17 lb (head unit and essential VESA hub); 6.61 lb (head unit and pro VESA hub)
Ports	1 RJ-45; 2 SuperSpeed USB Type-A 5Gbps signaling rate; 2 USB 2.0 Type-A
Expansion slots	1 M.2 2280
Wireless	Realtek RTL8821CE 802.11a/b/g/n/ac (1x1) Wi-Fi® and Bluetooth® 4.2 wireless card
Power	150 W external Smart AC power adapter, up to 89% efficiency, active PFC (advanced stand and advanced with swivel stand and pro VESA hub)
Sustainable impact specifications	Ocean-bound plastic in speaker enclosure; 30% post-consumer recycled plastic; Low Halogen; Outside box and corrugated cushions are 100% sustainably sourced and recyclable

Security management	Power-on password (via BIOS); Trusted Platform Module TPM 2.0 Embedded Security Chip; USB enable/disable (via BIOS); Security lock slot; Device security; Secure Boot; Administrator password (via BIOS); AMI BIOS ^[14]
UPC number	(ABA) 196548402342; (ABM) 196548402359

Additional specifications

Barcode reader Optional HP Engage One Pro Integrated Barcode Scanner Bluetooth version Bluetooth* 4.2 Cor Ebony black or ceramic white Color Ebony black or ceramic white Color gamut 45% NTSC Display brightness 250 Display brightness uom nits Display panel technology IPS Display resolution (pixels) 1920 x 1080 Display size (diagonal) uom " Display size (diagonal, imperial) 14 Display size (diagonal, metric) 35.6 Display surface treatment anti-glare Display surface treatment anti-glare Magnetic stripe reader 10 biplay head Memory Location Display head Memory Location 1 x 4 GB Memory layout (slots & size) 1 x 4 GB Memory size uom GB Memory size uom GB Memory type 2000 Memory speed 3200 Memory type DDR4 Memory type DDR4 Memory type		
Cettifications and compliances CEL Color Ebony black or ceramic white Color gamut 45% NTSC Display brightness 250 Display brightness uom nits Display panel technology IPS Display resolution (pixels) 1920 x 1080 Display size (diagonal) uom " Display size (diagonal, imperial) 14 Display size (diagonal, metric) 35.6 Display surface treatment anti-glare Display touchscreen type touch screen V/O Port location Display head Magnetic stripe reader Optional integrated magnetic stripe reader; Single-head, bi-directional, and encryption capable ^[6] Memory layout (slots & size) 1 x 4 GB Memory module type SODIMM Memory size uom GB Memory speed 3200 Memory type DDR4 Number of memory slots 1 Operating humidity range 10 to 90% RH Operating temperature range 0 to 35°C Operating temperature range 1 to 95°F Pr	Barcode reader	Optional HP Engage One Pro Integrated Barcode Scanner
Color Ebony black or ceramic white Color gamut 45% NTSC Display brightness 250 Display brightness uom nits Display panel technology IPS Display resolution (pixels) 1920 x 1080 Display resolution standard FHD Display size (diagonal, imperial) 14 Display size (diagonal, metric) 35.6 Display size (diagonal, metric) cm Display surface treatment anti-glare Display bright touchscreen type touch screen V/O Port Location Display head Magnetic stripe reader Optional integrated magnetic stripe reader; Single-head, bi-directional, and encryption capable (s) Memory layout (slots & size) 1 x 4 6B Memory module type 500IMM Memory size uom GB Memory speed 3200 Memory speed uom MHz Memory type DDR4 Number of memory slots 1 Operating humidity range 10 to 90% RH Operating temperature range 0 to 35°C Operating t	Bluetooth version	Bluetooth® 4.2
Color gamut 45% NTSC Display brightness 250 Display brightness um nits Display panel technology 1PS Display resolution (pixels) 1920 x 1080 Display resolution standard FHD Display size (diagonal, imperial) 14 Display size (diagonal, imperial) 14 Display size (diagonal, metric) 25.6 Display size (diagonal, metric) 26 Display size (diagonal, metric) 27 Display surface treatment 27 Display surface treatment 37 Display surface treatment 37 Display touchscreen type 40 Memory layout (slots & size) 1 x 4 GB Memory layout (slots & size) 1 x 4 GB Memory size uom 48 Memory size uom 48 Memory speed uom 48 Memory type 50 Display surface treatment 3200 Memory type 50 Display head 50 Memory type 50 Display head 61 Memory type 50 Display head 61 Memory type 50 Display head 61 Memory type 50 Display head 70 Display head 70 Memory size uom 68 Memory size uom 68 Memory speed uom 41 Memory type 50 Display head 70 Display head 70 Display head 70 Display head 70 Memory speed uom 61 MHz Memory type 50 Display head 70 Display head 70 Display head 70 Display head 70 Memory size uom 68 Memory speed uom 68 Memory type 70 Display head 70 Memory speed uom 70 MHz Memory type 70 Display head 70 The This This This This This This This This	Certifications and compliances	CEL
Display brightness uom nits Display panel technology IPS Display nesolution (pixels) 1920 x 1080 Display resolution standard FHD Display size (diagonal) uom " Display size (diagonal, imperial) 14 Display size (diagonal, metric) 35.6 Display surface treatment anti-glare Display surface treatment anti-glare Display touchscreen type touch screen I/O Port location Display head Magnetic stripe reader Optional integrated magnetic stripe reader; Single-head, bi-directional, and encryption capable ⁽⁶⁾ Memory layout (slots & size) 1 x 4 GB Memory module type SODIMM Memory size uom GB Memory speed 3200 Memory type DDR4 Number of memory slots 1 Operating humidity range 10 to 90% RH Operating temperature range 32 to 95°F Processor Brand Intel® Processor base frequency 1.2	Color	Ebony black or ceramic white
Display brightness uom nits Display panel technology IPS Display resolution (pixels) 1920 x 1080 Display resolution standard FHD Display size (diagonal) uom " Display size (diagonal, imperial) 14 Display size (diagonal, metric) 35.6 Display size (diagonal, metric) 35.6 Display size (diagonal, metric) anti-glare Display surface treatment anti-glare Display surface treatment Display touch screen V/O Port location Display head Magnetic stripe reader Optional integrated magnetic stripe reader; Single-head, bi-directional, and encryption capable ^[6] Memory layout (slots & size) 1 x 4 GB Memory size 4 Memory size 4 Memory size 0GB Memory speed 0GB Memory speed 0GB Memory speed 0GB Memory type DDR4 Number of memory slots 1 Operating humidity range 0 to 35°C Operating temperature range 0 to 59°F Processor Brand Intel® Processor base frequency 1.2	Color gamut	45% NTSC
Display panel technology IPS Display resolution (pixels) 1920 x 1080 Display resolution standard FHD Display size (diagonal) uom " Display size (diagonal, imperial) 14 Display size (diagonal, metric) uom 35.6 Display size (diagonal, metric) uom cm Display surface treatment anti-glare Display touchscreen type touch screen I/O Port location Display head Memory layout (slots & size) 1 x 4 GB Memory module type 50DIMM Memory size uom GB Memory speed 3200 Memory type DDR4 Number of memory slots 1 Operating humidity range 10 to 90% RH Operating temperature range 32 to 95°F Processor Brand Intel® Processor base frequency 1.2	Display brightness	250
Display resolution (pixels) Display resolution standard FHD Display size (diagonal uom Display size (diagonal, imperial) Display size (diagonal, imperial) Display size (diagonal, metric) Uom Display size (diagonal, metric) Uom Display size (diagonal, metric) Uom Display surface treatment Display surface treatment Display touchscreen type Uo Port location Display head Magnetic stripe reader Display bead Display ut (slots & size) Display bead Memory layout (slots & size) 1 x 4 GB Memory module type SODIMM Memory size Memory size uom GB Memory speed Memory speed Memory speed Memory speed Memory type DDR4 Number of memory slots 1 Operating temperature range Operating temperature range Display Memory speed Uo 95°F Processor Brand Intel® Processor Brand Intel® Processor Brand Intel® Processor Brand Display speed A HA HA HA HED HA HA HA HA HA HA HA HA HA H	Display brightness uom	nits
Display resolution standard FHD Display size (diagonal) uom " Display size (diagonal, imperial) 14 Display size (diagonal, metric) uom 35.6 Display size (diagonal, metric) uom cm Display surface treatment anti-glare Display touchscreen type touch screen I/O Port location Display head Memory layout (slots & size) 1 x 4 G8 Memory module type 50DIMM Memory size 4 Memory speed GB Memory speed uom MHz Memory type DDR4 Number of memory slots 1 Operating humidity range 0 to 90% RH Operating temperature range 0 to 95°F Operating temperature range 32 to 95°F Processor Brand Intel® Processor base frequency 1.2	Display panel technology	IPS
Display size (diagonal, imperial) Display size (diagonal, imperial) Display size (diagonal, metric) Umbassize (diagonal) Umbassize (diagon	Display resolution (pixels)	1920 x 1080
Display size (diagonal, imperial) Display size (diagonal, metric) Usplay size (diagonal, metric) Usplay size (diagonal, metric) Usplay surface treatment Display surface treatment Display touchscreen type VO Port location Display head Magnetic stripe reader Memory layout (slots & size) Display touchs & size) Display head Memory module type SODIMM Memory size 4 Memory size Memory size Memory speed Memory speed Memory speed Memory type DDR4 Number of memory slots Derating temperature range Operating temperature range Drocessor Brand Intel® Processor Brand Intel® Page A Intel® Processor Brand Display size (diagonal, metric) Intel® Display size (diagonal, metric) Intel® Display size (diagonal, metric) Intel® In	Display resolution standard	FHD
Display size (diagonal, metric) Display size (diagonal, metric) uom Display surface treatment Display touchscreen type VO Port location Magnetic stripe reader Memory layout (slots & size) Memory size Memory size Memory size Memory speed Memory speed Memory speed Memory type DDR4 Number of memory slots Operating humidity range Operating temperature range Operating temperature range Processor Brand Intel® Processor Brand Intel® Processor Brand Intel® Com Intel®	Display size (diagonal) uom	n
Display size (diagonal, metric) uom Display surface treatment anti-glare Display touchscreen type touch screen I/O Port location Display head Magnetic stripe reader Optional integrated magnetic stripe reader; Single-head, bi-directional, and encryption capable [6] Memory layout (slots & size) 1 × 4 GB Memory module type SODIMM Memory size uom GB Memory speed 3200 Memory speed wom MHz Memory type DDR4 Number of memory slots 1 Operating humidity range 10 to 90% RH Operating temperature range 22 to 95°F Processor Brand Intel® Processor Brand 1.2	Display size (diagonal, imperial)	14
uom Cm Display surface treatment anti-glare Display touchscreen type touch screen I/O Port location Display head Magnetic stripe reader Optional integrated magnetic stripe reader; Single-head, bi-directional, and encryption capable ^[6] Memory layout (slots & size) 1 x 4 GB Memory module type SODIMM Memory size uom GB Memory speed 3200 Memory type DDR4 Number of memory slots 1 Operating humidity range 10 to 90% RH Operating temperature range 0 to 35°C Operating temperature range 32 to 95°F Processor Brand Intel® Processor base frequency 1.2	Display size (diagonal, metric)	35.6
Display touchscreen type I/O Port location Magnetic stripe reader Memory layout (slots & size) Memory size Memory size uom Memory speed Memory speed Memory speed Memory type DDR4 Number of memory slots Operating temperature range Processor Brand Processor base frequency Display head Operating temperature range Display head Optional integrated magnetic stripe reader; Single-head, bi-directional, and encryption capable [6] At 8B Optional integrated magnetic stripe reader; Single-head, bi-directional, and encryption capable [6] At 8B At		cm
I/O Port location Display head Magnetic stripe reader Optional integrated magnetic stripe reader; Single-head, bi-directional, and encryption capable [6] Memory layout (slots & size) 1 x 4 GB Memory module type SODIMM Memory size 4 Memory size uom GB Memory speed 3200 Memory type DDR4 Number of memory slots 1 Operating humidity range 0 to 90% RH Operating temperature range 0 to 95°F Processor Brand Intel® Processor base frequency 1.2	Display surface treatment	anti-glare
Magnetic stripe reader Optional integrated magnetic stripe reader; Single-head, bi-directional, and encryption capable [6] Memory layout (slots & size) 1 × 4 GB Memory module type SODIMM Memory size 4 Memory speed 3200 Memory speed uom MHz Memory type DDR4 Number of memory slots 1 Operating humidity range 0 to 90% RH Operating temperature range 0 to 35°C Operating temperature range 32 to 95°F Processor Brand Intel® Processor base frequency 1.2	Display touchscreen type	touch screen
Magnetic stripe readerand encryption capable [6]Memory layout (slots & size)1 x 4 GBMemory module typeSODIMMMemory size4Memory size uomGBMemory speed3200Memory speed uomMHzMemory typeDDR4Number of memory slots1Operating humidity range10 to 90% RHOperating temperature range0 to 35°COperating temperature range32 to 95°FProcessor BrandIntel®Processor base frequency1.2	I/O Port location	Display head
Memory module typeSODIMMMemory size4Memory size uomGBMemory speed3200Memory speed uomMHzMemory typeDDR4Number of memory slots1Operating humidity range10 to 90% RHOperating temperature range0 to 35°COperating temperature range32 to 95°FProcessor BrandIntel®Processor base frequency1.2	Magnetic stripe reader	
Memory size4Memory size uomGBMemory speed3200Memory speed uomMHzMemory typeDDR4Number of memory slots1Operating humidity range10 to 90% RHOperating temperature range0 to 35°COperating temperature range32 to 95°FProcessor BrandIntel®Processor base frequency1.2	Memory layout (slots & size)	1 x 4 GB
Memory size uomGBMemory speed3200Memory speed uomMHzMemory typeDDR4Number of memory slots1Operating humidity range10 to 90% RHOperating temperature range0 to 35°COperating temperature range32 to 95°FProcessor BrandIntel®Processor base frequency1.2	Memory module type	SODIMM
Memory speed3200Memory speed uomMHzMemory typeDDR4Number of memory slots1Operating humidity range10 to 90% RHOperating temperature range0 to 35°COperating temperature range32 to 95°FProcessor BrandIntel®Processor base frequency1.2	Memory size	4
Memory speed uomMHzMemory typeDDR4Number of memory slots1Operating humidity range10 to 90% RHOperating temperature range0 to 35°COperating temperature range32 to 95°FProcessor BrandIntel®Processor base frequency1.2	Memory size uom	GB
Memory typeDDR4Number of memory slots1Operating humidity range10 to 90% RHOperating temperature range0 to 35°COperating temperature range32 to 95°FProcessor BrandIntel®Processor base frequency1.2	Memory speed	3200
Number of memory slots Operating humidity range 10 to 90% RH Operating temperature range Oto 35°C Operating temperature range 32 to 95°F Processor Brand Intel® Processor base frequency 1.2	Memory speed uom	MHz
Operating humidity range10 to 90% RHOperating temperature range0 to 35°COperating temperature range32 to 95°FProcessor BrandIntel®Processor base frequency1.2	Memory type	DDR4
Operating temperature range 0 to 35°C Operating temperature range 32 to 95°F Processor Brand Intel® Processor base frequency 1.2	Number of memory slots	1
Operating temperature range 32 to 95°F Processor Brand Intel® Processor base frequency 1.2	Operating humidity range	10 to 90% RH
Processor Brand Intel® Processor base frequency 1.2	Operating temperature range	0 to 35℃
Processor base frequency 1.2	Operating temperature range	32 to 95°F
	Processor Brand	Intel®
Processor cache 1.5 MB L2	Processor base frequency	1.2
	Processor cache	1.5 MB L2

Processor core	2
Processor family	Celeron [®]
Processor frequency UOM	GHz
Processor frequency technology	Intel® Turbo Boost Technology
Processor maximum frequency	3.0
Processor maximum frequency uom	GHz
Processor model	N6211
Processor threads	2
Storage capacity	128
Storage capacity uom 01	GB
Storage interface 01	PCIe [®]
Storage memory technology 01	TLC
Storage type	SSD
Storage type 01	SSD
UNSPSC code	43211505
Wireless Model	RTL8821CE
Wireless antenna	1x1
Wireless standard	802.11a/b/g/n/ac
Wireless supplier	Realtek

[6] Multi-core is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. Performance and clock frequency will vary depending on application workload and your hardware and software configurations. Intel's numbering, branding and/or naming is not a measurement of higher performance.

[7] Intel® Turbo Boost performance varies depending on hardware, software and overall system configuration. See http://www.intel.com/technology/turboboost/ for more information.

[12] Actual brightness will be lower with touch screen.

[14] Security Lock Slot available only for Advanced or Advanced Swivel Stands.

Disclaimer — Copyright

Intel, the Intel logo, Core, Celeron and Pentium are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries. Microsoft and Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. Linux® is the registered trademark of Linus Torvalds in the U.S. and other countries. AMD is a trademark of Advanced Micro Devices, Inc. Wi-fi 5 is a trademark of Wi-Fi Alliance®. ENERGY STAR® is a registered trademark of the U.S. Environmental Protection Agency.

© Copyright 2023 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements

accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Generated by Dynamic Collateral Tool – (ww-en) – Apr 26, 2023 6:42 AM UTC+0000