

# FARGO® HDP6600

<b>Print Method:</b>	HDP® Dye-Sublimation / Resin Thermal Transfer
<b>Resolution:</b>	600 dpi (23.6 dots/mm)
<b>Colors:</b>	Up to 16.7 million / 256 shades per pixel
<b>Print Ribbon Options:</b>	<ul style="list-style-type: none"> <li>• Full-color with resin black, YMCK*, 750 prints</li> <li>• Full-color with two resin black panels, YMCKK*, 600 prints</li> <li>• Full-color with fluorescing and resin black, YMCKF*, 600 prints</li> <li>• Full-color with resin black and heat seal panel for difficult-to-print surfaces, YMCKH*, 600 prints</li> <li>• Resin black, K*, 3000 prints</li> </ul>
<b>HDP Film Options:</b>	Clear, 1500 prints
<b>Overlamine Options:</b>	PolyGuard™ LMX Overlaminates are 1.0 mil thick, CR-80 patch size and come in rolls of 1000 prints. Options include full patch, half patch, UV resistant full patch, UV resistant half patch, left side cutout for smart chip, UV resistant left side cutout for smart chip, and High Secure Orbit design (universal orientation). All overlaminates are available in clear, standard holographic design or custom holographic design.
<b>Print Speed:**</b>	Batch Mode: <ul style="list-style-type: none"> <li>• Up to 230 cards per hour / 16 seconds per card (YMCK* with transfer)</li> <li>• Up to 126 cards per hour / 29 seconds per card (YMCKK* with transfer)</li> </ul>
<b>Accepted Standard Card Sizes:</b>	CR-80 (3.375"L x 2.125"W / 85.6mmL x 54mmW)
<b>Print Area:</b>	Over-the-edge on CR-80 cards
<b>Accepted Card Thickness:</b>	.030" (30 mil) to .040" (40 mil) / .762mm to 1.01mm
<b>Accepted Card Types:</b>	ABS, PVC, PET, PETG, proximity, smart and mag stripe cards, polycarbonate. Note: ABS and PVC cards are not recommended for use within the HDP6600 Lamination Module
<b>Input Card Cartridge Capacity:</b>	100 cards (.030" / .762mm)
<b>Output Hopper Card Capacity:</b>	200 cards (.030" / .762mm)
<b>Card Cleaning:</b>	Replaceable cleaning roller (included with each print ribbon)
<b>Memory</b>	1 GB RAM
<b>Display:</b>	User-friendly, SmartScreen™ Graphical OLED Control Panel
<b>Software Drivers:</b>	Windows® 7 / 10 / 11 / Server 2012 / Server 2016 / Server 2019 / Server 2022
<b>Encoding Options</b>	Supported smart card and magnetic stripe technologies: 125kHz (HID Prox) reader; 13.56 MHz (iCLASS® Standard/SE/SR/Seos, MIFARE Classic®, MIFARE Plus®, MIFARE DESFire® EV1, ISO 14443 A/B, ISO 15693) read/write encoder; contact smart card encoder reads from and writes to all ISO7816 1/2/3/4 memory and microprocessor smart cards (T=0, T=1) as well as synchronous cards; ISO magnetic stripe encoding, dual high- and low-coercivity, tracks 1, 2 and 3.
<b>Supported Access Control Credential Programming</b>	iCLASS® Standard/SE/SR/Seos, MIFARE Classic®, MIFARE DESFire® EV1, HID Prox (Also see the FARGO HDP6600 Card Encoding Modules Datasheet for additional information)
<b>Interface:</b>	USB 2.0, Ethernet (100 Mbps) with internal print server (IPv4- and IPv6-compatible; with support for SNMPv3)
<b>Operating Temperature:</b>	65° to 90° F / 18° to 32° C
<b>Humidity:</b>	20 - 80% non-condensing
<b>Dimensions:</b>	<ul style="list-style-type: none"> <li>• HDP6600: 13.0"H x 14.5"W x 12.0"D / 330mmH x 368mmW x 305mmD</li> <li>• HDP6600 + Dual-Sided Module: 13.0"H x 19.75"W x 12.0"D / 330mmH x 502mmW x 305mmD</li> <li>• HDP6600 Single-Sided + One Material Lam Module: 14.0"H x 30.5"W x 12.0"D / 356mmH x 775mmW x 305mmD</li> <li>• HDP6600 + Dual-Sided Module + One Material or Two Material Lam Module: 14.0"H x 35.75"W x 12.0"D / 356mmH x 908mmW x 305mmD</li> <li>• One Material or Two Material Lam Module: 14.0"H x 16.0"W x 9.5"D / 356mmH x 406mmW x 241mmD</li> </ul>
<b>Weight:</b>	<ul style="list-style-type: none"> <li>• HDP6600: 21.0 lbs. / 9.5 kg</li> <li>• HDP6600 + Dual-Sided Module: 24.6 lbs. / 11.2 kg</li> <li>• HDP6600 Single-Sided + One Material Lam Module: 35.7 lbs. / 16.2 kg</li> <li>• HDP6600 + Dual-Sided Module + One Material or Two Material Lam Module: 39.3 lbs. / 17.9 kg</li> <li>• One Material or Two Material Lam Module: 14.7 lbs. / 6.7 kg</li> </ul>
<b>Certifications***:</b>	UL, CE, FCC, BSMI, MIC, EAC, RCM, CCC, KCC, S-Mark
<b>Supply Voltage:</b>	100-240 VAC, 2.5A max
<b>Supply Frequency:</b>	50 Hz / 60 Hz
<b>Environmental/Energy Saving Feature</b>	GreenCircle® Certified card printer (base models only without encoders)
<b>Data Security</b>	AES-256 Data Encryption, Resin Scramble Data Protection, Password Protection
<b>Warranty:</b>	<ul style="list-style-type: none"> <li>• Printer - Three years**** including one year of free printer loaner support with option to purchase a second year of printer loaner support (U.S. only)</li> <li>• Printhead - Lifetime****; unlimited card passes</li> </ul>
<b>FARGO Secure Materials:</b>	FARGO Card Printer/Encoders require highly specialized media to function properly. To maximize printed card quality and durability, print-head life and printer/encoder reliability, use only HID Secure Materials. HID warranties are void, where not prohibited by law, when non-HID Secure Materials are used.

\* Indicates the ribbon type and the number of ribbon panels printed where Y=Yellow, M=Magenta, C=Cyan, K=Resin Black, I=Inhibit, F=Fluorescing, H=Heat Seal

\*\* Print speed indicates an approximate print speed and is measured from the time a card drops into the output hopper to the time the next card drops into the output hopper. Print speeds do not include encoding time or the time needed for the PC to process the image. Process time is dependent on the size of the file, the printhead resolution, the CPU, amount of RAM and the amount of available resources at the time of the print.

\*\*\* Please contact your HID Global Sales Representative or local HID Integrator for additional certification information

\*\*\*\* Three-year warranty available on printers and lifetime warranty available on printheads with completion of online printer registration. (Two-year warranty standard on both printer and printheads without online printer registration.)



hidglobal.com

North America: +1 512 776 9000 | Toll Free: 1 800 237 7769  
Europe, Middle East, Africa: +44 1440 714 850  
Asia Pacific: +852 3160 9800 | Latin America: +52 (55) 9171-1108

For more global phone numbers click here

© 2023 HID Global Corporation/ASSA ABLOY AB. All rights reserved.

2023-08-28-si-fargo-hdp6600-spec-en PLT-03894

Part of ASSA ABLOY



Learn about HID Global's green initiative @  
hidglobal.com/green

SPECIFICATIONS SHEET