

### Overview

### HP EliteBook 650 15.6 inch G10 Notebook PC



#### Left

- |  |  |
|--|--|
| 1. Internal Microphones (2)                      | 7. Clickpad  |
| 2. Webcam LED (Optional)                         | 8. Smartcard Reader (Optional)                                     |
| 3. Camera Shutter (Only available with webcam)   | 9. SuperSpeed USB Type-A 5Gbps signaling rate port (USB 3.2 Gen 1) |
| 4. 5MP IR, HD TNR or HD TNR IR Camera (Optional) | 10. Ethernet Port (RJ-45)  |
| 5. IR Camera LED (Optional)                      | 11. Nano Security Lock Slot (Lock sold separately)                 |
| 6. NFC Sensor                                    |  |

### Overview



#### Right

1. Power Button Key
  2. Speakers
  3. Power Connector
  4. Thunderbolt™ 4 with USB4 Type-C® 40Gbps signaling rate (USB Power Delivery, DisplayPort™ 1.4) <sup>1</sup>
  5. SuperSpeed USB Type-C® 10Gbps signaling rate (USB Power Delivery, DisplayPort™ 1.4)
  6. SuperSpeed USB Type-A 5Gbps signaling rate port (USB 3.2 Gen 1) (Powered Port)
  7. HDMI 2.1 Port (Cable not included)
  8. Audio Combo Jack
  9. External SIM Card Slot (Optional)
  10. Touch Fingerprint Sensor (Select Models)
1. SuperSpeed USB 20Gbps is not available with Thunderbolt™ 4

### Overview

#### At a Glance

- Choice of 13th generation Intel® Core™ i7, i5 and i3 processors
- Preinstalled with Windows 11 versions or FreeDOS
- Optional NVIDIA® GeForce® RTX2050 discrete graphics with 4 GB DDR6 dedicated video memory
- Fast and upgradeable dual channel DDR4 SODIMM memory up to 64 GB
- Choice of 39.6 cm (15.6") diagonal HD, Ultra Wide Viewing Angle FHD, Touch or Non-Touch screen option
- Features quiet and responsive HP Keyboard with the HP Programmable key and backlit options
- Choice of solid state drives up to 2 TB
- Multi-layered security with HP SureStart Gen7, HP Privacy Camera, HP Wolf Security (Includes HP Sure Sense and HP Sure Click), HP Secure Erase, Sure Run Gen5, Sure Recover Gen5, Touch Fingerprint reader, and Tamper Lock]
- Supports wireless options for connectivity on the go including gigabit-speed Wi-Fi® 6e and CAT16 4G/LTE WWAN
- Supports fast charging (50% in 30 minutes) with no impact on battery recharge cycles
- Designed to support HP docking options
- Passed MIL-STD 810H tests<sup>1</sup>
- Battery life up to 13 hours and 15 minutes
- Optimize your video calls with a 5MP+IR camera, HD+IR/HD camera and temporal noise reduction that adjusts to the lighting in your environment.
- 180° synchronized hinge allows the EliteBook to lay completely flat, without lifting the keyboard, and includes everyone with visibility from multiple angles.
- Can be wiped up to 1000 times with common household cleaning wipes<sup>2</sup>
- Synchronized hinge allows the EliteBook to ProBook to open to 177° +/- 3° without lifting the keyboard and offers visibility from multiple angles.

1. MIL-STD 810GH is not intended to demonstrate fitness of U.S. Department of Defense contract requirements or for military use. Test results are not a guarantee of future performance under these test conditions. Accidental damage requires an optional HP Accidental Damage Protection Care Pack.

2. See wipe manufacturer's instructions for disinfecting and the HP cleaning guide for HP tested wipe solutions at <http://h20195.www.2.hp.com/v2/GetDocument.aspx?docname=4AA7-7610ENW>

**NOTE: See important legal disclosures for all listed specs in their respective features sections.**

### Technical Specifications

#### PRODUCT NAME

HP EliteBook 650 15.6 inch G10 Notebook PC

#### OPERATING SYSTEMS

##### Preinstalled

- Windows 11 Pro <sup>1</sup>
- Windows 11 Pro Education <sup>1</sup>
- Windows 11 Home - HP recommends Windows 11 Pro for Business <sup>1</sup>
- Windows 11 Home Single Language – HP recommends Windows 11 Pro for Business <sup>1</sup>
- Windows 11 Pro (Windows 11 Enterprise or Windows 10 Enterprise available with a Volume Licensing Agreement) <sup>1</sup>
- Windows 11 Pro (preinstalled with Windows 10 Pro Downgrade)<sup>1,2</sup>
- FreeDOS

1. Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows is automatically updated and enabled. High speed internet and Microsoft account required. ISP fees may apply and additional requirements may apply over time for updates. See <http://www.windows.com>.

2. This system is preinstalled with Windows 10 Pro software and also comes with a license for Windows 11 Pro software and provision for recovery software. You may only use one version of the Windows software at a time. Switching between versions will require you to uninstall one version and install the other version. You must back up all data (files, photos, etc.) before uninstalling and installing operating systems to avoid loss of your data.

#### PROCESSORS

| Processor<br>3,4,5,6,7 | Cores | Number of P-cores | Number of E-cores | Threads | L3 Cache | Max Turbo Frequency |         | Base Frequency |         | Intel SIPP/vPro® Enterprise | Intel vPro® Essentials |
|------------------------|-------|-------------------|-------------------|---------|----------|---------------------|---------|----------------|---------|-----------------------------|------------------------|
|                        |       |                   |                   |         |          | P-cores             | E-cores | P-cores        | E-cores |                             |                        |
| Intel® Core™ i7-1370P  | 14    | 6                 | 8                 | 20      | 24 MB    | 5.2 GHz             | 3.9 GHz | 1.9 GHz        | 1.4 GHz | X                           |                        |
| Intel® Core™ i7-1365U  | 10    | 2                 | 8                 | 12      | 12 MB    | 5.2 GHz             | 3.9 GHz | 1.8 GHz        | 1.3 GHz | X                           |                        |
| Intel® Core™ i7-1355U  | 10    | 2                 | 8                 | 12      | 12 MB    | 5.0 GHz             | 3.7 GHz | 1.7 GHz        | 1.2 GHz |                             |                        |
| Intel® Core™ i5-1350P  | 12    | 4                 | 8                 | 16      | 12 MB    | 4.7 GHz             | 3.5 GHz | 1.9 GHz        | 1.4 GHz | X                           |                        |
| Intel® Core™ i5-1345U  | 10    | 2                 | 8                 | 12      | 12 MB    | 4.7 GHz             | 3.5 GHz | 1.6 GHz        | 1.2 GHz | X                           |                        |
| Intel® Core™ i5-1335U  | 10    | 2                 | 8                 | 12      | 12 MB    | 4.6 GHz             | 3.4 GHz | 1.3 GHz        | 0.9 GHz |                             | X                      |
| Intel® Core™ i3-1315U  | 6     | 2                 | 4                 | 8       | 10 MB    | 4.5 GHz             | 3.3 GHz | 1.2 GHz        | 0.9 GHz |                             |                        |

3. Multicore is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. Performance and clock frequency will vary depending on application

### Technical Specifications

workload and your hardware and software configurations. Intel's numbering, branding and/or naming is not a measurement of higher performance.

4. Processor speed denotes maximum performance mode; processors will run at lower speeds in battery optimization mode.

5. Intel® Turbo Boost performance varies depending on hardware, software and overall system configuration. See [www.intel.com/technology/turboboost](http://www.intel.com/technology/turboboost) for more information.

6. In accordance with Microsoft's support policy, HP does not support the Windows 8 or Windows 7 operating system on products configured with Intel and AMD 7th generation and forward processors or provide any Windows 8 or Windows 7 drivers on <http://www.support.hp.com>

7. Intel vPro® requires Windows 10 Pro 64 bit or higher, a vPro supported processor, vPro enabled chipset, vPro enabled wired LAN and/or Wi-Fi 6E WLAN and TPM 2.0. Some functionality requires additional 3rd party software in order to run. Features of vPro® Essentials and Enterprise vary. See <http://intel.com/vpro>

---

### CHIPSET

Chipset is integrated with processor

---

### GRAPHICS

#### Integrated

Intel® Iris® X<sup>e</sup> Graphics (Core i5 and Core i7) <sup>8</sup>

Intel® UHD Graphics (Core i3)

#### Discrete

NVIDIA® GeForce® RTX2050 (4 GB DDR6 dedicated)

#### Supports

Supports CUDA, Optimus, PhysX, GPU Boost 2.0

8. Intel® Iris® X<sup>e</sup> Graphics capabilities require system to be configured with Intel® Core™ i5 or i7 processors and dual channel memory. Intel® Iris® X<sup>e</sup> Graphics with Intel® Core™ i5 or 7 processors and single channel memory will only function as UHD graphics.

## Technical Specifications

### DISPLAY

#### Non-Touch

39.6 cm (15.6") diagonal FHD (1920x1080) UWVA, IPS anti-glare, Low Blue Light, 400 nits, 100% for 5MP IR camera with HP Eye Ease <sup>9,10,11</sup>

39.6 cm (15.6") diagonal, FHD (1920 x 1080), Low Blue Light IPS anti-glare, micro-edge, 400 nits, sRGB 100% eDP 1.4+PSR2 for HD + IR camera and WWAN with HP Eye Ease <sup>9,10,11</sup>

39.6 cm (15.6") diagonal FHD (1920x1080) UWVA eDP, anti-glare, LED, narrow bezel bent, 250 nits, 45% for HD + IR camera for WWAN <sup>9,10,11</sup>

39.6 cm (15.6") diagonal FHD (1920x1080) UWVA eDP, anti-glare, WLED, narrow bezel bent, 250 nits, 45% for HD camera for WWAN <sup>9,10,11</sup>

39.6 cm (15.6") diagonal HD (1920x1080) UWVA, eDP, anti-glare, WLED, narrow bezel bent, 250 nits, 45% for HD camera <sup>9,10,11</sup>

39.6 cm (15.6") diagonal FHD (1920x1080) UWVA eDP 1.2 w/o PSR, anti-glare, WLED, narrow bezel bent, 250 nits, 45% <sup>9,10,11</sup>

39.6 cm (15.6") diagonal FHD (1920x1080) UWVA eDP 1.2 w/o PSR, anti-glare, LED, narrow bezel bent, 250 nits, 45%, no-mic <sup>9,10,11</sup>

39.6 cm (15.6") diagonal HD (1366x768) SVA, eDP 1.2 w/o PSR, anti-glare, WLED, narrow bezel bent, 250 nits, 45% <sup>9,10,11</sup>

39.6 cm (15.6") diagonal HD (1366x768) SVA, eDP 1.2 w/o PSR, anti-glare, WLED, narrow bezel bent, 250 nits, 45% for HD camera <sup>9,10,11</sup>

#### Touch

39.6 cm (15.6") diagonal FHD UWVA eDP anti-glare narrow bezel bent touch-on-panel screen, 250 nits, 45% NTSC for HD camera (1920 x 1080) <sup>9,10,11,12</sup>

#### Display Size (Diagonal)

15.6" diagonal

39.6 cm (15.6") diagonal

9. HD content required to view HD images.

10. Sold separately or as an optional feature.

11. Resolutions are dependent upon monitor capability, and resolution and color depth settings.

12. Actual brightness will be lower with touchscreen.

### DOCKING (Sold Separately)

**Docking station model #1** HP Thunderbolt 120W G4 Dock

**Docking station model #2** HP Thunderbolt 280W G4 Dock

**Docking station model #3** HP USB-C Dock G5

**Docking station model #4** HP USB-C/A Universal Dock G2

**Docking station model #5** HP USB-C G5 Essential Dock

For additional aftermarket options and docking specs please see page 40.

## Technical Specifications

### STORAGE AND DRIVES

#### Primary Storage

- 2 TB PCIe® NVMe™ TLC 2280 Solid State Drive <sup>13</sup>
- 1 TB PCIe® NVMe™ TLC 2280 Self Encrypted OPAL2 Solid State Drive <sup>13</sup>
- 1 TB PCIe® Gen4x4 NVMe™ M.2 SSD TLC <sup>13,51</sup>
- 512 GB PCIe® NVMe™ TLC 2280 Self Encrypted OPAL2 Solid State Drive<sup>13</sup>
- 512 GB PCIe® NVMe™ TLC Solid State Drive <sup>13</sup>
- 512 GB PCIe® NVMe™ Value M.2 SSD <sup>13</sup>
- 256 GB PCIe® NVMe™ Value 2280 Self Encrypted OPAL2 Solid State Drive <sup>13</sup>
- 256 GB PCIe® NVMe™ Value M.2 SSD <sup>13</sup>

#### Secondary Storage

- 256 GB PCIe® NVMe™ Value 2230 2nd Solid State Drive <sup>14</sup>

13. For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 30 GB (for Windows 10 and 11) is reserved for system recovery software.

14. Secondary SSD slot (M.2 2230 form factor; Optional) is used for data storage only, not used for OS deployment, and is only available with non-WWAN base Unit AND Primary M.2 storage.

51. Available only to HK (Hong Kong), TW (Taiwan) and CN (China).

### MEMORY

#### Maximum Memory

- 64 GB DDR4-3200 SDRAM <sup>15</sup>

#### Memory

- 64 GB DDR4-3200 SDRAM (2x32GB) <sup>15</sup>
- 32 GB DDR4-3200 SDRAM (2x16GB) <sup>15</sup>
- 32 GB DDR4-3200 SDRAM (1x32GB) <sup>15</sup>
- 16 GB DDR4-3200 SDRAM (2x8GB) <sup>15</sup>
- 16 GB DDR4-3200 SDRAM (1x16GB) <sup>15</sup>
- 8 GB DDR4-3200 SDRAM (1x8GB) <sup>15</sup>
- 8 GB DDR4-3200 SDRAM (2x4GB) <sup>15</sup>

#### Memory Slots

- 2 SODIMM
- Both slots are customer accessible / upgradeable
- DDR4 PC4 SODIMMS (Raptor Lake runs at 3200)
- Supports Dual Channel Memory

15. Due to the non-industry standard nature of some third-party memory modules, we recommend HP branded memory to ensure compatibility. If you mix memory speeds, the system will perform at the lower memory speed.

### Technical Specifications

#### NETWORKING/COMMUNICATIONS

##### WLAN

Intel® AX211 Wi-Fi 6E +Bluetooth® 5.3 M.2 160MHz CNVi World-wide WLAN non-vPro® Wireless Card <sup>16</sup>

Intel® AX211 Wi-Fi 6E + Bluetooth® 5.3 M.2 160MHz CNVi World-wide WLAN vPro® Wireless Card <sup>16</sup>

##### WWAN

Intel® XMM™ 7560 R+ LTE-Advanced Pro <sup>17</sup>

##### NFC

NFC Mirage module (NXP NPC300 I2C 10mmx17mm)

##### Miracast

Native Miracast Support <sup>18</sup>

##### Ethernet

Intel® I219-LM 1 Gigabit Network Connection LOM (vPro) <sup>19</sup>

Intel® I219V 1 Gigabit Network Connection LOM (non-vPro) <sup>19</sup>

16. Wi-Fi 6E requires a Wi-Fi 6E router, sold separately, to function in the 6GHz band. Availability of public wireless access points limited. Wi-Fi 6E is backwards compatible with prior 802.11 specs. And available in countries where Wi-Fi 6E is supported.

17. WWAN module is an optional feature, requires factory configuration and requires separately purchased service contract. Check with service provider for coverage and availability in your area. Connection speeds will vary due to location, environment, network conditions, and other factors. 4G LTE not available on all products, in all regions.

18. Miracast is a wireless technology your PC can use to project your screen to TVs, projectors, and streaming.

19. The term "10/100/1000" or "Gigabit" Ethernet indicates compatibility with IEEE standard 802.3ab for Gigabit Ethernet, and does not connote actual operating speed of 1 Gb/s. For high-speed transmission, connection to a Gigabit Ethernet server and network infrastructure is required.

### Technical Specifications

#### AUDIO/MULTIMEDIA

##### Audio

2 Integrated stereo speakers  
Integrated microphone (Dual Array)

##### Speaker Power

2W/4ohm Per speaker

##### Webcam

720p HD camera with Temporal Noise Reduction <sup>9,10</sup>  
720p HD camera+IR Camera with Temporal Noise Reduction <sup>9,10</sup>  
5MP camera+IR with Temporal Noise Reduction<sup>9,10</sup>  
5 MP + IR camera for face authentication with Windows Hello

9. HD content required to view HD images.

10. Sold separately or as an optional feature.

---

#### KEYBOARDS/POINTING DEVICES/BUTTONS & FUNCTION KEYS

##### Keyboard

HP Premium Keyboard, spill resistant with optional backlit function <sup>20</sup>

##### Pointing Device

Clickpad with multi-touch gesture support

##### Function Keys

F1 - Display Switching  
F2 - Blank  
F3 - Brightness Down  
F4 - Brightness Up  
F5 - Audio Mute  
F6 - Volume Down  
F7 - Volume Up  
F8 - Mic Mute  
F9 - Blank or Backlit Toggle  
F10 - Insert  
F11 - Wireless  
F12 - Programmable key

##### Hidden Function Keys

Fn+R - Break  
Fn+S - Sys Rq  
Fn+C - Scroll Lock

20. Backlit keyboard is an optional feature.

---

### Technical Specifications

#### SOFTWARE AND SECURITY

##### Preinstalled Software

###### Software

HP Quick Drop <sup>21</sup>  
HP PC Hardware Diagnostics Windows  
MyHP with Video Controls  
HP Smart Support <sup>22</sup>  
HP Services Scan <sup>23</sup>  
HP Connection Optimizer  
HP Hotkey Support  
HP Support Assistant <sup>24</sup>  
HP Notifications  
HP Privacy Settings  
HP Power Manager  
Buy Microsoft Office (Sold separately)

##### Manageability Features

HP Connect <sup>25</sup>  
HP Image Assistant Gen5 (download)  
HP Manageability Integration Kit (download) <sup>26</sup>  
HP Client Management Script Library (download)  
HP Patch Assistant (download) <sup>27</sup>  
HP Driver Packs (download)  
HP Client Catalog (download)  
HP Cloud Recovery

##### Security Management

HP Wolf Security for Business <sup>28</sup> includes:  
HP Sure Click <sup>29</sup>  
HP Sure Sense <sup>30</sup>  
HP Sure Run <sup>31</sup>  
HP Sure Recover <sup>32</sup>  
HP Sure Start <sup>33</sup>  
HP Tamper Lock  
HP Sure Admin <sup>34</sup>

##### BIOS

HP BIOSphere Gen6 <sup>35</sup>  
HP Secure Erase <sup>36</sup>  
Absolute Persistence Module <sup>37</sup>  
BIOS Update via Network  
HP Wake on WLAN  
Secured-Core PC Enable <sup>38</sup>  
TPM 2.0 Embedded Security Chip (Common Criteria EAL4+ Certified) (FIPS 140-2 Level 2 Certified)  
HP Fingerprint Sensor <sup>39</sup>

##### Security

###### TPM

Model: Nuvoton NPCT760HABYX  
Version: 7.2.3.1

## Technical Specifications

Revision: TPM 2.0  
FIPS 140-2 Compliant: Yes

### Smartcard Reader

Model number: Alcor AU9560  
FIPS 201 Compliant: Yes

### IPv6 Support

Yes

### FirstNet Certified

Yes

### The BIOS on this notebook implements ISO/IEC 19678:2015 guidelines (formerly NIST 800-147).

UEFI version: 2.7  
Class: 3

21. HP Quick Drop requires Internet access and Windows 10 or higher PC preinstalled with HP QuickDrop app and either an Android device (phone or tablet) running Android 7 or higher with the Android HP QuickDrop app, and /or an iOS device (phone or tablet) running iOS 12 or higher with the iOS HP QuickDrop app.

22. HP Smart Support requires HP TechPulse to be installed. For more information about how to enable or to download HP Smart Support, please visit <http://www.hp.com/smart-support>.

23. HP Services Scan is provided with Windows Update on select products and will check entitlement on each hardware device to determine if an HP TechPulse-enabled service has been purchased, and will download applicable software automatically. HP TechPulse is a telemetry and analytics platform that provides critical data around devices and applications and is not sold as a standalone service. HP TechPulse follows stringent GDPR privacy regulations and is ISO27001, ISO27701, ISO27017 and SOC2 Type2 certified for Information Security. Internet access with connection to TechPulse portal is required. For full system requirements or to disable this feature, please visit <http://www.hpdaas.com/requirements>. Not applicable in China.

24. HP Support Assistant requires Windows and Internet access.

25. HP Connect for Microsoft Endpoint Manager is available from the Azure Market Place for HP Pro, Elite, Z and Point-of-Sale PCs managed with Microsoft Endpoint Manager. Subscription to Microsoft Endpoint Manager required and sold separately. Network connection required.

26. HP Manageability Integration Kit can be downloaded from <http://www8.hp.com/us/en/ads/clientmanagement/overview.html>.

27. HP Patch Assistant available on select HP PCs with the HP Manageability Kit that are managed through Microsoft System Center Configuration Manager. HP Manageability Integration Kit can be downloaded from <http://www8.hp.com/us/en/ads/clientmanagement/overview.html>.

28. HP Wolf Security for Business requires Windows 10 or higher, includes various HP security features and is available on HP Pro, Elite, RPOS and Workstation products. See product details for included security features..

29. HP Sure Click requires Windows 10 Pro or higher or Enterprise. See [https://bit.ly/2PrLT6A\\_SureClick](https://bit.ly/2PrLT6A_SureClick) for complete details.

30. HP Sure Sense is available on select HP PCs with Windows 10 Pro, Windows 10 Enterprise, Windows 11 Pro, or Windows 11 Enterprise OS

31. HP Sure Run Gen5 is available on select HP PCs and requires Windows 10 and higher.

32. HP Sure Recover Gen5 with Embedded Reimaging is an optional feature which requires Windows 10 and higher must be configured at purchase. You must back up important files, data, photos, videos, etc. before use to avoid loss of data. Network based recovery using Wi-Fi is only available on PCs with Intel Wi-Fi Module

33. HP Sure Start Gen7 is available on select HP PCs and requires Windows 10 and higher

34. HP Sure Admin requires Windows 10 or higher, HP BIOS, HP Manageability Integration Kit from <http://www.hp.com/go/clientmanagement> and HP Sure Admin Local Access Authenticator smartphone app from the Android or Apple store

35. HP BIOSphere Gen6 features may vary depending on the platform and configuration.

### Technical Specifications

36. HP Secure Erase for the methods outlined in the National Institute of Standards and Technology Special Publication 800-88 "Clear" sanitation method. HP Secure Erase does not support platforms with Intel® Optane™.
  37. Absolute firmware module is shipped turned off and can only be activated with the purchase a license subscription and full activation of the software agent. License subscriptions can be purchased for terms ranging multiple years. Service is limited, check with Absolute for availability outside the U.S. Certain conditions apply. For full details visit: <https://www.absolute.com/about/legal/agreements/absolute/>
  38. Secured-Core PC Enable requires an Intel® vPro®, AMD Ryzen™ Pro processor or Qualcomm® processor with SD850 or higher and requires 8 GB or more system memory. Secured-core PC is enabled from the factory.
  39. HP Fingerprint sensor is an optional feature that must be configured at purchase.
-

### Technical Specifications

#### POWER

##### Power Supply

AC Adapter 65 Watt nPFC Standard USB Type C® Straight 1.8m <sup>40</sup>

AC Adapter 65 Watt Smart nPFC EM Barrel 4.5mm New EM <sup>40</sup>

AC Adapter 65 Watt Smart nPFC Standard Barrel 4.5mm Right Angle 1.8m <sup>40</sup>

##### Battery

HP Long Life 3-cell, 51.3 Wh Polymer <sup>41,42</sup>

Compliant with UL 1642 Standard

##### Power Cord

3-wire plug - 1m <sup>40</sup>

##### Battery Life

Up to 13 hours and 15 minutes with 51whr battery (HP Long Life 3-Cell, 51 Whr Polymer, UMA graphic, Intel U15, Display set to 200 nits display (on a 400 nit display), 2\*4G memory, 256 GB SSD) <sup>43</sup>

Up to 12 hours and 30 minutes with 51whr battery (HP Long Life 3-Cell, 51 Whr Polymer, UMA graphic, Intel P28, Display set to 200 nits display (on a 400 nit display), 2\*4G memory, 256 GB SSD)<sup>43</sup>

##### Battery Weight

HP Long Life 3-cell - 51.3 Wh Polymer - .45 lb

HP Long Life 3-cell - 51.3 Wh Polymer - 203.56 g

40. Availability may vary by country.

41. Battery is internal and not replaceable by customer. Serviceable by warranty.

42. Actual battery Watt-hours (Wh) will vary from design capacity. Battery capacity will naturally decrease with shelf life, time, usage, environment, temperature, system configuration, loaded apps, features, power management settings and other factors.

43. MM18 battery life will vary depending on various factors including product model, configuration, loaded applications, features, use, wireless functionality, and power management settings. The maximum capacity of the battery will naturally decrease with time and usage. See [www.bapco.com](http://www.bapco.com) for additional details.

#### WEIGHTS & DIMENSIONS

##### Product Weight

Starting at 3.94 lb <sup>44</sup>

Starting at 1.78 kg <sup>44</sup>

##### Product Dimensions (W x D x H)

14.14 x 9.2 x 0.78 in

35.94 x 23.39 x 1.99 cm

##### Packaging Dimensions (W x D x H) <sup>45</sup>

12"-15" boxes (305mm height): 1200mm x 1000mm x 1080mm

16"-17" boxes (345mm height): 1200mm x 1000mm x 1200mm

44. Weight will vary by configuration. Does not include power adapter.

### Technical Specifications

45. Product packaging size varies based on options chosen. Please contact your HP representative for your packaging size details.

#### PORTS/SLOTS

- 1 Thunderbolt™ 4 with USB4™ Type-C® 40 Gbps signaling rate (USB Power Delivery, DisplayPort™ 1.4)<sup>46</sup>
- 1 SuperSpeed USB Type-C® 10Gbps signaling rate (USB Power Delivery, DisplayPort™ 1.4)
- 2 SuperSpeed USB Type-A 5Gbps signaling rate Port (1 Powered port)
- 1 AC power
- 1 HDMI 2.1<sup>47</sup>
- 1 Headphone/microphone combo jack
- 1 Nano SIM slot for WWAN (optional)
- 1 RJ-45
- 1 Smart Card Reader (optional)

46. SuperSpeed USB 20Gbps is not available with Thunderbolt™ 4

47. HDMI cable sold separately

#### SERVICE AND SUPPORT

1-year and 3-year limited warranties and 90 day software limited warranty options depending on country. Batteries have a default one year limited warranty. Refer to <http://www.hp.com/support/batterywarranty/> for additional battery information. On-site service and extended coverage is also available. HP Care Pack Services are optional extended service contracts that go beyond the standard limited warranties. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at: <http://www.hp.com/go/cpc>.<sup>48</sup>

48. HP Care Packs are sold separately. Service levels and response times for HP Care Packs may vary depending on your geographic location. Service starts on date of hardware purchase. Restrictions and limitations apply. For details, visit <http://www.hp.com/go/cpc>. HP services are governed by the applicable HP terms and conditions of service provided or indicated to Customer at the time of purchase. Customer may have additional statutory rights according to applicable local laws, and such rights are not in any way affected by the HP terms and conditions of service or the HP Limited Warranty provided with your HP Product.

## Technical Specifications

### SYSTEM UNIT

#### Stand-Alone Power Requirements (AC Power)

|                           |                             |
|---------------------------|-----------------------------|
| Nominal Operating Voltage | 19V                         |
| Average Operating Power   | 3.81W                       |
| Integrated graphics       | Yes                         |
| Discrete Graphics         | Yes                         |
| Max Operating Power       | Discrete < 65W<br>UMA < 45W |

#### Temperature

|               |   |
|---------------|---|
| Operating     | 32° to 95° F (0° to 35° C)<br>(No sustained direct exposure to sunlight)<br>(System performance may be reduced above 32°C (89.6°F)) |
| Non-operating | -4° to 140° F (-20° to 60° C)   |

#### Relative Humidity

|               |  |
|---------------|--|
| Operating     | 10% to 90% (non-condensing)  |
| Non-operating | 5% to 95%<br>(38.7° C (101.6° F) maximum wet bulb temperature; non-condensing) |

#### Shock

|               |                        |
|---------------|------------------------|
| Operating     | 40 G, 2 ms, half-sine  |
| Non-operating | 240 G, 2 ms, half-sine |

#### Random Vibration

|               |             |
|---------------|-------------|
| Operating     | 1.043 grams |
| Non-operating | 3.5 grams   |

#### Altitude (unpressurized)

|               |                      |
|---------------|----------------------|
| Operating     | 10,000 ft (3,048 m)  |
| Non-operating | 40,000 ft (12,192 m) |

#### Planned Industry Standard Certifications

|                          |  |
|--------------------------|--|
| Regulatory Model Number  | HSN-Q33C-5   |
| CSA/UL 62368-1           | Yes  |
| ENERGY STAR®             | Yes <sup>49</sup>  |
| EPEAT®                   | EPEAT® Gold in the United States <sup>50</sup>           |
| FCC/ICES/CISPR/VCCI      | Yes  |
| CE MARKING               | Yes  |
| GS Mark                  | Yes  |
|                          | Related commodity should comply with ISO 9241 Standards. |
| China CCC/SRRC           | Yes  |
| Taiwan BSMI/NCC          | Yes  |
| Korea KCC/KC/KES         | Yes  |
| Ukraine NSoC/TEC         | Yes  |
| EAEU Compliance          | Yes  |
| Saudi Arabian Compliance | Yes  |
| TCO                      | Yes  |
| Low Blue Light           | Yes  |
| WW RoHS                  | Yes  |

## Technical Specifications

49. Configurations of the HP EliteBook 650 15.6 inch G10 Notebook PC that are ENERGY STAR® qualified are identified as HP EliteBook 650 15.6 inch G10 Notebook PC ENERGY STAR on HP websites and on <http://www.energystar.gov>.

50. Based on US EPEAT® registration according to IEEE 1680.1-2018 EPEAT®. EPEAT® status varies by country. Visit <http://www.epeat.net> for more information.

### DISPLAYS

1. Actual brightness will be lower with touchscreen or HP Sure View.

**NOTE:** All specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.

|   |   |                            |
|---|---|----------------------------|
| <b>Panel LCD 15.6 inch FHD (1920x1080) Anti-Glare WLED UWVA 45percent cg 250nits eDP 1.2 w/o PSR bent Touch on Panel NWBZ</b> | <b>Outline Dimensions (W x H x D)</b>                       | 350.960 x 205.740 (max)    |
|   | <b>Active Area</b>  | 344.160 x 193.590 mm (typ) |
|   | <b>Weight</b>   | 380 g (max)                |
|   | <b>Diagonal Size</b>  | 15.6                       |
|   | <b>Surface Treatment</b>                                    | Anti-Glare On-cell         |
|   | <b>Touch Enabled</b>  | Yes                        |
|   | <b>Contrast Ratio</b>                                       | 600:1 (typ)                |
|   | <b>Refresh Rate</b>   | 60 Hz                      |
|   | <b>Brightness</b>   | 250 nits <sup>1</sup>      |
|   | <b>Pixel Resolution - Format</b>                            | 1920 x 1080 (FHD)          |
|   | <b>Backlight</b>  | LED                        |
|   | <b>Pixel Resolution</b>                                     | RGB                        |
|   | <b>Color Gamut Coverage</b>                                 | NTSC 45%                   |
|   | <b>Color Depth</b>  | 6                          |
|   | <b>Viewing Angle</b>  | UWVA 85/85/85/85           |
|   | <b>Low Blue Light</b>                                       | No                         |
|   | <b>Power Consumption (W, EBL@ 150nits max/ 200nits max)</b> | 2.54 (Max) / 3.12 (Max)    |

|   |                                       |                            |
|---|---------------------------------------|----------------------------|
| <b>15.6 in FHD (1920 x 1080) Anti-Glare UWVA Low Blue Light sRGB NB2X 400 eDP 1.4+PSR2 Low-Power 100 bent LCD Panel</b> | <b>Outline Dimensions (W x H x D)</b> | 349.460 x 204.790 (max)    |
|   | <b>Active Area</b>                    | 344.160 x 193.590 mm (typ) |
|   | <b>Weight</b>                         | 310 g (max)                |
|   | <b>Diagonal Size</b>                  | 15.6 (inch)                |
|   | <b>Surface Treatment</b>              | Anti-Glare                 |
|   | <b>Touch Enabled</b>                  | No                         |
|   | <b>Contrast Ratio</b>                 | 1200:1 (typ)               |
|   | <b>Refresh Rate</b>                   | 60 Hz                      |
|   | <b>Brightness</b>                     | 400 nits <sup>1</sup>      |
|   | <b>Pixel Resolution - Format</b>      | 1920 x 1080 (FHD)          |
|   | <b>Backlight</b>                      | WLED                       |
|   | <b>Pixel Resolution</b>               | RGB                        |
|   | <b>Color Gamut Coverage</b>           | sRGB 100%                  |

### Technical Specifications

|   |                        |
|---|------------------------|
| <b>Color Depth</b>  | 8                      |
| <b>Viewing Angle</b>  | UWVA 89/89/89/89       |
| <b>Low Blue Light</b>                                       | Yes                    |
| <b>Power Consumption (W, EBL@ 150nits max/ 200nits max)</b> | 1.27 (max) / 1.5 (max) |

|  |   |                                   |
|--|---|-----------------------------------|
| <b>15.6 inch FHD (1920x1080)<br/>Anti-Glare WLED UWVA<br/>45percent cg 250nits eDP<br/>1.2 w/o PSR bent NWBZ</b> | <b>Outline Dimensions (W x H x D)</b>                       | 350.960 x 205.540 (max)           |
|  | <b>Active Area</b>  | 344.160 x 193.590 mm (typ)        |
|  | <b>Weight</b>   | 370 g (max)                       |
|  | <b>Diagonal Size</b>  | 15.6                              |
|  | <b>Surface Treatment</b>                                    | Anti-Glare                        |
|  | <b>Touch Enabled</b>  | No                                |
|  | <b>Contrast Ratio</b>                                       | 600:1 (typ)                       |
|  | <b>Refresh Rate</b>   | 60 Hz                             |
|  | <b>Brightness</b>   | 250 nits <sup>1</sup>             |
|  | <b>Pixel Resolution - Format</b>                            | 1920 x 1080 (FHD)                 |
|  | <b>Backlight</b>  | LED                               |
|  | <b>Pixel Resolution</b>                                     | RGB                               |
|  | <b>Color Gamut Coverage</b>                                 | NTSC 45%                          |
|  | <b>Color Depth</b>  | 6 (Hi FRC w/ condition to enable) |
|  | <b>Viewing Angle</b>  | UWVA 85/85/85/85                  |
|  | <b>Low Blue Light</b>                                       | No                                |
|  | <b>Power Consumption (W, EBL@ 150nits max/ 200nits max)</b> | 2.62 (Max) / 3.27 (Max)           |

|   |                                       |                            |
|---|---------------------------------------|----------------------------|
| <b>15.6-in HD (1366x768)<br/>Anti-Glare WLED SVA<br/>45percent cg 250nits eDP<br/>1.2 w/o PSR NWBZ bent</b> | <b>Outline Dimensions (W x H x D)</b> | 350.960 x 205.540 (max)    |
|   | <b>Active Area</b>                    | 344.230 x 193.540 mm (typ) |
|   | <b>Weight</b>                         | 370 g (max)                |
|   | <b>Diagonal Size</b>                  | 15.6                       |
|   | <b>Surface Treatment</b>              | Anti-Glare                 |
|   | <b>Touch Enabled</b>                  | No                         |
|   | <b>Contrast Ratio</b>                 | 300:1 (typ)                |
|   | <b>Refresh Rate</b>                   | 60 Hz                      |
|   | <b>Brightness</b>                     | 250 nits <sup>1</sup>      |
|   | <b>Pixel Resolution - Format</b>      | 1366 x 768 (HD)            |
|   | <b>Backlight</b>                      | LED                        |
|   | <b>Pixel Resolution</b>               | RGB                        |
|   | <b>Color Gamut Coverage</b>           | NTSC 45%                   |
|   | <b>Color Depth</b>                    | 6                          |

### Technical Specifications

|   |                         |
|---|-------------------------|
| <b>Viewing Angle</b>  | SVA 45/45/15/35         |
| <b>Low Blue Light</b>   | No                      |
| <b>Power Consumption (W, EBL@<br/>150nits max/ 200nits max)</b> | 2.49 (Max) / 2.78 (Max) |

---

## Technical Specifications

**STORAGE AND DRIVES**

For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 30 GB (for Windows 10 and 11) is reserved for system recovery software.

|                                       |                                 |                     |
|---------------------------------------|---------------------------------|---------------------|
| <b>SSD 256GB 2230 PCIe NVMe Value</b> | <b>Form Factor</b>              | M.2 2230            |
|                                       | <b>Capacity</b>                 | 256 GB              |
|                                       | <b>NAND Type</b>                | Value               |
|                                       | <b>Interface</b>                | PCIe NVMe           |
|                                       | <b>Maximum Sequential Read</b>  | 2000 MB/s $\pm$ 20% |
|                                       | <b>Maximum Sequential Write</b> | 900 MB/s $\pm$ 20%  |
|                                       | <b>Logical Blocks</b>           | 500118192           |
|                                       | <b>Features</b>                 | Pyrite; TRIM; L1.2  |

|                                       |                                 |                          |
|---------------------------------------|---------------------------------|--------------------------|
| <b>SSD 256GB 2280 PCIe NVMe Value</b> | <b>Form Factor</b>              | M.2 2280                 |
|                                       | <b>Capacity</b>                 | 256GB                    |
|                                       | <b>NAND Type</b>                | Value                    |
|                                       | <b>Interface</b>                | PCIe NVMe                |
|                                       | <b>Maximum Sequential Read</b>  | 2000 MB/s $\pm$ 20%      |
|                                       | <b>Maximum Sequential Write</b> | 900 MB/s $\pm$ 20%       |
|                                       | <b>Logical Blocks</b>           | 500118192                |
|                                       | <b>Features</b>                 | ATA Security; TRIM; L1.2 |

|  |                                 |                     |
|--|---------------------------------|---------------------|
| <b>256GB PCIe 2280 NVMe Self Encrypted OPAL2 Value Solid State Drive</b> | <b>Form Factor</b>              | M.2 2280            |
|  | <b>Capacity</b>                 | 256 GB              |
|  | <b>NAND Type</b>                | Opal2 Value         |
|  | <b>Interface</b>                | 0.02 lb (10 g)      |
|  | <b>Weight</b>                   | PCIe NVMe Gen4X4    |
|  | <b>Maximum Sequential Read</b>  | 2000 MB/s $\pm$ 20% |
|  | <b>Maximum Sequential Write</b> | 900 MB/s $\pm$ 20%  |
|  | <b>Logical Blocks</b>           | 500,118,192         |
| <b>Features</b>  | Pyrite 2.0; TRIM; L1.2          |                     |

|                                       |                                 |                        |
|---------------------------------------|---------------------------------|------------------------|
| <b>SSD 512GB 2280 PCIe NVMe Value</b> | <b>Form Factor</b>              | M.2 2280               |
|                                       | <b>Capacity</b>                 | 512GB                  |
|                                       | <b>NAND Type</b>                | Value                  |
|                                       | <b>Interface</b>                | PCIe NVMe              |
|                                       | <b>Maximum Sequential Read</b>  | 2200 MB/s $\pm$ 20%    |
|                                       | <b>Maximum Sequential Write</b> | 1000 MB/s $\pm$ 20%    |
|                                       | <b>Logical Blocks</b>           | 1000215216             |
|                                       | <b>Features</b>                 | Pyrite 2.0, TRIM; L1.2 |

## Technical Specifications

|   |                                 |                        |
|---|---------------------------------|------------------------|
| <b>512GB PCIe-4x4 2280 NVMe Self Encrypted OPAL2 Three Layer Cell Solid State Drive</b> | <b>Form Factor</b>              | M.2 2280               |
|   | <b>Capacity</b>                 | 512 GB                 |
|   | <b>NAND Type</b>                | Opal2 TLC              |
|   | <b>Interface</b>                | PCIe NVMe Gen4X4       |
|   | <b>Maximum Sequential Read</b>  | 6400 MB/s $\pm$ 20%    |
|   | <b>Maximum Sequential Write</b> | 3500 MB/s $\pm$ 20%    |
|   | <b>Logical Blocks</b>           | 1,000,215,216          |
|   | <b>Features</b>                 | Pyrite 2.0, TRIM; L1.2 |

|  |                                 |                        |
|--|---------------------------------|------------------------|
| <b>SSD 512GB 2280 PCIe-4x4 NVMe Three Layer Cell</b> | <b>Form Factor</b>              | M.2 2280               |
|  | <b>Capacity</b>                 | 512 GB                 |
|  | <b>NAND Type</b>                | TLC                    |
|  | <b>Interface</b>                | PCIe NVMe Gen4X4       |
|  | <b>Maximum Sequential Read</b>  | 6400 MB/s $\pm$ 20%    |
|  | <b>Maximum Sequential Write</b> | 3500 MB/s $\pm$ 20%    |
|  | <b>Logical Blocks</b>           | 1,000,215,216          |
|  | <b>Features</b>                 | Pyrite 2.0, TRIM; L1.2 |

|   |                                 |                        |
|---|---------------------------------|------------------------|
| <b>1TB PCIe-4x4 2280 NVMe Self Encrypted OPAL2 Three Layer Cell Solid State Drive</b> | <b>Form Factor</b>              | M.2 2280               |
|   | <b>Capacity</b>                 | 1 TB                   |
|   | <b>NAND Type</b>                | Opal2 TLC              |
|   | <b>Interface</b>                | PCIe NVMe Gen4X4       |
|   | <b>Maximum Sequential Read</b>  | 6400 MB/s $\pm$ 20%    |
|   | <b>Maximum Sequential Write</b> | 5000 MB/s $\pm$ 20%    |
|   | <b>Logical Blocks</b>           | 2,000,409,264          |
|   | <b>Features</b>                 | Pyrite 2.0, TRIM; L1.2 |

|  |                                 |                        |
|--|---------------------------------|------------------------|
| <b>SSD 1 TB 2280 PCIe NVMe Value<sup>1</sup></b> | <b>Form Factor</b>              | M.2 2280               |
|  | <b>Capacity</b>                 | 1TB                    |
|  | <b>NAND Type</b>                | TLC                    |
|  | <b>Interface</b>                | PCIe NVMe Gen4X4       |
|  | <b>Maximum Sequential Read</b>  | 3200 MB/s $\pm$ 20%    |
|  | <b>Maximum Sequential Write</b> | 2700 MB/s $\pm$ 20%    |
|  | <b>Logical Blocks</b>           | 2,000,409,264          |
|  | <b>Features</b>                 | Pyrite 2.0; TRIM; L1.2 |

1. Available only to HK (Hong Kong), TW (Taiwan) and CN (China).

|  |                                 |                     |
|--|---------------------------------|---------------------|
| <b>SSD 2TB 2280 PCIe-4x4 NVMe Three Layer Cell</b> | <b>Form Factor</b>              | M.2 2280            |
|  | <b>Capacity</b>                 | 2 TB                |
|  | <b>NAND Type</b>                | TLC                 |
|  | <b>Interface</b>                | PCIe NVMe Gen4X4    |
|  | <b>Maximum Sequential Read</b>  | 6400 MB/s $\pm$ 20% |
|  | <b>Maximum Sequential Write</b> | 5000 MB/s $\pm$ 20% |

### Technical Specifications

|                       |                        |
|-----------------------|------------------------|
| <b>Logical Blocks</b> | 4,000,797,360          |
| <b>Features</b>       | Pyrite 2.0, TRIM; L1.2 |

### NETWORKING/COMMUNICATIONS

|  |                               |  |
|--|-------------------------------|--|
| <b>Intel® AX211 Wi-Fi 6E + Bluetooth® 5.3 M.2 160MHz CNVi World-wide WLAN vPro Wireless Card<sup>1</sup></b> | <b>Wireless LAN Standards</b> | IEEE 802.11a<br>IEEE 802.11b<br>IEEE 802.11g<br>IEEE 802.11n<br>IEEE 802.11ac<br>IEEE 802.11ax<br>IEEE 802.11d<br>IEEE 802.11e<br>IEEE 802.11h<br>IEEE 802.11i<br>IEEE 802.11k<br>IEEE 802.11r<br>IEEE 802.11v   |
|  | <b>Interoperability</b>       | Wi-Fi certified  |
|  | <b>Frequency Band</b>         | <ul style="list-style-type: none"> <li>•802.11b/g/n/ax<br/>2.402 – 2.482 GHz</li> <li>•802.11a/n/ac/ax<br/>4.9 – 4.95 GHz (Japan)</li> <li>5.15 – 5.25 GHz</li> <li>5.25 – 5.35 GHz</li> <li>5.47 – 5.725 GHz</li> <li>5.825 – 5.850 GHz</li> <li>5.955 – 6.415 GHz</li> <li>6.435 – 6.515 GHz</li> <li>6.535 – 6.875 GHz</li> <li>6.895 – 7.115 GHz</li> </ul>  |
|  | <b>Data Rates</b>             | <ul style="list-style-type: none"> <li>• 802.11b: 1, 2, 5.5, 11 Mbps</li> <li>• 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps</li> <li>• 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps</li> <li>• 802.11n: max 300Mbps</li> <li>• 802.11ac : 1733Mbps</li> <li>• 802.11ax : max 2.4Gbps</li> </ul>   |
|  | <b>Modulation</b>             | Direct Sequence Spread Spectrum  |
|  | <b>Security<sup>2</sup></b>   | OFDM, BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM, 1024QAM<br><ul style="list-style-type: none"> <li>• IEEE and WiFi compliant 64 / 128 bit WEP encryption for a/b/g mode only</li> <li>• AES-CCMP: 128 bit in hardware</li> <li>• 802.1x authentication</li> <li>• WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES.</li> <li>• WPA2 certification</li> <li>• WPA3 certification</li> <li>• IEEE 802.11i</li> <li>• WAPI</li> </ul> |

## Technical Specifications

|  |   |
|--|---|
| <b>Network Architecture Models</b>       | Ad-hoc (Peer to Peer)<br>Infrastructure (Access Point Required)   |
| <b>Roaming</b>                           | IEEE 802.11 compliant roaming between access points   |
| <b>Output Power <sup>3</sup></b>         | <ul style="list-style-type: none"> <li>• 802.11b : +17dBm minimum</li> <li>• 802.11g : +16dBm minimum</li> <li>• 802.11a : +17dBm minimum</li> <li>• 802.11n HT20(2.4GHz) : +14dBm minimum</li> <li>• 802.11n HT40(2.4GHz) : +13dBm minimum</li> <li>• 802.11n HT20(5GHz) : +14dBm minimum</li> <li>• 802.11n HT40(5GHz) : +13dBm minimum</li> <li>• 802.11ac VHT80(5GHz) : +10dBm minimum</li> <li>• 802.11ac VHT160(5GHz) : +10dBm minimum</li> <li>• 802.11ax HE40(2.4GHz) : +12dBm minimum</li> <li>• 802.11ax HE80(5GHz) : +10dBm minimum</li> <li>• 802.11ax HE160(5GHz) : +10dBm minimum</li> </ul>                        |
| <b>Power Consumption</b>                 | <ul style="list-style-type: none"> <li>• Transmit mode 2.0 W</li> <li>• Receive mode 1.6 W</li> <li>• Idle mode (PSP) 180 mW (WLAN Associated)</li> <li>• Idle mode 50 mW (WLAN unassociated)</li> <li>• Connected Standby 10mW</li> <li>• Radio disabled 8 mW</li> </ul>   |
| <b>Power Management</b>                  | ACPI and PCI Express compliant power management<br>802.11 compliant power saving mode   |
| <b>Receiver Sensitivity <sup>4</sup></b> | <ul style="list-style-type: none"> <li>• 802.11b, 1Mbps : -93.5dBm maximum</li> <li>• 802.11b, 11Mbps : -84dBm maximum</li> <li>• 802.11a/g, 6Mbps : -86dBm maximum</li> <li>• 802.11a/g, 54Mbps : -72dBm maximum</li> <li>• 802.11n, MCS07 : -67dBm maximum</li> <li>• 802.11n, MCS15 : -64dBm maximum</li> <li>• 802.11ac, MCS0(VHT80) : -84dBm maximum</li> <li>• 802.11ac, MCS9(VHT80) : -59dBm maximum</li> <li>• 802.11ac, MCS9(VHT160) : -58.5dBm maximum</li> <li>• 802.11ax, MCS11(HE40): -57dBm maximum</li> <li>• 802.11ax, MCS11(HE80): -54dBm maximum</li> <li>• 802.11ax, MCS11(HE160): -53.5dBm maximum</li> </ul> |
| <b>Antenna type</b>                      | High efficiency antenna with spatial diversity, mounted in the display enclosure<br>Two embedded dual band 2.4/5 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications   |
| <b>Form Factor</b>                       | PCI-Express M.2 MiniCard  |
| <b>Dimensions</b>                        | 1. Type 2230 : 2.3 x 22.0 x 30.0 mm<br>2. Type 1216: 1.67 x 12.0 x 16.0 mm  |
| <b>Weight</b>                            | 1. Type 2230 : 2.8g<br>2. Type 1216: 1.3g   |
| <b>Operating Voltage</b>                 | 3.3v +/- 9%   |
| <b>Temperature</b>                       | <b>Operating</b> 14° to 158° F (-10° to 70° C)  |

### Technical Specifications

|                     |                      |   |
|---------------------|----------------------|---|
| <b>Humidity</b>     | <b>Non-operating</b> | −40° to 176° F (−40° to 80° C)            |
|                     | <b>Operating</b>     | 10% to 90% (non-condensing)               |
| <b>Altitude</b>     | <b>Non-operating</b> | 5% to 95% (non-condensing)                |
|                     | <b>Operating</b>     | 0 to 10,000 ft (3,048 m)                  |
| <b>LED Activity</b> | <b>Non-operating</b> | 0 to 50,000 ft (15,240 m)                 |
|                     |                      | LED Amber – Radio OFF; LED OFF – Radio ON |

#### HP Integrated Module with Bluetooth 4.0/4.1/4.2/5.0/5.1/5.2/5.3 Wireless Card

|   |  |
|---|--|
| <b>Bluetooth Specification</b>                    | 4.0/4.1/4.2/5.0/5.1/5.2/5.3 Compliant  |
| <b>Frequency Band</b>                             | 2402 to 2480 MHz   |
| <b>Number of Available Channels</b>               | Legacy : 0~79 (1 MHz/CH)<br>BLE : 0~39 (2 MHz/CH)  |
| <b>Data Rates and Throughput</b>                  | Legacy : 3 Mbps data rate; throughput up to 2.17 Mbps<br>BLE : 1 Mbps data rate; throughput up to 0.2 Mbps<br>Legacy : Synchronous Connection Oriented links up to 3, 64 kbps, voice channels<br>Legacy : Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)   |
| <b>Transmit Power</b>                             | The Bluetooth component shall operate as a Class II Bluetooth device with a maximum transmit power of + 9.5 dBm for BR and EDR.  |
| <b>Power Consumption</b>                          | Peak (Tx): 330 mW<br>Peak (Rx): 230 mW<br>Selective Suspend: 17 mW   |
| <b>Bluetooth Software Supported Link Topology</b> | Bluetooth Software   |
| <b>Power Management Certifications</b>            | Microsoft Windows ACPI, and USB Bus Support<br>FCC (47 CFR) Part 15C, Section 15.247 & 15.249  |
| <b>Power Management Certifications</b>            | ETS 300 328, ETS 300 826<br>Low Voltage Directive IEC950<br>UL, CSA, and CE Mark   |
| <b>Bluetooth Profiles Supported</b>               | BT4.1-ESR 5/6/7 Compliance<br>LE Link Layer Ping<br>LE Dual Mode<br>LE Link Layer<br>LE Low Duty Cycle Directed Advertising<br>LE L2CAP Connection Oriented Channels<br>Train Nudging & Interlaced Scan<br>BT4.2 ESR08 Compliance<br>LE Secure Connection- Basic/Full<br>LE Privacy 1.2 –Link Layer Privacy<br>LE Privacy 1.2 –Extended Scanner Filter Policies<br>LE Data Packet Length Extension<br>FAX Profile (FAX)<br>Basic Imaging Profile (BIP)2<br>Headset Profile (HSP)<br>Hands Free Profile (HFP) |

### Technical Specifications

Advanced Audio Distribution Profile (A2DP)  
 BT5.2  
 ESR9/10 Compliance  
 LE Advertisement Extensions  
 Channel Selection Algo  
 Limited High Duty Cycle Non-Connectable Advertising  
 2Mbps LE  
 LE Long Range  
 BT5.3  
 Host to Controller Encryption Key Control Enhancements  
 Compliance to the latest Errata Section 12.3 of BT 5.3 specification

1. Wi-Fi 6E requires a Wi-Fi 6E router, sold separately, to function in the 6GHz band. Availability of public wireless access points limited. Wi-Fi 6E is backwards compatible with prior 802.11 specs. And available in countries where Wi-Fi 6E is supported. Wi-Fi 6E is designed to support gigabit data rate when transferring files between two devices connected to the same router. Requires a wireless router, sold separately, that supports 80MHz and higher channels.
2. Check latest software/driver release for updates on supported security features.
3. The FCC has declared as of September 1, 2014 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels.
4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

|   |                               |  |
|---|-------------------------------|--|
| <b>Intel® AX211 Wi-Fi 6E + Bluetooth® 5.3 M.2 160MHz CNVi World-wide WLAN non-vPro Wireless Card <sup>1</sup></b> | <b>Wireless LAN Standards</b> | IEEE 802.11a<br>IEEE 802.11b<br>IEEE 802.11g<br>IEEE 802.11n<br>IEEE 802.11ac<br>IEEE 802.11ax<br>IEEE 802.11d<br>IEEE 802.11e<br>IEEE 802.11h<br>IEEE 802.11i<br>IEEE 802.11k<br>IEEE 802.11r<br>IEEE 802.11v                   |
|   | <b>Interoperability</b>       | Wi-Fi certified  |
|   | <b>Frequency Band</b>         | •802.11b/g/n/ax<br>2.402 – 2.482 GHz<br>•802.11a/n/ac/ax<br>4.9 – 4.95 GHz (Japan)<br>5.15 – 5.25 GHz<br>5.25 – 5.35 GHz<br>5.47 – 5.725 GHz<br>5.825 – 5.850 GHz<br>5.955 – 6.415 GHz<br>6.435 – 6.515 GHz<br>6.535 – 6.875 GHz |

## Technical Specifications

|   |  |
|---|--|
|   | 6.895 – 7.115 GHz  |
| <b>Data Rates</b>                       | <ul style="list-style-type: none"> <li>• 802.11b: 1, 2, 5.5, 11 Mbps</li> <li>• 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps</li> <li>• 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps</li> <li>• 802.11n: max 300Mbps</li> <li>• 802.11ac : 1733Mbps</li> <li>• 802.11ax : max 2.4Gbps</li> </ul>   |
| <b>Modulation</b>                       | Direct Sequence Spread Spectrum<br>OFDM, BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM, 1024QAM   |
| <b>Security<sup>2</sup></b>             | <ul style="list-style-type: none"> <li>• IEEE and WiFi compliant 64 / 128 bit WEP encryption for a/b/g mode only</li> <li>• AES-CCMP: 128 bit in hardware</li> <li>• 802.1x authentication</li> <li>• WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES.</li> <li>• WPA2 certification</li> <li>• WPA3 certification</li> <li>• IEEE 802.11i</li> <li>• WAPI</li> </ul>  |
| <b>Network Architecture Models</b>      | Ad-hoc (Peer to Peer)<br>Infrastructure (Access Point Required)  |
| <b>Roaming</b>                          | IEEE 802.11 compliant roaming between access points  |
| <b>Output Power<sup>3</sup></b>         | <ul style="list-style-type: none"> <li>• 802.11b : +17dBm minimum</li> <li>• 802.11g : +16dBm minimum</li> <li>• 802.11a : +17dBm minimum</li> <li>• 802.11n HT20(2.4GHz) : +14dBm minimum</li> <li>• 802.11n HT40(2.4GHz) : +13dBm minimum</li> <li>• 802.11n HT20(5GHz) : +14dBm minimum</li> <li>• 802.11n HT40(5GHz) : +13dBm minimum</li> <li>• 802.11ac VHT80(5GHz) : +10dBm minimum</li> <li>• 802.11ac VHT160(5GHz) : +10dBm minimum</li> <li>• 802.11ax HE40(2.4GHz) : +12dBm minimum</li> <li>• 802.11ax HE80(5GHz) : +10dBm minimum</li> <li>• 802.11ax HE160(5GHz) : +10dBm minimum</li> </ul> |
| <b>Power Consumption</b>                | <ul style="list-style-type: none"> <li>• Transmit mode 2.0 W</li> <li>• Receive mode 1.6 W</li> <li>• Idle mode (PSP) 180 mW (WLAN Associated)</li> <li>• Idle mode 50 mW (WLAN unassociated)</li> <li>• Connected Standby 10mW</li> <li>• Radio disabled 8 mW</li> </ul>  |
| <b>Power Management</b>                 | ACPI and PCI Express compliant power management<br>802.11 compliant power saving mode  |
| <b>Receiver Sensitivity<sup>4</sup></b> | <ul style="list-style-type: none"> <li>• 802.11b, 1Mbps : -93.5dBm maximum</li> <li>• 802.11b, 11Mbps : -84dBm maximum</li> <li>• 802.11a/g, 6Mbps : -86dBm maximum</li> <li>• 802.11a/g, 54Mbps : -72dBm maximum</li> <li>• 802.11n, MCS07 : -67dBm maximum</li> <li>• 802.11n, MCS15 : -64dBm maximum</li> <li>• 802.11ac, MCS0(VHT80) : -84dBm maximum</li> </ul>   |

## Technical Specifications

|  |  |
|--|--|
|  | <ul style="list-style-type: none"> <li>• 802.11ac, MCS9(VHT80) : -59dBm maximum</li> <li>• 802.11ac, MCS9(VHT160) : -58.5dBm maximum</li> <li>• 802.11ax, MCS11(HE40): -57dBm maximum</li> <li>• 802.11ax, MCS11(HE80): -54dBm maximum</li> <li>• 802.11ax, MCS11(HE160): -53.5dBm maximum</li> </ul>                |
| <b>Antenna type</b>  | High efficiency antenna with spatial diversity, mounted in the display enclosure   |
|  | Two embedded dual band 2.4/5 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications  |
| <b>Form Factor</b>   | PCI-Express M.2 MiniCard   |
| <b>Dimensions</b>  | 1. Type 2230 : 2.3 x 22.0 x 30.0 mm<br>2. Type 1216: 1.67 x 12.0 x 16.0 mm   |
| <b>Weight</b>  | 1. Type 2230 : 2.8g<br>2. Type 1216: 1.3g  |
| <b>Operating Voltage</b>   | 3.3v +/- 9%  |
| <b>Temperature</b>   | <b>Operating</b> 14° to 158° F (-10° to 70° C)<br><b>Non-operating</b> -40° to 176° F (-40° to 80° C)  |
| <b>Humidity</b>  | <b>Operating</b> 10% to 90% (non-condensing)<br><b>Non-operating</b> 5% to 95% (non-condensing)  |
| <b>Altitude</b>  | <b>Operating</b> 0 to 10,000 ft (3,048 m)<br><b>Non-operating</b> 0 to 50,000 ft (15,240 m)  |
| <b>LED Activity</b>  | LED Amber – Radio OFF; LED OFF – Radio ON  |
| <b>HP Integrated Module with Bluetooth 4.0/4.1/4.2/5.0/5.1/5.2/5.3 Wireless Card</b> |  |
| <b>Bluetooth Specification</b>   | 4.0/4.1/4.2/5.0/5.1/5.2/5.3 Compliant  |
| <b>Frequency Band</b>  | 2402 to 2480 MHz   |
| <b>Number of Available Channels</b>  | Legacy : 0~79 (1 MHz/CH)<br>BLE : 0~39 (2 MHz/CH)  |
| <b>Signaling Data Rate</b>   | Legacy : 3 Mbps data rate; throughput up to 2.17 Mbps<br>BLE : 1 Mbps data rate; throughput up to 0.2 Mbps<br>Legacy : Synchronous Connection Oriented links up to 3, 64 kbps, voice channels<br>Legacy : Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5) |
| <b>Transmit Power</b>  | The Bluetooth component shall operate as a Class II Bluetooth device with a maximum transmit power of + 9.5 dBm for BR and EDR.  |
| <b>Power Consumption</b>   | Peak (Tx): 330 mW<br>Peak (Rx): 230 mW<br>Selective Suspend: 17 mW   |
| <b>Bluetooth Software Supported Link Topology</b>                                    | Bluetooth Software   |
| <b>Power Management</b>  | Microsoft Windows ACPI, and USB Bus Support  |
| <b>Certifications</b>  | FCC (47 CFR) Part 15C, Section 15.247 & 15.249   |
| <b>Power Management Certifications</b>   | ETS 300 328, ETS 300 826<br>Low Voltage Directive IEC950   |

## Technical Specifications

### Bluetooth Software Supported

UL, CSA, and CE Mark

BT4.1-ESR 5/6/7 Compliance

LE Link Layer Ping

LE Dual Mode

LE Link Layer

LE Low Duty Cycle Directed Advertising

LE L2CAP Connection Oriented Channels

Train Nudging & Interlaced Scan

BT4.2 ESR08 Compliance

LE Secure Connection- Basic/Full

LE Privacy 1.2 –Link Layer Privacy

LE Privacy 1.2 –Extended Scanner Filter Policies

LE Data Packet Length Extension

FAX Profile (FAX)

Basic Imaging Profile (BIP)2

Headset Profile (HSP)

Hands Free Profile (HFP)

Advanced Audio Distribution Profile (A2DP)

BT5.2

ESR9/10 Compliance

LE Advertisement Extensions

Channel Selection Algo

Limited High Duty Cycle Non-Connectable Advertising

2Mbps LE

LE Long Range

BT5.3

Host to Controller Encryption Key Control Enhancements

Compliance to the latest Errata Section 12.3 of BT 5.3 specification

1. Wi-Fi 6E requires a Wi-Fi 6E router, sold separately, to function in the 6GHz band. Availability of public wireless access points limited. Wi-Fi 6E is backwards compatible with prior 802.11 specs. And available in countries where Wi-Fi 6E is supported. Wi-Fi 6E is designed to support gigabit data rate when transferring files between two devices connected to the same router. Requires a wireless router, sold separately, that supports 80MHz and higher channels.
2. Check latest software/driver release for updates on supported security features.
3. The FCC has declared as of September 1, 2014 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels.
4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

## Technical Specifications

|   |  |   |
|---|--|---|
| <b>Intel® XMM™ 7560 R+<br/>LTE-Advanced Pro<sup>1</sup></b> | <b>Technology/Operating<br/>bands</b>              | FDD LTE: 2100 (Band 1), 1900 (Band 2), 1800 (Band 3),<br>1700/2100 (Band 4), 850 (Band 5), 2600 (Band 7), 900 (Band 8), 700<br>(Band 12 lower), 700 (Band 13 upper), 700 (Band 14 upper), 700<br>(Band 17 lower), 850 (Band 18 lower), 850 (Band 19 upper), 800<br>(Band 20), 1900 (Band 25), 850 (Band 26), 700 (Band 28), 700 (Band<br>29 RX only), 2300 (Band 30), 1700/2100 (Band 66), 600 (band 71).<br>TDD LTE: 2100 (Band 34), 2600 (Band 38), 1900 (Band 39), 2400<br>(Band 40), 2500 (Band 41), 3500 (Band 42), 3700 (Band 43), 3700<br>(band 48), 5200 (Band 46 RX only) MHz;<br>HSPA+: 2100 (Band 1), 1900 (Band 2), 1700/2100 (Band 4),<br>850 (Band 5), 900 (Band 8) MHz |
|   | <b>Wireless protocol standards</b>                 | 3GPP Release 12 LTE Specification DL-CAT.16, DL 100MHz BW<br>throughput up to 978Mbps; UL-CAT.13 40MHz throughput up to<br>150Mbps<br>WCDMA R99, 3GPP Release 5, 6, 7 and 8 UMTS Specification<br>Standalone GPS/Beidou/Glonass, A-GPS (MS-A, MS-B)   |
|   | <b>GPS<br/>GPS bands</b>                           | 1575.42 MHz ± 1.023 MHz, GLONASS 1596-1607MHz, Beidou<br>1561.098 MHz   |
|   | <b>Maximum data rates</b>                          | LTE: 978 Mbps (Download), 150 Mbps (Upload)<br>DC-HSPA+: 42 Mbps (Download), 5.76 Mbps (Upload)<br>HSPA+: 21Mbps (Download), 5.76 Mbps (Upload)   |
|   | <b>Maximum output power</b>                        | LTE: 23 dBm in all band except B41<br>LTE B41 HPUE = 26dBm<br>HSPA+: 23.5 dBm   |
|   | <b>Maximum power<br/>consumption</b>               | LTE: 1,200 mA (peak); 900 mA (average)<br>HSPA+: 1,100 mA (peak); 800 mA (average)  |
|   | <b>Form Factor</b>                                 | M.2, 3042-S3 Key B  |
|   | <b>Weight</b>                                      | 6 g   |
|   | <b>Dimensions<br/>(Length x Width x Thickness)</b> | 42 x 30 x 2.3 mm  |
|   | <b>embedded eSIM</b>                               | Support   |

1. Mobile Broadband is an optional feature, Connection requires wireless data service contract, network support, and is not available in all areas. Contact service providers determine the coverage area and availability. Connection speeds will vary due to location, environment, network conditions, and other factors. 4G LTE is not available on all products, in all regions.

## Technical Specifications

|   |   |  |
|---|---|--|
| <b>NFC Mirage module (NXP NPC300 I2C 10mmx17mm)</b> | <b>Dimensions (L x W x H)</b>   | Module 25 mm by 10 mm by 2.0 mm  |
|   | <b>Chipset</b>  | NPC300   |
|   | <b>System interface</b>   | I2C  |
|   | <b>NFC RF standards</b>   | ISO/IEC 14443 A<br>ISO/IEC 14443 B<br>ISO/IEC 15693<br>ISO/IEC 18092<br>ECMA-340 NFCIP-1 Target and Initiator<br>ECMA-320 NFCIP-2  |
|   | <b>NFC Forum Support</b>  | Tag Type 1, Type 2, Type3 and Type 4, NFCIP-1 and NFCIP-2  |
|   | <b>Reader (PCD-VCD) Mode</b>  | ISO/IEC 14443 A<br>ISO/IEC 14443 B<br>ISO/IEC 15693<br>MIFARE 1K<br>MIFARE 4K<br>MIFARE DESFire<br>FeliCa<br>Jewel and Topaz cards |
|   | <b>Card Emulation (PICC-VICC) Mode</b>                                | ISO/IEC 14443 A<br>ISO/IEC 14443 B and B'<br>MIFARE<br>FeliCa  |
|   | <b>Frequency</b>  | 13.56 MHz  |
|   | <b>NFC Modes Supported</b>  | Reader/Writer, Peer-to-Peer  |
|   | <b>Raw RF Data Rates</b>  | 106, 212, 424, 848 kbps  |
|   | <b>Operating temperature</b>  | 0°C to 70°C  |
|   | <b>Storage temperature</b>  | -20°C to 125°C   |
|   | <b>Humidity</b>   | 10-90% operating<br>5-95% non-operating  |
|   | <b>Supply Operating voltage</b>                                       | 4.35 to 5.25 Volts   |
|   | <b>I/O Voltage</b>  | 1.8V or 3.3V   |
|   | <b>Power Consumption (Booster enable, VBAT= 3.3V, VCC_BOOST = 5V)</b> |  |
|   | <b>Mode</b>   | Power Consumption, Typical   |
|   | <b>Polling</b>  | 7.3 mA   |
|   | <b>Detected Test Tag Type 1</b>                                       | Total 283.8 mA<br>Net Module 236.8 mA  |
|   | <b>Detected Test Tag Type 2</b>                                       | Total 288.8 mA<br>Net Module 241.8 mA  |
|   | <b>Detected Test Tag Type 3</b>                                       | Total 287.7 mA<br>Net Module 240.7 mA  |
|   | <b>Detected Test Tag Type 4</b>                                       | Total 282.3 mA<br>Net Module 235.3 mA  |
|   | <b>Antenna</b>  | Antenna connector, 0.5mm pitch, 7 connector FPC. Antenna matching is external to module.   |

## Technical Specifications

|   |                                     |  |
|---|-------------------------------------|--|
| <b>Intel® I219-LM 1 Gigabit Network Connection LOM (vPro)</b> | <b>Connector</b>                    | RJ-45  |
|   | <b>System Interface</b>             | PCI (Intel proprietary) + SMBus  |
|   | <b>Data rates supported</b>         | 10 Mbit/s operation (10BASE-T; IEEE 802.3i; IEEE 802.3 clauses 13-14)<br>100 Mbit/s operation (100BASE-TX; IEEE 802.3u; IEEE 802.3 clauses 21-30)<br>1000 Mbit/s operation (1000BASE-T; IEEE 802.3ab; IEEE 8023 clauses 40)<br>Auto-Negotiation (Automatic Speed Selection)<br>Full Duplex Operation at all Speeds, Half Duplex operation at 10 and 100 Mbit/s       |
|   | <b>IEEE Compliance</b>              | IEEE 802.1p QoS (Quality of Service) Support<br>IEEE 802.1q VLAN support<br>IEEE 802.3x Flow Control (IEEE 802.3 clauses 31-32; configurable)<br>IEEE 802.3az EEE (Energy Efficient Ethernet)  |
|   | <b>Performance</b>                  | TCP/IP/UDP Checksum Offload (configurable)<br>Protocol Offload (ARP & NS)<br>Large send offload and Giant send offload<br>Receiving Side Scaling (Hash Mode Only)<br>Jumbo Frame 9K  |
|   | <b>Power consumption</b>            | Cable Disconnection: 25mW<br>100Mbps Full Run: 450mW<br>1000bp Full Run: 1000mW<br>WoL Enable(S3/S4/S5): 50mW<br>WoL Disable(S3/S4/S5): 25mW   |
|   | <b>Power Management</b>             | ACPI compliant – multiple power modes<br>Situation-sensitive features reduce power consumption<br>Advanced link down power saving for reducing link down power consumption   |
|   | <b>Management Interface</b>         | Auto MDI/MDIX Crossover cable detection  |
|   | <b>IT Manageability</b>             | Wake-on-LAN from modern standby or sleep state (Magic Packet and Microsoft Wake-Up Frame); Wake-on-LAN from off (Magic Packet only)<br>PXE 2.1 Remote Boot<br>Statistics Gathering (SNMP MIB II, Ethernet-like MIB, Ethernet MIB (802.3x, clause 30))<br>Comprehensive diagnostic and configuration software suite<br>Virtual Cable Doctor for Ethernet cable status |
|   | <b>Security &amp; Manageability</b> | Intel® vPro™ support with appropriate Intel® chipset components  |

## Technical Specifications

|   |                                     |  |
|---|-------------------------------------|--|
| <b>Intel® I219v 1 Gigabit Network Connection LOM (non-vPro)</b> | <b>Connector</b>                    | RJ-45  |
|   | <b>System Interface</b>             | PCI (Intel proprietary) + SMBus  |
|   | <b>Data rates supported</b>         | 10 Mbit/s operation (10BASE-T; IEEE 802.3i; IEEE 802.3 clauses 13-14)<br>100 Mbit/s operation (100BASE-TX; IEEE 802.3u; IEEE 802.3 clauses 21-30)<br>1000 Mbit/s operation (1000BASE-T; IEEE 802.3ab; IEEE 8023 clauses 40)<br>Auto-Negotiation (Automatic Speed Selection)<br>Full Duplex Operation at all Speeds, Half Duplex operation at 10 and 100 Mbit/s       |
|   | <b>IEEE Compliance</b>              | IEEE 802.1p QoS (Quality of Service) Support<br>IEEE 802.1q VLAN support<br>IEEE 802.3x Flow Control (IEEE 802.3 clauses 31-32; configurable)<br>IEEE 802.3az EEE (Energy Efficient Ethernet)  |
|   | <b>Performance</b>                  | TCP/IP/UDP Checksum Offload (configurable)<br>Protocol Offload (ARP & NS)<br>Large send offload and Giant send offload<br>Receiving Side Scaling (Hash Mode Only)<br>Jumbo Frame 9K  |
|   | <b>Power consumption</b>            | Cable Disconnection: 25mW<br>100Mbps Full Run: 450mW<br>1000bp Full Run: 1000mW<br>WoL Enable(S3/S4/S5): 50mW<br>WoL Disable(S3/S4/S5): 25mW   |
|   | <b>Power Management</b>             | ACPI compliant – multiple power modes<br>Situation-sensitive features reduce power consumption<br>Advanced link down power saving for reducing link down power consumption   |
|   | <b>Management Interface</b>         | Auto MDI/MDIX Crossover cable detection  |
|   | <b>IT Manageability</b>             | Wake-on-LAN from modern standby or sleep state (Magic Packet and Microsoft Wake-Up Frame); Wake-on-LAN from off (Magic Packet only)<br>PXE 2.1 Remote Boot<br>Statistics Gathering (SNMP MIB II, Ethernet-like MIB, Ethernet MIB (802.3x, clause 30))<br>Comprehensive diagnostic and configuration software suite<br>Virtual Cable Doctor for Ethernet cable status |
|   | <b>Security &amp; Manageability</b> | Intel® vPro™ support with appropriate Intel® chipset components  |

### Technical Specifications

#### POWER

1. Actual battery Watt-hours (Wh) will vary from design capacity. Battery capacity will naturally decrease with shelf life, time, usage, environment, temperature, system configuration, loaded apps, features, power management settings and other factors

|   |  |   |
|---|--|---|
| <b>AC Adapter 65 Watt nPFC Standard USB Type C® Straight 1.8m</b> | <b>Dimensions (H x W x D)</b>              | 3.543 x 2.008 x 1.122 in (9.0 x 5.1 x 2.85 cm)  |
|   | <b>Weight</b>                              | 0.53 lb (240 g) max<br>(Not including power cord. Power cord varies by country.)  |
|   | <b>Input</b>                               | 100~240VAC  |
|   | <b>Input Efficiency</b>                    | Average Efficiency of 25%, 50%, 75%, 100% load condition with 115Vac/230Vac Spec:<br>5V : 81.5%<br>9V : 86.7%<br>12V : 88%<br>15V : 88%<br>20V : 89%  |
|   | <b>Input frequency range</b>               | 47 ~ 63 Hz  |
|   | <b>Input AC current</b>                    | Max. 1.6 A at 90 Vac  |
| <b>Output</b>   | <b>Output power</b>                        | 5V/15W<br>9V/27W<br>12V/60W<br>15V/60W<br>20V/65W   |
|   | <b>DC output</b>                           | 5V/9V/12V/15V/20V   |
|   | <b>Hold-up time</b>                        | 100% load 5ms at 115 Vac input  |
|   | <b>Output current limit</b>                | <8.0A   |
| <b>Connector</b>  |  | USB TYPE C®   |
| <b>Environmental Design</b>                                       | <b>Operating temperature</b>               | 32°F to 95°F (0°to 35°C)  |
|   | <b>Non-operating (storage) temperature</b> | -4°F to 185°F (-20°to 85°C)   |
|   | <b>Altitude</b>                            | 0 to 16,400 ft (0 to 5000m)   |
|   | <b>Humidity</b>                            | 20% to 95%  |
|   | <b>Storage Humidity</b>                    | 10% to 95%  |
| <b>EMI and Safety Certifications</b>                              |  | CE Mark - full compliance with LVD and EMC directives<br>Worldwide safety standards - IEC60950-1 and IEC62368-1 : 2018, EN62368-1:2014+A11, UL 62368-1<br>Agency approvals - C-UL-US, TUV/GS, TUV/PSE, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC and CECP, CU(EAC), EAEU, KCC (Safety+EMC) and K-MEPS, NOM-001 and 029 NYCE, NRcan, NRCS, ISC, SEC, PSB, Argentina S-mark, Australia RCM, BIS, BSMI, UAE, UKCA DoC |

|  |                               |  |
|--|-------------------------------|--|
| <b>AC Adapter 65 Watt Smart nPFC EM Barrel 4.5mm</b> | <b>Dimensions (H x W x D)</b> | 4.016 x 2.165 x 1.181 in (10.2 x 5.5 x 3 cm)                                     |
|  | <b>Weight</b>                 | 0.58 lb (265 g) max<br>(Not including power cord. Power cord varies by country.) |
|  | <b>Input</b>                  | 100 ~ 240VAC   |
|  | <b>Input Efficiency</b>       | 88.0 % at 115 Vac and 89.0 % at 230Vac   |
|  | <b>Input frequency range</b>  | 47 ~ 63 Hz   |

### Technical Specifications

|                             |  |   |
|-----------------------------|--|---|
| <b>Output</b>               | <b>Input AC current</b>                    | Max. 1.7 A at 90 Vac  |
|                             | <b>Output power</b>                        | 65W   |
|                             | <b>DC output</b>                           | 19.5V   |
|                             | <b>Hold-up time</b>                        | 100% load 5ms at 115 Vac input/80% load<br>10ms at 115 Vac input  |
| <b>Connector</b>            | <b>Output current limit</b>                | <11.0A  |
| <b>Environmental Design</b> |  | 4.5mm Barrel Type   |
|                             | <b>Operating temperature</b>               | 32°F to 95°F (0° to 35°C)   |
|                             | <b>Non-operating (storage) temperature</b> | -4°F to 185°F (-20° to 85°C)  |
|                             | <b>Altitude</b>                            | 0 to 16,400 ft (0 to 5000m)   |
|                             | <b>Humidity</b>                            | 20% to 95%  |
|                             | <b>Storage Humidity</b>                    | 10% to 95%  |
|                             | <b>EMI and Safety Certifications</b>       | CE Mark - full compliance with LVD and EMC directives<br>Worldwide safety standards - IEC60950-1 and IEC62368-1 : 2018, EN62368-1:2014+A11, UL62368-1<br>Agency approvals - C-UL-US, TUV/GS, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC and CECP, BIS, UKCA DoC |

|   |  |  |  |
|---|--|--|--|
| <b>AC Adapter 65 Watt Smart nPFC Standard Barrel 4.5mm Right Angle 1.8m</b> | <b>Dimensions (H x W x D)</b>              | 3.543 x 2.008 x 1.122 in (9.0 x 5.1 x 2.85 cm)                                   |  |
|   | <b>Weight</b>                              | 0.55 lb (250 g) max<br>(Not including power cord. Power cord varies by country.) |  |
|   | <b>Input</b>                               |  | 100 ~ 240VAC   |
|   |  | <b>Input Efficiency</b>  | 88.0 % at 115 Vac and 89.0 % at 230Vac                           |
|   |  | <b>Input frequency range</b>   | 47 ~ 63 Hz   |
|   | <b>Output</b>                              | <b>Input AC current</b>  | Max. 1.7 A at 90 Vac   |
|   |  | <b>Output power</b>  | 65W  |
|   |  | <b>DC output</b>   | 19.5V  |
|   |  | <b>Hold-up time</b>  | 100% load 5ms at 115 Vac input/80% load<br>10ms at 115 Vac input |
|   |  | <b>Output current limit</b>  | <11.0A   |
| <b>Connector</b>  |  | 4.5mm Barrel Type  |  |
| <b>Environmental Design</b>   | <b>Operating temperature</b>               | 32°F to 95°F (0° to 35°C)  |  |
|   | <b>Non-operating (storage) temperature</b> | -4°F to 185°F (-20° to 85°C)   |  |
|   | <b>Altitude</b>                            | 0 to 16,400 ft (0 to 5000m)  |  |
|   | <b>Humidity</b>                            | 20% to 95%   |  |
|   | <b>Storage Humidity</b>                    | 10% to 95%   |  |

### Technical Specifications

#### EMI and Safety Certifications

CE Mark - full compliance with LVD and EMC directives  
 Worldwide safety standards - IEC60950-1 and IEC62368-1 : 2018, EN62368-1:2014+A11, UL62368-1  
 Agency approvals - C-UL-US, TUV/GS, TUV/PSE, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC and CECP, CU(EAC), EAEU, KCC(Safety+EMC) and K-MEPS, NOM-001 and 029 NYCE, NRcan, NRCS, ISC, SEC, PSB, Argentina S-mark, Australia GEMS and RCM, BIS, BSMI, UAE, UKCA DoC

#### RH 51Whr Long Life Polymer Fast Charge 3 cell Battery<sup>1</sup>

#### Weight

0.2025 kg (0.446 lb)

#### Cells/Type

3cell Lithium-Ion Polymer cell / 566075

#### Energy

**Voltage** 11.58V

**Amp-hour capacity** 4.431Ah

**Watt-hour capacity<sup>1</sup>** 51.3Wh

#### Temperature

**Operating (Charging)** 32° to 113° F (0° to 45° C)

**Operating (Discharging)** 14° to 122° F (-10° to 60° C)

**Optional Travel Battery Available** No

1. Actual battery Watt-hours (Wh) will vary from design capacity. Battery capacity will naturally decrease with shelf life, time, usage, environment, temperature, system configuration, loaded apps, features, power management settings and other factors.

---

## Technical Specifications

### AUDIO

|   |   |
|---|---|
| <b>HD Stereo Codec</b>                  | Realtek ALC3247   |
| <b>Audio I/O Ports</b>                  | Headset connector supports a CTIA style headset and is re-taskable as a Microphone-in or Headphone-out port   |
| <b>Internal Speaker Amplifier</b>       | ALC 3247 has Embedded Class-D 2W Stereo Amplifier   |
| <b>Multi-streaming Capable Sampling</b> | Playback multi-streaming can be enabled in the audio control panel to allow independent audio streams to be sent to/from the front and rear jacks or integrated speaker.  |
| <b>Wavetable Syntheses</b>              | Independent sampling rates for DAC's and ADC's; supports resolutions from 16 to 24-bit; 44.1 kHz:<br>Internal SPK/Headphone/External MIC<br>24bit,48000Hz:<br>Digital MIC |
| <b>Analog Audio</b>                     | Support 3.5mm Headset: CTIA only and Headphone-out  |
| <b># of Channels on Line-Out</b>        | We do not support Line-Out  |
| <b>Internal Speaker</b>                 | Yes   |

---

### FINGERPRINT READER

|                                    |                             |
|------------------------------------|-----------------------------|
| <b>Sensor vendor</b>               | ELAN 80ST                   |
| <b>Sensor type</b>                 | Capacitive                  |
| <b>DPI resolution</b>              | 508 DPI                     |
| <b>Scan area</b>                   | 80x80 pixels                |
| <b>False Rejection Rate</b>        | <3%                         |
| <b>False Acceptance Rate</b>       | < 0.001%                    |
| <b>Mobile Voltage Operation</b>    | 2.7~3.6V                    |
| <b>Operating Temperature</b>       | -20°C - +80°C               |
| <b>Current Consumption</b>         | 35mA peak                   |
| <b>Image</b>                       |                             |
| <b>Low Latency Wait For Finger</b> | 900uA                       |
| <b>Capture Rate</b>                | Capture Rate: 50 frame/sec  |
| <b>ESD Resistance</b>              | IEC 61000-4-2 4B (+15KV)    |
| <b>Detection Matrix</b>            | 508 dpi / 4x4mm sensor area |

---

### Technical Specifications

#### ENVIRONMENTAL DATA

|  |  |                     |                     |
|--|--|---------------------|---------------------|
| <b>Eco-Label Certifications &amp; declarations</b>                         | <p>This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks:</p> <ul style="list-style-type: none"> <li>• IT ECO declaration</li> <li>• US ENERGY STAR®</li> <li>• US Federal Energy Management Program (FEMP)</li> <li>• EPEAT<sup>a</sup> Gold registered in the United States. See <a href="http://www.epeat.net">http://www.epeat.net</a> for registration status in your country.</li> <li>• TCO Certified</li> <li>• China Energy Conservation Program (CECP)</li> <li>• China State Environmental Protection Administration (SEPA)</li> <li>• Taiwan Green Mark</li> <li>• Korea Eco-label</li> <li>• Japan PC Green label*</li> </ul> |                     |                     |
| <b>Sustainable Impact Specifications</b>                                   | <ul style="list-style-type: none"> <li>• Ocean-bound plastic in speaker</li> <li>• 5% post-consumer recycled plastic</li> <li>• 50% recycled metal</li> <li>• Low halogen</li> <li>• Outside Box and corrugated cushions are 100% sustainably sourced and recyclable</li> <li>• Molded Paper Pulp Cushion inside box is 100% sustainably sourced and recyclable</li> <li>• Bulk packaging available</li> </ul>   |                     |                     |
| <b>System Configuration</b>  | <p>The configuration used for the Energy Consumption and Declared Noise Emissions data for the Notebook model is based on a “Typically Configured Notebook”.</p>   |                     |                     |
| <b>Energy Consumption (in accordance with US ENERGY STAR® test method)</b> | <b>115VAC, 60Hz</b>  | <b>230VAC, 50Hz</b> | <b>100VAC, 50Hz</b> |
| Normal Operation (Sort idle)   | 4.28 W   | 4.36 W              | 4.37 W              |
| Normal Operation (Long idle)   | 1.25 W   | 1.37 W              | 1.25 W              |
| Sleep  | 1.25 W   | 1.37 W              | 1.25 W              |
| Off  | 0.3 W  | 0.35 W              | 0.31 W              |
|  | <p><b>NOTE:</b><br/>Energy efficiency data listed is for an ENERGY STAR® compliant product if offered within the model family. HP computers marked with the ENERGY STAR® Logo are compliant with the applicable U.S. Environmental Protection Agency (EPA) ENERGY STAR® specifications for computers. If a model family does not offer ENERGY STAR® compliant configurations, then energy efficiency data listed is for a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system.</p>  |                     |                     |
| <b>Heat Dissipation*</b>   | <b>115VAC, 60Hz</b>  | <b>230VAC, 50Hz</b> | <b>100VAC, 50Hz</b> |
| Normal Operation (Short idle)  | 14.6 BTU/hr  | 14.9 BTU/hr         | 14.9 BTU/hr         |
| Normal Operation (Long idle)   | 4.3 BTU/hr   | 4.7 BTU/hr          | 4.3 BTU/hr          |
| Sleep  | 4.3 BTU/hr   | 4.7 BTU/hr          | 4.3 BTU/hr          |

### Technical Specifications

| Off  | 1.0 BTU/hr  | 1.2 BTU/hr   | 1.1 BTU/hr |
|--|---|--|------------|
|  | *NOTE: Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.   |  |            |
| <b>Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296)</b> | Sound Power (L <sub>WAd</sub> , bels)   | Sound Pressure (L <sub>pAm</sub> , decibels)                                       |            |
| Typically Configured – Idle  | 2.6   | 13.9   |            |
| Fixed Disk – Random writes   | 2.6   | 14.0   |            |
| Optical Drive – Sequential reads   | 3.1   | 24.4   |            |
| <b>Longevity and Upgrading</b>   | This product can be upgraded, possibly extending its useful life by several years. Upgradeable features and/or components contained in the  |  |            |
|  | Spare parts are available throughout the warranty period and or for up to “5” years after the end of production.  |  |            |
| <b>Additional Information</b>  | <ul style="list-style-type: none"> <li>This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2011/65/EC.</li> <li>This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive – 2002/96/EC.</li> <li>This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).</li> <li>This product is in compliance with the IEEE 1680 (EPEAT) standard at the Gold level, see <a href="http://www.epeat.net">www.epeat.net</a></li> <li>Plastics parts weighing over 25 grams used in the product are marked per ISO11469 and ISO1043.</li> <li>This product is 93.5% recycle-able when properly disposed of at end of life.</li> </ul>  |  |            |
| <b>Packaging Materials</b>   | <b>External:</b>  | PAPER/Corrugated   | 245 g      |
|  |   | PAPER/Corrugated   | 50 g       |
|  |   | PAPER/Molded Pulp  | 96 g       |
|  | <b>Internal:</b>  | PLASTIC/Polyethylene low density - LDPE  | 10 g       |
|  |   | The plastic packaging material contains at least 0.0% recycled content.            |            |
|  |   | The corrugated paper packaging materials contains at least 61.0% recycled content. |            |
| <b>RoHS Compliance</b>   | <p>HP Inc. complies fully with materials regulations. We were among the first companies to extend the restrictions in the European Union (EU) Restriction of Hazardous Substances (RoHS) Directive to our products worldwide through the HP GSE. HP has contributed to the development of related legislation in Europe, as well as China, India, and Vietnam.</p> <p>We believe the RoHS directive and similar laws play an important role in promoting industry-wide elimination of substances of concern. We have supported the inclusion of additional substances—including PVC, BFRs, and certain phthalates—in future RoHS legislation that pertains to electrical and electronics products.</p> <p>We met our voluntary objective to achieve worldwide compliance with the new EU RoHS requirements for virtually all relevant products by July 2013, and we will continue to extend the</p> |  |            |

### Technical Specifications

|                               |  |
|-------------------------------|--|
|                               | <p>scope of the commitment to include further restricted substances as regulations continue to evolve.</p> <p>To obtain a copy of the HP RoHS Compliance Statement, see <a href="#">HP RoHS position statement</a>.</p>  |
| <p><b>Material Usage</b></p>  | <p>This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at <a href="http://www.hp.com/hpinfo/globalcitizenship/environment/supplychain/gen_specifications.html">http://www.hp.com/hpinfo/globalcitizenship/environment/supplychain/gen_specifications.html</a>):</p> <ul style="list-style-type: none"> <li>• Asbestos</li> <li>• Certain Azo Colorants</li> <li>• Certain Brominated Flame Retardants – may not be used as flame retardants in plastics</li> <li>• Cadmium</li> <li>• Chlorinated Hydrocarbons</li> <li>• Chlorinated Paraffins</li> <li>• Bis(2-Ethylhexyl) phthalate (DEHP)</li> <li>• Benzyl butyl phthalate (BBP)</li> <li>• Dibutyl phthalate (DBP)</li> <li>• Diisobutyl phthalate (DIBP)</li> <li>• Formaldehyde</li> <li>• Halogenated Diphenyl Methanes</li> <li>• Lead carbonates and sulfates</li> <li>• Lead and Lead compounds</li> <li>• Mercuric Oxide Batteries</li> <li>• Nickel – finishes must not be used on the external surface designed to be frequently handled or carried by the user.</li> <li>• Ozone Depleting Substances</li> <li>• Polybrominated Biphenyls (PBBs)</li> <li>• Polybrominated Biphenyl Ethers (PBEBs)</li> <li>• Polybrominated Biphenyl Oxides (PBBOs)</li> <li>• Polychlorinated Biphenyl (PCB)</li> <li>• Polychlorinated Terphenyls (PCT)</li> <li>• Polyvinyl Chloride (PVC) – except for wires and cables, and certain retail packaging has been voluntarily removed from most applications.</li> <li>• Radioactive Substances</li> <li>• Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)</li> </ul> |
| <p><b>Packaging Usage</b></p> | <p>HP follows these guidelines to decrease the environmental impact of product packaging:</p> <ul style="list-style-type: none"> <li>• Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials.</li> <li>• Eliminate the use of ozone-depleting substances (ODS) in packaging materials.</li> <li>• Design packaging materials for ease of disassembly.</li> <li>• Maximize the use of post-consumer recycled content materials in packaging materials.</li> <li>• Use readily recyclable packaging materials such as paper and corrugated materials.</li> <li>• Reduce size and weight of packages to improve transportation fuel efficiency.</li> <li>• Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.</li> </ul>  |

### Technical Specifications

|   |   |
|---|---|
| <b>End-of-life Management and Recycling</b>         | <p>HP offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: <a href="http://www.hp.com/go/reuse-recycle">http://www.hp.com/go/reuse-recycle</a> or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.</p> <p>The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: <a href="http://www.hp.com/go/recyclers">http://www.hp.com/go/recyclers</a>. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.</p> |
| <b>HP, Inc. Corporate Environmental Information</b> | <p>For more information about HP's commitment to the environment:</p> <p>Global Citizenship Report<br/> <a href="http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html">http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html</a></p> <p>Eco-label certifications<br/> <a href="http://www8.hp.com/us/en/hp-information/environment/ecolabels.html">http://www8.hp.com/us/en/hp-information/environment/ecolabels.html</a></p> <p>ISO 14001 certificates:<br/> <a href="http://h20195.www2.hp.com/V2/GetDocument.aspx?docname=c04755842">http://h20195.www2.hp.com/V2/GetDocument.aspx?docname=c04755842</a><br/> and<br/> <a href="http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf">http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf</a></p>  |
| <b>footnotes</b>                                    | <ul style="list-style-type: none"> <li>• Percentage of ocean-bound plastic contained in each component varies by product</li> <li>• Recycled plastic content percentage is based on the definition set in the IEEE 1680.1-2018 standard.</li> <li>• External power supplies, WWAN modules, power cords, cables and peripherals excluded.</li> <li>• 100% outer box packaging and corrugated cushions made from sustainably sourced certified and recycled fibers.</li> <li>• Fiber cushions made from 100% recycled wood fiber and organic materials.</li> <li>• Plastic cushions are made from &gt;90% recycled plastic.</li> <li>• Recycled metal is expressed as a percentage of the total weight of the metal according to ISO 14021 definitions for metal parts over 25 grams.</li> </ul>  |

### COUNTRY OF ORIGIN

China

### Options and Accessories (Sold separately and availability may vary by country)

#### DOCKING (Sold Separately)

|  |  |
|--|--|
| <b>Docking station model #1</b>  | HP Thunderbolt 120W G4 Dock  |
| <b>Total number of supported displays (incl. the notebook display)</b> | 4  |
| <b>Max. resolutions supported</b>                                      | Quad 4K @60Hz<br>Dual 8K single cable@30 for TB hosts or USB-C hosts DP 1.4 with DSC in high res mode  |
| <b>Dock Connectors</b>   | 2xDP, 1xHDMI, 1xTB, 1xUSB-C Alt Mode   |
| <b>Technical limitations</b>   | Maximum resolution and display support is dependent on the maximum capability of the notebook.<br>Thunderbolt Hosts:<br>Maximum of (4) displays with maximum resolution of 5K@ 30Hz running Thunderbolt host.<br>Maximum resolution possible is dual 8K displays @ 60Hz running Thunderbolt host or running a non-Thunderbolt host in high resolution mode @30Hz<br>Non-Thunderbolt hosts:<br>The highest resolution for dual displays running a non-Thunderbolt host in multi-function mode is<br>(1) 5K dual cable (using both DP ports) +(1) 4K on USB-C DP port<br>Non-Thunderbolt hosts support (3) displays with a maximum resolution of (2) 5K single cable + (1) 4K UHD @ 60 Hz in high resolution mode. In multi-function mode the maximum resolution for (3) displays is (2) 5K single cable @ 30Hz + (1) 4K UHD @ 30Hz. |
| <b>Docking station model #2</b>  | HP Thunderbolt 280W G4 Dock  |
| <b>Total number of supported displays (incl. the notebook display)</b> | 4  |
| <b>Max. resolutions supported</b>                                      | Quad 4K @60Hz<br>Dual 8K single cable@30 for TB hosts or USB-C hosts DP 1.4 with DSC in high res mode  |
| <b>Dock Connectors</b>   | 2xDP, 1xHDMI, 1xTB, 1xUSB-C Alt Mode   |
| <b>Technical limitations</b>   | Maximum resolution and display support is dependent on the maximum capability of the notebook.<br>Thunderbolt Hosts:<br>Maximum of (4) displays with maximum resolution of 5K@ 30Hz running Thunderbolt host.<br>Maximum resolution possible is dual 8K displays @ 60Hz running Thunderbolt host or running a non-Thunderbolt host in high resolution mode @30Hz<br>Non-Thunderbolt hosts:<br>The highest resolution for dual displays running a non-Thunderbolt host in multi-function mode is<br>(1) 5K dual cable (using both DP ports) +(1) 4K on USB-C DP port<br>Non-Thunderbolt hosts support (3) displays with a maximum resolution of (2) 5K single cable + (1) 4K UHD @ 60 Hz in high resolution mode. In multi-function mode the maximum resolution for (3) displays is (2) 5K single cable @ 30Hz + (1) 4K UHD @ 30Hz. |
| <b>Docking station model #3</b>  | HP USB-C Dock G5   |

### Options and Accessories (Sold separately and availability may vary by country)

|  |   |
|--|---|
| <b>Total number of supported displays (incl. the notebook display)</b> | 3   |
| <b>Max. resolutions supported</b>                                      | Dual 5K@ 30Hz + (1) 4K UHD (multi-function mode)  |
| <b>Dock Connectors</b>   | 1xHDMI, 2xDP  |
| <b>Technical limitations</b>   | <p>Maximum resolution and display support is dependent on the maximum capability of the notebook.</p> <p>Highest resolution with dual displays is two 8K@ 60Hz host in High Resolution mode.</p> <p>Three maximum displays supported are two 5K@ 30 Hz on DP ports plus one 4K UHD@ 30 Hz on HDMI in Multi-function mode</p> <p>The highest resolution for a non-Thunderbolt host in Multi-function mode is a single 5K dual cable (using both DP ports) + (1) 4K on HDMI port.</p> |
| <br>   |   |
| <b>Docking station model #4</b>  | HP USB-C/A Universal Dock G2  |
| <b>Total number of supported displays (incl. the notebook display)</b> | 3   |
| <b>Max. resolutions supported</b>                                      | Dual 4K @ 60Hz<br>Single 5K @ 60Hz  |
| <b>Dock Connectors</b>   | 1xHDMI, 2xDP  |
| <b>Technical limitations</b>   | <p>Maximum resolution and display support is dependent on the maximum capability of the notebook.</p> <p>The best resolution for dual or triple displays is 4K UHD@ 60Hz.</p> <p>For use with the USB-A adapter that comes in the box the maximum number of displays supported is (2) 4k x 60 Hz on the Type-A Gen 1 connection from the host.</p>  |
| <br>   |   |
| <b>Docking station model #5</b>  | HP USB-C G5 Essential Dock  |
| <b>Total number of supported displays (incl. the notebook display)</b> | 3   |
| <b>Max. resolutions supported</b>                                      | <p>For hosts that support DisplayPort 1.4 with Display Stream Compression:</p> <p>3x FHD @ 60 Hz<br/>3x QHD @ 60 Hz<br/>3x 4K @ 60 Hz</p> <p>For hosts that support DisplayPort 1.3/1.4:</p> <p>3x FHD @ 60 Hz<br/>3x QHD @ 60 Hz<br/>2x 4K @ 60 Hz</p>   |
| <b>Dock Connectors</b>   | 1 x HDMI, 2 x DP  |
| <b>Technical limitations</b>   | Video resolution depends on the capability of the host machine. This dock provides up to 65W of power delivery to the host machine.   |

### Options and Accessories (Sold separately and availability may vary by country)

| Type                                     | Description                               | Part Number |
|--|---|-------------|
| <b>Audio</b>                             | HP Wired USB-A Stereo Headset             | 428K6AA     |
|  | HP Wired 3.5mm Stereo Headset             | 428K7AA     |
|  | HP 365 BT Speaker                         | 567D3AA#ACJ |
| <b>Video</b>                             | HP 325 FHD USB-A Webcam                   | 53X27AA     |
|  | HP 965 4K USB-A STR Webcam                | 695J5AA     |
| <b>Cases</b>                             | HP Prelude G2 15.6 Backpack               | 1E7D6AA     |
|  | HP Prelude G2 15.6 Top Load               | 1E7D7AA     |
|  | HP Prelude Pro Recycled 15.6 Backpack     | 1X644AA     |
|  | HP Prelude Pro Recycled 15.6 Top Load     | 1X645AA     |
|  | HP Renew Business 15.6 Laptop Bag         | 3E5F8AA     |
|  | HP Renew Business 17.3 Laptop Backpack    | 3E2U5AA     |
|  | HP Renew Business 17.3 Laptop Bag         | 3E2U6AA     |
|  | HP Renew Executive 16 Laptop Backpack     | 6B8Y1AA     |
| HP Renew Executive 16 Laptop Bag         | 6B8Y2AA                                   |             |
| <b>Docking</b>                           | HP USB-C 120W G5 Dock                     | 5TW10AA     |
|  | HP USB-C/A 120W G2 Universal Dock         | 5TW13AA     |
|  | HP Thunderbolt 120W G4 Dock               | 4J0A2AA     |
|  | HP Thunderbolt 280W G4 Dock               | 4J0G4AA     |
| <b>Hub</b>                               | HP 4K USB-C Multiport Hub                 | 6G842AA     |
|  | HP Universal USB-C Multiport Hub          | 50H55AA     |
|  | HP USB-C Travel Dock G2                   | 7PJ38AA     |
|  | HP USB-C to USB-A Hub                     | Z6A00AA     |
| <b>Adapter</b>                           | HP USB-C to RJ45 Adapter G2               | 4Z527AA     |
|  | HP USB 3.0 to Gigabit RJ45 Adapter G2     | 4Z7Z7AA     |
|  | HP HDMI to VGA Adapter                    | H4F02AA     |
|  | HP USB-C to DisplayPort Adapter           | N9K78AA     |
|  | HP USB-C to HDMI 2.0 Adapter              | 1WC36AA     |
|  | HP USB-C to USB 3.0 Adapter               | N2Z63AA     |
|  | HP USB-C to VGA Adapter                   | N9K76AA     |
| <b>Keyboard/Combo</b>                    | HP 125 WD USB Keyboard                    | 266C9AA     |
|  | HP 320K WD USB Keyboard                   | 9SR37AA     |
|  | HP 355 Compact Multi-Device BT Keyboard   | 692S9AA     |
|  | HP 455 Programmable Wireless Keyboard     | 4R177AA     |
|  | HP 975 USB+BT Dual-Mode Wireless Keyboard | 3Z726AA     |
|  | HP 155 Wired Mouse and Keyboard Combo     | 5B8C0AA#ACJ |
|  | HP 225 Wired Mouse and Keyboard Combo     | 286J4AA     |
| HP 235 Wireless Mouse and Keyboard Combo | 1Y4D0AA                                   |             |

### Options and Accessories (Sold separately and availability may vary by country)

|                  |  |             |
|------------------|--|-------------|
|                  | HP 655 Wireless Keyboard and Mouse Combo   | 4R009AA     |
|                  | HP Wired Desktop 320MK Mouse and Keyboard  | 95R36AA     |
|                  | HP Wireless Rechargeable 950MK Mouse and Keyboard                                | 3M165AA     |
| <b>Mouse</b>     | HP 125 USB-A Wired Mouse   | 265A9AA     |
|                  | HP 128 USB Laser Wired Mouse   | 265D9AA     |
|                  | HP 155 USB-A Wired Mouse   | 5B8B7AA#ACJ |
|                  | HP 235 Wireless 2.4GHz Slim Wireless Mouse                                       | 4E407AA     |
|                  | HP 320M USB-A Wired Mouse  | 9VA80AA     |
|                  | HP 435 Bluetooth 5.0 + Wireless 2.4GHz Multi-Device Wireless Mouse               | 3B4Q5AA     |
|                  | HP 715 Rechargeable Multi-Device Bluetooth 5.0 + Wireless 2.4GHz Bluetooth Mouse | 6E6F0AA     |
|                  | HP 925 Ergonomic Vertical Bluetooth 5.0 + Wireless 2.4GHz Wireless Mouse         | 6H1A5AA     |
|                  | HP Creator USB-A+Bluetooth 935 Wireless Mouse Black                              | 1D0K8AA     |
|                  | HP USB Premium Wireless Mouse  | 1JR31AA     |
|                  | HP USB-A+Bluetooth Multi-Device 635 Wireless Mouse Black                         | 1D0K2AA     |
|                  | HP USB-A+Bluetooth Travel Bluetooth Mouse  | 6SP30AA     |
| <b>Power</b>     | HP 45W USB-C LC AC Power Adapter   | 1MZ01AA     |
|                  | HP 65W 4.5 mm Smart AC Power Adapter   | H6Y89AA     |
|                  | HP 65W GaN USB-C Laptop Charger  | 600Q7AA     |
|                  | HP 65W USB-C Laptop Charger  | 671R3AA     |
|                  | HP 65W USB-C LC AC Power Adapter   | 1P3K6AA     |
|                  | HP 90W 4.5 mm Smart AC Power Adapter   | H6Y90AA     |
| <b>Commodity</b> | HP USB DVD-Writer EXT ODD  | F2B56AA     |
|                  | HP Nano Keyed Cable Lock   | 1AJ39AA     |
|                  | HP Nano Master Keyed Cable Lock  | 1AJ40AA     |
|                  | HP SureKey Standard/Nano/Wedge Cable Lock  | 6UW42AA     |
|                  | HP Combination Nano Cable Lock   | 63B28AA     |
|                  | HP Essential Combination Nano Cable Lock   | 63B31AA     |

### Change Log

| <b>Date of change:</b> | <b>Version History:</b> |         | <b>Description of change:</b>                |
|------------------------|-------------------------|---------|--|
| March 30, 2023         | V1 to V2                | Added   | Battery life and updated At a Glance section |
| April 24, 2023         | V2 to V3                | Updated | WWAN CAT in At a Glance section              |
| May 18, 2023           | V3 to V4                | Updated | Storage and Drives section                   |
|                        | V4 to V5                |         |  |
|                        |                         |         |  |
|                        |                         |         |  |
|                        |                         |         |  |

© Copyright 2023 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Intel, Core and Intel vPro are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries. DisplayPort™ and the DisplayPort™ logo are trademarks owned by the Video Electronics Standards Association (VESA®) in the United States and other countries. USB Type-C® and USB-C® are trademarks of USB Implementers Forum. ENERGY STAR is a registered trademark of the U.S. Environmental Protection Agency. Microsoft and Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.