

		M430WL	M380HL
Display Technology		0.65" DLP	
Light Output (lumens)		4,300 normal / Eco = variable	3,800 normal / Eco = variable
Resolution	Native	WXGA 1280 x 800	1080p 1920 x 1080
	Maximum	4K@30Hz 3840 x 2160	
Contrast Ratio (up to)		2,000:1	1,800:1
Light source Life (up to)		20,000 hours	
Screen Size (diagonal)		30 to 300 in. / 0.76 to 7.6m	
Throw Ratio		1.5 - 2.35:1	1.4 - 2.24:1
Projection Distance		3 - 50 ft. / 0.9 - 15.2m	
Projection Angle		7.7 - 9.8° tele / 12.1 - 15.4° wide (at 60°)	
Lens	Zoom	Manual	
	Zoom Ratio	1.6:1	
	Focus	Manual	
	F-number, f-number	F:2.5~3.26 / f=20.911~32.62mm	
	Shift	Manual (H = 0 / V = 0%~ +15%)	
Keystone Correction		Horizontal (manual), Vertical (manual)	
Synchronization Range	Horizontal	15, 24 to 100kHz (RGB: 24kHz or over)	
	Vertical	48 to 100, 120Hz	
Supported Video Standards			
SD/HD Video Signal Compatibility		4K UHD, 1080p, 1080i, 720p, 576p, 576i, 480p, 480i	
PC Signal Compatibility		VGA, SVGA, XGA, SXGA, WUXGA	
Macintosh Compatibility		Yes	
Input/Output Terminals	RGB1 (analog)	VGA 15 pin D-sub	
	RGB2 (analog)		
	RGB1 (Digital)		
	RGB2 (digital)	HDMI (v2.2 w/HDCPv1.4)	
	RGB3 (digital)	HDMI (v2.2 w/HDCPv1.4)	
	RGB4 (digital)		
	RGB5 (digital)		
	RGB6 (digital)		
	Option Slot		
	Video	RCA	
	Audio 1	Stereo Mini Jack	
	Audio 2		
	Audio Out	Stereo Mini Jack	
	Monitor Out		
	USB Type A	Power, (1.5A)	
	USB Type A (behind cover)		
USB Type B	USB Service		
Wired LAN port			
3D Sync Line			
Audio		10W mono	
External Control		RS-232 (D-Sub 9pin), IR	
Sync Compatibility			
Power Requirements		100 - 240V AC, 50/60Hz	
Input Current		3A	
Power Consumption		240W / 180W / 0.5W	
Installation Orientation		Floor/Front, Floor/Rear, Ceiling/Front, Ceiling/Rear	
Dimensions (WxDxH)		13.3 x 4.7 x 10.4 in. (337 x 119.3 x 265 mm)	
Net Weight		9.7 lbs. (4.4 kg)	
Fan Noise		34 dB normal / 31 dB eco	
Regulations		USA: TUV (UL62368-1) FCC Part15 Class B, Canada: CAN/CSA (62368-1-14) ICES-003 Issue 7	
Operating Temperature		41° - 104°F / 5° - 40°C	
Humidity		20-85% non-condensing	
Storage		14° - 140°F / -10° - 60°C	

		PE506WL	PE506UL	PE456USL
Display Technology		0.64" LCD w MLA		0.64" LCD w MLA
Light Output (lumens)		5,200 normal / Eco = variable		4,500 normal / Eco = variable
Resolution	Native	WXGA 1280 x 800	WUXGA 1920 x 1200	WUXGA 1920 x 1200
	Maximum	4K@30Hz 3840 x 2160		4K@30Hz 3840 x 2160
Contrast Ratio (up to)		3,000,000:1 with dynamic contrast		3,000,000:1 with dynamic contrast
Light source Life (up to)		20,000 hours		20,000 hours
Screen Size (diagonal)		30 to 300 in. / 0.76 to 7.6m		55 - 130 in. / 1.4 - 3.3m
Throw Ratio		1.2 - 2.1:1	1.2 - 2.0:1	0.44:1
Projection Distance		2.6 - 44.3 ft. / 0.8 - 13.5m		1.7 to 4.16 ft. / 0.517 to 1.268m
Projection Angle		0 to 9.6° tele / 0 to 15.9° wide	0 to 10.8° tele / 0 to 17.0° wide	34.5° (at 80°)
Lens	Zoom	Manual		Fixed
	Zoom Ratio	1.7:1	1.6:1	Fixed
	Focus	Manual		Manual
	F-number, f-number	F= 1.7~2.2, f= 17.4 to 29.0mm	F= 1.5~2.1, f= 17.2 to 27.6mm	F:1.6 / f=6.39mm
	Shift	Manual (H = +/- 26% / V = 0%~+55%)	Manual (H = +/- 29% / V = 0%~+60%)	
Keystone Correction		+/- 30° horizontal, +/- 30° vertical		+/- 15° horizontal (manual), +/- 15° vertical (manual + auto)
Synchronization Range	Horizontal	15 to 100KHz (RGB: 24kHz or over)		15 to 100KHz (RGB: 24kHz or over)
	Vertical	24 to 85Hz		24 to 85Hz
Supported Video Standards				
SD/HD Video Signal Compatibility		4K UHD, 1080p, 1080i, 720p, 576p, 576i, 480p, 480i		4K UHD, 1080p, 1080i, 720p, 576p, 576i, 480p, 480i
PC Signal Compatibility		VGA, SVGA, XGA, SXGA, SXGA+, WUXGA		VGA, SVGA, XGA, SXGA, SXGA+, WUXGA
Macintosh Compatibility		Yes		Yes
Input/Output Terminals	RGB1 (analog)	VGA 15 pin D-sub		VGA 15 pin D-sub
	RGB2 (analog)			
	RGB1 (Digital)			
	RGB2 (digital)	HDMI (w/HDCPv1.4)		HDMI (w/HDCPv1.4)
	RGB3 (digital)	HDMI (w/HDCPv1.4)		HDMI (w/HDCPv1.4)
	RGB4 (digital)			
	RGB5 (digital)			
	RGB6 (digital)			
	Option Slot			
	Video			
	Audio 1	Stereo Mini Jack		Stereo Mini Jack
	Audio 2			
	Audio Out	Stereo Mini Jack		Stereo Mini Jack
	Monitor Out	VGA 15 pin D-sub		VGA 15 pin D-sub
	USB Type A	Wireless LAN (optional), Memory, (2A)		Wireless LAN (optional), Memory, (2A)
USB Type A (behind cover)				
USB Type B	USB Service		USB Service	
Wired LAN port		RJ45 (100Base-TX/10Base-T)		RJ45 (100Base-TX/10Base-T)
3D Sync Line				
Audio		16W mono		16W mono
External Control		RS-232 (D-Sub 9pin), IR, RJ-45		RS-232 (D-Sub 9pin), IR, RJ-45
Sync Compatibility				
Power Requirements		100 - 240V AC, 50/60Hz		100 - 240V AC, 50/60Hz
Input Current		4.5 - 1.6A	4.5 - 1.6A	4.5 - 1.6A
Power Consumption		330W / 212W / 187W / 2W / 0.5W	352W / 228W / 201W / 2W / 0.5W	352W / 228W / 201W / 2W / 0.5W
Installation Orientation		Floor/Front, Floor/Rear, Ceiling/Front, Ceiling/Rear		Floor/Front, Floor/Rear, Ceiling/Front, Ceiling/Rear
Dimensions (WxDxH)		15.9 x 5.4 x 14.1 in. (405 x 137 x 358 mm)		15.9 x 6.5 x 15.9 in. (405 x 164 x 404 mm)
Net Weight		17.3 lbs. (7.85 kg)	17.5 lbs. (7.95 kg)	17.9 lbs. (8.1 kg)
Fan Noise		37 dB normal / 27 dB eco		37 dB normal / 27 dB eco
Regulations		USA: UL (UL60950-1/UL62368-1) FCC Part15 Class B, Canada: CAN/CSA (62368-1-14) ICES-003 Issue 7		USA: UL (UL60950-1/UL62368-1) FCC Part15 Class B, Canada: CAN/CSA (62368-1-14) ICES-003 Issue 7
Operating Temperature		32° - 104°F / 0° - 40°C		32° - 104°F / 0° - 40°C
Humidity		20-88% non-condensing		20-88% non-condensing
Storage		14° - 122°F / -10° - 50°C		14° - 122°F / -10° - 50°C

		P547UL	P627UL
Display Technology		0.64" LCD w MLA	
Light Output (lumens)		5,400 normal / Eco = variable	6,200 normal / Eco = variable
Resolution	Native	WUXGA 1920 x 1200	
	Maximum	4K@30Hz 3840 x 2160	
Contrast Ratio (up to)		3,000,000:1 with dynamic contrast	
Light source Life (up to)		20,000 hours	
Screen Size (diagonal)		30 to 300 in. / 0.76 to 7.62m	
Throw Ratio		1.23 - 2.0:1	
Projection Distance		2.6 - 42.3 ft. / 0.8 - 12.9m	
Projection Angle		0 to 10.7° tele / 0 to 17.1° wide	
Lens	Zoom	Manual	
	Zoom Ratio	1.6:1	
	Focus	Manual	
	F-number, f-number	F= 1.5~2.1, f= 17.2 to 27.7mm	
	Shift	Manual (H = +/- 29% / V = 0%~+60%)	
Keystone Correction		+/- 30° horizontal, +/- 30° vertical	
Synchronization Range	Horizontal	15 to 100KHz (RGB: 24kHz or over)	
	Vertical	50 to 120Hz	
Supported Video Standards			
SD/HD Video Signal Compatibility		4K UHD, 1080p, 1080i, 720p, 576p, 576i, 480p, 480i	
PC Signal Compatibility		VGA, SVGA, XGA, WXGA, SXGA, WUXGA	
Macintosh Compatibility		Yes	
Input/Output Terminals	RGB1 (analog)	VGA 15 pin D-sub	
	RGB2 (analog)		
	RGB1 (Digital)		
	RGB2 (digital)	HDMI (w/HDCPv1.4)	
	RGB3 (digital)	HDMI (w/HDCPv1.4)	
	RGB4 (digital)	HDBaseT (w/HDCPv1.4)	
	RGB5 (digital)		
	RGB6 (digital)		
	Option Slot		
	Video		
	Audio 1	Stereo Mini Jack	
	Audio 2		
	Audio Out	Stereo Mini Jack	
	Monitor Out		
USB Type A	Memory, (2A)		
USB Type A (behind cover)	Wireless LAN (optional)		
USB Type B	USB Service		
Wired LAN port		RJ45 (100Base-TX/10Base-T)	
3D Sync Line			
Audio		20W mono	
External Control		RS-232 (D-Sub 9pin), IR, RJ-45	
Sync Compatibility			
Power Requirements		100 - 240V AC, 50/60Hz	
Input Current		5.1 - 2.1A	
Power Consumption		303W / 222W / 2W / 0.3W	328W / 239W / 2W / 0.3W
Installation Orientation		Floor/Front, Floor/Rear, Ceiling/Front, Ceiling/Rear	
Dimensions (WxDxH)		18.9 x 16.0 x 5.6 in. / 480 x 407 x 142.5mm	
Net Weight		20.7 lbs. / 9.4 kg	
Fan Noise		26 dB normal / 22 dB eco	27 dB normal / 22 dB eco
Regulations		"USA: UL60950-1:2nd edition,2014, UL62368-1:2nd Edition, FDA, FCC Part15 Subpart B(ANSI C63.4:2014), Proposition65, TPCH Canada: CAN/CSA C22.2 No.62368-1-14,2nd Edition,2014, ICES-003 Issue7(ANSI C63.4:2014)"	
Operating Temperature		32° - 104°F / 0° - 40°C	
Humidity		20-80% non-condensing	
Storage		14° - 122°F / -10° - 50°C	

		PA703UL	PA804UL	PA1004UL	
Display Technology		0.76" LCD w MLA	0.76" LCD w MLA		
Light Output (lumens)		7,000 normal / Eco = variable	8,200 Boost Mode / Eco = variable	10,000 Boost Mode / Eco = variable	
Resolution	Native	WUXGA 1920 x 1200	WUXGA 1920 x 1200		
	Maximum	4K 4096 x 2160	4K 4096 x 2160		
Contrast Ratio (up to)		2,500,000:1 with auto iris	3,000,000:1 with auto iris		
Light source Life (up to)		20,000 hours	20,000 hours		
Screen Size (diagonal)		50 to 500 in. / 1.27 to 12.7m	50 to 500 in. / 1.27 to 12.7m		
Throw Ratio		NP44ML-01LK: 0.32:1	NP44ML-02LK: 0.32:1		
		NP40ZL: 0.79 - 1.11	NP40ZL: 0.79 - 1.11		
		NP41ZL: 1.30 - 3.02	NP41ZL: 1.30 - 3.02		
		NP43ZL: 2.88 - 5.93	NP43ZL: 2.88 - 5.93		
			NP11FL: 0.8:1		
			NP12ZL: 1.16 - 1.56:1		
			NP13ZL: 1.46 - 3.02:1		
			NP14ZL: 2.90 - 4.79:1		
			NP15ZL: 4.59 - 7.02:1		
Projection Distance		2.5 to 68.5 ft. / 0.74 to 20.9m	2.5 to 68.5 ft. / 0.74 to 20.9m		
Projection Angle		10.3 to 10.8° tele / 13.7 to 14.5° wide	10.3 to 10.8° tele / 13.7 to 14.5° wide		
Lens	Zoom	Motorized	Motorized		
	Zoom Ratio	Variable	Variable		
	Focus	Motorized	Motorized		
	F-number, f-number		NP44ML-01LK: F=2.0, f= 6.27mm	NP44ML-01LK: F=2.0, f= 6.27mm	
			NP40ZL: F=2.0 to 2.5, f= 13.3 to 18.6mm	NP40ZL: F=2.0 to 2.5, f= 13.3 to 18.6mm	
			NP41ZL: F=1.7 to 2.0, f= 21.8 to 49.8mm	NP41ZL: F=1.7 to 2.0, f= 21.8 to 49.8mm	
			NP43ZL: F=2.2 to 2.6, f= 49.7 to 99.8mm	NP43ZL: F=2.2 to 2.6, f= 49.7 to 99.8mm	
			NP11FL: F= 2.3, f= 13.2mm		
		(NP12ZL) F= 2.2 to 2.69, f= 19.4 to 25.3mm			
		(NP13ZL) F= 1.7 to 2.37, f= 24.2 to 48.6mm			
		(NP14ZL) F= 2.2 to 2.64, f= 48.5 to 77.6mm			
		(NP15ZL) F=2.2 to 2.7, f= 76.6 to 116.5mm			
	Shift	Motorized +0.5/-0.1 vertical, +/-30 horizontal	Motorized +0.5/-0.1 vertical, +/-30 horizontal		
Keystone Correction		+/- 40° horizontal, +/- 40° vertical	+/- 40° horizontal, +/- 40° vertical		
Synchronization Range	Horizontal	Analog: 15-100kHz, Digital: 15-153kHz	Analog: 15-100kHz, Digital: 15-153kHz		
	Vertical	Analog: 48-120Hz, Digital: 24-120Hz	Analog: 48-120Hz, Digital: 24-120Hz		
Supported Video Standards		NTSC, NTSC4.43, PAL, PAL-60, PAL-M, PAL-N, SECAM	NTSC, NTSC4.43, PAL, PAL-60, PAL-M, PAL-N, SECAM		
SD/HD Video Signal Compatibility		4K, 1080p, 1080i, 720p, 576p, 576i, 480p, 480i			
PC Signal Compatibility		VGA, SVGA, XGA, SXGA, SXGA+, UXGA, WUXGA, 4K			
Macintosh Compatibility		Yes	Yes		
Input/Output Terminals	RGB1 (analog)	VGA 15 pin D-sub, Component video using ADP-CV1E adapter			
	RGB2 (analog)				
	RGB1 (Digital)				
	RGB2 (digital)	HDMI (V2.0) w/HDCP (V1.4/2.2)	HDMI (V2.0) w/HDCP (V1.4/2.2)		
	RGB3 (digital)	HDMI (V2.0) w/HDCP (V1.4/2.2)	HDMI (V2.0) w/HDCP (V1.4/2.2)		
	RGB4 (digital)	DisplayPort w/HDCP (V1.4)	DisplayPort w/HDCP (V1.4)		
	RGB5 (digital)	HDBaseT w/HDCP (V1.4/2.2)	HDBaseT w/HDCP (V1.4/2.2)		
	RGB6 (digital)				
	Option Slot				
	Video				
	Audio 1	Stereo Mini Jack			
	Audio 2				
	Audio Out				
Monitor Out	HDBaseT				
USB Type A					
USB Type A (behind cover)					
USB Type B					
Wired LAN port					
3D Sync Line		3Pin D			
Audio					
External Control		RS-232, IR, HDBaseT, Stereo Mini, RJ-45			
Sync Compatibility		Separate Sync / Composite Sync / Sync on G			
Power Requirements		100 - 240V AC, 50/60Hz			
Input Current		10.5A - 4.5A	8.6A - 3.8A	10.5A - 4.6A	
Power Consumption		647W / 414W / 0.64W / 0.11	635W / 515W / 0.8W / 0.22W	750W / 610W / 0.8W / 0.22W	
Installation Orientation		Floor/Front, Floor/Rear, Ceiling/Front, Ceiling/Rear			
Dimensions (WxDxH)		22.8 x 19.4 x 8.2 in. / 580 x 494 x 208mm	23.6 x 8.5 x 19.3 in. / 599 x 216 x 490mm		
Net Weight		40.1lbs. / 18.2 kg	53.1 lbs. / 24.1 kg	53.8 lbs. / 24.4 kg	
Fan Noise		42 dB normal / 34 dB eco	30 dB normal / 28 dB eco	35 dB normal / 32 dB eco	
Regulations		USA: FCC Part15 Subpart B(ANSI C63.4:2014), UL62368-1:2nd Edition Canada: CSA C22.2 No.60950-1-07,2nd Edition,2014, NOM	USA UL60950-1: 2nd edition, FCC Part15 Subpart B(ANSI C63.4:2014), CAN/CSA C22.2 No.60950-1-07,2nd Edition,2014, ICES-003 Issue6(ANSI C63.4:2014)		
Operating Temperature		41° - 104°F / 5° - 40°C			
Humidity		20-80% non-condensing			
Storage		14° - 122°F / -10° - 50°C			

		PV710UL	PV800UL	
Display Technology		0.76" LCD w MLA		
Light Output (lumens)		7,100 Boost Mode / Eco = variable	8,000 Boost Mode / Eco = variable	
Resolution	Native	WUXGA 1920 x 1200		
	Maximum	4K 4096 x 2160		
Contrast Ratio (up to)		3,000,000:1 with auto iris		
Light source Life (up to)		20,000 hours		
Screen Size (diagonal)		50 to 500 in. / 1.27 to 12.7m		
Throw Ratio		NP13ZL: 1.46 - 3.02:1		
		NP44ML-02LK: 0.32:1		
		NP40ZL: 0.79 - 1.11		
		NP41ZL: 1.30 - 3.02		
		NP43ZL: 2.88 - 5.93		
Projection Distance		2.5 to 68.5 ft. / 0.74 to 20.9m		
Projection Angle		10.3 to 10.8° tele / 13.7 to 14.5° wide		
Lens	Zoom	Manual	Motorized	
	Zoom Ratio	Variable		
	Focus	Manual	Motorized	
	F-number, f-number		(NP13ZL) F= 1.7 to 2.37, f= 24.2 to 48.6mm	
			NP44ML-01LK: F=2.0, f= 6.27mm	
			NP40ZL: F=2.0 to 2.5, f= 13.3 to 18.6mm	
		NP41ZL: F=1.7 to 2.0, f= 21.8 to 49.8mm		
Shift	Motorized +0.5/-0.1 vertical, +/-30 horizontal			
Keystone Correction		+/- 30° horizontal, +/- 30° vertical		
Synchronization Range	Horizontal	Analog: 15-100kHz, Digital: 15-153kHz		
	Vertical	Analog: 48-120Hz, Digital: 24-120Hz		
Supported Video Standards		NTSC, NTSC4.43, PAL, PAL-60, PAL-M, PAL-N, SECAM		
SD/HD Video Signal Compatibility				
PC Signal Compatibility				
Macintosh Compatibility		Yes		
Input/Output Terminals	RGB1 (analog)			
	RGB2 (analog)			
	RGB1 (Digital)			
	RGB2 (digital)	HDMI (V2.0) w/HDCP (V1.4/2.2)		
	RGB3 (digital)	HDMI (V2.0) w/HDCP (V1.4/2.2)		
	RGB4 (digital)			
	RGB5 (digital)	HDBaseT w/HDCP (V1.4/2.2)		
	RGB6 (digital)			
	Option Slot			
	Video			
	Audio 1			
	Audio 2			
	Audio Out			
	Monitor Out			
	USB Type A			
USB Type A (behind cover)				
USB Type B				
Wired LAN port				
3D Sync Line				
Audio				
External Control		RS-232, IR, HDBaseT, RJ-45		
Sync Compatibility		Separate Sync / Composite Sync / Sync on G		
Power Requirements		100 - 240V AC, 50/60Hz		
Input Current		5.3A - 2.2A	6.1A - 2.5A	
Power Consumption		412W / 456W / 0.6W / 0.17W	445W / 490W / 0.6W / 0.17W	
Installation Orientation		Floor/Front, Floor/Rear, Ceiling/Front, Ceiling/Rear		
Dimensions (WxDxH)		19.8 x 16.2 x 6.6 in. / 503 x 411 x 168mm		
Net Weight		24.7 lbs. / 11.2 kg	24.7 lbs. / 11.2 kg	
Fan Noise		40 dB normal / 31 dB eco	42 dB normal / 33 dB eco	
Regulations		USA UL60950-1: 2nd edition, FCC Part15 Subpart B(ANSI C63.4:2014), CAN/CSA C22.2 No.60950-1-07,2nd Edition,2014, ICES-003 Issue6(ANSI C63.4:2014)		
Operating Temperature		32° - 113°F / 0° - 45°C		
Humidity		20-80% non-condensing		
Storage		14° - 122°F / -10° - 50°C		

		PX1004UL	PX2201UL	
Display Technology		0.67" DMD	DLP (0.96" DMD)	
Light Output (lumens)		10,000 normal / Eco = variable	21,500 (Center)	
Resolution	Native	WUXGA 1920 x 1200	WUXGA 1920 x 1200	
	Maximum	4K 4096 x 2160	WQXGA 2560 x 1600	
Contrast Ratio (up to)		15,000:1 with dynamic contrast	10,000:1 with dynamic contrast	
Light source Life (up to)		20,000 hours	20,000 hours	
Screen Size (diagonal)		30 to 300 in. / 0.76 to 7.62m	40 to 500 in. / 1.02 to 12.7m	
Throw Ratio		NP39ML: 0.38:1	NP45ZL: 0.9 - 1.2:1	
		NP31ZL: 0.75 - 0.93:1	NP46ZL: 1.2 - 1.56:1	
		NP16FL: 0.76:1	NP47ZL: 1.5 - 2.0:1	
		NP17ZL: 1.25 - 1.79:1	NP48ZL: 2.0 - 4.0:1	
		NP18ZL: 1.73 - 2.27:1	NP49ZL: 4.0-7.0:1	
		NP19ZL: 2.22 - 3.67:1		
		NP20ZL: 3.58 - 5.38:1		
		NP21ZL 5.31 - 8.26:1		
Projection Distance		2.1 to 179.8 ft. / 0.64 to 54.8m	3.3 to 247.4 ft. / 1.0 to 75.4m	
Projection Angle		2.1 to 19.1° tele / 3.3 to 24.0° wide	10.3 to 10.8° tele / 13.7 to 14.5° wide	
Lens	Zoom	Motorized	Motorized	
	Zoom Ratio	Variable	Variable	
	Focus	Motorized	Motorized	
	F-number, f-number		NP39ML: F=2.0, f=5.64mm	NP45ZL: F=2.2 to 2.53, f= 19.34 to 25.76mm
			NP31ZL: F=1.96 to 2.3, f=11.3 to 14.1mm	NP46ZL: F=2.18 to 2.66, f= 25.69 to 33.22mm
			NP-16FL: F=1.85, f=11.6mm	NP47ZL: F=2.17 to 2.65, f= 31.90 to 42.20mm
			NP17ZL: F=1.85 to 2.5, f=18.7 to 26.5mm	NP48ZL: F=2.17 to 2.65, f= 42.60 to 84.80mm
			NP18ZL: F=1.64 to 1.86, f=25.7 to 33.7mm	NP49ZL: F=2.2 to 2.57, f= 83.93 to 146.85mm
		NP19ZL: F=1.86 to 2.48, f=32.9 to 54.2mm		
	NP20ZL: F=1.85 to 2.4, f=52.8 to 79.1mm			
	NP21ZL: F=1.85 to 2.48, f=78.5 to 121.9mm			
	Shift	Motorized +0.59 vertical, +/-28 horizontal	+50/-10% Vertical, +/-30% Horizontal	
Keystone Correction		+/- 40° horizontal, +/- 40° vertical	+/- 60° horizontal, +/- 40° vertical	
Synchronization Range	Horizontal	Analog: 15-100kHz, Digital: 15-153kHz	Analog: 15-100kHz, Digital: 15-153kHz	
	Vertical	Analog: 48-120Hz, Digital: 24-120Hz	Analog: 48-120Hz, Digital: 24-120Hz	
Supported Video Standards		NTSC, NTSC4.43, PAL, PAL-60, PAL-M, PAL-N, SECAM	NTSC, NTSC4.43, PAL, PAL-60, PAL-M, PAL-N, SECAM	
SD/HD Video Signal Compatibility				
PC Signal Compatibility				
Macintosh Compatibility		Yes	Yes	
Input/Output Terminals	RGB1 (analog)		VGA 15 pin D-sub, Component video using ADP-CV1E adapter	
	RGB2 (analog)	5-BNC	5-BNC	
	RGB1 (Digital)		HDMI (V2.0) w/HDCP (V1.4/2.2)	
	RGB2 (digital)	HDMI (V1.4) w/HDCP	HDMI (V2.0) w/HDCP (V1.4/2.2)	
	RGB3 (digital)	DisplayPort w/HDCP	DisplayPort w/HDCP (V1.4)	
	RGB4 (digital)	HDBaseT	DVI-D w/HDCP (V1.4/2.2)	
	RGB5 (digital)		HDBaseT w/HDCP (V1.4/2.2)	
	RGB6 (digital)		3G-SDI	
	Option Slot	OPS		
	Video			
	Audio 1			
	Audio 2			
	Audio Out			
	Monitor Out	HDMI (V1.4) w/HDCP	VGA 15 pin D-sub	
USB Type A				
USB Type A (behind cover)				
USB Type B				
Wired LAN port				
3D Sync Line		3Pin D	BNC	
Audio				
External Control		RS-232, IR, HDBaseT, Stereo Mini , RJ-45	RS-232, IR, DDC/CI	
Sync Compatibility		Separate Sync / Composite Sync / Sync on G	Separate Sync / Composite Sync / Sync on G	
Power Requirements		100 - 240V AC, 50/60Hz	200 - 240V AC, 50/60Hz	
Input Current		11.8A - 5.2A	8.7A	
Power Consumption		1220W/625W/4.3W/0.2W	1922W / 1779W / 1461W / 4.8W / 0.4W	
Installation Orientation		Floor/Front, Floor/Rear, Ceiling/Front, Ceiling/Rear	Floor/Front, Floor/Rear, Ceiling/Front, Ceiling/Rear	
Dimensions (WxDxH)		19.7 x 22.8 x 8.5 in. / 500 x 583 x 216mm	20.9 x 10.8 x 29.4 in. / 530 x 275 x 748 mm	
Net Weight		63.9 lbs. / 29.0 kg	112.4 lbs. / 67 kg	
Fan Noise		42 dB normal / 37 dB eco	45 dB normal	
Regulations		USA: UL(UL60950-1, Laser + Lamp (IEC60825-1 + IEC62471), FCC Part15 Class A Canada: CUL(UL60950-1, Laser + Lamp (IEC60825-1 + IEC62471), ICES-003 Class A		
Operating Temperature		41° - 104°F / 5° - 40°C	41° - 104°F / 5° - 40°C	
Humidity		20-80% non-condensing	20-80% non-condensing	
Storage		14° - 122°F / -10° - 50°C	14° - 122°F / -10° - 50°C	

PH3501QL			
Display Technology			
Light Output (lumens)		35,000 normal / Eco = variable	
Resolution	Native	DC4K 4096 x 2160	
	Maximum	4K 4096 x 2160	
Contrast Ratio (up to)		2,000:1 with dynamic contrast	
Light source Life (up to)		20,000 hours	
Screen Size (diagonal)		50 to 500 in. / 1.27 to 12.7m	
Throw Ratio	L2K-10F1: 0.93:1		
	L4K-11ZM: 1.24 - 1.73:1		
	L4K-15ZM: 1.52 - 2.10:1		
	L4K-20ZM: 1.98 - 3.34:1		
	L2K-30ZM: 2.71 - 3.92:1		
	L2K-43ZM1: 3.91 - 5.52:1		
L2K-55ZM1: 5.00 - 7.80:1			
Projection Distance		2.5 to 68.5 ft. / 0.74 to 20.9m	
Projection Angle		10.3 to 10.8° tele / 13.7 to 14.5° wide	
Lens	Zoom	Motorized	
	Zoom Ratio	Variable	
	Focus	Motorized	
	F-number, f-number	L2K-10F1: F=2.5, f= 28.95mm	
		L4K-11ZM: F=2.5, f= 38.5 to 53.7mm	
		L4K-15ZM: F=2.5, f= 47.5 to 65.6mm	
		L4K-20ZM: F=2.5, f= 61.4 to 105.2mm	
		L2K-30ZM: F=2.5, f= 85.0 to 121.6mm	
		L2K-43ZM1: F=2.5, f= 122.8 to 172.3mm	
	L2K-55ZM1: F=2.5, f= 156.5 to 243.1mm		
	L2K-10F1:	Motorized +/-0.27 Vertical, +/-0.08 Horizontal	
	L4K-11ZM:		
	L4K-15ZM:		
	L4K-20ZM:	Motorized +/-0.17 Vertical, +/-0.50 Horizontal	
	L2K-30ZM:		
	L2K-43ZM1:		
	Shift	L2K-55ZM1: Motorized +/-0.31 Vertical, +/-0.10 Horizontal	
Keystone Correction		+/- 40° horizontal, +/- 40° vertical	
Synchronization Range	Horizontal	Analog: 15-100kHz, Digital: 15-153kHz	
	Vertical	Analog: 48-120Hz, Digital: 24-120Hz	
Supported Video Standards		NTSC, NTSC4.43, PAL, PAL-60, PAL-M, PAL-N, SECAM	
SD/HD Video Signal Compatibility		4K, 1080p, 1080i, 720p, 576p, 576i, 480p, 480i	
PC Signal Compatibility		VGA, SVGA, XGA, SXGA, SXGA+, UXGA, WUXGA, 4K	
Macintosh Compatibility		Yes	
Input/Output Terminals	RGB1 (analog)	VGA 15 pin D-sub, Component video using ADP-CV1E adapter	
	RGB2 (analog)		
	RGB1 (Digital)	HDMI (V2.0) w/HDCP (V1.4/2.2) - 4096 x 2160 @ 60p, 12 bit 4:4:4	
	RGB2 (digital)	HDMI (V2.0) w/HDCP (V1.4/2.2) - 4096 x 2160 @ 60p, 12 bit 4:4:4	
	RGB3 (digital)	DisplayPort w/HDCP (V1.4) - 4096 x 2160 @ 60p, 12 bit 4:4:4	
	RGB4 (digital)	DisplayPort w/HDCP (V1.4) - 4096 x 2160 @ 60p, 12 bit 4:4:4	
	RGB5 (digital)	HDBaseT w/HDCP (V1.4/2.2) - 4096 x 2160 @ 60p, 8 bit 4:2:0	
	RGB6 (digital)	Quad 3G-SDI	
	Option Slot		
	Video		
	Audio 1		
	Audio 2		
	Audio Out		
Monitor Out			
USB Type A			
USB Type A (behind cover)			
USB Type B			
Wired LAN port			
3D Sync Line		15 pin	
Audio			
External Control		RS-232, IR, HDBaseT, Stereo Mini, RJ-45	
Sync Compatibility		Separate Sync / Composite Sync / Sync on G	
Power Requirements		220 - 240V AC, 50/60Hz Single Phase	
Input Current		30A	
Power Consumption		4705W / 205W	
Installation Orientation			
Dimensions (WxDxH)		27.4 x 46.5 x 17.9 in. / 697 x 1180 x 455mm	
Net Weight		372.6 lbs. / 169 kg	
Fan Noise		55 dB normal	
Regulations		"UL60950-1 (2nd)/FCC Part15 Class A (Marking: UL) CSA60950-1/ICES-003 Class A (Marking: CAN ICES-38(A)/NMB-38(A)) EN60950-1/EN55022 Class A, EN55032 Class A, EN55024, EN61000-3-2/-3-3/-3-11/-3-12 (Marking CE) IEC60825-1 Edition3 2014 : Class1, IEC62471 2006 : RG3, FDA(21 CFR 1040.10 and 1040.11) IEC60825-1 Edition3 2014 : Class1, IEC62471 2006 : RG3 "	
Operating Temperature		41° - 104°F / 5° - 40°C	
Humidity		20-80% non-condensing	
Storage		14° - 122°F / -10° - 50°C	

3D Reform, Advanced AccuBlend, AutoSense and ECO Mode are trademarks of Sharp NEC Display Solutions. HDMI, the HDMI Logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC. All other brand or product names are trademarks or registered trademarks of their respective holders. Product specifications subject to change.