senerated 2024-06-30, check for the latest version www.msi.com/datasheet. The information provided in this document is intended for informational purposes only and is subject to change without notice.



GeForce RTX™ 4070 Ti SUPER 16G VENTUS 3X OC









SPECIFICATIONS

Model Name	GeForce RTX™ 4070 Ti SUPER 16G VENTUS 3X OC
Graphics Processing Unit	NVIDIA [®] GeForce RTX™ 4070 Ti SUPER
Interface	PCI Express® Gen 4
Core Clocks	Extreme Performance: 2655 MHz (MSI Center) Boost: 2640 MHz
Cores	8448 Units
Memory	16GB GDDR6X
Memory Bus	256-bit
Output	DisplayPort x 3 (v1.4a) HDMI [™] x 1 (Supports 4K@120Hz HDR, 8K@60Hz HDR, and Variable Refresh Rate as specified in HDMI [™] 2.1a)
HDCP Support	Υ
Power consumption	285 W
Power Connectors	16-pin x 1
Recommended PSU (W)	700 W
Card Dimension(mm)	308 x 120 x 50 mm
Weight (Card / Package)	1107g / 1661g
Maximum Displays	4
G-SYNC™ technology	Y
Digital Maximum Resolution	7680 x 4320

CONNECTIONS



FEATURES



Afterburner

Take full control with the most recognized and widely used graphics card overclocking software in the world.





Three fans and a huge heatsink ensure a cool and quiet experience for you.



TORX FAN 4.0

A masterpiece of teamwork, fan blades work in pairs to create unprecedented levels of focused air pressure.



Core Pipe

Precision-machined heat pipes ensure max contact to the GPU and spread heat along the full length of the heatsink.



Airflow Control

Don't sweat it, Airflow Control guides the air to exactly where it needs to be for maximum cooling.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.



Reinforcing Backplate

The reinforcing backplate features a flow-through design that provides additional ventilation.



Copper Baseplate

A solid nickel-plated copper baseplate transfers heat from the GPU to all heat pipes for better cooling.