

### Overview

#### HPE Aruba Networking CX 6300 Switch Series

The HPE Aruba Networking CX 6300 Switch Series is a modern, flexible, and intelligent family of stackable switches ideal for enterprise network access, aggregation, core, and data center top of rack (ToR) deployments. Created for game-changing operational efficiency with built-in security and resiliency, the HPE Aruba Networking CX 6300 switches provide the foundation for high-performance networks supporting IoT, mobile and cloud applications.

Built from the ground up with a combination of cutting-edge hardware, software and analytics and automation tools, the stackable HPE Aruba Networking CX 6300 switches are part of the HPE Aruba Networking CX switching portfolio, designed for today's enterprise campus, branch and data center networks. By combining a modern, fully programmable OS with the HPE Aruba Network Analytics Engine, the HPE Aruba Networking CX 6300 switches provide industry leading monitoring and troubleshooting capabilities for the access layer.

A powerful HPE Aruba Networking Gen7 ASIC architecture delivers performance and robust feature support with flexible programmability for tomorrow's applications. The HPE Aruba Virtual Stacking Framework (VSF) allows for stacking of up to 10 switches, providing scale and simplified management. This flexible series has built-in wirespeed 1/10/25/50GbE uplinks and supports high density IEEE 802.3bt high power PoE. HPE Smart Rate multi-gigabit Ethernet paves the way for high-speed access points and IoT devices by delivering fast connectivity and high power PoE using existing cabling. Modular models offer redundancy and PoE customization with hot-swappable power supplies and fans. Back-to-front airflow available in switch bundle for hot-cold aisle top-of-rack (TOR) and out-of-band-management (OOBM) data center deployments.

HPE Aruba Networking Dynamic Segmentation extends HPE Aruba Networking's foundational wireless role-based policy capability to HPE Aruba Networking wired switches. What this means is that the same security, user experience and simplified IT management can be enjoyed throughout the network. Regardless of how users and IoT devices connect, consistent policies are enforced across wired and wireless networks, keeping traffic secure and separate.



HPE Aruba Networking CX 6300 Switch Series

---

## Overview

### Key Features

- Stackable Layer 3 switches with BGP, EVPN, VXLAN, VRF, and OSPF with robust security and QoS
- High performance 880 Gbps system switching capacity, 660 MPPS of system throughput and up to 200 Gbps stacking bandwidth (400 Gbps at full duplex)
- Compact 1U switches with full density HPE Smart Rate (1G/2.5G/5G/10GbE) multi-gigabit, up to 90W PoE (Class 8) and 10G LRM SFP+ available on select models
- Power-to-port switch bundle with back-to-front airflow ideal for data center 1GbE ToR and OOBM deployments
- Three stackable, high-performance Layer 2-only CX 6300L access switches with HPE Smart Rate Multi-Gigabit and MACsec encryption
- Built-in high speed 1/10/25/50GbE uplinks<sup>1</sup>
- 50GbE connectivity with 50GbE DACs<sup>1</sup>
- Intelligent monitoring, visibility, and remediation with HPE Aruba Network Analytics Engine
- Manage via single pane of glass with HPE Aruba Networking Central across wired, wireless, and WAN
- HPE Aruba Networking NetEdit support for automated configuration and verification
- HPE Aruba Networking Dynamic Segmentation enables secure and simple access for users and IoT

**Notes:** <sup>1</sup>50G capability is for use with 50G DACs for both interconnect and VSF stacking. 50G transceivers and DACs are not supported on S0E91A and S0X44A switch models, which requires QSFP to SFP56 DAC cable for VSF stacking with other CX 6300F and CX 6300M switch models only. VSF stacking not supported on 1G ports.

---

### What's New

- Stackable Layer 3 switches with BGP, EVPN, VXLAN, VRF, and OSPF with robust security and QoS, now supporting MACsec 256, PTP, AVB and LRM.
  - Stackable Layer 3 switches with BGP, EVPN, VXLAN, VRF, and OSPF with robust security and QoS, now supporting MACsec 256, PTP, AVB and LRM..
  - Series includes full density HPE Smart Rate (1/2.5/5/10GbE) multi-gigabit and up to 90W PoE, SFP+ model and switch bundle with power-to-port airflow for data center 1GbE ToR and OOBM deployments.
  - Built-in high speed 10/25/40/50/100GbE uplinks (50GbE for DAC connectivity only) with intelligent monitoring and visibility via HPE Aruba Networking Network Analytics Engine.
  - Manage via single pane of glass with HPE Aruba Networking Central across wired, wireless, and WAN. Dynamic Segmentation enables enhanced security and simple access for users and IoT.
  - HPE Data Center Networking Solution SKU (R9F63A) for HPE integrated and mixed use HPE Compute, HPE Storage and HPE Aruba Networking configuration and deployments.
- 



## Standard Features

### AOS-CX - A Modern Operating System

The HPE Aruba Networking CX 6300 Switch Series is based on AOS-CX, a modern, database-driven operating system that automates and simplifies many critical and complex network tasks. A built-in time series database enables customers and developers to utilize software scripts for historical troubleshooting, as well as analysis of past trends. This helps predict and avoid future problems due to scale, security, and performance bottlenecks. Because AOS-CX is built on a modular architecture with a stateful database, our operating system provides the following unique capabilities:

- Easy access to all network state information allows unique visibility and analytics
- REST APIs and Python scripting for fine-grained programmability of network tasks
- A micro-services architecture that enables full integration with other workflow systems and services
- Continuous telemetry data with WebSocket subscriptions for event driven automation
- Continual state synchronization that provides superior fault tolerance and high availability
- All software processes communicate with the database rather than each other, ensuring near real-time state and resiliency and allowing individual software modules to be independently upgraded for higher availability.

Every CX switch includes AOS-CX at no cost and with an active, perpetual set of native features which has everything needed to deploy, connect, and troubleshoot an enterprise network, including:

- Network Analytics Engine (NAE)
- Dynamic Segmentation
- Switch Stacking
- High Availability and Resiliency
- Quality of Service (QoS)
- Layer 2 Switching
- Layer 3 Services and Routing
- IP Multicast
- Network Security

In addition to the native features available in AOS-CX, we offer an optional, term-based HPE Aruba Networking CX Advanced Feature Pack that unlocks visibility and advanced security use cases.

For more information, read the [HPE Aruba Networking CX Feature Pack Ordering Guide](#).

---

### HPE Aruba Networking Central - Unified Single Pane of Glass Management

HPE Aruba Networking Central is an AI-powered solution that simplifies IT operations, improves agility, and reduces costs by unifying management of all network infrastructure. Built for enterprise-grade resiliency and security, while simple enough for smaller businesses with limited IT staff, HPE Aruba Networking Central is your single point of visibility and control that spans the entire network --from branch to data center, wired and wireless LAN to WAN.

Available as a cloud-based or on-premises solution, HPE Aruba Networking Central is designed to simplify day zero through day two operations with streamlined workflows for tasks such as virtual switch stack creation, automated monitoring using AI-powered insights and NAE, as well as a unified view of all devices and users, both wired and wireless. Comprehensive switch management capabilities include configuration, on-boarding, monitoring, troubleshooting, and reporting.

A HPE Aruba Networking Central Foundation license subscription enables comprehensive switch management capabilities that include configuration, onboarding, monitoring, troubleshooting, and reporting. A HPE Aruba Networking Central Advanced license expands these capabilities with premium security and AIOps, including the HPE Aruba Central NetConductor Fabric Wizard and Policy Manager to enable dynamic segmentation and distributed enforcement at a global scale.

Additionally, an HPE Aruba Networking Central Advanced subscription enables the CX Advanced Feature Pack so there is no need to separately purchase a CX Advanced Feature Pack. This streamlines operational efficiency, reducing the need for your IT team to keep track of multiple subscriptions, active terms, and renewal dates.



---

## Standard Features

For more information on HPE Aruba Networking Central subscriptions, see the [HPE Aruba Networking Central SaaS Subscription Ordering Guide](#).

---

### HPE Aruba Networking Network Analytics Engine – Advanced Monitoring and Diagnostics

For enhanced visibility and troubleshooting, HPE Aruba Networking's Network Analytics Engine (NAE) automatically monitors and analyzes events that can impact network health. Advanced telemetry and automation provide the ability to easily identify and troubleshoot networks, system, application, and security related issues easily, using python agents, CLI-based agents, and REST APIs.

Advanced telemetry and automation provide the ability to easily identify and troubleshoot network, system, application, and security related issues easily, through the use of python agents, CLI-based agents, CLI-based agents and REST APIs.

The Time Series Database (TSDB) stores configuration and operational state data, making it available to quickly resolve network issues. The data may also be used to analyze trends, identify anomalies, and predict future capacity requirements.

HPE Aruba Networking Central uses NAE and agents to deliver switch monitoring, analytics, and enhanced troubleshooting for wired assurance. HPE Aruba Networking Switch Multi-Edit Software and third-party tools such as ServiceNow and Slack provide the intelligence to integrate NAE alerts into IT service management processes, speeding problem resolution.

---

### HPE Aruba NetEdit – Automated Switch Configuration and Management

The entire HPE Aruba Networking CX portfolio empowers IT teams to orchestrate multiple switch configuration changes for smooth end-to-end service rollouts. HPE Aruba Networking NetEdit introduces automation that allows for rapid network-wide changes and ensures policy conformance post network updates. Intelligent capabilities include search, editing, validation (including conformance checking), deployment and audit features. Capabilities include:

- Centralized configuration with validation for consistency and compliance
- Time savings via simultaneous viewing and editing of multiple configurations
- Customized validation tests for corporate compliance and network change analysis
- Automated large-scale configuration deployment without programming
- Network health and topology visibility via HPE Aruba Networking NAE integration

**Notes:** A separate software license is required to use HPE Aruba Networking NetEdit.

---

### HPE Aruba Networking CX Mobile App – True Deployment Convenience

An easy-to-use mobile app simplifies connecting and managing HPE Aruba Networking CX 6300 Switch Series for any size project. Switch information can also be imported into HPE Aruba Networking NetEdit for simplified configuration management and to continuously validate the conformance of configurations anywhere in the network. The HPE Aruba Networking CX Mobile App is available for download.

---

### HPE Aruba Networking ASICs - Programmable Innovation

Based on over 30 years of continuous investment, HPE Aruba Networking's ASICs create the basis for innovative and agile software feature advancements, unparalleled performance, and deep visibility. These programmable ASICs are purpose-built to allow for a tighter integration of switch hardware and software within campus and data center architectures to optimize performance and capacity. Virtual Output Queuing (VOQ) isolates congestion prevents Head of Line Blocking (HOLB) and allows full line rate on outgoing (egress) ports. Flexible ASIC resources enable HPE Aruba Networking's NAE solution to inspect all data, which allows for industry-leading analytics capabilities. The HPE Aruba Networking CX 6300 Switch Series is based on the HPE Aruba Networking Gen7 ASIC architecture.

---

### HPE Aruba Networking Dynamic Segmentation – Campus and Branch Fabric

The HPE Aruba Networking Dynamic Segmentation solution enables seamless mobility, consistent policy enforcement, and automated configurations for wired and wireless clients across networks of all sizes. It unifies role-based access and policy enforcement across LAN, WLAN, and SD-WAN networks with centralized policy definition and dedicated enforcement points, ensuring that users and devices can only communicate with destinations consistent with their role—keeping traffic secure and separate.



## Standard Features

Dynamic Segmentation is based on establishing least privilege access to IT resources by segmenting traffic based on identity, a fundamental concept of both Zero Trust and SASE frameworks where trust is based on roles and policies, not on where and how a user or device connects.

This innovation begins with colorless ports and role-based micro-segmentation technologies. Colorless ports allow wired clients to connect to any switch port, with the configuration automated using RADIUS-based access control. This eliminates the need for manual on-boarding of clients, including IoT devices, onto the network.

Role-based micro-segmentation delivers benefits of reduced subnet and VLAN sprawl, simplified policy definition, and scalable policy enforcement by introducing the concept of client user roles. Independent of network constructs such as VLANs and VRFs, clients can be grouped into a user role based on their identity, allowing the colorless ports technology to be extended to the centralized overlay fabric, as clients are on-boarded with automatic tunnel creation based on the associated user roles policy. The user roles policy offers the choice between micro-segmentation using centralized and unified policy enforcement for wireless and wired traffic with Layer 7 stateful firewall on gateways or a distributed approach with a Layer 4 role-role ACL on switches.

Dynamic Segmentation provides scale and flexibility in network design by allowing the stretching of VLANs and subnets across the entire network with an EVPN/VXLAN-based distributed overlay fabric. Fabric overlays use VXLAN or VXLAN-GBP tunnels on the data plane and provide the option of a Multi-Protocol BGP EVPN control plane for large deployments, or a static Layer 2 control plane for simplified deployments.

---

## Mobility and IoT Performance

The HPE Aruba Networking CX 6300 Switch Series uses a fully distributed architecture that utilizes the HPE Aruba Networking Gen7 ASICs. This ensures that our switches offer very low latency, increased packet buffering, and adaptive power consumption. All switching and routing are wire-speed to meet the demands of bandwidth-intensive applications today and in the future. Each switch includes the following:

- Up to 1760 Gbps in non-blocking bandwidth and up to 1310 Mpps for forwarding
- 1/10/25/40/50/100G uplinks<sup>1</sup> and large TCAM sizes ideal for mobility and IoT deployments in large campuses with several thousand clients
- Selectable queue configurations that allow for increased performance by defining a number of queues and associated memory buffering to best meet the requirements of network applications

**Notes:** <sup>1</sup>50G capability is for use with 50G DACs for both interconnect and VSF stacking. 50G transceivers and DACs are not supported on S0E91A and S0X44A switch models, which requires QSFP to SFP56 DAC cable for VSF stacking with other CX 6300F and CX 6300M switch models only. VSF stacking not supported on 1G ports.

---

## VSF Stacking - Scale and Simplicity

The HPE Aruba Networking Virtual Switching Framework (VSF) allows you to quickly grow your network using high performance front plane stacking. Additional features include:

- Support for up to 10 switches (or members) in a stack via chain or ring topology
  - Flexibility to create stacks that span longer distances such as hundreds of meters across campuses to kilometers between sites using long-range 10GbE/25GbE transceivers
  - Flexibility to mix both modular and fixed HPE Aruba Networking CX 6300 Switch Series models within a single stack to meet your deployment requirements
  - Simplified configuration and management as the switches act as a single chassis when stacked
  - High availability by design using VSF in-service software upgrades for ISSU orchestration and no downtime or restart when upgrading within the same major release (requires at least a 2 member VSF stack)
  - The HPE Aruba Networking CX Mobile app provides support for a validated stack deployment that ensure that all stack links and uplinks are connected properly
- 



## Standard Features

### An HPE Aruba Networking CX 6300 Switch Series Switch for Any Enterprise Environment

Whether in the branch office or a small to large enterprise environment, you can choose from 24 and 48 ports of HPE Smart Rate Multi-Gigabit. Each switch includes four high-speed built-in uplinks that auto-negotiate from 1GbE, 10GbE to 50GbE<sup>1</sup> to deliver non-blocking performance. Fixed format (F) models include built-in power supplies. The modular (M) models have rear slots for hot swappable power supplies that allow you to customize your PoE requirements, and its fans are field replaceable. Additional highlights:

- Compact 1U models support:
  - 24 and 48 ports of HPE Smart Rate Multi-gigabit Ethernet IEEE 802.3bz (100M/1GbE/2.5GbE/5GbE/10GbE) supporting high power IEEE 802.3bt Class 6 (60W) to Class 8 (90W)
  - High density 24 port SFP+ model which is ideal for aggregation
  - 1/10/25/50GbEuplink<sup>1</sup> port connectivity
- HPE Smart Rate Multi-Gigabit (IEEE 802.3bz) Ethernet supports high speed wireless access points
- For deployments that need higher port and PoE density, the 6300 supports up to 90W of PoE in a 48-port switch for a total of 2880W of PoE.
- Industry standard IEEE 802.3bt High Power PoE support (Class 8) provides up to 90W per port for support of the latest IoT devices and APs. PoE support for IEEE 802.3at Power over Ethernet (PoE+) provides up to 30W per port as well as any IEEE 802.3af-compliant end device
- Support for pre-standard PoE detection provides power to legacy PoE devices
- High availability with always-on PoE that supplies PoE power even during scheduled reboots and firmware upgrades
- Quick PoE supplies PoE power to powered devices as soon as the switch is plugged into AC power so device can initialize at the same time as the switch OS boots up
- Support for Energy Efficient Ethernet IEEE 802.3az reduces power consumption during periods of low network traffic
- Support for top-of-rack (ToR) and out-of-band management (OOBM) data center deployments with HPE Aruba Networking CX 6300M power-to-port bundle that delivers required power-to-port (back to front) airflow
- Auto-MDIX provides automatic adjustments for straight-through or crossover cables on all 10M/100M/1G and Smart Rate ports
- Unsupported Transceiver Mode (UTM) allows to insert and enable all unsupported 1/10/25/50GbE transceivers and cables. Note that there is no warranty nor support for the transceiver/cable when this feature is used.
- IPv6 capabilities include:
  - IPv6 host enables switches to be managed in an IPv6 network
  - Dual stack (IPv4 and IPv6) transitions from IPv4 to IPv6, supporting connectivity for both protocols
  - MLD snooping forwards IPv6 multicast traffic to the appropriate interface
  - IPv6 ACL/QoS supports ACL and QoS for IPv6 network traffic
  - IPv6 routing supports Static and OSPFv3 protocols
  - Security provides RA guard, DHCPv6 protection, dynamic IPv6 lockdown, ND snooping, IPv6 Destination Guard, IPv6 DHCP Guard, and IPv6 Router Advertisement Guard
- Jumbo frames allow for high-performance backups and disaster-recovery systems; provides a maximum frame size of 9198 bytes
- Packet storm protection against broadcast and multicast storms with user-defined thresholds
- Smart link enables simple, fast converging link redundancy and load balancing with dual uplinks avoiding Spanning Tree complexities

**Notes:** <sup>1</sup>50G capability is for use with 50G DACs for both interconnect and VSF stacking. 50G transceivers and DACs are not supported on S0E91A and S0X44A switch models, which requires QSFP to SFP56 DAC cable for VSF stacking with other CX 6300F and CX 6300M switch models only. VSF stacking not supported on 1G ports.



## Standard Features

### CX 6300L layer 2 switches

Three CX 6300L switch models are available for customers needing scalability, high-capacity, and cost-effective connectivity in the access layer. Features include:

- 24 ports of SR10 (1G/2.5G/5G/10G) or 48 ports of SR5 (1G/2.5G/5G) HPE Smart Rate Multi-gigabit Ethernet downlinks that support high power IEEE 802.3bt Class 6 (60W) to Class 8 (90W) PoE and MACsec 256 data link layer encryption
- Scalability with VSF front-plane stacking up to 10 CX 6300L switch members (does not stack with CX 6300F or CX 6300M switches)
- Layer 2 switching with support for IPv4 based static routing, quality of service (QoS), access control lists (ACL), and User-Based Tunneling for Dynamic Segmentation
- Modular, hot-swappable power supplies and fans that allow you to customize for PoE requirements and field replacement needs

**Notes:**<sup>1</sup>50G capability is for use with 50G DACs for both interconnect and VSF stacking. 50G transceivers and DACs are not supported on S0E91A and S0X44A switch models, which requires QSFP to SFP56 DAC cable for VSF stacking with other CX 6300F and CX 6300M switch models only. VSF stacking not supported on 1G ports.

---

### CX 6300M bundle for data centers

The CX 6300M 48 port power-to-port switch bundle serves as a top of rack (ToR) switch for 1GbE servers and also as a 1GbE out-of-band management (OOBM) switch for data centers server racks. Features include:

- Power-to-port bundle (JL762A) includes 48 port 1GbE switch with 2 x Fan Trays (JL761A) and 1 x power supply (JL760A)
- Back (power-side) to front (1GbE port side) airflow
- 1/10/25/50GbE<sup>1</sup> SFP uplinks

**Notes:**<sup>1</sup>50G capability is for use with 50G DACs for both interconnect and VSF stacking. 50G transceivers and DACs are not supported on S0E91A and S0X44A switch models, which requires QSFP to SFP56 DAC cable for VSF stacking with other CX 6300F and CX 6300M switch models only. VSF stacking not supported on 1G ports.

---

### High Availability and Resiliency

To ensure a high degree of up-time we offer high availability and multicast features needed for a full Layer 3 deployment at access and aggregation such as PBR, BFD, MSDP, BSR, and IP SLA without the need for software licenses. This includes:

- Hot Swappable Power Supplies available in the HPE Aruba Networking CX 6300 “M” models
    - Provides N+1 and N+N redundancy for high reliability in the event of power line or supply failures
    - Optional secondary power supplies to increase the total available PoE power
    - Fixed power supplies in HPE Aruba Networking CX 6300 “F” models
  - Bidirectional Forward Detection (BFD) enables sub-second failure detection for rapid routing protocol re-balancing, supporting both IPV4 and IPV6 networks.
  - Virtual Router Redundancy Protocol (VRRP) allows groups of two routers to dynamically create highly available routed environments in IPV4 and IPV6 networks
  - Uni-directional Link Detection (UDLD) to monitor link connectivity and shut down ports at both ends if uni- directional traffic is detected, preventing loops in STP- based networks
  - IEEE 802.3ad LACP supports up to 256 LAGs, each with up to 8 links per LAG; and provides support for static or dynamic groups and a user-selectable hashing algorithm
  - IEEE 802.1s Multiple Spanning Tree provides high link availability in VLAN environments where multiple spanning trees are required; and legacy support for IEEE 802.1d and IEEE 802.1w
  - IEEE 802.3ad link-aggregation-control protocol (LACP) and port trunking support static and dynamic trunks where each trunk supports up to eight links (ports) per static trunk
  - Support for Microsoft Network Load Balancer (NLB) for server applications
  - Ethernet Ring Protection Switching (ERPS) supports rapid protection and recovery in a ring topology.
  - Hot-Patching support and ISSU for standalone HPE Aruba Networking CX 6300 and for HPE Aruba Networking CX 6300 with VSF Stacking
-

## Standard Features

### Quality of Service (QoS) features

To support congestion actions and traffic prioritization, the HPE Aruba Networking CX 6300 Series includes the following:

- Strict priority (SP) queuing and Deficit Weighted Round Robin (DWRR)
- Traffic prioritization (IEEE 802.1p) for real-time classification into 8 priority levels that are mapped to 8 queues
- Layer 4 prioritization based on TCP/UDP port numbers
- Class of Service (CoS) sets the IEEE 802.1p priority tag based on IP address, IP Type of Service (ToS), Layer 3 protocol, TCP/UDP port number, source port, and DiffServ
- Rate limiting sets per-port ingress enforced maximums and per-port, per-queue minimums
- Transmission rates of egressing frames can be limited on a per-queue basis using Egress Queue Shaping (EQS)
- Large buffers for graceful congestion management

### Simplified Configuration and Management

In addition to HPE Aruba Networking Central, the HPE Aruba Networking CX Mobile App, HPE Aruba Networking NetEdit and HPE Aruba Network Analytics Engine, the HPE Aruba Networking CX 6300 series offers the following:

- Built-in programmable and easy to use REST API interface
- HPE Aruba Networking AirWave on-premises and HPE Aruba Networking Central cloud-based management
- Zero-Touch Provisioning (ZTP) simplifies installation of switching infrastructure using DHCP-based or HPE Aruba Networking Activate-based process with HPE Aruba Networking AirWave and HPE Aruba Networking Central
- Scalable ASIC-based wire speed network monitoring and accounting with no impact on network performance; network operators can gather a variety of network statistics and information for capacity planning and real-time network monitoring purposes
- Management interface control enables or disables each of the following depending on security preferences, console port, or reset button
- Industry-standard CLI with a hierarchical structure for reduced training time and expense. Delivers increased productivity in multivendor environments
- Management security restricts access to critical configuration commands, provides multiple privilege levels with password protection and local and remote syslog capabilities allow logging of all access
- SNMP v2c/v3 provides SNMP read and trap support of industry standard Management Information Base (MIB), and private extensions
- SNMP support includes: Write Set Speed and Duplex, Write Port Security, Write POE Priority, Write Config Mgmt, SNMP-Read single OID for average CPU and memory, SNMP MIB View
- SNMP Trap include: Transceiver Traps (insertion/removal), SNMP Trap, SNMP MIB-SNMB Authentication, SNMPv2 MIB, Port Sec MIB-Port Sec, Config MIB-Running Config Change, Config MIB, AAA Server MIB, AAA Server State
- Remote monitoring (RMON) with standard SNMP to monitor essential network functions. Supports events, alarms, history, and statistics groups as well as a private alarm extension group; RMON and sFlow provide advanced monitoring and reporting capabilities for statistics, history, alarms and events
- IP Flow Information Export (IPFix) enables client flow information collection to enhance visibility
- Simplifies configuration while onboarding switches with Zero Touch Provisioning by using Dynamic Border Gateway Protocol (BGP) peering to establish a peer group of switches within an IP range
- Enhanced visibility during client onboarding, providing insights on latency, failures, and error events
- Client telemetries and application visibility using IP Flow Information Export (IPFix), Deep Packet Inspection (DPI) and traffic insights
- Simplifies configuration while onboarding switches with Zero Touch Provisioning by using Dynamic Border Gateway Protocol (BGP) peering to establish a peer group of switches within an IP range
- Enhanced visibility during client onboarding, providing insights on latency, failures, and error events
- TFTP and SFTP support offers different mechanisms for configuration updates; trivial FTP (TFTP) allows bidirectional transfers over a TCP/IP network; Secure File Transfer Protocol (SFTP) runs over an SSH tunnel to provide additional security
- Debug and sampler utility supports ping and traceroute for IPv4 and IPv6
- Network Time Protocol (NTP) synchronizes timekeeping among distributed time servers and clients; keeps timekeeping consistent among all clock-dependent devices within the network so the devices can provide diverse applications based on the consistent time
- IEEE 802.1AB Link Layer Discovery Protocol (LLDP) advertises and receives management information from adjacent



## Standard Features

devices on a network, facilitating easy mapping by network management applications

- Dual flash images provides independent primary and secondary operating system files for backup while upgrading
- Assignment of descriptive names to ports for easy identification
- Multiple configuration files can be stored to a flash image
- Ingress and egress port monitoring enable more efficient network problem solving
- Unidirectional link detection (UDLD) monitors the link between two switches and blocks the ports on both ends of the link if the link goes down at any point between the two devices
- Power down mode delivers energy savings by allowing the switch to power down most of the switch, except a clock which will boot up the switch when scheduled
- IP SLA for Voice monitors quality of voice traffic using the UDP Jitter and UDP Jitter for VoIP tests
- Precision Time Protocol (PTP) allows for precise clock synchronization across distributed network switches as defined in IEEE 1588. Transparent Clock (PTP-TC) and Boundary Clock (PTP-BC) are needed for time critical applications like Audio Video Bridging (AVB), smart grid power automation, financial systems and more. Boundary Clock makes use of 2-Step time stamping mode.

---

## Layer 2 Switching

The following layer 2 services are supported:

- VLAN support and tagging for IEEE 802.1Q (4094 VLAN IDs)
- Jumbo packet support improves the performance of large data transfers; supports frame size of up to 9198 bytes
- IEEE 802.1v protocol VLANs isolate select non-IPv4 protocols automatically into their own VLANs
- Rapid Per-VLAN Spanning Tree (RPVST+) allows each VLAN to build a separate spanning tree to improve link bandwidth usage; is compatible with PVST+
- MVRP allows automatic learning and dynamic assignment of VLANs
- VXLAN encapsulation (tunnelling) protocol for overlay network that enables a more scalable virtual network deployment
- Bridge Protocol Data Unit (BPDU) tunnelling Transmits STP BPDUs transparently, allowing correct tree calculations across service providers, WANs, or MANs
- Port mirroring duplicates port traffic (ingress and egress) to a monitoring port; supports 4 mirroring groups
- STP supports standard IEEE 802.1D STP, IEEE 802.1w Rapid Spanning Tree Protocol (RSTP) for faster convergence, and IEEE 802.1s Multiple Spanning Tree Protocol (MSTP)
- Internet Group Management Protocol (IGMP) Controls and manages the flooding of multicast packets in a Layer 2 network
- IPv4 Multicast in VXLAN/EVPN Overlay support allows PIM-SM/IGMP snooping in the VXLAN Overlay
- IPv6 VXLAN/EVPN Overlay support, allows IPv6 traffic over the VXLAN overlay
- VXLAN ARP/ND suppression allows minimization of ARP and ND traffic flooding within individual VXLAN segments, thus optimizing the VXLAN network
- QinQ support to improve the VLAN utilization by adding another 802.1Q tag to tagged packets

---

## Layer 3 Services

The following layer 3 services are supported:

- Bidirectional Forwarding Detection (BFD) enables link connectivity monitoring and reduces network convergence time for static route, OSPFv2 and VRRP
- User Datagram Protocol (UDP) helper function allows UDP broadcasts to be directed across router interfaces to specific IP unicast or subnet broadcast addresses and prevents server spoofing for UDP services such as DHCP
- Loopback interface address defines an address in Open Shortest Path First (OSPF), improving diagnostic capability
- Route maps provide more control during route redistribution; allow filtering and altering of route metrics
- Address Resolution Protocol (ARP) determines the MAC address of another IP host in the same subnet; supports static ARPs; gratuitous ARP allows detection of duplicate IP addresses; proxy ARP allows normal ARP operation between subnets or when subnets are separated by a Layer 2 network
- Dynamic Host Configuration Protocol (DHCP) simplifies the management of large IP networks and supports client; DHCP Relay enables DHCP operation across subnets
- DHCP server centralizes and reduces the cost of IPv4 address management
- Domain Name System (DNS) provides a distributed database that translates domain names and IP addresses, which

## Standard Features

simplifies network design; supports client and server

- mDNS (Multicast Domain Name System) Gateway enables discovery of mDNS groups across L3 boundaries
- Generic Routing Encapsulation (GRE) enables tunneling traffic from site-to-site over a Layer 3 path
- Supports internal loopback testing for maintenance purposes and increased availability; loopback detection protects against incorrect cabling or network configurations and can be enabled on a per-port or per-VLAN basis for added flexibility
- IP sub-interface is a virtual interface created by dividing physical interface into multiple logical interfaces tagged using different VLAN-IDs. A physical interface can be a regular physical, Split port or LAG L3 interface. A sub-interface is used for many uses-cases such as VRF-lite interconnection and inter-vlan routing (router on-a-stick)

## Layer 3 Routing

The following layer 3 routing services are supported:

- Border Gateway Protocol (BGP) provides IPv4 and IPv6 routing, which is scalable, robust, and flexible
- Border Gateway Protocol 4 (BGP-4) delivers an implementation of the Exterior Gateway Protocol (EGP) utilizing path vectors; uses TCP for enhanced reliability for the route discovery process; reduces bandwidth consumption by advertising only incremental updates; supports extensive policies for increased flexibility; scales to very large networks with graceful restart capability
- Equal-Cost Multipath (ECMP) enables multiple equal-cost links in a routing environment to increase link redundancy and scale bandwidth
- Multi-protocol BGP (MP-BGP) enables sharing of IPv6 routes using BGP and connections to BGP peers using IPv6
- Routing Information Protocol version 2 (RIPv2) provides an easy to configure routing protocol for small networks as while RIPv2 provides support for small IPv6 networks
- Open shortest path first (OSPF) delivers faster convergence; uses link-state routing Interior Gateway Protocol (IGP), which supports ECMP, NSSA, and MD5 authentication for increased security and graceful restart for faster failure recovery
- OSPF provides OSPFv2 for IPv4 routing and OSPFv3 for IPv6 routing
- Static IP routing provides manually configured routing; includes ECMP capability
- Policy-based routing uses a classifier to select traffic that can be forwarded based on policy set by the network administrator
- Static IPv4 and IPv6 routing provides simple manually configured IPv4 and IPv6 routes
- IP performance optimization provides a set of tools to improve the performance of IPv4 networks; includes directed broadcasts, customization of TCP parameters, support of ICMP error packets, and extensive display capabilities
- Dual IP stack maintains separate stacks for IPv4 and IPv6 to ease the transition from an IPv4-only network to an IPv6-only network design

## Security

The HPE Aruba Networking CX 6300 Switch Series comes with an integrated trusted platform module (TPM) for platform integrity. This ensures the boot process started from a trusted combination of HPE Aruba Networking AOS-CX switches. Other security features include:

- AOS-CX uses FIPS 140-2 validated cryptography for protection of sensitive information.
- Access control list (ACL) support for both IPv4 and IPv6; allows for filtering traffic to prevent unauthorized users from accessing the network, or for controlling network traffic to save resources; rules can either deny or permit traffic to be forwarded; rules can be based on a Layer 2 header or a Layer 3 protocol header
- ACLs also provide filtering based on the IP field, source/ destination IP address/subnet, and source/ destination TCP/UDP port number on a per-VLAN or per-port basis
- Enrollment over Secure Transport (EST) enables secure certificate enrollment, allowing for easier enterprise management of PKI
- Remote Authentication Dial-In User Service (RADIUS)
- Terminal Access Controller Access-Control System (TACACS+) delivers an authentication tool using TCP with encryption of the full authentication request, providing additional security
- Management access security for both on- and off- box authentication for administrative access. RADIUS or TACACS+ can be used to provide encrypted user authentication. Additionally, TACACS+ can also provide admin authorization services
- Control Plane Policing sets rate limit on control protocols to protect CPU overload from DOS attacks
- Supports multiple user authentication methods. Uses an IEEE 802.1X supplicant on the client in conjunction with a

---

## Standard Features

RADIUS server to authenticate in accordance with industry standards

- Supports MAC-based client authentication
- Concurrent IEEE 802.1X, Web, and MAC authentication schemes per switch port accepts up to 32 sessions of IEEE 802.1X, Web, and MAC authentications
- DHCP protection blocks DHCP packets from unauthorized DHCP servers, preventing denial-of-service attacks
- Secure management access delivers secure encryption of all access methods (CLI, GUI, or MIB) through SSHv2, SSL, and/or SNMPv3
- Switch CPU protection provides automatic protection against malicious network traffic trying to shut down the switch
- ICMP throttling defeats ICMP denial-of-service attacks by enabling any switch port to automatically throttle ICMP traffic
- Identity-driven ACL enables implementation of a highly granular and flexible access security policy and VLAN assignment specific to each authenticated network user
- STP BPDU port protection blocks Bridge Protocol Data Units (BPDUs) on ports that do not require BPDUs, preventing forged BPDU attacks
- Dynamic IP lockdown works with DHCP protection to block traffic from unauthorized hosts, preventing IP source address spoofing
- Dynamic ARP protection blocks ARP broadcasts from unauthorized hosts, preventing eavesdropping or theft of network data
- STP root guard protects the root bridge from malicious attacks or configuration mistakes
- Port security allows access only to specified MAC addresses, which can be learned or specified by the administrator
- MAC address lockout prevents particular configured MAC addresses from connecting to the network
- Source-port filtering allows only specified ports to communicate with each other
- Secure shell encrypts all transmitted data for secure remote CLI access over IP networks
- Secure Sockets Layer (SSL) encrypts all HTTP traffic, allowing secure access to the browser-based management GUI in the switch
- Secure FTP allows secure file transfer to and from the switch; protects against unwanted file downloads or unauthorized copying of a switch configuration file
- Critical Authentication Role ensures that important infrastructure devices such as IP phones are allowed network access even in the absence of a RADIUS server
- MAC Pinning allows non-chatty legacy devices to stay authenticated by pinning client MAC addresses to the port until the clients logoff or get disconnected
- Security banner displays a customized security policy when users log in to the switch
- RadSec enables RADIUS authentication and accounting data to be passed safely and reliably across insecure networks
- Private VLAN (PVLAN) provides traffic isolation between users on the same VLAN; typically, a switch port can only communicate with other ports in the same community and/or an uplink port, regardless of VLAN ID or destination MAC address. This extends network security by restricting peer-peer communication to prevent variety of malicious attacks.
- Auto VLAN Creation automates VLAN creation on access switches for authenticated clients.
- DHCP smart relay allows the DHCP relay agent to use secondary IP addresses when the DHCP server does not reply the DHCP-OFFER message
- IEEE 802.1AE MACsec provides switch-to-switch and switch-to-host security on a link between two ports using standard encryption and authentication, available on uplink and downlink ports

---

## Visibility and Advanced Security

Customers can choose to upgrade the active, embedded CX Foundation license to the term based CX Advanced license to unlock the following benefits for their business:

- Delivers deep visibility with HPE Aruba Networking CX Edge Insights for application recognition, identification, and flow capture from layer 4 to layer 7. CX Edge Insights enables granular datapoint collection with search, sort, and reporting as well as the ability to recognize 22 categories and more than 3700 applications.
-

---

## Standard Features

### Multicast

- IGMP Snooping allows multiple VLANs to receive the same IPv4 multicast traffic, lessening network bandwidth demand by reducing multiple streams to each VLAN
  - Multicast Listener Discovery (MLD) enables discovery of IPv6 multicast listeners; support MLD v1 and v2
  - Protocol Independent Multicast (PIM) defines modes of IPv4 and IPv6 multicasting to allow one-to-many and many-to-many transmission of information; supports PIM Sparse Mode (SM), Source-Specific Multicast (SSM), and Dense Mode (DM) for both IPv4 and IPv6
  - Internet Group Management Protocol (IGMP) utilizes Any-Source Multicast (ASM) to manage IPv4 multicast networks; supports IGMPv1, v2, and v3
  - Multicast Service Discovery Protocol (MSDP) efficiently routes multicast traffic through core networks
  - MSDP for Anycast RP is an intra-domain feature that provides redundancy and load-sharing capabilities
- 

### Convergence

- IP multicast routing includes PIM Sparse, Source Specific Multicast, and Dense modes to route IP multicast traffic
  - IP multicast snooping (data-driven IGMP) prevents flooding of IP multicast traffic
  - Protocol Independent Multicast for IPv6 supports one-to-many and many-to-many media casting use cases such as IPTV over IPv6 networks
  - LLDP-MED (Media Endpoint Discovery) defines a standard extension of LLDP that stores values for parameters such as QoS and VLAN to automatically configure network devices such as IP phones
  - PoE allocations supports multiple methods (allocation by usage or class, with LLDP and LLDP-MED) to allocate PoE power for more efficient power management and energy savings.
  - Auto VLAN configuration for voice RADIUS VLAN uses a standard RADIUS attribute and LLDP-MED to automatically configure a VLAN for IP phones
  - CDPv2 uses CDPv2 to configure legacy IP phones
- 

### Additional information

- Green initiative support for RoHS (EN 50581:2012) and WEEE regulations
  - TAA-compliant CX 6300 switches are available for order
- 

### Customer First, Customer Last Support

When your network is important to your business, then your business needs the backing of HPE Aruba Networking Support Services. Partner with HPE Aruba Networking product experts to increase your team productivity, keep pace with technology advances, software releases, and obtain break-fix support.

- HPE Aruba Networking Pro Care adds fast access to senior HPE Aruba Networking TAC engineers, who are assigned as a single point of contact for case management, reducing the time spent addressing and resolving issues.

For complete details on Foundation Care and HPE Aruba Networking Pro Care, please visit:

<https://www.arubanetworks.com/supportservices/>

---

### Warranty, Services and Support

- Limited Lifetime Warranty, see <https://www.arubanetworks.com/support-services/product-warranties/> for warranty and support information included with your product purchase
  - For Software Releases and Documentation, refer to <https://asp.arubanetworks.com/downloads>
  - For more detailed information on HPE Aruba Networking AOS-CX software release and features, please visit the [AOS-CX Switch Software Documentation Portal](#)
  - Explore and compare switch features for each platform and software release on the [HPE Aruba Networking Switch Feature Navigator](#)
  - For support and services information, visit <https://www.arubanetworks.com/support-services/arubacare/>
- 



## Configuration Information

### BTO Models

#### HPE Aruba Networking CX 6300M

Rule #	Description	SKU
1, 2, 3, 4, 6, 8	<p>HPE Aruba Networking CX 6300M 24-port SFP+ and 4-port SFP56 Switch</p> <ul style="list-style-type: none"> <li>HPE Aruba Networking 6300M 24-port SFP+ and 4-port SFP56 Switch</li> <li>Must Select PSU Min1 / Max2 (250W JL085A, 250W JL757A) Mix OK</li> <li>Includes Fantrays Min2 / Max 2 (JL669B)</li> <li>Min=0 \ Max= 24 SFP/SFP+ 100M/1/10G Transceivers</li> <li>Min=0 \ Max = 4 SFP/SFP+/SFP28/SFP56 1/10/25/50G+I43+I69:I76+I69:I80+I43+I69:I69:I104</li> </ul>	JL658A
5, 8, 9, 11, 12, 13, 14	<p>HPE Aruba Networking 6300M 48p SR10 1G/2.5G/5G/10G PTP/AVB Class8 PoE and 4p 100G MACsec Switch</p> <ul style="list-style-type: none"> <li>Aruba 6300M 48p SR10 1G/2.5G/5G/10G PTP/AVB Class 8 PoE and 4p 100G MACsec Switch</li> <li>Must Select PSU Min1 / Max2 (680W JL086A,1050W JL087A, 1600W JL670A, 1050W JL758A) Mix OK</li> <li>Includes Fantrays Min2 / Max 2 (JL669B)</li> <li>Min=0 \ Max = 4 QSFP56 50G Transceiver</li> <li>QSA28 Adapter Min=0 \ Max=4, ports 49-52 (rule11)</li> <li>1U - Height</li> </ul>	SOE91A
1, 2, 3, 4, 8	<p>HPE Aruba Networking CX 6300M 48-port HPE Smart Rate 1/2.5/5GbE Class 6 PoE and 4-port SFP56 Switch</p> <ul style="list-style-type: none"> <li>HPE Aruba Networking 6300M 48-port HPE Smart Rate 1/2.5/5GbE Class 6 PoE and 4-port SFP56 Switch</li> <li>Must Select PSU Min1 / Max2 (680W JL086A,1050W JL087A, 1600W JL670A, 1050W JL758A) Mix OK</li> <li>Includes Fantrays Min2 / Max 2 (JL669B)</li> <li>Min=0 \ Max = 4 SFP/SFP+/SFP28/SFP56 1/10/25/50G Transceiver</li> <li>1U - Height</li> </ul>	JL659A
2, 3, 4, 8	<p>HPE Aruba Networking CX 6300M 48p HPE Smart Rate 1G/2.5G/5G Class8 PoE 2p 50G 2p 25G Switch</p> <ul style="list-style-type: none"> <li>HPE Aruba Networking 6300M 48p HPE Smart Rate 1G/2.5G/5G CL8 PoE and 2p 50G and 2p 25G Switch</li> <li>Must Select PSU Min1 / Max2 (680W JL086A,1050W JL087A, 1600W JL670A, 1050W JL758A) Mix OK</li> <li>Includes Fantrays Min2 / Max 2 (JL669B)</li> <li>Min=0 \ Max = 2 SFP+/SFP28 10/25 Transceiver (Ports 49/50)</li> <li>Min=0 \ Max = 2 SFP+/SFP28/SFP56 10/25/50G Transceiver (Ports 51/52)</li> <li>1U - Height</li> </ul>	R8S90A
1, 2, 3, 4, 8	<p>HPE Aruba Networking CX 6300M 24-port HPE Smart Rate 1/2.5/5GbE Class 6 PoE and 4-port SFP56 Switch</p> <ul style="list-style-type: none"> <li>HPE Aruba Networking 6300M 24-port HPE Smart Rate 1/2.5/5GbE Class 6 PoE and 4-port SFP56 Switch</li> <li>Must Select PSU Min1 / Max2 (680W JL086A,1050W JL087A, 1600W JL670A, 1050W JL758A) Mix OK</li> <li>Includes 1 Fan tray (JL669B), with 1 open slot with blank cover</li> <li>Min=0 \ Max = 4 SFP/SFP+/SFP28/SFP56 1/10/25/50G Transceiver</li> <li>1U - Height</li> </ul>	JL660A

## Configuration Information

2, 3, 4, 8	<p>HPE Aruba Networking CX 6300M 24p Smart Rate 1G/2.5G/5G/10G Class6 PoE 2p 50G 2p 25G Switch</p> <ul style="list-style-type: none"> <li>• HPE Aruba Networking 6300M 24p HPE Smart Rate 1G/2.5G/5G/10G CL6 PoE and 2p 50G and 2p 25G Switch</li> <li>• Must Select PSU Min1 / Max2 (680W JL086A,1050W JL087A, 1600W JL670A, 1050W JL758A) Mix OK</li> <li>• Includes Fantrays Min2 / Max 2 (JL669B)</li> <li>• Min=0 \ Max = 2 SFP+/SFP28 10/25 Transceiver (Ports 25/26)</li> <li>• Min=0 \ Max = 2 SFP+/SFP28/SFP56 10/25/50G Transceiver (Ports 27/28)</li> <li>• 1U - Height</li> </ul>	R8S89A
1, 2, 3, 4, 8	<p>HPE Aruba Networking CX 6300M 48-port 1GbE Class 4 PoE and 4-port SFP56 Switch</p> <ul style="list-style-type: none"> <li>• HPE Aruba Networking 6300M 48-port 1GbE Class 4 PoE and 4-port SFP56 Switch</li> <li>• Must Select PSU Min1 / Max2 (680W JL086A,1050W JL087A, 1600W JL670A, 1050W JL758A) Mix OK</li> <li>• Includes 1 Fan tray (JL669B), with 1 open slot with blank cover</li> <li>• Min=0 \ Max = 4 SFP/SFP+/SFP28/SFP56 1/10/25/50G Transceiver</li> <li>• 1U - Height</li> </ul>	JL661A
1, 2, 3, 4, 7, 8	<p>HPE Aruba Networking CX 6300M 12p CL8 PoE 36p CL6 PoE Smart Rate 1G/2.5G/5G 2p 50G 2p 10G Switch</p> <ul style="list-style-type: none"> <li>• HPE Aruba Networking 6300M 12p Class8 PoE and 36p Class6 PoE HPE Smart Rate 1G/2.5G/5G and 2p 50G and 2p 25G Switch</li> <li>• Must Select PSU Min1 / Max2 (680W JL086A,1050W JL087A, 1600W JL670A, 1050W JL758A) Mix OK</li> <li>• Includes Fantrays Min2 / Max 2 (JL669B)</li> <li>• Min=0 \ Max = 2 SFP+ 10/25/50G Transceiver (LRM Supported) (Ports 49/50)</li> <li>• Min=0 \ Max = 2 SFP/SFP+/SFP28/SFP56 1/10/25/50G Transceiver (Ports 51/52)</li> <li>• 1U - Height</li> </ul>	R8S91A
1, 2, 3, 4, 8	<p>HPE Aruba Networking CX 6300M 24-port 1GbE Class 4 PoE and 4-port SFP56 Switch</p> <ul style="list-style-type: none"> <li>• HPE Aruba Networking 6300M 24-port 1GbE Class 4 PoE and 4-port SFP56 Switch</li> <li>• Must Select PSU Min1 / Max2 (680W JL086A,1050W JL087A, 1600W JL670A, 1050W JL758A) Mix OK</li> <li>• Includes 1 Fan tray (JL669B), with 1 open slot with blank cover</li> <li>• Min=0 \ Max = 4 SFP/SFP+/SFP28/SFP56 1/10/25/50G Transceiver</li> <li>• 1U - Height</li> </ul>	JL662A
1, 2, 3, 4, 7, 8, 14	<p>HPE Aruba Networking CX 6300M 24p SFP+ LRM support and 2p 50G and 2p 25G MACSec Switch</p> <ul style="list-style-type: none"> <li>• HPE Aruba Networking 6300M 24p SFP+ LRM support and 2p 50G and 2p 25G MACsec Switch</li> <li>• Must Select PSU Min1 / Max2 (250W JL085A, 250W JL757A) Mix OK</li> <li>• Includes Fantrays Min2 / Max2 (JL669B)</li> <li>• Min=0 \ Max = 24 SFP/SFP+ Transceiver (LRM Supported Ports 1-24)</li> <li>• Min=0 \ Max = 2 SFP+/SFP28 10/25/50G Transceiver (Ports 25/26)</li> <li>• Min=0 \ Max = 2 SFP+/SFP28/SFP56 10/25/50G Transceiver (Ports 27/28)</li> <li>• 1U - Height</li> </ul>	R8S92A
1, 2, 3, 4, 8	<p>HPE Aruba Networking CX 6300M 48-port 1GbE and 4-port SFP56 Switch</p> <ul style="list-style-type: none"> <li>• HPE Aruba Networking 6300M 48-port 1GbE and 4-port SFP56 Switch</li> <li>• Must Select PSU Min1 / Max2 (250W JL085A, 250W JL757A) Mix OK</li> <li>• Includes 1 Fan tray (JL669B), with 1 open slot with blank cover</li> <li>• Min=0 \ Max = 4 SFP/SFP+/SFP28/SFP56 1/10/25/50G Transceiver (Ports 25/26)</li> <li>• 1U - Height</li> </ul>	JL663A

## Configuration Information

- [1](#), [2](#), [3](#), [4](#), [8](#) HPE Aruba Networking CX 6300M 24-port 1GbE and 4-port SFP56 Switch JL664A
- HPE Aruba Networking 6300M 24-port 1GbE and 4-port SFP56 Switch
  - Must Select PSU Min1 / Max2 (250W JL085A, 250W JL757A) Mix OK
  - Includes 1 Fan tray (JL669B), with 1 open slot with blank cover
  - Min=0 \ Max = 4 SFP/SFP+/SFP28/SFP56 1/10/25/50G Transceiver
  - 1U - Height
- [1](#), [2](#), [3](#), [4](#), [5](#), [8](#) HPE Aruba Networking CX 6300M 48p 1GbE 4p SFP56 Power-to-Port 2 Fan Trays 1 PSU Bundle JL762A
- HPE Aruba Networking 6300M 48-port 1GbE and 4-port SFP56 Power-to-Port 2 Fan Trays 1 PSU Bundle
  - Includes 1 Pwr2Prt PSU, can select Min0 / Max1 (250W JL760A)
  - Includes 2 Pwr2Prt Fan trays (JL761A), with no open slots
  - Min=0 \ Max = 4 SFP/SFP+/SFP28/SFP56 1/10/25/50G Transceiver
  - 1U - Height
- HPE Aruba Networking CX 6300M 48p 1GbE 4p SFP56 Power-to-Port 2 Fan Trays 1 PSU Bundle PDU JL762A#B2B
- C15 PDU Jumper Cord (NA/MEX/TW/JP) (J9943A)
- HPE Aruba Networking CX 6300M 48p 1GbE 4p SFP56 Power-to-Port 2 Fan Trays 1 PSU Bundle PDU JL762A#B2C
- C15 PDU Jumper Cord (ROW) (J9944A)
- HPE Aruba Networking CX 6300M 48p 1GbE 4p SFP56 Power-to-Port 2 Fan Trays 1 PSU Bundle 220v JL762A#B2E
- HPE 2.5m C15 to NEMA 6-20P Pwr. Cord (JL336A)
- HPE Aruba Networking CX 6300M 48p 1GbE 4p SFP56 Power-to-Port 2 Fan Trays 1 PSU Bundle NoLoc JL762A#AC3
- No Localized Power Cord Selected. Use J9955A to obtain a Locking Plug Power Cord (L6-20P)
- ### HPE Aruba Networking CX 6300M TAA
- [1](#), [2](#), [3](#), [4](#), [8](#) HPE Aruba Networking 6300M 24p 10M/100M/1G Class4 PoE 4p SFP56 50G TAA Switch SOF99A
- HPE Aruba Networking 6300M 24p 1GbE Class 4 PoE and 4p SFP56 TAA Switch
  - Must Select PSU Min1 / Max2 (680W JL086A,1050W JL087A, 1600W JL670A, 1050W JL758A) Mix OK
  - Includes 1 Fan tray (JL669B), with 1 open slot with blank cover
  - Min=0 \ Max = 4 SFP/SFP+/SFP28/SFP56 1/10/25/50G Transceiver
  - 1U - Height
- [1](#), [2](#), [3](#), [4](#), [8](#) HPE Aruba Networking 6300M 48p 10M/100M/1G 4p SFP56 50G TAA Switch SOG00A
- HPE Aruba Networking 6300M 48p 1GbE and 4p SFP56 TAA Switch
  - Must Select PSU Min1 / Max2 (250W JL085A, 250W JL757A) Mix OK
  - Includes 1 Fan tray (JL669B), with 1 open slot with blank cover
  - Min=0 \ Max = 4 SFP/SFP+/SFP28/SFP56 1/10/25/50G Transceiver
  - 1U - Height
- [1](#), [2](#), [3](#), [4](#), [8](#) HPE Aruba Networking 6300M 24p 10M/100M/1G 4p SFP56 50G TAA Switch SOG01A
- HPE Aruba Networking 6300M 24p 1GbE and 4p SFP56 TAA Switch
  - Must Select PSU Min1 / Max2 (250W JL085A, 250W JL757A) Mix OK
  - Includes 1 Fan tray (JL669B), with 1 open slot with blank cover
  - Min=0 \ Max = 4 SFP/SFP+/SFP28/SFP56 1/10/25/50G Transceiver
  - 1U - Height

## Configuration Information

<a href="#">1, 2, 3, 4, 6, 8</a>	<p>HPE Aruba Networking 6300M 24p SFP+ 1G/10G 4p SFP56 50G TAA Switch</p> <ul style="list-style-type: none"> <li>• HPE Aruba Networking 6300M 24p SFP+ and 4p SFP56 TAA Switch</li> <li>• Must Select PSU Min1 / Max2 (250W JL085A, 250W JL757A) Mix OK</li> <li>• Includes Fantrays Min2 / Max 2 (JL669B)</li> <li>• Min=0 \ Max= 24 SFP/SFP+ 100M/1/10G Transceivers</li> <li>• Min=0 \ Max = 4 SFP/SFP+/SFP28/SFP56 1/10/25/50G Transceiver</li> <li>• 1U - Height</li> </ul>	SOG03A
<a href="#">1, 2, 3, 4, 8</a>	<p>HPE Aruba Networking 6300M 48p Smart Rate 1G/2.5G/5G Class6 PoE 4p SFP56 50G TAA Switch</p> <ul style="list-style-type: none"> <li>• HPE Aruba Networking 6300M 48p HPE Smart Rate 1/2.5/5GbE Class 6 PoE and 4p SFP56 TAA Switch</li> <li>• Must Select PSU Min1 / Max2 (680W JL086A,1050W JL087A, 1600W JL670A, 1050W JL758A) Mix OK</li> <li>• Includes Fantrays Min2 / Max 2 (JL669B)</li> <li>• Min=0 \ Max = 4 SFP/SFP+/SFP28/SFP56 1/10/25/50G Transceiver</li> <li>• 1U - Height</li> </ul>	SOG04A
<a href="#">1, 2, 3, 4, 8</a>	<p>HPE Aruba Networking 6300M 24p Smart Rate 1G/2.5G/5G Class6 PoE 4p SFP56 50G TAA Switch</p> <ul style="list-style-type: none"> <li>• HPE Aruba Networking 6300M 24p HPE Smart Rate 1/2.5/5GbE Class 6 PoE and 4p SFP56 TAA Switch</li> <li>• Must Select PSU Min1 / Max2 (680W JL086A,1050W JL087A, 1600W JL670A, 1050W JL758A) Mix OK</li> <li>• Includes 1 Fan tray (JL669B), with 1 open slot with blank cover</li> <li>• Min=0 \ Max = 4 SFP/SFP+/SFP28/SFP56 1/10/25/50G Transceiver</li> <li>• 1U - Height</li> </ul>	SOG05A
<a href="#">1, 2, 3, 4, 8</a>	<p>HPE Aruba Networking 6300M 48p 10M/100M/1G Class4 PoE 4p SFP56 50G TAA Switch</p> <ul style="list-style-type: none"> <li>• HPE Aruba Networking 6300M 48p 1GbE Class 4 PoE and 4p SFP56 TAA Switch</li> <li>• Must Select PSU Min1 / Max2 (680W JL086A,1050W JL087A, 1600W JL670A, 1050W JL758A) Mix OK</li> <li>• Includes 1 Fan tray (JL669B), with 1 open slot with blank cover</li> <li>• Min=0 \ Max = 4 SFP/SFP+/SFP28/SFP56 1/10/25/50G Transceiver</li> <li>• 1U - Height</li> </ul>	SOG06A
<a href="#">8, 9, 11, 12, 13, 14</a>	<p>HPE Aruba Networking 6300M 48p SR10 1G/2.5G/5G/10G PTP/AVB Class8 PoE 4p 100G MACsec TAA Switch</p> <ul style="list-style-type: none"> <li>• HPE Aruba Networking 6300M 48p SR10 1G/2.5G/5G/10G PTP/AVB Class 8 PoE and 4p 100G MACsec TAA Switch</li> <li>• Must Select PSU Min1 / Max2 (680W JL086A,1050W JL087A, 1600W JL670A, 1050W JL758A) Mix OK</li> <li>• Includes Fantrays Min2 / Max 2 (JL669B)</li> <li>• Min=0 \ Max = 4 QSFP+/QSFP56/QSFP28 50G Transceiver</li> <li>• QSA28 Adapter Min=0 \ Max=4, ports 49-52 (rule11)</li> <li>• 1U - Height</li> </ul>	SOX44A
<a href="#">1, 2, 3, 4, 5, 8</a>	<p>HPE Aruba Networking 6300M 48p 10M/100M/1G 4p SFP56 50G Power-to-Port 2xFan PSU TAA Bundle</p> <ul style="list-style-type: none"> <li>• HPE Aruba Networking 6300M 48p 1GbE and 4p SFP56 Power-to-Port 2 Fan Trays 1 PSU TAA Switch Bundle</li> <li>• Includes 1 Pwr2Prt PSU, can select Min0 / Max1 (250W JL760A)</li> <li>• Includes 2 Pwr2Prt Fan trays (JL761A), with no open slots</li> <li>• Min=0 \ Max = 4 SFP/SFP+/SFP28/SFP56 1/10/25/50G Transceiver</li> <li>• 1U - Height"</li> </ul>	SOG02A



## Configuration Information

HPE Aruba Networking 6300M 48p 10M/100M/1G 4p SFP56 50G Back-to-Front 2xFan PSU TAA Bundle PDU SOG02A#B2B

- C15 PDU Jumper Cord (NA/MEX/TW/JP) (J9943A)

HPE Aruba Networking 6300M 48p 10M/100M/1G 4p SFP56 50G Back-to-Front 2xFan PSU TAA Bundle PDU SOG02A#B2C

- C15 PDU Jumper Cord (ROW) (J9944A)

HPE Aruba Networking 6300M 48p 10M/100M/1G 4p SFP56 50G Back-to-Front 2xFan PSU TAA 220v Bundle SOG02A#B2E

- HPE 2.5m C15 to NEMA 6-20P Pwr Cord(JL336A)

HPE Aruba Networking 6300M 48p 10M/100M/1G 4p SFP56 50G Back-to-Front 2xFan PSU TAA Bundle No Loc SOG02A#AC3

- No Localized Power Cord Selected. Use J9955A to obtain a Locking Plug Power Cord (L6-20P)

### 6300F TAA

1, 2, 3, 4,  
5, 8

HPE Aruba Networking 6300F 48p 10M/100M/1G Class4 PoE 4p SFP56 50G TAA Switch SOG95A

- HPE Aruba Networking 6300F 48-port 1GbE Class 4 PoE and 4-port SFP56 TAA Switch
- Includes Non-Pluggable, Internal PSU behind sheetmetal Chassis Frame
- Includes Non-Pluggable, Internal Fans behind sheetmetal Chassis Frame
- Min=0 \ Max = 4 SFP/SFP+/SFP28/SFP56 1/10/25/50G Transceiver
- 1U - Height

HPE Aruba Networking 6300F 48p 10M/100M/1G Class4 PoE 4p SFP56 50G TAA PDU Switch SOG95A#B2B

- C15 PDU Jumper Cord (NA/MEX/TW/JP) (J9943A)

HPE Aruba Networking 6300F 48p 10M/100M/1G Class4 PoE 4p SFP56 50G TAA PDU Switch SOG95A#B2C

- C15 PDU Jumper Cord (ROW) (J9944A)

HPE Aruba Networking 6300F 48p 10M/100M/1G Class4 PoE 4p SFP56 50G TAA 220v Switch SOG95A#B2E

- HPE 2.5m C15 to NEMA 6-20P Pwr Cord(JL336A)

HPE Aruba Networking 6300F 48p 10M/100M/1G Class4 PoE 4p SFP56 50G TAA Switch No Loc SOG95A#AC3

- No Localized Power Cord Selected. Use J9955A to obtain a Locking Plug Power Cord (L6-20P)

1, 2, 3, 4,  
5, 8

HPE Aruba Networking 6300F 24p 10M/100M/1G Class4 PoE 4p SFP56 50G TAA Switch SOG96A

- HPE Aruba Networking 6300F 24-port 1GbE Class 4 PoE and 4-port SFP56 TAA Switch
- Includes Non-Pluggable, Internal PSU behind sheetmetal Chassis Frame
- Includes Non-Pluggable, Internal Fans behind sheetmetal Chassis Frame
- Min=0 \ Max = 4 SFP/SFP+/SFP28/SFP56 1/10/25/50G Transceiver
- 1U - Height

HPE Aruba Networking 6300F 24p 10M/100M/1G Class4 PoE 4p SFP56 50G TAA PDU Switch SOG96A#B2B

- C15 PDU Jumper Cord (NA/MEX/TW/JP) (J9943A)

HPE Aruba Networking 6300F 24p 10M/100M/1G Class4 PoE 4p SFP56 50G TAA PDU Switch SOG96A#B2C

- C15 PDU Jumper Cord (ROW) (J9944A)

HPE Aruba Networking 6300F 24p 10M/100M/1G Class4 PoE 4p SFP56 50G TAA 220v Switch SOG96A#B2E

- HPE 2.5m C15 to NEMA 6-20P Pwr Cord(JL336A)

HPE Aruba Networking 6300F 24p 10M/100M/1G Class4 PoE 4p SFP56 50G TAA Switch No Loc SOG96A#AC3

- No Localized Power Cord Selected. Use J9955A to obtain a Locking Plug Power Cord (L6-20P)

## Configuration Information

1, 2, 3, 4, 5, 8	HPE Aruba Networking 6300F 48p 10M/100M/1G 4p SFP56 50G TAA Switch	S0G97A
	<ul style="list-style-type: none"> <li>• HPE Aruba Networking 6300F 48-port 1GbE and 4-port SFP56 TAA Switch</li> <li>• Includes Non-Pluggable, Internal PSU behind sheetmetal Chassis Frame</li> <li>• Includes Non-Pluggable, Internal Fans behind sheetmetal Chassis Frame</li> <li>• Min=0 \ Max = 4 SFP/SFP+/SFP28/SFP56 1/10/25/50G Transceiver</li> <li>• 1U - Height</li> </ul>	
	HPE Aruba Networking 6300F 48p 10M/100M/1G 4p SFP56 50G TAA PDU Switch	S0G97A#B2B
	<ul style="list-style-type: none"> <li>• C13 PDU Jumper Cord (NA/MEX/TW/JP)</li> </ul>	
	HPE Aruba Networking 6300F 48p 10M/100M/1G 4p SFP56 50G TAA PDU Switch	S0G97A#B2C
	<ul style="list-style-type: none"> <li>• C13 PDU Jumper Cord (ROW)</li> </ul>	
	HPE Aruba Networking 6300F 48p 10M/100M/1G 4p SFP56 50G TAA 220v Switch	S0G97A#B2E
	<ul style="list-style-type: none"> <li>• HPE 2.3m C13 to NEMA 6-15P Pwr Cord(J9936A)</li> </ul>	
	HPE Aruba Networking 6300F 48p 10M/100M/1G 4p SFP56 50G TAA Switch No Loc	S0G97A#AC3
	<ul style="list-style-type: none"> <li>• No Localized Power Cord Selected. Use J9955A to obtain a Locking Plug Power Cord (L6-20P)</li> </ul>	
1, 2, 3, 4, 5, 8	HPE Aruba Networking 6300F 24p 10M/100M/1G 4p SFP56 50G TAA Switch	S0G98A
	<ul style="list-style-type: none"> <li>• HPE Aruba Networking 6300F 24-port 1GbE and 4-port SFP56 TAA Switch</li> <li>• Includes Non-Pluggable, Internal PSU behind sheetmetal Chassis Frame</li> <li>• Includes Non-Pluggable, Internal Fans behind sheetmetal Chassis Frame</li> <li>• Min=0 \ Max = 4 SFP/SFP+/SFP28/SFP56 1/10/25/50G Transceiver</li> <li>• 1U - Height</li> </ul>	
	HPE Aruba Networking 6300F 24p 10M/100M/1G 4p SFP56 50G TAA PDU Switch	S0G98A#B2B
	<ul style="list-style-type: none"> <li>• C13 PDU Jumper Cord (NA/MEX/TW/JP)</li> </ul>	
	HPE Aruba Networking 6300F 24p 10M/100M/1G 4p SFP56 50G TAA PDU Switch	S0G98A#B2C
	<ul style="list-style-type: none"> <li>• C13 PDU Jumper Cord (ROW)</li> </ul>	
	HPE Aruba Networking 6300F 24p 10M/100M/1G 4p SFP56 50G TAA 220v Switch	S0G98A#B2E
	<ul style="list-style-type: none"> <li>• HPE 2.3m C13 to NEMA 6-15P Pwr Cord(J9936A)</li> </ul>	
	HPE Aruba Networking 6300F 24p 10M/100M/1G 4p SFP56 50G TAA Switch No Loc	S0G98A#AC3
	<ul style="list-style-type: none"> <li>• No Localized Power Cord Selected. Use J9955A to obtain a Locking Plug Power Cord (L6-20P)</li> </ul>	
	<b>HPE Aruba Networking CX 6300F</b>	
<b>Rule #</b>	<b>Description</b>	<b>SKU</b>
1, 2, 3, 4, 5, 8	HPE Aruba Networking CX 6300F 48-port 1GbE Class 4 PoE and 4-port SFP56 Switch	JL665A
	<ul style="list-style-type: none"> <li>• Includes Non-Pluggable, Internal PSU behind sheetmetal Chassis Frame</li> <li>• Includes Non-Pluggable, Internal Fans behind sheetmetal Chassis Frame</li> <li>• Min=0 \ Max = 4 SFP/SFP+/SFP28/SFP56 1/10/25/50G Transceiver</li> <li>• 1U - Height</li> </ul>	
	HPE Aruba Networking CX 6300F 48-port 1GbE Class 4 PoE and 4-port SFP56 Switch PDU	JL665A#B2B
	<ul style="list-style-type: none"> <li>• C15 PDU Jumper Cord (NA/MEX/TW/JP) (J9943A)</li> </ul>	
	HPE Aruba Networking CX 6300F 48-port 1GbE Class 4 PoE and 4-port SFP56 Switch PDU	JL665A#B2C
	<ul style="list-style-type: none"> <li>• C15 PDU Jumper Cord (ROW) (J9944A)</li> </ul>	
	HPE Aruba Networking CX 6300F 48-port 1GbE Class 4 PoE and 4-port SFP56 Switch 220v	JL665A#B2E
	<ul style="list-style-type: none"> <li>• HPE 2.5m C15 to NEMA 6-20P Pwr. Cord (JL336A)</li> </ul>	
	HPE Aruba Networking CX 6300F 48-port 1GbE Class 4 PoE and 4-port SFP56 Switch NoLoc	JL665A#AC3
	<ul style="list-style-type: none"> <li>• No Localized Power Cord Selected. Use J9955A to obtain a Locking Plug Power Cord (L6-20P)</li> </ul>	

## Configuration Information

1, 2, 3, 4, 5, 8	HPE Aruba Networking CX 6300F 24-port 1GbE Class 4 PoE and 4-port SFP56 Switch	JL666A
	<ul style="list-style-type: none"> <li>• Includes Non-Pluggable, Internal PSU behind sheetmetal Chassis Frame</li> <li>• Includes Non-Pluggable, Internal Fans behind sheetmetal Chassis Frame</li> <li>• Min=0 \ Max = 4 SFP/SFP+/SFP28/SFP56 1/10/25/50G Transceiver</li> <li>• 1U - Height</li> </ul>	
	HPE Aruba Networking CX 6300F 24-port 1GbE Class 4 PoE and 4-port SFP56 Switch PDU	JL666A#B2B
	<ul style="list-style-type: none"> <li>• C15 PDU Jumper Cord (NA/MEX/TW/JP) (J9943A)</li> </ul>	
	HPE Aruba Networking CX 6300F 24-port 1GbE Class 4 PoE and 4-port SFP56 Switch PDU	JL666A#B2C
	<ul style="list-style-type: none"> <li>• C15 PDU Jumper Cord (ROW) (J9944A)</li> </ul>	
	HPE Aruba Networking CX 6300F 24-port 1GbE Class 4 PoE and 4-port SFP56 Switch 220v	JL666A#B2E
	<ul style="list-style-type: none"> <li>• HPE 2.5m C15 to NEMA 6-20P Pwr. Cord (JL336A)</li> </ul>	
	HPE Aruba Networking CX 6300F 24-port 1GbE Class 4 PoE and 4-port SFP56 Switch NoLoc	JL666A#AC3
	<ul style="list-style-type: none"> <li>• No Localized Power Cord Selected. Use J9955A to obtain a Locking Plug Power Cord (L6-20P)</li> </ul>	
1, 2, 3, 4, 5, 8	HPE Aruba Networking CX 6300F 48-port 1GbE and 4-port SFP56 Switch	JL667A
	<ul style="list-style-type: none"> <li>• Includes Non-Pluggable, Internal PSU behind sheetmetal Chassis Frame</li> <li>• Includes Non-Pluggable, Internal Fans behind sheetmetal Chassis Frame</li> <li>• Min=0 \ Max = 4 SFP/SFP+/SFP28/SFP56 1/10/25/50G Transceiver</li> <li>• 1U - Height</li> </ul>	
	HPE Aruba Networking CX 6300F 48-port 1GbE and 4-port SFP56 Switch PDU	JL667A#B2B
	<ul style="list-style-type: none"> <li>• C13 PDU Jumper Cord (NA/MEX/TW/JP)</li> </ul>	
	HPE Aruba Networking CX 6300F 48-port 1GbE and 4-port SFP56 Switch PDU	JL667A#B2C
	<ul style="list-style-type: none"> <li>• C13 PDU Jumper Cord (ROW)</li> </ul>	
	HPE Aruba Networking CX 6300F 48-port 1GbE and 4-port SFP56 Switch 220v	JL667A#B2E
	<ul style="list-style-type: none"> <li>• HPE 2.3m C13 to NEMA 6-15P Pwr. Cord (J9936A)</li> </ul>	
	HPE Aruba Networking CX 6300F 48-port 1GbE and 4-port SFP56 Switch NoLoc	JL667A#AC3
	<ul style="list-style-type: none"> <li>• No Localized Power Cord Selected. Use J9955A to obtain a Locking Plug Power Cord (L6-20P)</li> </ul>	
1, 2, 3, 4, 5, 8	HPE Aruba Networking CX 6300F 24-port 1GbE and 4-port SFP56 Switch	JL668A
	<ul style="list-style-type: none"> <li>• Includes Non-Pluggable, Internal PSU behind sheetmetal Chassis Frame</li> <li>• Includes Non-Pluggable, Internal Fans behind sheetmetal Chassis Frame</li> <li>• Min=0 \ Max = 4 SFP/SFP+/SFP28/SFP56 1/10/25/50G Transceiver</li> <li>• 1U - Height</li> </ul>	
	HPE Aruba Networking CX 6300F 24-port 1GbE and 4-port SFP56 Switch PDU	JL668A#B2B
	<ul style="list-style-type: none"> <li>• C13 PDU Jumper Cord (NA/MEX/TW/JP)</li> </ul>	
	HPE Aruba Networking CX 6300F 24-port 1GbE and 4-port SFP56 Switch PDU	JL668A#B2C
	<ul style="list-style-type: none"> <li>• C13 PDU Jumper Cord (ROW)</li> </ul>	
	HPE Aruba Networking CX 6300F 24-port 1GbE and 4-port SFP56 Switch 220v	JL668A#B2E
	<ul style="list-style-type: none"> <li>• HPE 2.3m C13 to NEMA 6-15P Pwr. Cord (J9936A)</li> </ul>	
	HPE Aruba Networking CX 6300F 24-port 1GbE and 4-port SFP56 Switch NoLoc	JL668A#AC3
	<ul style="list-style-type: none"> <li>• No Localized Power Cord Selected. Use J9955A to obtain a Locking Plug Power Cord (L6-20P)</li> </ul>	



## Configuration Information

### HPE Aruba Networking CX 6300L

2, 3, 4, 8	HPE Aruba Networking 6300L 24p Smart Rate 1G/2.5G/5G/10G CL6 2p SFP56 50G 2p SFP28 25G L2 Switch	S3L75A
	<ul style="list-style-type: none"> <li>• HPE Aruba Networking 6300L 24p Smart Rate 1G/2.5G/5G/10G Class6 PoE 2p 50G and 2p 25G L2 Switch</li> <li>• Must Select PSU Min1 / Max2 (680W JL086A,1050W JL087A, 1600W JL670A, 1050W JL758A) Mix OK</li> <li>• Includes Fantrays Min2 / Max 2 (JL669B)</li> <li>• Min=0 \ Max = 2 SFP+/SFP28/SFP56 10/25/50G Transceiver (Ports 25/26)</li> <li>• Min=0 \ Max = 2 SFP+ or 2 SFP28 10/25 Transceiver (Ports 27/28)</li> <li>• 1U - Height</li> </ul>	
2, 3, 4, 8	HPE Aruba Networking 6300L 48p Smart Rate 100M/1G/2.5G/5G CL8 2p SFP56 50G 2p SFP28 25G L2 Switch	S3L76A
	<ul style="list-style-type: none"> <li>• HPE Aruba Networking 6300L 48p Smart Rate 1G/2.5G/5G Class8 PoE 2p 50G and 2p 25G L2 Switch</li> <li>• Must Select PSU Min1 / Max2 (680W JL086A,1050W JL087A, 1600W JL670A, 1050W JL758A) Mix OK</li> <li>• Includes Fantrays Min2 / Max 2 (JL669B)</li> <li>• Min=0 \ Max = 2 SFP+/SFP28/SFP56 10/25/50G Transceiver (Ports 49/50)</li> <li>• Min=0 \ Max = 2 SFP+ or 2 SFP28 10/25 Transceiver (Ports 51/52)</li> <li>• 1U - Height</li> </ul>	
1, 2, 3, 4, 7, 8	HPE ANW 6300L 48p Smart Rate 100M/1G/2.5G/5G Class6/8 2p SFP56 50G 2p SFP+ 1G/10G LRM Layer2 Sw	S3L77A
	<ul style="list-style-type: none"> <li>• HPE Aruba Networking 6300L 48p Smart Rate 1G/2.5G/5G Class8/6 PoE 2p 50G and 2p 10G LRM L2 Switch</li> <li>• Must Select PSU Min1 / Max2 (680W JL086A,1050W JL087A, 1600W JL670A, 1050W JL758A) Mix OK</li> <li>• Includes Fantrays Min2 / Max 2 (JL669B)</li> <li>• Min=0 \ Max = 2 SFP+/SFP28/SFP56 10/25/50G Transceiver (Ports 49/50)</li> <li>• Min=0 \ Max = 2 SFP or 2 SFP+ 1/10 Transceiver (LRM Supported) (Ports 51/52)</li> <li>• 1U - Height</li> </ul>	

### Configuration Rules

Rule #	Description	SKU
1	<b>The following Transceivers install into this Switch: (Use BTO only when adding to switch)</b>	
	HPE Aruba Networking 1G SFP LC SX 500m OM2 MMF Transceiver	J4858D
	HPE Aruba Networking 1G SFP LC LX 10km SMF Transceiver	J4859D
	HPE Aruba Networking 1G SFP LC LH 70km SMF Transceiver	J4860D
	HPE Aruba Networking 1G SFP RJ45 T 100m Cat5e Transceiver	J8177D
	HPE Aruba Networking 1G SFP LC SX 500m MMF TAA Transceiver	JL745A
	HPE Aruba Networking 1G SFP LC LX 10km SMF TAA Transceiver	JL746A
	HPE Aruba Networking 1G SFP RJ45 T 100m Cat5e TAA Transceiver	JL747A
2	<b>The following Transceivers install into this Switch: (Use BTO only when adding to switch)</b>	
	HPE Aruba Networking 10GBASE-T SFP+ RJ45 30m Cat6A Transceiver	JL563B
	HPE Aruba Networking 10GBASE-T SFP+ RJ45 30m Cat6A Transceiver	JL563C
	HPE Aruba Networking 10G SFP+ LC SR 300m OM3 MMF Transceiver	J9150D
	HPE Aruba Networking 10G SFP+ LC LR 10km SMF Transceiver	J9151E
	HPE Aruba Networking 10G SFP+ LC ER 40km SMF Transceiver	J9153D
	HPE Aruba Networking 10G SFP+ LC SR 300m MMF TAA Transceiver	JL748A
	HPE Aruba Networking 10G SFP+ LC LR 10km SMF TAA Transceiver	JL749A
	HPE Aruba Networking 10G SMF Simplex LC BiDi 40km-Downstream 1330/1270 Transceiver	R9X54A

## Configuration Information

	HPE Aruba Networking 10G SMF Simplex LC BiDi 40km-Upstream 1270/1330 Transceiver	R9X55A
	HPE Aruba Networking 10G SR SFP+ LC 400m OM4 MMF C-Class Transceiver	S2P30A
	HPE Aruba Networking 10G LR SFP+ LC 10km SMF C-Class Transceiver	S2P31A
	HPE Aruba Networking 10G ER SFP+ LC 40km SMF C-Class Transceiver	S2P32A
	HPE Aruba Networking 10G SFP+ to SFP+ 1m Direct Attach Copper Cable	J9281D
	HPE Aruba Networking 10G SFP+ to SFP+ 3m Direct Attach Copper Cable	J9283D
<b>3</b>	<b>The following Transceivers install into this Switch: (Use BTO only when adding to switch)</b>	
	HPE Aruba Networking 25G ER LC 40km SMF Transceiver	SOV69A
	HPE Aruba Networking 25G BiDi 10km-Downstream 1330/1270 Transceiver	S1C96A
	HPE Aruba Networking 25G BiDi 10km-Upstream 1270/1330 Transceiver	S1C98A
	HPE Aruba Networking 25G SFP28 LC SR 100m MMF Transceiver	JL484A
	HPE Aruba Networking 25G SFP28 LC eSR 400m MMF Transceiver	JL485A
	HPE Aruba Networking 25G SFP28 LC LR 10km SMF Transceiver	JL486A
	HPE Aruba Networking 25G SR SFP28 LC 100m MMF C-Class Transceiver	S2P33A
	HPE Aruba Networking 25G LR SFP28 LC 10km SMF C-Class Transceiver	S2P34A
	HPE Aruba Networking 25G SFP28 to SFP28 0.65m Direct Attach Cable	JL487A
	HPE Aruba Networking 25G SFP28 to SFP28 3m Direct Attach Copper Cable	JL488A
	HPE Aruba Networking 25G SFP28 to SFP28 5m Direct Attach Copper Cable	JL489A
	HPE Aruba Networking 25G SFP28 to SFP28 3m Active Optical Cable	ROM44A
	HPE Aruba Networking 25G SFP28 to SFP28 7m Active Optical Cable	ROM45A
	HPE Aruba Networking 25G SFP28 to SFP28 15m Active Optical Cable	ROZ21A
<b>4</b>	<b>The following Transceivers install into this Switch: (Use BTO only when adding to switch)</b>	
	HPE Aruba Networking 50G eSR 300m MMF Transceiver	SOV64A
	HPE Aruba Networking 50G LR 10km SMF Transceiver	SOV65A
	HPE Aruba Networking 50G ER 40km SMF Transceiver	SOV66A
	HPE Aruba Networking 50G BiDi 10km-Downstream 1330/1270 Transceiver	S1C92A
	HPE Aruba Networking 50G BiDi 10km-Upstream 1270/1330 Transceiver	S1C94A
	HPE Aruba Networking 50G SFP56 to SFP56 0.65m Direct Attach Copper Cable	ROM46A
	HPE Aruba Networking 50G SFP56 to SFP56 3m Direct Attach Copper Cable	ROM47A
	HPE Aruba Networking 50G SFP56 LC SR 100m MMF Transceiver	ROM48A
	HPE Aruba Networking 50G QSFP56 to SFP56 0.65m DAC Cable	S1J07A
	HPE Aruba Networking 50G QSFP56 to SFP56 3m DAC Cable	S1J08A
<b>5</b>	<b>Localization required on orders without #B2B, #B2C, #B2E or #AC3 options.</b>	
<b>6</b>	<b>The following Transceivers install into this Switch: (Use BTO only when adding to switch)</b>	
	HPE Aruba Networking 100M SFP LC FX 2km MMF Transceiver	J9054D
<b>7</b>	<b>The following Transceivers install into this Switch and is only available on LRM Supported ports. See AOS-Switch and AOS-CX Transceiver Guide (Edition 12) for port compatibility: (Use BTO only when adding to switch)</b>	
	HPE Aruba Networking 10G SFP+ LC LRM 220m OM2 MMF Transceiver	J9152D
<b>8</b>	<b>If ANY Option is integrated OD1 to this Switch, then the Switch requires OD1. (Box level integration is not allowed)</b>	
<b>9</b>	<b>The following Transceivers install into this Switch using QSFP56 side of cable: (Use BTO only when adding to switch)</b>	
	HPE Aruba Networking 50G QSFP56 to SFP56 0.65m DAC Cable	S1J07A
	HPE Aruba Networking 50G QSFP56 to SFP56 3m DAC Cable	S1J08A
<b>11</b>	<b>If qty1 of the folowing QSA28 Adapter(845970-B21) is selected, then increase max SFP28 Port qty by 1 and allow user selection of the following SFP Transceivers. Refer to qty and port restrictions for individual Switch in the "Additional Info" sections: (Use BTO only when adding to switch)</b>	
	HPE Aruba Networking 10G SFP+ LC SR 300m OM3 MMF Transceiver	J9150D

## Configuration Information

HPE Aruba Networking 10G SFP+ LC LR 10km SMF Transceiver	J9151E
HPE Aruba Networking 10G SFP+ LC ER 40km SMF Transceiver	J9153D
HPE Aruba Networking 10G SFP+ LC SR 300m MMF TAA Transceiver	JL748A
HPE Aruba Networking 10G SFP+ LC LR 10km SMF TAA Transceiver	JL749A
HPE Aruba Networking 25G SFP28 LC SR 100m MMF Transceiver	JL484A
HPE Aruba Networking 25G SFP28 LC eSR 400m MMF Transceiver	JL485A
HPE Aruba Networking 25G SFP28 LC LR 10km SMF Transceiver	JL486A
HPE Aruba Networking 25G ER LC 40km SMF Transceiver	SOV69A
HPE Aruba Networking 25G BiDi 10km-Downstream 1330/1270 Transceiver	S1C96A
HPE Aruba Networking 25G BiDi 10km-Upstream 1270/1330 Transceiver	S1C98A
HPE Aruba Networking 25G SFP28 to SFP28 3m Active Optical Cable	ROM44A
HPE Aruba Networking 25G SFP28 to SFP28 7m Active Optical Cable	ROM45A
HPE Aruba Networking 25G SFP28 to SFP28 15m Active Optical Cable	ROZ21A

### 12 The following Transceivers install into this Switch: (Use BTO only when adding to switch)

HPE Aruba Networking 100G SR2 MPO QSFP28 100m MMF Transceiver	S1C93A
HPE QSFP28 to SFP28 Adapter	845970-B21
HPE Aruba Networking 100G QSFP28 LC CWDM4 2km SMF Transceiver	ROZ30A
HPE Aruba Networking 100G QSFP28 LC LR4 10km SMF 2-strand Transceiver	JL310A
HPE Aruba Networking 100G QSFP28 MPO SR4 100m 12-fiber MPO OM3 MMF Transceiver	JL309A
HPE Aruba Networking 100G QSFP28 LC ER4L 40km SMF Transceiver	JL743A
HPE Aruba Networking 100G QSFP28 LC FR1 SMF 2km Transceiver	R9B63A
HPE Aruba Networking 100G QSFP28 to QSFP28 3m Direct Attach Copper Cable	JL307A
HPE Aruba Networking 100G QSFP28 to QSFP28 1m Direct Attach Copper Cable	ROZ25A
HPE Aruba Networking 100G QSFP28 to QSFP28 5m Direct Attach Copper Cable	ROZ26A
HPE Aruba Networking 100G QSFP28 to QSFP28 2m Active Optical Cable	JL856A
HPE Aruba Networking 100G QSFP28 to QSFP28 7m Active Optical Cable	ROZ27A
HPE Aruba Networking 100G QSFP28 to QSFP28 15m Active Optical Cable	ROZ28A
HPE Aruba Networking 100G QSFP28 to QSFP28 30m Active Optical Cable	ROZ29A

### 13 The following Transceivers install into this Switch(Use BTO only when adding to switch)

HPE Networking X142 40G QSFP+ MPO SR4 Transceiver	JH231A
HPE Networking X142 40G QSFP+ LC LR4 SM Transceiver	JH232A
HPE Networking X142 40G QSFP+ MPO eSR4 300M Transceiver	JH233A
HPE Aruba Networking 40G QSFP+ LC Bidirectional 150m MMF 2-strand Transceiver	JL308A
HPE Aruba Networking 40G QSFP+ LC ER4 40km SMF Transceiver	Q9G82A
HPE Networking X242 40G QSFP+ to QSFP+ 1m Direct Attach Copper Cable	JH234A
HPE Networking X242 40G QSFP+ to QSFP+ 3m Direct Attach Copper Cable	JH235A
HPE Networking X242 40G QSFP+ to QSFP+ 5m Direct Attach Copper Cable	JH236A
HPE Aruba Networking 40G QSFP+ to QSFP+ 7m Active Optical Cable	ROZ22A
HPE Aruba Networking 40G QSFP+ to QSFP+ 15m Active Optical Cable	ROZ23A
HPE Aruba Networking 40G QSFP+ to QSFP+ 30m Active Optical Cable	ROZ24A

### 14 The following Transceivers install into this Switch (Use BTO only when adding to switch)

HPE Aruba Networking 25G LR SFP28 LC 10km SMF TAA Transceiver	S2N63A
---	--------

- Notes:**
- Drop down under power supply should offer the following options and results:
  - Switch/Router/Power Supply to PDU Power Cord - #B2B in North America, Mexico, Taiwan, and Japan or #B2C ROW. (Watson Default B2B or B2C for Rack Level CTO)
  - Switch/Router/Power Supply to Wall Power Cord - Localized Option (Watson Default for BTO and Box Level CTO)
  - High Volt Switch/Router/Power Supply to Wall Power Cord - #B2E Option. (Offered only in North America, Mexico, Taiwan, and Japan)
  - No Power Cord - #AC3 Option

## Configuration Information

- [OCA Blue Notes: Locking Power Cord \(J9955A\) L6-20P is available through the OCA Accessories tab](#)
- [OCA Only Model Selection Form>HPE Aruba Networking > Switches > HPE Aruba Networking OS > AOS-CX: HPE Aruba Networking 6300 Switch Series](#)

### Rack Level Integration CTO Models

#### HPE Aruba Networking CX 6300M

Rule #	Description	SKU
<a href="#">1, 2, 3, 4, 6, 8</a>	<p>HPE Aruba Networking CX 6300M 24-port SFP+ and 4-port SFP56 Switch</p> <ul style="list-style-type: none"> <li>• HPE Aruba Networking 6300M 24-port SFP+ and 4-port SFP56 Switch</li> <li>• Must Select PSU Min1 / Max2 (250W JL085A, 250W JL757A) Mix OK</li> <li>• Includes Fantrays Min2 / Max 2 (JL669B)</li> <li>• Min=0 \ Max= 24 SFP/SFP+ 100M/1/10G Transceivers</li> <li>• Min=0 \ Max = 4 SFP/SFP+/SFP28/SFP56 1/10/25/50G Transceiver</li> <li>• 1U - Height</li> </ul>	JL658A
<a href="#">5, 6, 7, 10, 11, 12, 13, 14</a>	<p>HPE Aruba Networking 6300M 48p SR10 1G/2.5G/5G/10G PTP/AVB Class8 PoE and 4p 100G MACsec Switch</p> <ul style="list-style-type: none"> <li>• Aruba 6300M 48p SR10 1G/2.5G/5G/10G PTP/AVB Class 8 PoE and 4p 100G MACsec Switch</li> <li>• Must Select PSU Min1 / Max2 (680W JL086A,1050W JL087A, 1600W JL670A, 1050W JL758A) Mix OK</li> <li>• Includes Fantrays Min2 / Max 2 (JL669B)</li> <li>• Min=0 \ Max = 4 QSFP56 50G Transceiver</li> <li>• QSA28 Adapter Min=0 \ Max=4, ports 49-52 (rule11)</li> <li>• 1U - Height</li> </ul>	SOE91A
<a href="#">1, 2, 3, 4, 6</a>	<p>HPE Aruba Networking CX 6300M 48-port HPE Smart Rate 1/2.5/5GbE Class 6 PoE and 4-port SFP56 Switch</p> <ul style="list-style-type: none"> <li>• HPE Aruba Networking 6300M 48-port HPE Smart Rate 1/2.5/5GbE Class 6 PoE and 4-port SFP56 Switch</li> <li>• Must Select PSU Min1 / Max2 (680W JL086A,1050W JL087A, 1600W JL670A, 1050W JL758A) Mix OK</li> <li>• Includes Fantrays Min2 / Max 2 (JL669B)</li> <li>• Min=0 \ Max = 4 SFP/SFP+/SFP28/SFP56 1/10/25/50G Transceiver</li> <li>• 1U - Height</li> </ul>	JL659A
<a href="#">2, 3, 4, 6</a>	<p>HPE Aruba Networking CX 6300M 48p HPE Smart Rate 1G/2.5G/5G Class8 PoE 2p 50G 2p 25G Switch</p> <ul style="list-style-type: none"> <li>• HPE Aruba Networking 6300M 48p HPE Smart Rate 1G/2.5G/5G CL8 PoE and 2p 50G and 2p 25G Switch</li> <li>• Must Select PSU Min1 / Max2 (680W JL086A,1050W JL087A, 1600W JL670A, 1050W JL758A) Mix OK</li> <li>• Includes Fantrays Min2 / Max 2 (JL669B)</li> <li>• Min=0 \ Max = 2 SFP+/SFP28 10/25/50G Transceiver (Ports 49/50)</li> <li>• Min=0 \ Max = 2 SFP+/SFP28/SFP56 10/25 Transceiver (Ports 51/52)</li> <li>• 1U - Height</li> </ul>	R8S90A

## Configuration Information

1, 2, 3, 4, 6	HPE Aruba Networking CX 6300M 24-port HPE Smart Rate 1/2.5/5GbE Class 6 PoE and 4-port SFP56 Switch	JL660A
	<ul style="list-style-type: none"> <li>• HPE Aruba Networking 6300M 24-port HPE Smart Rate 1/2.5/5GbE Class 6 PoE and 4-port SFP56 Switch</li> <li>• Must Select PSU Min1 / Max2 (680W JL086A,1050W JL087A, 1600W JL670A, 1050W JL758A) Mix OK</li> <li>• Includes 1 Fan tray (JL669B), with 1 open slot with blank cover</li> <li>• Min=0 \ Max = 4 SFP/SFP+/SFP28/SFP56 1/10/25/50G Transceiver</li> <li>• 1U - Height</li> </ul>	
2, 3, 4, 6	HPE Aruba Networking CX 6300M 24p Smart Rate 1G/2.5G/5G/10G Class6 PoE 2p 50G 2p 25G Switch	R8S89A
	<ul style="list-style-type: none"> <li>• HPE Aruba Networking 6300M 24p HPE Smart Rate 1G/2.5G/5G/10G CL6 PoE and 2p 50G and 2p 25G Switch</li> <li>• Must Select PSU Min1 / Max2 (680W JL086A,1050W JL087A, 1600W JL670A, 1050W JL758A) Mix OK</li> <li>• Includes Fantrays Min2 / Max 2 (JL669B)</li> <li>• Min=0 \ Max = 2 SFP+/SFP28 10/25/50G Transceiver (Ports 25/26)</li> <li>• Min=0 \ Max = 2 SFP+/SFP28/SFP56 10/25 Transceiver (Ports 27/28)</li> <li>• 1U - Height</li> </ul>	
1, 2, 3, 4, 6	HPE Aruba Networking CX 6300M 48-port 1GbE Class 4 PoE and 4-port SFP56 Switch	JL661A
	<ul style="list-style-type: none"> <li>• HPE Aruba Networking 6300M 48-port 1GbE Class 4 PoE and 4-port SFP56 Switch</li> <li>• Must Select PSU Min1 / Max2 (680W JL086A,1050W JL087A, 1600W JL670A, 1050W JL758A) Mix OK</li> <li>• Includes 1 Fan tray (JL669B), with 1 open slot with blank cover</li> <li>• Min=0 \ Max = 4 SFP/SFP+/SFP28/SFP56 1/10/25/50G Transceiver</li> <li>• 1U - Height</li> </ul>	
1, 2, 3, 4, 6, 9	HPE Aruba Networking CX 6300M 12p CL8 PoE 36p CL6 PoE Smart Rate 1G/2.5G/5G 2p 50G 2p 10G Switch	R8S91A
	<ul style="list-style-type: none"> <li>• HPE Aruba Networking 6300M 12p Class8 PoE and 36p Class6 PoE HPE Smart Rate 1G/2.5G/5G and 2p 50G and 2p 10G Switch</li> <li>• Must Select PSU Min1 / Max2 (680W JL086A,1050W JL087A, 1600W JL670A, 1050W JL758A) Mix OK</li> <li>• Includes Fantrays Min2 / Max 2 (JL669B)</li> <li>• Min=0 \ Max = 2 SFP+/SFP28/SFP56 10/25/50G Transceiver (Ports 49/50)</li> <li>• Min=0 \ Max = 2 SFP/SFP+ 1/10 Transceiver (LRM Supported) (Ports 51/52)</li> <li>• 1U - Height</li> </ul>	
1, 2, 3, 4, 6	HPE Aruba Networking CX 6300M 24-port 1GbE Class 4 PoE and 4-port SFP56 Switch	JL662A
	<ul style="list-style-type: none"> <li>• HPE Aruba Networking 6300M 24-port 1GbE Class 4 PoE and 4-port SFP56 Switch</li> <li>• Must Select PSU Min1 / Max2 (680W JL086A,1050W JL087A, 1600W JL670A, 1050W JL758A) Mix OK</li> <li>• Includes 1 Fan tray (JL669B), with 1 open slot with blank cover</li> <li>• Min=0 \ Max = 4 SFP/SFP+/SFP28/SFP56 1/10/25/50G Transceiver</li> <li>• 1U - Height</li> </ul>	
1, 2, 3, 4, 6, 9, 14	HPE Aruba Networking CX 6300M 24p SFP+ LRM support and 2p 50G and 2p 25G MACSec Switch	R8S92A
	<ul style="list-style-type: none"> <li>• HPE Aruba Networking 6300M 24p SFP+ LRM support and 2p 50G and 2p 25G MACSec Switch</li> <li>• Must Select PSU Min1 / Max2 (250W JL085A, 250W JL757A) Mix OK</li> <li>• Includes Fantrays Min2 / Max 2 (JL669B)</li> <li>• Min=0 \ Max = 24 SFP/SFP+ Transceiver (LRM Supported Ports 1-24)</li> <li>• Min=0 \ Max = 2 SFP+/SFP28/SFP56 10/25/50G Transceiver (Ports 25/26)</li> </ul>	



## Configuration Information

	<ul style="list-style-type: none"> <li>• Min=0 \ Max = 2 SFP+/SFP28 1/10/25 Transceiver (Ports 27/28)</li> <li>• 1U - Height</li> </ul>	
<a href="#">1, 2, 3, 4, 6</a>	HPE Aruba Networking CX 6300M 48-port 1GbE and 4-port SFP56 Switch	JL663A
	<ul style="list-style-type: none"> <li>• HPE Aruba Networking 6300M 48-port 1GbE and 4-port SFP56 Switch</li> <li>• Must Select PSU Min1 / Max2 (250W JL085A, 250W JL757A) Mix OK</li> <li>• Includes 1 Fan tray (JL669B), with 1 open slot with blank cover</li> <li>• Min=0 \ Max = 4 SFP/SFP+/SFP28/SFP56 1/10/25/50G Transceiver</li> <li>• 1U - Height</li> </ul>	
<a href="#">1, 2, 3, 4, 6</a>	HPE Aruba Networking CX 6300M 24-port 1GbE and 4-port SFP56 Switch	JL664A
	<ul style="list-style-type: none"> <li>• HPE Aruba Networking 6300M 24-port 1GbE and 4-port SFP56 Switch</li> <li>• Must Select PSU Min1 / Max2 (250W JL085A, 250W JL757A) Mix OK</li> <li>• Includes 1 Fan tray (JL669B), with 1 open slot with blank cover</li> <li>• Min=0 \ Max = 4 SFP/SFP+/SFP28/SFP56 1/10/25/50G Transceiver</li> <li>• 1U - Height"</li> </ul>	
<a href="#">1, 2, 3, 4, 5, 6, 7</a>	HPE Aruba Networking CX 6300M 48p 1GbE 4p SFP56 Power-to-Port 2 Fan Trays 1 PSU Bundle	JL762A
	<ul style="list-style-type: none"> <li>• HPE Aruba Networking 6300M 48-port 1GbE and 4-port SFP56 Power-to-Port 2 Fan Trays 1 PSU Bundle</li> <li>• Includes 1 Pwr2Prt PSU, can select Min0 / Max1 (250W JL760A)</li> <li>• Includes 2 Pwr2Prt Fan trays (JL761A), with no open slots</li> <li>• Min=0 \ Max = 4 SFP/SFP+/SFP28/SFP56 1/10/25/50G Transceiver</li> <li>• 1U - Height</li> </ul>	
	HPE Aruba Networking CX 6300M 48p 1GbE 4p SFP56 Power-to-Port 2 Fan Trays 1 PSU Bundle PDU	JL762A#B2B
	<ul style="list-style-type: none"> <li>• C15 PDU Jumper Cord (NA/MEX/TW/JP) (J9943A)</li> </ul>	
	HPE Aruba Networking CX 6300M 48p 1GbE 4p SFP56 Power-to-Port 2 Fan Trays 1 PSU Bundle PDU	JL762A#B2C
	<ul style="list-style-type: none"> <li>• C15 PDU Jumper Cord (ROW) (J9944A)</li> </ul>	
	HPE Aruba Networking CX 6300M 48p 1GbE 4p SFP56 Power-to-Port 2 Fan Trays 1 PSU Bundle 220v	JL762A#B2E
	<ul style="list-style-type: none"> <li>• HPE 2.5m C15 to NEMA 6-20P Pwr. Cord (JL336A)</li> </ul>	
	HPE Aruba Networking CX 6300M 48p 1GbE 4p SFP56 Power-to-Port 2 Fan Trays 1 PSU Bundle NoLoc	JL762A#AC3
	<ul style="list-style-type: none"> <li>• No Localized Power Cord Selected. Use J9955A to obtain a Locking Plug Power Cord (L6-20P)</li> </ul>	

### HPE Aruba Networking CX 6300M TAA

<a href="#">1, 2, 3, 4, 6</a>	HPE Aruba Networking 6300M 24p 10M/100M/1G Class4 PoE 4p SFP56 50G TAA Switch	S0F99A
	<ul style="list-style-type: none"> <li>• HPE Aruba Networking 6300M 24p 1GbE Class 4 PoE and 4p SFP56 TAA Switch</li> <li>• Must Select PSU Min1 / Max2 (680W JL086A,1050W JL087A, 1600W JL670A, 1050W JL758A) Mix OK</li> <li>• Includes 1 Fan tray (JL669B), with 1 open slot with blank cover</li> <li>• Min=0 \ Max = 4 SFP/SFP+/SFP28/SFP56 1/10/25/50G Transceiver</li> <li>• 1U - Height</li> </ul>	
<a href="#">1, 2, 3, 4, 6</a>	HPE Aruba Networking 6300M 48p 10M/100M/1G 4p SFP56 50G TAA Switch	S0G00A
	<ul style="list-style-type: none"> <li>• HPE Aruba Networking 6300M 48p 1GbE and 4p SFP56 TAA Switch</li> <li>• Must Select PSU Min1 / Max2 (250W JL085A, 250W JL757A) Mix OK</li> <li>• Includes 1 Fan tray (JL669B), with 1 open slot with blank cover</li> <li>• Min=0 \ Max = 4 SFP/SFP+/SFP28/SFP56 1/10/25/50G Transceiver</li> <li>• 1U - Height</li> </ul>	



## Configuration Information

<a href="#">1, 2, 3, 4, 6</a>	<p>HPE Aruba Networking 6300M 24p 10M/100M/1G 4p SFP56 50G TAA Switch</p> <ul style="list-style-type: none"> <li>• HPE Aruba Networking 6300M 24p 1GbE and 4p SFP56 TAA Switch</li> <li>• Must Select PSU Min1 / Max2 (250W JL085A, 250W JL757A) Mix OK</li> <li>• Includes 1 Fan tray (JL669B), with 1 open slot with blank cover</li> <li>• Min=0 \ Max = 4 SFP/SFP+/SFP28/SFP56 1/10/25/50G Transceiver</li> <li>• 1U - Height</li> </ul>	SOG01A
<a href="#">1, 2, 3, 4, 6, 8</a>	<p>HPE Aruba Networking 6300M 24p SFP+ 1G/10G 4p SFP56 50G TAA Switch</p> <ul style="list-style-type: none"> <li>• HPE Aruba Networking 6300M 24p SFP+ and 4p SFP56 TAA Switch</li> <li>• Must Select PSU Min1 / Max2 (250W JL085A, 250W JL757A) Mix OK</li> <li>• Includes Fantrays Min2 / Max 2 (JL669B)</li> <li>• Min=0 \ Max= 24 SFP/SFP+ 100M/1/10G Transceivers</li> <li>• Min=0 \ Max = 4 SFP/SFP+/SFP28/SFP56 1/10/25/50G Transceiver</li> <li>• 1U - Height</li> </ul>	SOG03A
<a href="#">1, 2, 3, 4, 6</a>	<p>HPE Aruba Networking 6300M 48p Smart Rate 1G/2.5G/5G Class6 PoE 4p SFP56 50G TAA Switch</p> <ul style="list-style-type: none"> <li>• HPE Aruba Networking 6300M 48p HPE Smart Rate 1/2.5/5GbE Class 6 PoE and 4p SFP56 TAA Switch</li> <li>• Must Select PSU Min1 / Max2 (680W JL086A,1050W JL087A, 1600W JL670A, 1050W JL758A) Mix OK</li> <li>• Includes Fantrays Min2 / Max 2 (JL669B)</li> <li>• Min=0 \ Max = 4 SFP/SFP+/SFP28/SFP56 1/10/25/50G Transceiver</li> <li>• 1U - Height</li> </ul>	SOG04A
<a href="#">1, 2, 3, 4, 6</a>	<p>HPE Aruba Networking 6300M 24p Smart Rate 1G/2.5G/5G Class6 PoE 4p SFP56 50G TAA Switch</p> <ul style="list-style-type: none"> <li>• HPE Aruba Networking 6300M 24p HPE Smart Rate 1/2.5/5GbE Class 6 PoE and 4p SFP56 TAA Switch</li> <li>• Must Select PSU Min1 / Max2 (680W JL086A,1050W JL087A, 1600W JL670A, 1050W JL758A) Mix OK</li> <li>• Includes 1 Fan tray (JL669B), with 1 open slot with blank cover</li> <li>• Min=0 \ Max = 4 SFP/SFP+/SFP28/SFP56 1/10/25/50G Transceiver</li> <li>• 1U - Height</li> </ul>	SOG05A
<a href="#">1, 2, 3, 4, 6</a>	<p>HPE Aruba Networking 6300M 48p 10M/100M/1G Class4 PoE 4p SFP56 50G TAA Switch</p> <ul style="list-style-type: none"> <li>• HPE Aruba Networking 6300M 48p 1GbE Class 4 PoE and 4p SFP56 TAA Switch</li> <li>• Must Select PSU Min1 / Max2 (680W JL086A,1050W JL087A, 1600W JL670A, 1050W JL758A) Mix OK</li> <li>• Includes 1 Fan tray (JL669B), with 1 open slot with blank cover</li> <li>• Min=0 \ Max = 4 SFP/SFP+/SFP28/SFP56 1/10/25/50G Transceiver</li> <li>• 1U - Height</li> </ul>	SOG06A
<a href="#">6, 7, 10, 11, 12, 13</a>	<p>HPE Aruba Networking 6300M 48p SR10 1G/2.5G/5G/10G PTP/AVB Class8 PoE 4p 100G MACsec TAA Switch</p> <ul style="list-style-type: none"> <li>• Aruba 6300M 48p SR10 1G/2.5G/5G/10G PTP/AVB Class 8 PoE and 4p 100G MACsec TAA Switch</li> <li>• Must Select PSU Min1 / Max2 (680W JL086A,1050W JL087A, 1600W JL670A, 1050W JL758A) Mix OK</li> <li>• Includes Fantrays Min2 / Max 2 (JL669B)</li> <li>• Min=0 \ Max = 4 QSFP+/QSFP56/QSFP28 50G Transceiver</li> <li>• QSA28 Adapter Min=0 \ Max=4, ports 49-52 (rule11)</li> <li>• 1U - Height</li> </ul>	SOX44A

## Configuration Information

1, 2, 3, 4, 5, 6, 7	<p>HPE Aruba Networking 6300M 48p 10M/100M/1G 4p SFP56 50G Power-to-Port 2xFan PSU TAA Bundle</p> <ul style="list-style-type: none"> <li>• "HPE Aruba Networking 6300M 48p 1GbE and 4p SFP56 Power-to-Port 2 Fan Trays 1 PSU TAA Switch Bundle</li> <li>• Includes 1 Pwr2Prt PSU, can select Min0 / Max1 (250W JL760A)</li> <li>• Includes 2 Pwr2Prt Fan trays (JL761A), with no open slots</li> <li>• Min=0 \ Max = 4 SFP/SFP+/SFP28/SFP56 1/10/25/50G Transceiver</li> <li>• 1U - Height"</li> </ul> <p>HPE Aruba Networking 6300M 48p 10M/100M/1G 4p SFP56 50G Back-to-Front 2xFan PSU TAA Bundle PDU</p> <ul style="list-style-type: none"> <li>• C15 PDU Jumper Cord (NA/MEX/TW/JP) (J9943A)</li> </ul> <p>HPE Aruba Networking 6300M 48p 10M/100M/1G 4p SFP56 50G Back-to-Front 2xFan PSU TAA Bundle PDU</p> <ul style="list-style-type: none"> <li>• C15 PDU Jumper Cord (ROW) (J9944A)</li> </ul> <p>HPE Aruba Networking 6300M 48p 10M/100M/1G 4p SFP56 50G Back-to-Front 2xFan PSU TAA 220v Bundle</p> <ul style="list-style-type: none"> <li>• HPE 2.5m C15 to NEMA 6-20P Pwr Cord(JL336A)</li> </ul> <p>HPE Aruba Networking 6300M 48p 10M/100M/1G 4p SFP56 50G Back-to-Front 2xFan PSU TAA Bundle No Loc</p> <ul style="list-style-type: none"> <li>• No Localized Power Cord Selected. Use J9955A to obtain a Locking Plug Power Cord (L6-20P)</li> </ul>	SOG02A  SOG02A#B2B  SOG02A#B2C  SOG02A#B2E  SOG02A#AC3
<b>6300F TAA</b>		
1, 2, 3, 4, 5, 6, 7	<p>HPE Aruba Networking 6300F 48p 10M/100M/1G Class4 PoE 4p SFP56 50G TAA Switch</p> <ul style="list-style-type: none"> <li>• HPE Aruba Networking 6300F 48-port 1GbE Class 4 PoE and 4-port SFP56 TAA Switch</li> <li>• Includes Non-Pluggable, Internal PSU behind sheetmetal Chassis Frame</li> <li>• Includes Non-Pluggable, Internal Fans behind sheetmetal Chassis Frame</li> <li>• Min=0 \ Max = 4 SFP/SFP+/SFP28/SFP56 1/10/25/50G Transceiver</li> <li>• 1U - Height</li> </ul> <p>HPE Aruba Networking 6300F 48p 10M/100M/1G Class4 PoE 4p SFP56 50G TAA PDU Switch</p> <ul style="list-style-type: none"> <li>• C15 PDU Jumper Cord (NA/MEX/TW/JP) (J9943A)</li> </ul> <p>HPE Aruba Networking 6300F 48p 10M/100M/1G Class4 PoE 4p SFP56 50G TAA PDU Switch</p> <ul style="list-style-type: none"> <li>• C15 PDU Jumper Cord (ROW) (J9944A)</li> </ul> <p>HPE Aruba Networking 6300F 48p 10M/100M/1G Class4 PoE 4p SFP56 50G TAA 220v Switch</p> <ul style="list-style-type: none"> <li>• HPE 2.5m C15 to NEMA 6-20P Pwr Cord(JL336A)</li> </ul> <p>HPE Aruba Networking 6300F 48p 10M/100M/1G Class4 PoE 4p SFP56 50G TAA Switch No Loc</p> <ul style="list-style-type: none"> <li>• No Localized Power Cord Selected. Use J9955A to obtain a Locking Plug Power Cord (L6-20P)</li> </ul>	SOG95A  SOG95A#B2B  SOG95A#B2C  SOG95A#B2E  SOG95A#AC3
1, 2, 3, 4, 5, 6, 7	<p>HPE Aruba Networking 6300F 24p 10M/100M/1G Class4 PoE 4p SFP56 50G TAA Switch</p> <ul style="list-style-type: none"> <li>• HPE Aruba Networking 6300F 24-port 1GbE Class 4 PoE and 4-port SFP56 TAA Switch</li> <li>• Includes Non-Pluggable, Internal PSU behind sheetmetal Chassis Frame</li> <li>• Includes Non-Pluggable, Internal Fans behind sheetmetal Chassis Frame</li> <li>• Min=0 \ Max = 4 SFP/SFP+/SFP28/SFP56 1/10/25/50G Transceiver</li> <li>• 1U - Height</li> </ul> <p>HPE Aruba Networking 6300F 24p 10M/100M/1G Class4 PoE 4p SFP56 50G TAA PDU Switch</p> <ul style="list-style-type: none"> <li>• C15 PDU Jumper Cord (NA/MEX/TW/JP) (J9943A)</li> </ul> <p>HPE Aruba Networking 6300F 24p 10M/100M/1G Class4 PoE 4p SFP56 50G TAA PDU Switch</p> <ul style="list-style-type: none"> <li>• C15 PDU Jumper Cord (ROW) (J9944A)</li> </ul>	SOG96A  SOG96A#B2B  SOG96A#B2C

## Configuration Information

	HPE Aruba Networking 6300F 24p 10M/100M/1G Class4 PoE 4p SFP56 50G TAA 220v Switch	SOG96A#B2E
	<ul style="list-style-type: none"> <li>HPE 2.5m C15 to NEMA 6-20P Pwr Cord(JL336A)</li> </ul>	
	HPE Aruba Networking 6300F 24p 10M/100M/1G Class4 PoE 4p SFP56 50G TAA Switch No Loc	SOG96A#AC3
	<ul style="list-style-type: none"> <li>No Localized Power Cord Selected. Use J9955A to obtain a Locking Plug Power Cord (L6-20P)</li> </ul>	
1, 2, 3, 4, 5, 6, 7	HPE Aruba Networking 6300F 48p 10M/100M/1G 4p SFP56 50G TAA Switch	SOG97A
	<ul style="list-style-type: none"> <li>HPE Aruba Networking 6300F 48-port 1GbE and 4-port SFP56 TAA Switch</li> <li>Includes Non-Pluggable, Internal PSU behind sheetmetal Chassis Frame</li> <li>Includes Non-Pluggable, Internal Fans behind sheetmetal Chassis Frame</li> <li>Min=0 \ Max = 4 SFP/SFP+/SFP28/SFP56 1/10/25/50G Transceiver</li> <li>1U - Height</li> </ul>	
	HPE Aruba Networking 6300F 48p 10M/100M/1G 4p SFP56 50G TAA PDU Switch	SOG97A#B2B
	<ul style="list-style-type: none"> <li>C13 PDU Jumper Cord (NA/MEX/TW/JP)</li> </ul>	
	HPE Aruba Networking 6300F 48p 10M/100M/1G 4p SFP56 50G TAA PDU Switch	SOG97A#B2C
	<ul style="list-style-type: none"> <li>C13 PDU Jumper Cord (ROW)</li> </ul>	
	HPE Aruba Networking 6300F 48p 10M/100M/1G 4p SFP56 50G TAA 220v Switch	SOG97A#B2E
	<ul style="list-style-type: none"> <li>HPE 2.3m C13 to NEMA 6-15P Pwr Cord(J9936A)</li> </ul>	
	HPE Aruba Networking 6300F 48p 10M/100M/1G 4p SFP56 50G TAA Switch No Loc	SOG97A#AC3
	<ul style="list-style-type: none"> <li>No Localized Power Cord Selected. Use J9955A to obtain a Locking Plug Power Cord (L6-20P)</li> </ul>	
1, 2, 3, 4, 5, 6, 7	HPE Aruba Networking 6300F 24p 10M/100M/1G 4p SFP56 50G TAA Switch	SOG98A
	<ul style="list-style-type: none"> <li>HPE Aruba Networking 6300F 24-port 1GbE and 4-port SFP56 TAA Switch</li> <li>Includes Non-Pluggable, Internal PSU behind sheetmetal Chassis Frame</li> <li>Includes Non-Pluggable, Internal Fans behind sheetmetal Chassis Frame</li> <li>Min=0 \ Max = 4 SFP/SFP+/SFP28/SFP56 1/10/25/50G Transceiver</li> <li>1U - Height</li> </ul>	
	HPE Aruba Networking 6300F 24p 10M/100M/1G 4p SFP56 50G TAA PDU Switch	SOG98A#B2B
	<ul style="list-style-type: none"> <li>C13 PDU Jumper Cord (NA/MEX/TW/JP)</li> </ul>	
	HPE Aruba Networking 6300F 24p 10M/100M/1G 4p SFP56 50G TAA PDU Switch	SOG98A#B2C
	<ul style="list-style-type: none"> <li>C13 PDU Jumper Cord (ROW)</li> </ul>	
	HPE Aruba Networking 6300F 24p 10M/100M/1G 4p SFP56 50G TAA 220v Switch	SOG98A#B2E
	<ul style="list-style-type: none"> <li>HPE 2.3m C13 to NEMA 6-15P Pwr Cord(J9936A)</li> </ul>	
	HPE Aruba Networking 6300F 24p 10M/100M/1G 4p SFP56 50G TAA Switch No Loc	SOG98A#AC3
	<ul style="list-style-type: none"> <li>No Localized Power Cord Selected. Use J9955A to obtain a Locking Plug Power Cord (L6-20P)</li> </ul>	

### HPE Aruba Networking CX 6300F

Rule #	Description	SKU
1, 2, 3, 4, 5, 6, 7	HPE Aruba Networking CX 6300F 48-port 1GbE Class 4 PoE and 4-port SFP56 Switch	JL665A
	<ul style="list-style-type: none"> <li>Includes Non-Pluggable, Internal PSU behind sheetmetal Chassis Frame</li> <li>Includes Non-Pluggable, Internal Fans behind sheetmetal Chassis Frame</li> <li>Min=0 \ Max = 4 SFP/SFP+/SFP28/SFP56 1/10/25/50G Transceiver</li> <li>1U - Height</li> </ul>	
	HPE Aruba Networking CX 6300F 48-port 1GbE Class 4 PoE and 4-port SFP56 Switch PDU	JL665A#B2B
	<ul style="list-style-type: none"> <li>C15 PDU Jumper Cord (NA/MEX/TW/JP) (J9943A)</li> </ul>	
	HPE Aruba Networking CX 6300F 48-port 1GbE Class 4 PoE and 4-port SFP56 Switch PDU	JL665A#B2C
	<ul style="list-style-type: none"> <li>C15 PDU Jumper Cord (ROW) (J9944A)</li> </ul>	

## Configuration Information

	HPE Aruba Networking CX 6300F 48-port 1GbE Class 4 PoE and 4-port SFP56 Switch 220v	JL665A#B2E
	<ul style="list-style-type: none"> <li>• HPE 2.5m C15 to NEMA 6-20P Pwr. Cord (JL336A)</li> </ul>	
	HPE Aruba Networking CX 6300F 48-port 1GbE Class 4 PoE and 4-port SFP56 Switch NoLoc	JL665A#AC3
	<ul style="list-style-type: none"> <li>• No Localized Power Cord Selected. Use J9955A to obtain a Locking Plug Power Cord (L6-20P)</li> </ul>	
1, 2, 3, 4, 5, 6, 7	HPE Aruba Networking CX 6300F 24-port 1GbE Class 4 PoE and 4-port SFP56 Switch	JL666A
	<ul style="list-style-type: none"> <li>• Includes Non-Pluggable, Internal PSU behind sheetmetal Chassis Frame</li> <li>• Includes Non-Pluggable, Internal Fans behind sheetmetal Chassis Frame</li> <li>• Min=0 \ Max = 4 SFP/SFP+/SFP28/SFP56 1/10/25/50G Transceiver</li> <li>• 1U - Height</li> </ul>	
	HPE Aruba Networking CX 6300F 24-port 1GbE Class 4 PoE and 4-port SFP56 Switch PDU	JL666A#B2B
	<ul style="list-style-type: none"> <li>• C15 PDU Jumper Cord (NA/MEX/TW/JP) (J9943A)</li> </ul>	
	HPE Aruba Networking CX 6300F 24-port 1GbE Class 4 PoE and 4-port SFP56 Switch PDU	JL666A#B2C
	<ul style="list-style-type: none"> <li>• C15 PDU Jumper Cord (ROW) (J9944A)</li> </ul>	
	HPE Aruba Networking CX 6300F 24-port 1GbE Class 4 PoE and 4-port SFP56 Switch 220v	JL666A#B2E
	<ul style="list-style-type: none"> <li>• HPE 2.5m C15 to NEMA 6-20P Pwr. Cord (JL336A)</li> </ul>	
	HPE Aruba Networking CX 6300F 24-port 1GbE Class 4 PoE and 4-port SFP56 Switch NoLoc	JL666A#AC3
	<ul style="list-style-type: none"> <li>• No Localized Power Cord Selected. Use J9955A to obtain a Locking Plug Power Cord (L6-20P)</li> </ul>	
1, 2, 3, 4, 5, 6, 7	HPE Aruba Networking CX 6300F 48-port 1GbE and 4-port SFP56 Switch	JL667A
	<ul style="list-style-type: none"> <li>• Includes Non-Pluggable, Internal PSU behind sheetmetal Chassis Frame</li> <li>• Includes Non-Pluggable, Internal Fans behind sheetmetal Chassis Frame</li> <li>• Min=0 \ Max = 4 SFP/SFP+/SFP28/SFP56 1/10/25/50G Transceiver</li> <li>• 1U - Height</li> </ul>	
	HPE Aruba Networking CX 6300F 48-port 1GbE and 4-port SFP56 Switch PDU	JL667A#B2B
	<ul style="list-style-type: none"> <li>• C13 PDU Jumper Cord (NA/MEX/TW/JP)</li> </ul>	
	HPE Aruba Networking CX 6300F 48-port 1GbE and 4-port SFP56 Switch PDU	JL667A#B2C
	<ul style="list-style-type: none"> <li>• C13 PDU Jumper Cord (ROW)</li> </ul>	
	HPE Aruba Networking CX 6300F 48-port 1GbE and 4-port SFP56 Switch 220v	JL667A#B2E
	<ul style="list-style-type: none"> <li>• HPE 2.3m C13 to NEMA 6-15P Pwr. Cord (J9936A)</li> </ul>	
	HPE Aruba Networking CX 6300F 48-port 1GbE and 4-port SFP56 Switch NoLoc	JL667A#AC3
	<ul style="list-style-type: none"> <li>• No Localized Power Cord Selected. Use J9955A to obtain a Locking Plug Power Cord (L6-20P)</li> </ul>	
1, 2, 3, 4, 5, 6, 7	HPE Aruba Networking CX 6300F 24-port 1GbE and 4-port SFP56 Switch	JL668A
	<ul style="list-style-type: none"> <li>• Includes Non-Pluggable, Internal PSU behind sheetmetal Chassis Frame</li> <li>• Includes Non-Pluggable, Internal Fans behind sheetmetal Chassis Frame</li> <li>• Min=0 \ Max = 4 SFP/SFP+/SFP28/SFP56 1/10/25/50G Transceiver</li> <li>• 1U - Height</li> </ul>	
	HPE Aruba Networking CX 6300F 24-port 1GbE and 4-port SFP56 Switch PDU	JL668A#B2B
	<ul style="list-style-type: none"> <li>• C13 PDU Jumper Cord (NA/MEX/TW/JP)</li> </ul>	
	HPE Aruba Networking CX 6300F 24-port 1GbE and 4-port SFP56 Switch PDU	JL668A#B2C
	<ul style="list-style-type: none"> <li>• C13 PDU Jumper Cord (ROW)</li> </ul>	
	HPE Aruba Networking CX 6300F 24-port 1GbE and 4-port SFP56 Switch 220v	JL668A#B2E
	<ul style="list-style-type: none"> <li>• HPE 2.3m C13 to NEMA 6-15P Pwr. Cord (J9936A)</li> </ul>	
	HPE Aruba Networking CX 6300F 24-port 1GbE and 4-port SFP56 Switch NoLoc	JL668A#AC3

## Configuration Information

- No Localized Power Cord Selected. Use J9955A to obtain a Locking Plug Power Cord (L6-20P)

### HPE Aruba Networking CX 6300F

2, 3, 4, 6	HPE Aruba Networking 6300L 24p Smart Rate 1G/2.5G/5G/10G CL6 2p SFP56 50G 2p SFP28 25G L2 Switch	<b>S3L75A</b>
	<ul style="list-style-type: none"> <li>HPE Aruba Networking 6300L 24p Smart Rate 1G/2.5G/5G/10G Class6 PoE 2p 50G and 2p 25G L2 Switch</li> <li>Must Select PSU Min1 / Max2 (680W JL086A,1050W JL087A, 1600W JL670A, 1050W JL758A) Mix OK</li> <li>Includes Fantrays Min2 / Max 2 (JL669B)</li> <li>Min=0 \ Max = 2 SFP+/SFP28/SFP56 10/25/50G Transceiver (Ports 25/26)</li> <li>Min=0 \ Max = 2 SFP+ or 2 SFP28 10/25 Transceiver (Ports 27/28)</li> <li>1U - Height</li> </ul>	
2, 3, 4, 6	HPE Aruba Networking 6300L 48p Smart Rate 100M/1G/2.5G/5G CL8 2p SFP56 50G 2p SFP28 25G L2 Switch	<b>S3L76A</b>
	<ul style="list-style-type: none"> <li>HPE Aruba Networking 6300L 48p Smart Rate 1G/2.5G/5G Class8 PoE 2p 50G and 2p 25G L2 Switch</li> <li>Must Select PSU Min1 / Max2 (680W JL086A,1050W JL087A, 1600W JL670A, 1050W JL758A) Mix OK</li> <li>Includes Fantrays Min2 / Max 2 (JL669B)</li> <li>Min=0 \ Max = 2 SFP+/SFP28/SFP56 10/25/50G Transceiver (Ports 49/50)</li> <li>Min=0 \ Max = 2 SFP+ or 2 SFP28 10/25 Transceiver (Ports 51/52)</li> <li>1U - Height</li> </ul>	
1, 2, 3, 4, 6, 9	HPE ANW 6300L 48p Smart Rate 100M/1G/2.5G/5G Class6/8 2p SFP56 50G 2p SFP+ 1G/10G LRM Layer2 Sw	<b>S3L77A</b>
	<ul style="list-style-type: none"> <li>HPE Aruba Networking 6300L 48p Smart Rate 1G/2.5G/5G Class8/6 PoE 2p 50G and 2p 10G LRM L2 Switch</li> <li>Must Select PSU Min1 / Max2 (680W JL086A,1050W JL087A, 1600W JL670A, 1050W JL758A) Mix OK</li> <li>Includes Fantrays Min2 / Max 2 (JL669B)</li> <li>Min=0 \ Max = 2 SFP+/SFP28/SFP56 10/25/50G Transceiver (Ports 49/50)</li> <li>Min=0 \ Max = 2 SFP or 2 SFP+ 1/10 Transceiver (LRM Supported) (Ports 51/52)</li> <li>1U - Height</li> </ul>	

### Configuration Rules

Rule #	Description	SKU
1	The following Transceivers install into this Switch (Use #0D1 quoted to switch if switch is CTO) - if applicable: HPE Aruba Networking 100M SFP LC FX 2km MMF Transceiver	J9054D
<b>Notes:</b>	<b>Not supported in the SFP56 Ports</b> HPE Aruba Networking 1G SFP LC SX 500m OM2 MMF Transceiver HPE Aruba Networking 1G SFP LC LX 10km SMF Transceiver HPE Aruba Networking 1G SFP LC LH 70km SMF Transceiver HPE Aruba Networking 1G SFP RJ45 T 100m Cat5e Transceiver HPE Aruba Networking 1G SFP LC SX 500m MMF TAA Transceiver HPE Aruba Networking 1G SFP LC LX 10km SMF TAA Transceiver HPE Aruba Networking 1G SFP RJ45 T 100m Cat5e TAA Transceiver	J4858D J4859D J4860D J8177D JL745A JL746A JL747A
2	The following Transceivers install into this Switch (Use #0D1 quoted to switch if switch is CTO) - if applicable: HPE Aruba Networking 10GBASE-T SFP+ RJ45 30m Cat6A Transceiver HPE Aruba Networking 10GBASE-T SFP+ RJ45 30m Cat6A Transceiver	JL563B JL563C

## Configuration Information

HPE Aruba Networking 10G SFP+ LC SR 300m OM3 MMF Transceiver	J9150D
HPE Aruba Networking 10G SFP+ LC LR 10km SMF Transceiver	J9151E
HPE Aruba Networking 10G SFP+ LC ER 40km SMF Transceiver	J9153D
HPE Aruba Networking 10G SFP+ LC SR 300m MMF TAA Transceiver	JL748A
HPE Aruba Networking 10G SFP+ LC LR 10km SMF TAA Transceiver	JL749A
HPE Aruba Networking 10G SMF Simplex LC BiDi 40km-Downstream 1330/1270 Transceiver	R9X54A
HPE Aruba Networking 10G SMF Simplex LC BiDi 40km-Upstream 1270/1330 Transceiver	R9X55A
HPE Aruba Networking 10G SR SFP+ LC 400m OM4 MMF C-Class Transceiver	S2P30A
HPE Aruba Networking 10G LR SFP+ LC 10km SMF C-Class Transceiver	S2P31A
HPE Aruba Networking 10G ER SFP+ LC 40km SMF C-Class Transceiver	S2P32A
HPE Aruba Networking 10G SFP+ to SFP+ 1m Direct Attach Copper Cable	J9281D
HPE Aruba Networking 10G SFP+ to SFP+ 3m Direct Attach Copper Cable	J9283D

### 3 The following Transceivers install into this Switch (Use #0D1 quoted to switch if switch is CTO) - if applicable:

HPE Aruba Networking 25G ER LC 40km SMF Transceiver	SOV69A
HPE Aruba Networking 25G BiDi 10km-Downstream 1330/1270 Transceiver	S1C96A
HPE Aruba Networking 25G BiDi 10km-Upstream 1270/1330 Transceiver	S1C98A
HPE Aruba Networking 25G SFP28 LC SR 100m MMF Transceiver	JL484A
HPE Aruba Networking 25G SFP28 LC eSR 400m MMF Transceiver	JL485A
HPE Aruba Networking 25G SFP28 LC LR 10km SMF Transceiver	JL486A
HPE Aruba Networking 25G SR SFP28 LC 100m MMF C-Class Transceiver	S2P33A
HPE Aruba Networking 25G LR SFP28 LC 10km SMF C-Class Transceiver	S2P34A
HPE Aruba Networking 25G SFP28 to SFP28 0.65m Direct Attach Cable	JL487A
HPE Aruba Networking 25G SFP28 to SFP28 3m Direct Attach Copper Cable	JL488A
HPE Aruba Networking 25G SFP28 to SFP28 5m Direct Attach Copper Cable	JL489A
HPE Aruba Networking 25G SFP28 to SFP28 3m Active Optical Cable	ROM44A
HPE Aruba Networking 25G SFP28 to SFP28 7m Active Optical Cable	ROM45A
HPE Aruba Networking 25G SFP28 to SFP28 15m Active Optical Cable	ROZ21A

### 4 The following Transceivers install into this Switch (Use #0D1 quoted to switch if switch is CTO) - if applicable:

HPE Aruba Networking 50G eSR 300m MMF Transceiver	SOV64A
HPE Aruba Networking 50G LR 10km SMF Transceiver	SOV65A
HPE Aruba Networking 50G ER 40km SMF Transceiver	SOV66A
HPE Aruba Networking 50G BiDi 10km-Downstream 1330/1270 Transceiver	S1C92A
HPE Aruba Networking 50G BiDi 10km-Upstream 1270/1330 Transceiver	S1C94A
HPE Aruba Networking 50G SFP56 LC SR 100m MMF Transceiver	ROM48A
HPE Aruba Networking 50G SFP56 to SFP56 0.65m Direct Attach Copper Cable	ROM46A
HPE Aruba Networking 50G SFP56 to SFP56 3m Direct Attach Copper Cable	ROM47A
HPE Aruba Networking 50G QSFP56 to SFP56 0.65m DAC Cable	S1J07A
HPE Aruba Networking 50G QSFP56 to SFP56 3m DAC Cable	S1J08A

### 5 Localization required on orders without #B2B, #B2C, #B2E or #AC3 options.

### 6 If the CTO Switch Chassis needs to be racked, Then the CTO Base Model needs to integrate (with #0D1) to the HPE Network Rack.

### 7 When Switches are Factory Racked with this power supply, Then B2B, or B2C should be the Defaulted Power Cable option on the Power Supplies. (See Drop down remark in "Internal Power Supplies" section.)

### 8 The following Transceivers install into this Switch: (Use 0D1 quoted to switch if switch is CTO) - if applicable:



## Configuration Information

- 9 The following Transceivers install into this Switch and is only available on LRM Supported ports. See AOS-Switch and AOS-CX Transceiver Guide (Edition 12) for port compatibility: (Use BTO only when adding to switch) (Use OD1 quoted to switch if switch is CTO) - if applicable:  
HPE Aruba Networking 10G SFP+ LC LRM 220m OM2 MMF Transceiver J9152D
- 10 The following Transceivers install into this Switch using QSFP56 side of cable(Use OD1 quoted to switch if switch is CTO) - if applicable:
- 11 If qty1 of the following QSA28 Adapter(845970-B21) is selected, then increase max SFP28 Port qty by 1 and allow user selection of the following SFP Transceivers. Refer to qty and port restrictions for individual Switch in the "Additional Info" sections: (Use BTO only when adding to switch)
- HPE Aruba Networking 10G SFP+ LC SR 300m OM3 MMF Transceiver J9150D  
HPE Aruba Networking 10G SFP+ LC LR 10km SMF Transceiver J9151E  
HPE Aruba Networking 10G SFP+ LC ER 40km SMF Transceiver J9153D  
HPE Aruba Networking 10G SFP+ LC SR 300m MMF TAA Transceiver JL748A  
HPE Aruba Networking 10G SFP+ LC LR 10km SMF TAA Transceiver JL749A  
HPE Aruba Networking 25G SFP28 LC SR 100m MMF Transceiver JL484A  
HPE Aruba Networking 25G SFP28 LC eSR 400m MMF Transceiver JL485A  
HPE Aruba Networking 25G SFP28 LC LR 10km SMF Transceiver JL486A  
HPE Aruba Networking 25G ER LC 40km SMF Transceiver SOV69A  
HPE Aruba Networking 25G BiDi 10km-Downstream 1330/1270 Transceiver S1C96A  
HPE Aruba Networking 25G BiDi 10km-Upstream 1270/1330 Transceiver S1C98A  
HPE Aruba Networking 25G SFP28 to SFP28 3m Active Optical Cable ROM44A  
HPE Aruba Networking 25G SFP28 to SFP28 7m Active Optical Cable ROM45A  
HPE Aruba Networking 25G SFP28 to SFP28 15m Active Optical Cable ROZ21A
- 12 The following Transceivers install into this Switch: (Use BTO only when adding to switch)
- HPE Aruba Networking 100G SR2 MPO QSFP28 100m MMF Transceiver S1C93A  
HPE QSFP28 to SFP28 Adapter 845970-B21  
HPE Aruba Networking 100G QSFP28 LC CWDM4 2km SMF Transceiver ROZ30A  
HPE Aruba Networking 100G QSFP28 LC LR4 10km SMF 2-strand Transceiver JL310A  
HPE Aruba Networking 100G QSFP28 MPO SR4 100m 12-fiber MPO OM3 MMF Transceiver JL309A  
HPE Aruba Networking 100G QSFP28 LC ER4L 40km SMF Transceiver JL743A  
HPE Aruba Networking 100G QSFP28 LC FR1 SMF 2km Transceiver R9B63A  
HPE Aruba Networking 100G QSFP28 to QSFP28 3m Direct Attach Copper Cable JL307A  
HPE Aruba Networking 100G QSFP28 to QSFP28 1m Direct Attach Copper Cable ROZ25A  
HPE Aruba Networking 100G QSFP28 to QSFP28 5m Direct Attach Copper Cable ROZ26A  
HPE Aruba Networking 100G QSFP28 to QSFP28 2m Active Optical Cable JL856A  
HPE Aruba Networking 100G QSFP28 to QSFP28 7m Active Optical Cable ROZ27A  
HPE Aruba Networking 100G QSFP28 to QSFP28 15m Active Optical Cable ROZ28A  
HPE Aruba Networking 100G QSFP28 to QSFP28 30m Active Optical Cable ROZ29A
- 13 The following Transceivers install into this Switch(Use BTO only when adding to switch)
- HPE Networking X142 40G QSFP+ MPO SR4 Transceiver JH231A  
HPE Networking X142 40G QSFP+ LC LR4 SM Transceiver JH232A  
HPE Networking X142 40G QSFP+ MPO eSR4 300M Transceiver JH233A  
HPE Aruba Networking 40G QSFP+ LC Bidirectional 150m MMF 2-strand Transceiver JL308A  
HPE Aruba Networking 40G QSFP+ LC ER4 40km SMF Transceiver Q9G82A  
HPE Networking X242 40G QSFP+ to QSFP+ 1m Direct Attach Copper Cable JH234A  
HPE Networking X242 40G QSFP+ to QSFP+ 3m Direct Attach Copper Cable JH235A  
HPE Networking X242 40G QSFP+ to QSFP+ 5m Direct Attach Copper Cable JH236A  
HPE Aruba Networking 40G QSFP+ to QSFP+ 7m Active Optical Cable ROZ22A  
HPE Aruba Networking 40G QSFP+ to QSFP+ 15m Active Optical Cable ROZ23A



## Configuration Information

	HPE Aruba Networking 40G QSFP+ to QSFP+ 30m Active Optical Cable	R0Z24A
14	The following Transceivers install into this Switch(Use BTO only when adding to switch)	
	HPE Aruba Networking 25G LR SFP28 LC 10km SMF TAA Transceiver	S2N63A
<b>Notes:</b>	<ul style="list-style-type: none"> <li>- Drop down under power supply should offer the following options and results:             <ul style="list-style-type: none"> <li>o Switch/Router/Power Supply to PDU Power Cord - #B2B in North America, Mexico, Taiwan, and Japan or #B2C ROW. (OCA Default B2B or B2C for Rack Level CTO)</li> <li>o Switch/Router/Power Supply to Wall Power Cord - Localized Option (OCA Default for BTO)</li> <li>o High Volt Switch/Router/Power Supply to Wall Power Cord - B2E Option. (Offered only in North America, Mexico, Taiwan, and Japan)</li> <li>o No Power Cord - #AC3 Option</li> </ul> </li> <li>- Locking Power Cord (J9955A) L6-20P is available through the OCA Accessories tab</li> </ul>	

## Transceivers

Remarks:	Description	SKU
	<b>SFP Transceivers</b>	
	HPE Aruba Networking 100M SFP LC FX 2km MMF Transceiver	J9054D
<b>Notes:</b>	Not supported on SFP56 Ports	
	HPE Aruba Networking 1G SFP LC SX 500m OM2 MMF Transceiver	J4858D
	HPE Aruba Networking 1G SFP LC LX 10km SMF Transceiver	J4859D
	HPE Aruba Networking 1G SFP LC LH 70km SMF Transceiver	J4860D
	HPE Aruba Networking 1G SFP RJ45 T 100m Cat5e Transceiver	J8177D
	HPE Aruba Networking 1G SFP LC SX 500m MMF TAA Transceiver	JL745A
	HPE Aruba Networking 1G SFP LC LX 10km SMF TAA Transceiver	JL746A
	HPE Aruba Networking 1G SFP RJ45 T 100m Cat5e TAA Transceiver	JL747A
	<b>SFP+ Transceivers</b>	
	HPE Aruba Networking 10GBASE-T SFP+ RJ45 30m Cat6A Transceiver	JL563B
	<ul style="list-style-type: none"> <li>• Not compatible with COTA(S0E91A, SOX44A)</li> </ul>	
	HPE Aruba Networking 10GBASE-T SFP+ RJ45 30m Cat6A Transceiver	JL563C
	HPE Aruba Networking 10G SFP+ LC SR 300m OM3 MMF Transceiver	J9150D
	HPE Aruba Networking 10G SFP+ LC LR 10km SMF Transceiver	J9151E
	HPE Aruba Networking 10G SFP+ LC ER 40km SMF Transceiver	J9153D
	HPE Aruba Networking 10G SFP+ LC SR 300m MMF TAA Transceiver	JL748A
	HPE Aruba Networking 10G SFP+ LC LR 10km SMF TAA Transceiver	JL749A
	HPE Aruba Networking 10G SR SFP+ LC 400m OM4 MMF C-Class Transceiver	S2P30A
	HPE Aruba Networking 10G LR SFP+ LC 10km SMF C-Class Transceiver	S2P31A
	HPE Aruba Networking 10G ER SFP+ LC 40km SMF C-Class Transceiver	S2P32A
	HPE Aruba Networking 10G SFP+ to SFP+ 1m Direct Attach Copper Cable	J9281D
	<ul style="list-style-type: none"> <li>• Not compatible with COTA(S0E91A, SOX44A)</li> </ul>	
	HPE Aruba Networking 10G SFP+ to SFP+ 3m Direct Attach Copper Cable	J9283D
	<ul style="list-style-type: none"> <li>• Not compatible with COTA(S0E91A, SOX44A)</li> </ul>	
	<b>SFP28 Transceivers</b>	
	HPE Aruba Networking 25G ER LC 40km SMF Transceiver	S0V69A
	<ul style="list-style-type: none"> <li>• All models/Ports that support 25G</li> <li>• NOT R8S91A: 51-52</li> <li>• COTA: YES thru QSA28 (Min0-Max4)</li> </ul>	
	HPE Aruba Networking 25G BiDi 10km-Downstream 1330/1270 Transceiver	S1C96A
	<ul style="list-style-type: none"> <li>• All models/Ports that support 25G</li> <li>• NOT R8S91A: 51-52</li> </ul>	

## Configuration Information

- COTA: YES thru QSA28 (Min0-Max4)

HPE Aruba Networking 25G BiDi 10km-Upstream 1270/1330 Transceiver	S1C98A
<ul style="list-style-type: none"> <li>• All models/Ports that support 25G</li> <li>• NOT R8S91A: 51-52</li> <li>• COTA: YES thru QSA28 (Min0-Max4)</li> </ul>	
HPE Aruba Networking 25G SFP28 LC SR 100m MMF Transceiver	JL484A
HPE Aruba Networking 25G SFP28 LC eSR 400m MMF Transceiver	JL485A
HPE Aruba Networking 25G LR SFP28 LC 10km SMF TAA Transceiver	S2N63A
HPE Aruba Networking 25G SFP28 LC LR 10km SMF Transceiver	JL486A
HPE Aruba Networking 25G SR SFP28 LC 100m MMF C-Class Transceiver	S2P33A
HPE Aruba Networking 25G LR SFP28 LC 10km SMF C-Class Transceiver	S2P34A
HPE Aruba Networking 25G SFP28 to SFP28 0.65m Direct Attach Cable	JL487A
HPE Aruba Networking 25G SFP28 to SFP28 3m Direct Attach Copper Cable	JL488A
HPE Aruba Networking 25G SFP28 to SFP28 5m Direct Attach Copper Cable	JL489A
HPE Aruba Networking 25G SFP28 to SFP28 3m Active Optical Cable	ROM44A
HPE Aruba Networking 25G SFP28 to SFP28 7m Active Optical Cable	ROM45A
HPE Aruba Networking 25G SFP28 to SFP28 15m Active Optical Cable	ROZ21A

### QSFP + Transceivers

HPE Networking X142 40G QSFP+ MPO SR4 Transceiver	JH231A
HPE Networking X142 40G QSFP+ LC LR4 SM Transceiver	JH232A
HPE Networking X142 40G QSFP+ MPO eSR4 300M Transceiver	JH233A
HPE Aruba Networking 40G QSFP+ LC Bidirectional 150m MMF 2-strand Transceiver	JL308A
HPE Aruba Networking 40G QSFP+ LC ER4 40km SMF Transceiver	Q9G82A
HPE Networking X242 40G QSFP+ to QSFP+ 1m Direct Attach Copper Cable	JH234A
HPE Networking X242 40G QSFP+ to QSFP+ 3m Direct Attach Copper Cable	JH235A
HPE Networking X242 40G QSFP+ to QSFP+ 5m Direct Attach Copper Cable	JH236A
HPE Aruba Networking 40G QSFP+ to QSFP+ 7m Active Optical Cable	ROZ22A
HPE Aruba Networking 40G QSFP+ to QSFP+ 15m Active Optical Cable	ROZ23A
HPE Aruba Networking 40G QSFP+ to QSFP+ 30m Active Optical Cable	ROZ24A

**Notes:** [Only COTA ports 49-52 \(Min0-Max4\)](#)

### SFP56 Transceivers

HPE Aruba Networking 50G eSR 300m MMF Transceiver	SOV64A
<ul style="list-style-type: none"> <li>• All models/Ports that support 50G</li> <li>• NOT R8S91A: 51-52</li> <li>• NO Cota models</li> </ul>	
HPE Aruba Networking 50G LR 10km SMF Transceiver	SOV65A
<ul style="list-style-type: none"> <li>• All models/Ports that support 50G</li> <li>• NOT R8S91A: 51-52</li> <li>• NO Cota models</li> </ul>	
HPE Aruba Networking 50G ER 40km SMF Transceiver	SOV66A
<ul style="list-style-type: none"> <li>• All models/Ports that support 50G</li> <li>• NOT R8S91A: 51-52</li> <li>• NO Cota models</li> </ul>	
HPE Aruba Networking 50G BiDi 10km-Downstream 1330/1270 Transceiver	S1C92A
<ul style="list-style-type: none"> <li>• All models/Ports that support 50G</li> <li>• NOT R8S91A: 51-52</li> <li>• NO Cota models</li> </ul>	



## Configuration Information

HPE Aruba Networking 50G BiDi 10km-Upstream 1270/1330 Transceiver S1C94A

- All models/Ports that support 50G
- NOT R8S91A: 51-52
- NO Cota models

HPE Aruba Networking 50G SFP56 to SFP56 0.65m Direct Attach Copper Cable ROM46A

- Not supported on SFP

HPE Aruba Networking 50G SFP56 to SFP56 3m Direct Attach Copper Cable ROM47A

HPE Aruba Networking 50G SFP56 LC SR 100m MMF Transceiver ROM48A

HPE Aruba Networking 50G QSFP56 to SFP56 0.65m DAC Cable S1J07A

HPE Aruba Networking 50G QSFP56 to SFP56 3m DAC Cable S1J08A

### QSFP28 Transceivers

HPE Aruba Networking 100G SR2 MPO QSFP28 100m MMF Transceiver S1C93A

HPE 100Gb QSFP28 Bidirectional Transceiver 845972-B21

HPE Aruba Networking 100G QSFP28 LC CWDM4 2km SMF Transceiver ROZ30A

HPE Aruba Networking 100G QSFP28 LC LR4 10km SMF 2-strand Transceiver JL310A

HPE Aruba Networking 100G QSFP28 MPO SR4 100m 12-fiber MPO OM3 MMF Transceiver JL309A

HPE Aruba Networking 100G QSFP28 LC ER4L 40km SMF Transceiver JL743A

HPE Aruba Networking 100G QSFP28 LC FR1 SMF 2km Transceiver R9B63A

HPE Aruba Networking 100G QSFP28 to QSFP28 3m Direct Attach Copper Cable JL307A

HPE Aruba Networking 100G QSFP28 to QSFP28 1m Direct Attach Copper Cable ROZ25A

HPE Aruba Networking 100G QSFP28 to QSFP28 5m Direct Attach Copper Cable ROZ26A

HPE Aruba Networking 100G QSFP28 to QSFP28 2m Active Optical Cable JL856A

HPE Aruba Networking 100G QSFP28 to QSFP28 7m Active Optical Cable ROZ27A

HPE Aruba Networking 100G QSFP28 to QSFP28 15m Active Optical Cable ROZ28A

HPE Aruba Networking 100G QSFP28 to QSFP28 30m Active Optical Cable ROZ29A

**Notes:** Only COTA ports 49-52 (Min0-Max4)

### QSFP56 Transceivers

HPE Aruba Networking 50G QSFP56 to SFP56 0.65m DAC Cable S1J07A

HPE Aruba Networking 50G QSFP56 to SFP56 3m DAC Cable S1J08A

**Notes:** Only COTA ports 49-52 (Min0-Max4)

### Transceivers for LRM Adapter

HPE Aruba Networking 10G SFP+ LC LRM 220m OM2 MMF Transceiver J9152D

**Notes:** Compatible on LRM supported ports for R8S91A and R8S92A

### QSA28 Adapter

1 HPE QSFP28 to SFP28 Adapter 845970-B21

### Configuration Rules

**Rule # Description**

**OCA Display Notes:**

If selecting the 845970-B21 - QSFP28 to SFP28 Adapter, then see Aruba Transceiver Guide for details.

## Power Supplies

System (std 0 // max 2) User Selection (min 1 // max 2) per enclosure

JL762A, SOGO2A System (std 1 // max 2) User Selection (min 0 // max 1) per enclosure

**Rule # Description SKU**

1, 3 HPE Aruba Networking X372 54VDC 1600W 110-240VAC Power Supply JL670A

- Uses 1 x C15, 1600w

## Configuration Information

	HPE Aruba Networking X372 54VDC 1600W 110-240VAC Power Supply PDU	JL670A#B2B
	<ul style="list-style-type: none"> <li>• C15 PDU Jumper Cord (NA/MEX/TW/JP) (J9943A)</li> </ul>	
	HPE Aruba Networking X372 54VDC 1600W 110-240VAC Power Supply PDU	JL670A#B2C
	<ul style="list-style-type: none"> <li>• C15 PDU Jumper Cord (ROW) (J9944A)</li> </ul>	
	HPE Aruba Networking X372 54VDC 1600W 110-240VAC Power Supply 220v	JL670A#B2E
	<ul style="list-style-type: none"> <li>• HPE 2.5m C15 to NEMA 6-20P Pwr Cord (JL336A)</li> </ul>	
	HPE Aruba Networking X372 54VDC 1600W 110-240VAC Power Supply NoLoc	JL670A#AC3
	<ul style="list-style-type: none"> <li>• No Localized Power Cord Selected. Use J9955A to obtain a Locking Plug Power Cord (L6-20P)</li> </ul>	
1, 2	HPE Aruba Networking X371 12VDC 250W 100-240VAC Power Supply	JL085A
	<ul style="list-style-type: none"> <li>• Uses 1 x C13, 250w</li> </ul>	
	HPE Aruba Networking X371 12VDC 250W 100-240VAC Power Supply PDU	JL085A#B2B
	<ul style="list-style-type: none"> <li>• C13 PDU Jumper Cord (NA/MEX/TW/JP) (J9943A)</li> </ul>	
	HPE Aruba Networking X371 12VDC 250W 100-240VAC Power Supply PDU	JL085A#B2C
	<ul style="list-style-type: none"> <li>• C13 PDU Jumper Cord (ROW) (JL697A)</li> </ul>	
	HPE Aruba Networking X371 12VDC 250W 100-240VAC Power Supply 220v	JL085A#B2E
	<ul style="list-style-type: none"> <li>• HPE 2.5m C13 to NEMA 6-20P Pwr Cord (JL336A)</li> </ul>	
	HPE Aruba Networking X371 12VDC 250W 100-240VAC Power Supply	JL085A#AC3
	<ul style="list-style-type: none"> <li>• No Localized Power Cord Selected. Use J9955A to obtain a Locking Plug Power Cord (L6-20P)</li> </ul>	
2	HPE Aruba Networking CX 6300M 250W 36-72VDC Input Non-PoE Power Supply	JL757A
	<ul style="list-style-type: none"> <li>• DC supply, comes with DC power cable, only mix with AC PSU JL085A 250W</li> </ul>	
1, 4	HPE Aruba Networking X371 12VDC 250W 100-240VAC Power-to-Port Power Supply	JL760A
	<ul style="list-style-type: none"> <li>• Uses 1 x C13, 250w</li> </ul>	
	HPE Aruba Networking X371 12VDC 250W 100-240VAC Power-to-Port Power Supply PDU	JL760A#B2B
	<ul style="list-style-type: none"> <li>• C13 PDU Jumper Cord (NA/MEX/TW/JP) (J9943A)</li> </ul>	
	HPE Aruba Networking X371 12VDC 250W 100-240VAC Power-to-Port Power Supply PDU	JL760A#B2C
	<ul style="list-style-type: none"> <li>• C13 PDU Jumper Cord (ROW) (J9944A)</li> </ul>	
	HPE Aruba Networking X371 12VDC 250W 100-240VAC Power-to-Port Power Supply 220v	JL760A#B2E
	<ul style="list-style-type: none"> <li>• HPE 2.5m C13 to NEMA 6-20P Pwr Cord (JL336A)</li> </ul>	
	HPE Aruba Networking X371 12VDC 250W 100-240VAC Power-to-Port Power Supply NoLoc	JL760A#AC3
	<ul style="list-style-type: none"> <li>• No Localized Power Cord Selected. Use J9955A to obtain a Locking Plug Power Cord (L6-20P)</li> </ul>	
1, 3	HPE Aruba Networking X372 54VDC 680W 100-240VAC Power Supply	JL086A
	<ul style="list-style-type: none"> <li>• Uses 1 x C15, 680w</li> </ul>	
	HPE Aruba Networking X372 54VDC 680W 100-240VAC Power Supply PDU	JL086A#B2B
	<ul style="list-style-type: none"> <li>• C15 PDU Jumper Cord (NA/MEX/TW/JP) (J9943A)</li> </ul>	
	HPE Aruba Networking X372 54VDC 680W 100-240VAC Power Supply PDU	JL086A#B2C
	<ul style="list-style-type: none"> <li>• C15 PDU Jumper Cord (ROW) (J9944A)</li> </ul>	
	HPE Aruba Networking X372 54VDC 680W 100-240VAC Power Supply 220v	JL086A#B2E
	<ul style="list-style-type: none"> <li>• HPE 2.5m C15 to NEMA 6-20P Pwr Cord (JL336A)</li> </ul>	
	HPE Aruba Networking X372 54VDC 680W 100-240VAC Power Supply	JL086A#AC3
	<ul style="list-style-type: none"> <li>• No Localized Power Cord Selected. Use J9955A to obtain a Locking Plug Power Cord (L6-20P)</li> </ul>	
3, 5	HPE Aruba Networking CX 6300M 1050W 36-72VDC Input PoE Power Supply	JL758A
	<ul style="list-style-type: none"> <li>• DC supply, comes with DC power cable, only mix with AC PSU JL087A 1050W</li> </ul>	

## Configuration Information

1, 3	HPE Aruba Networking X372 54VDC 1050W 110-240VAC Power Supply	JL087A
	<ul style="list-style-type: none"> <li>• Uses 1 x C15, 1050w</li> </ul>	
	HPE Aruba Networking X372 54VDC 1050W 110-240VAC Power Supply PDU	JL087A#B2B
	<ul style="list-style-type: none"> <li>• C15 PDU Jumper Cord (NA/MEX/TW/JP) (J9943A)</li> </ul>	
	HPE Aruba Networking X372 54VDC 1050W 110-240VAC Power Supply PDU	JL087A#B2C
	<ul style="list-style-type: none"> <li>• C15 PDU Jumper Cord (ROW) (J9944A)</li> </ul>	
	HPE Aruba Networking X372 54VDC 1050W 110-240VAC Power Supply 220v	JL087A#B2E
	<ul style="list-style-type: none"> <li>• HPE 2.5m C15 to NEMA 6-20P Pwr Cord (JL336A)</li> </ul>	
	HPE Aruba Networking X372 54VDC 1050W 110-240VAC Power Supply	JL087A#AC3
	<ul style="list-style-type: none"> <li>• No Localized Power Cord Selected. Use J9955A to obtain a Locking Plug Power Cord (L6-20P)</li> </ul>	

### Configuration Rules

Rule #	Description	SKU
1	Localization (Wall Power Cord) required on orders without #B2B, #B2C, (PDU Power Cord) or #B2E. (See Localization Menu)	
2	The Following Switches are compatible with this PSU	
	HPE Aruba Networking CX 6300M 24-port SFP+ and 4-port SFP56 Switch	JL658A
	HPE Aruba Networking CX 6300M 48-port 1GbE and 4-port SFP56 Switch	JL663A
	HPE Aruba Networking CX 6300M 24-port 1GbE and 4-port SFP56 Switch	JL664A
	HPE Aruba Networking CX 6300M 24p SFP+ LRM support and 2p 50G and 2p 25G MACSec Switch	R8S92A
	HPE Aruba Networking 6300M 24p SFP+ 1G/10G 4p SFP56 50G TAA Switch	SOG03A
	HPE Aruba Networking 6300M 48p 10M/100M/1G 4p SFP56 50G TAA Switch	SOG00A
	HPE Aruba Networking 6300M 24p 10M/100M/1G 4p SFP56 50G TAA Switch	SOG01A
3	The Following Switches are compatible with this PSU	
	HPE Aruba Networking CX 6300M 48-port HPE Smart Rate 1/2.5/5GbE Class 6 PoE and 4-port SFP56 Switch	JL659A
	HPE Aruba Networking CX 6300M 24-port HPE Smart Rate 1/2.5/5GbE Class 6 PoE and 4-port SFP56 Switch	JL660A
	HPE Aruba Networking CX 6300M 48-port 1GbE Class 4 PoE and 4-port SFP56 Switch	JL661A
	HPE Aruba Networking CX 6300M 24-port 1GbE Class 4 PoE and 4-port SFP56 Switch	JL662A
	HPE Aruba Networking CX 6300M 48p HPE Smart Rate 1G/2.5G/5G Class8 PoE 2p 50G 2p 25G Switch	R8S90A
	HPE Aruba Networking CX 6300M 24p Smart Rate 1G/2.5G/5G/10G Class6 PoE 2p 50G 2p 25G Switch	R8S89A
	HPE Aruba Networking CX 6300M 12p CL8 PoE 36p CL6 PoE Smart Rate 1G/2.5G/5G 2p 50G 2p 10G Switch	R8S91A
	HPE Aruba Networking 6300M 48p Smart Rate 1G/2.5G/5G Class6 PoE 4p SFP56 50G TAA Switch	SOG04A
	HPE Aruba Networking 6300M 24p Smart Rate 1G/2.5G/5G Class6 PoE 4p SFP56 50G TAA Switch	SOG05A
	HPE Aruba Networking 6300M 48p 10M/100M/1G Class4 PoE 4p SFP56 50G TAA Switch	SOG06A
	HPE Aruba Networking 6300M 24p 10M/100M/1G Class4 PoE 4p SFP56 50G TAA Switch	SOF99A
	HPE Aruba Networking 6300L 48p Smart Rate 100M/1G/2.5G/5G CL8 2p SFP56 50G 2p SFP28 25G L2 Switch	S3L76A
	HPE Aruba Networking 6300L 24p Smart Rate 1G/2.5G/5G/10G CL6 2p SFP56 50G 2p SFP28 25G L2 Switch	S3L75A
	HPE ANW 6300L 48p Smart Rate 100M/1G/2.5G/5G Class6/8 2p SFP56 50G 2p SFP+ 1G/10G LRM Layer2 Sw	S3L77A
	HPE Aruba Networking CX 6300M 24p SFP+ LRM support and 2p 50G and 2p 25G MACSec Switch	R8S92A
	HPE Aruba Networking 6300M 48p SR10 1G/2.5G/5G/10G PTP/AVB Class8 PoE and 4p 100G MACsec Switch	S0E91A

## Configuration Information

	HPE Aruba Networking 6300M 48p SR10 1G/2.5G/5G/10G PTP/AVB Class8 PoE 4p 100G MACsec TAA Switch	SOX44A
4	<b>The Following Switch is only compatible with this Power to Port PSU;</b> HPE Aruba Networking CX 6300M 48p 1GbE 4p SFP56 Power-to-Port 2 Fan Trays 1 PSU Bundle HPE Aruba Networking 6300M 48p 10M/100M/1G 4p SFP56 50G Power-to-Port 2xFan PSU TAA Bundle	JL762A SOG02A
5	<b>It is recommended that the JL758A 1050W PSU NOT be mixed with the JL670A 1600W PSU.</b>	
<b>Notes:</b>	<ul style="list-style-type: none"> <li>– If you want the Locking Power Cord (J9955A) L6-20P, then you must order this power cord through the Accessories tab</li> <li>– Drop down under power supply should offer the following options and results:</li> <li>– Switch/Router to PDU Power Cord - #B2B in NA, Mexico, Taiwan, and Japan or #B2C ROW. (OCA Default B2B or B2C for Rack Level CTO)</li> <li>– Switch/Router/Power Supply to Wall Power Cord - Localized Option (OCA Default for BTO and Box Level CTO)</li> <li>– High Volt Switch/Router/Power Supply to Wall Power Cord - #B2E Option. (Offered only in North America, Mexico, Taiwan, and Japan)</li> <li>– No Localized Power Cord Selected - #AC3 Option</li> </ul>	
	<b>PSU Options</b> For JL670A, JL085A, JL760A, JL086A, JL087A (std 0 // max 1) User Selection (min 0 // max 1) per PSU	
	HPE Networking 2.0m C13 to C14 PDU India Power Cord	JL671A
	<ul style="list-style-type: none"> <li>• C13 India PDU Cable for Factory Racked Systems Only</li> </ul>	
	HPE Networking 2.5m C15 to C14 PDU India Power Cord	JL672A
	<ul style="list-style-type: none"> <li>• C15 India PDU Cable for Factory Racked Systems Only</li> </ul>	
<b>Notes:</b>	<ul style="list-style-type: none"> <li>– This cable is intended for India use only. Typically, power cord is ordered when power supply option #AC3 is selected.</li> <li>– These PDU cables are for Solutions shipping to India.</li> </ul>	

## Switch Options

### Fan Trays

- JL658A, JL659A, JL762A, SOG02A System (std 2 // max 2) User Selection (min 0 // max 0) per enclosure
- JL660A, JL661A, JL662A, JL663A, JL664A System (std 1 // max 2) User Selection (min 0 // max 1) per enclosure
- R8S90A, R8S89A, R8S91A, R8S92A System (std 2 // max 2) User Selection (min 0 // max 0) per enclosure
- S0F99A, S0G00A, S0G01A, S0G03A, S0G04A, S0G05A, S0G06A System (std 1 // max 2) User Selection (min 0 // max 1) per enclosure
- S3L75A, S3L76A, S3L77A System (std 2 // max 2) User Selection (min 0 // max 0) per enclosure
- S0E91A, SOX44A System (std 2 // max 2) User Selection (min 0 // max 0) per enclosure

Rule#	Description	SKU
	HPE Aruba Networking X751 Front to Back Fan Tray	JL669B
1	HPE Aruba Networking CX 6300M Power-to-Port Fan Tray	JL761A
2	HPE Aruba Networking X741 Port-to-Power Fan	JL714A

### Configuration Rules

Rule #	Description	SKU
1	<b>The Following Switch is only compatible with this Power to Port FanTray</b> HPE Aruba Networking CX 6300M 48p 1GbE 4p SFP56 Power-to-Port 2 Fan Trays 1 PSU Bundle HPE Aruba Networking 6300M 48p 10M/100M/1G 4p SFP56 50G Power-to-Port 2xFan PSU TAA Bundle	JL762A SOG02A



## Configuration Information

2	<p>The Following Switches are ONLY compatible with this Port to Power FanTray;</p> <p>HPE Aruba Networking 6300M 48p SR10 1G/2.5G/5G/10G PTP/AVB Class8 PoE and 4p 100G MACsec Switch <span style="float: right;">S0E91A</span></p> <p>HPE Aruba Networking 6300M 48p SR10 1G/2.5G/5G/10G PTP/AVB Class8 PoE 4p 100G MACsec TAA Switch <span style="float: right;">S0X44A</span></p>	
<b>Notes:</b>	<ul style="list-style-type: none"> <li>- When configuring JL658A, JL659A, JL762A, R8S90A, R8S89A, R8S91A, R8S92A, S0E91A, S0X44A, S3L75A, S3L76A, S3L77A, S0G02A</li> <li>- This switch includes 2 Fan Trays. No additional Fan Trays necessary</li> <li>- When configuring JL660A, JL661A, JL662A, JL663A, JL664A, S0G05A, S0G06A, S0F99A, S0G00A, S0G01A</li> <li>- This switch includes 1 Fan Tray. 2nd Fan Tray optional.</li> </ul>	
	<p><b>Rack Mount Kits</b></p> <p>System (std 0 // max 1) User Selection (min 0 // max 1) per enclosure</p> <p>HPE Aruba Networking X414 1U Universal 4-post Rack Mount Kit <span style="float: right;">J9583B</span></p>	
<b>Notes:</b>	<p>If the switch will be factory racked into an HPE Universal Rack, then (Min 1) of the 4 Post Rack Mount kit is required.</p>	
	<p><b>Air Duct Kit</b></p> <p>For System (std 0 // max 1) User Selection (min 0 // max 1) per Switch</p> <p>HPE Aruba Networking X544 Universal 4-post Duct Kit (Must order 4-post rack mount kit) <span style="float: right;">JL716A</span></p>	
<b>Notes:</b>	<ul style="list-style-type: none"> <li>- Only for Power to Port Bundles</li> <li>- If the Switch Bundle will be Factory Racked, then this Duct Kit is required with #0D1 for the Power to Port Switch Bundles: JL762A</li> <li>- For optimal performance, it is recommended that the user select the Duct Kit for Power to Port Switch Bundles</li> <li>- If this Air Duct Kit is selected, then the following 4 Post Rack Mount kit must be selected: J9583B – HPE Aruba Networking X414 1U Universal 4-post Rack Mount Kit</li> </ul>	
	<p><b>India PDU Cable</b></p> <p>For JL665A, JL666A, JL667A, JL668A, JL762A (std 0 // max 1) User Selection (min 0 // max 1) per enclosure</p> <p>For S0G95A, S0G96A, S0G97A, S0G98A, S0G02A (std 0 // max 1) User Selection (min 0 // max 1) per enclosure</p>	
3	<p>HPE Networking 2.0m C13 to C14 PDU India Power Cord <span style="float: right;">JL671A</span></p> <ul style="list-style-type: none"> <li>• C13 India PDU Cable for Factory Racked Systems Only</li> </ul>	
2	<p>HPE Networking 2.5m C15 to C14 PDU India Power Cord <span style="float: right;">JL672A</span></p> <ul style="list-style-type: none"> <li>• C15 India PDU Cable for Factory Racked Systems Only</li> </ul>	
	<p><b>Configuration Rules</b></p>	
<b>Rule #</b>	<b>Description</b>	<b>SKU</b>
2	This Power Cord is compatible with the following Switches: JL665A, JL666A, S0G95A, S0G96A, JL762A, S0G02A	
3	This Power Cord is compatible with the following Switches: JL667A, JL668A, S0G97A, S0G98A	
<b>Notes:</b>	These PDU cables are for Solutions shipping to India.	
	<p><b>USB Console Cables</b></p> <p>System (std 0 // max 99) User Selection (min 0 // max 99) per switch</p>	
1	HPE Aruba Networking USBA-RJ45 PIN3TX-6RX 2.5m Cable <span style="float: right;">R8Z87A</span>	
	HPE Aruba Networking USBA-RJ45 PC-to-Switch PIN6TX-3RX 2.5m Cable <span style="float: right;">R9G48B</span>	
1	HPE Aruba Networking USB-A reversible to USB-C PC-to-Switch 3m Cable <span style="float: right;">R9J32A</span>	
1	HPE Aruba Networking USB-C to USB-C PC-to-Switch 3m Cable <span style="float: right;">R9J33A</span>	

## Configuration Information

Rule #	Configuration Rules Description	SKU
1	<p>This cable is only compatible with the following Switches; JL658A, JL659A, R8S90A, JL660A, R8S89A, JL661A, R8S91A, JL662A, R8S92A, JL663A, JL664A, JL762A, JL665A, JL666A, JL667A, JL668A, SOE91A, SOF99A, SOG00A, SOG01A, SOG03A, SOG04A, SOG05A, SOG06A, SOX44A, S3L75A, S3L76A, S3L77A, SOG02A, SOG95A, SOG96A, SOG97A, SOG98A</p> <p><b>Switch Options</b> System (std 0 // max 99) User Selection (min 0 // max 99) per switch HPE Aruba Networking CX Switch Bluetooth Adapter</p>	S1H23A
<b>Notes:</b>	<p>This cable is only compatible with the following Switches; JL658A, JL659A, R8S90A, JL660A, R8S89A, JL661A, R8S91A, JL662A, R8S92A, JL663A, JL664A, JL762A, JL665A, JL666A, JL667A, JL668A, SOE91A, SOF99A, SOG00A, SOG01A, SOG03A, SOG04A, SOG05A, SOG06A, SOX44A, S3L75A, S3L76A, S3L77A, SOG02A, SOG95A, SOG96A, SOG97A, SOG98A</p>	

## Software

HPE Aruba Networking CX Mobile App <https://www.arubanetworks.com/products/networking/switches/cx-mobileapp/>

Remarks	Description	SKU
	<p><b>HPE Aruba Networking AOS-CX Software</b></p> <p><b>HPE Aruba Networking CX Advanced Software Licenses</b></p> <p>HPE Aruba Networking CX Software 63xx Switch Advanced 1-year Subscription E-STU SOT77AAE</p> <p>HPE Aruba Networking CX Software 63xx Switch Advanced 3-year Subscription E-STU SOT78AAE</p> <p>HPE Aruba Networking CX Software 63xx Switch Advanced 5-year Subscription E-STU SOT79AAE</p> <p>HPE Aruba Networking CX Software 63xx Switch Advanced 7-year Subscription E-STU SOT80AAE</p> <p>HPE Aruba Networking CX Software 63xx Switch Advanced 10-year Subscription E-STU SOT76AAE</p> <p><b>HPE Aruba Networking NetEdit</b></p> <p><b>Single Node Subscription</b></p> <p>HPE Aruba Networking NetEdit Single Node 1yr Subscription E-STU JL639AAE</p> <p>HPE Aruba Networking NetEdit Single Node 3yr Subscription E-STU JL640AAE</p> <p><b>HPE Aruba Networking Central</b></p>	
<b>Notes:</b>	<p>For details and complete listing of HPE Aruba Networking Central licensing options, please see <a href="https://www.arubanetworks.com/assets/ds/DS_ArubaCentral.pdf">https://www.arubanetworks.com/assets/ds/DS_ArubaCentral.pdf</a> HPE Aruba Networking Central Data Sheet <a href="https://www.arubanetworks.com/assets/ds/DS_ArubaCentral.pdf">https://www.arubanetworks.com/assets/ds/DS_ArubaCentral.pdf</a></p> <p><b>Cloud Services / 63XX/38XX Switch Foundation Subscriptions</b></p>	
2	HPE Aruba Networking Central Switch Class-3 Foundation 1 year Subscription E-STU	Q9Y78AAE
2	HPE Aruba Networking Central Switch Class-3 Foundation 3 year Subscription E-STU	Q9Y79AAE
2	HPE Aruba Networking Central Switch Class-3 Foundation 5 year Subscription E-STU	Q9Y80AAE
2	HPE Aruba Networking Central Switch Class-3 Foundation 7 year Subscription E-STU	Q9Y81AAE
2	HPE Aruba Networking Central Switch Class3 Foundation 10-year Subscription E-STU	R3K02AAE
	<p><b>On-Prem Services / 63XX/38XX Switch Foundation Subscriptions</b></p>	
3	HPE Aruba Networking Central on Prem Switch Class-3 Foundation 1 year Subscription E-STU	R6U83AAE
3	HPE Aruba Networking Central on Prem Switch Class-3 Foundation 3 year Subscription E-STU	R6U84AAE
3	HPE Aruba Networking Central on Prem Switch Class-3 Foundation 5 year Subscription E-STU	R6U85AAE
3	HPE Aruba Networking Central on Prem Switch Class-3 Foundation 7 year Subscription E-STU	R6U86AAE
3	HPE Aruba Networking Central on Prem Switch Class-3 Foundation 10 year Subscription E-STU	R6U87AAE



## Configuration Information

### On-Prem Services / 63XX/38XX Switch Foundation Subscriptions

3	HPE Aruba Networking Central on Prem Switch Class-3 Foundation 1 year Subscription E-STU	R6U83AAE
3	HPE Aruba Networking Central on Prem Switch Class-3 Foundation 3 year Subscription E-STU	R6U84AAE
3	HPE Aruba Networking Central on Prem Switch Class-3 Foundation 5 year Subscription E-STU	R6U85AAE
3	HPE Aruba Networking Central on Prem Switch Class-3 Foundation 7 year Subscription E-STU	R6U86AAE
3	HPE Aruba Networking Central on Prem Switch Class-3 Foundation 10 year Subscription E-STU	R6U87AAE

### On-Prem Services / 63XX/38XX Switch Advanced Subscriptions

3	HPE Aruba Networking Central On-Premises Switch Class3 Advanced 1-year Subscription E-STU	R6V03AAE
3	HPE Aruba Networking Central On-Premises Switch Class3 Advanced 3-year Subscription E-STU	R6V04AAE
3	HPE Aruba Networking Central On-Premises Switch Class3 Advanced 5-year Subscription E-STU	R6V05AAE
3	HPE Aruba Networking Central On-Premises Switch Class3 Advanced 7-year Subscription E-STU	R6V06AAE
3	HPE Aruba Networking Central On-Premises Switch Class3 Advanced 10-year Subscription E-STU	R6V07AAE

### FedRAMP Services / 63XX/38XX Switch Foundation Subscriptions

6	HPE Aruba Networking Central 63xx/38xx Switch Foundation Government 1-year Subscription E-STU	R8K99AAE
6	HPE Aruba Networking Central 63xx/38xx Switch Foundation Government 3-year Subscription E-STU	R8L00AAE
6	HPE Aruba Networking Central 63xx/38xx Switch Foundation Government 5-year Subscription E-STU	R8L01AAE
6	HPE Aruba Networking Central 63xx/38xx Switch Foundation Government 7-year Subscription E-STU	R8L02AAE
6	HPE Aruba Networking Central 63xx/38xx Switch Foundation Government 10-year Subscription E-STU	R8L03AAE

### Configuration Rules

Rule #	Description	SKU
2	<a href="#">Add the Central Cloud Skus to the HPE Aruba Networking Catalog as Standalone: HPE Aruba Networking &gt; Network Management &gt; Central &gt; Cloud Services</a>	
3	<a href="#">Add the Central On-Prem Skus to the HPE Aruba Networking Catalog as Standalone: HPE Aruba Networking &gt; Network Management &gt; Central &gt; On-Prem Services</a>	
6	<a href="#">Add the Central FedRAMP Service Skus to the HPE Aruba Networking Catalog as Standalone: HPE Aruba Networking &gt; Network Management &gt; Central &gt; FedRAMP</a>	

### HPE Aruba Networking Fabric Composer

#### Single Node Subscription

HPE Aruba Networking Fabric Composer Device Management Service Tier 3 Switch 1y Subscription E-STU	R8D18AAE
HPE Aruba Networking Fabric Composer Device Management Service Tier 3 Switch 3y Subscription E-STU	R8D19AAE
HPE Aruba Networking Fabric Composer Device Management Service Tier 3 Switch 5y Subscription E-STU	R8D20AAE

## As-a-Service

### HPE Aruba Networking Central

#### Cloud Services / 63XX/38XX Switch Foundation Subscriptions

HPE Aruba Networking Central Switch Class-3 Foundation 1 year Subscription SaaS	Q9Y78AAS
HPE Aruba Networking Central Switch Class-3 Foundation 3 year Subscription SaaS	Q9Y79AAS
HPE Aruba Networking Central Switch Class-3 Foundation 5 year Subscription SaaS	Q9Y80AAS
HPE Aruba Networking Central Switch Class-3 Foundation 7 year Subscription SaaS	Q9Y81AAS



## Configuration Information

HPE Aruba Networking Central Switch Class-3 Foundation 10 year Subscription SaaS R3K02AAS

**Notes:** [Add the Central Cloud Skus to the HPE Aruba Networking Catalog as Standalone: HPE Aruba Networking > Network Management > Central > Cloud Services](#)

### Cloud Services / Switch Advanced AAS Licenses

HPE Aruba Networking Central Switch Class-3 Advanced 1 year Subscription SaaS SOW52AAS

HPE Aruba Networking Central Switch Class-3 Advanced 3 year Subscription SaaS SOW53AAS

HPE Aruba Networking Central Switch Class-3 Advanced 5 year Subscription SaaS SOW54AAS

HPE Aruba Networking Central Switch Class-3 Advanced 7 year Subscription SaaS SOW55AAS

HPE Aruba Networking Central Switch Class-3 Advanced 10 year Subscription SaaS SOW56AAS

HPE Aruba Networking Central Switch Class-3 Advanced 1 year Subscription SaaS SOW77AAS

HPE Aruba Networking Central Switch Class-3 Advanced 3 year Subscription SaaS SOW78AAS

HPE Aruba Networking Central Switch Class-3 Advanced 5 year Subscription SaaS SOW79AAS

HPE Aruba Networking Central Switch Class-3 Advanced 7 year Subscription SaaS SOW80AAS

HPE Aruba Networking Central Switch Class-3 Advanced 10 year Subscription SaaS SOW81AAS

**Notes:** [For IRIS reference only. No action required for OCX and Clic](#)



## Technical Specifications

HPE Aruba Networking CX 6300M 48p SR10 PTP/AVB Class8 PoE 4p 100G MACsec Switch (S0E91A)		
<b>Description</b>	48x ports SmartRate 100M <sup>2</sup> /1G/2.5G/5G/10G BaseT Class 8 PoE ports supporting up to 90W per port (MACsec) 4x 10G/25G/40G/100G QSFP/QSFP28 ports (MACsec) Supports PoE Standards IEEE 802.3af, 802.3at and 802.3bt (up to 90W) 1x USB-C Console Port (higher priority than RJ45 console port) 1x RJ45 console port 1x OOBM 1x USB Type A Host port  <b>Notes:</b> <sup>1</sup> 50G capability is for use with 50G DACs for both interconnect and VSF stacking. 50G transceivers and DACs are not supported on S0E91A and S0X44A switch models, which requires QSFP to SFP56 DAC cable for VSF stacking with other CX 6300F and CX 6300M switch models only. VSF stacking not supported on 1G ports.	
<b>Power Supplies</b>	2 field-replaceable, hot-swappable power supply slots 1 minimum power supply required (ordered separately) Supported PSUs JL086A JL087A JL670A JL758A Max PoE Power: 2640W	
<b>Fans</b>	Switch has three fan tray slots and comes with three JL714A fan trays installed <ul style="list-style-type: none"> <li>• Min 3 fan trays required.</li> <li>• Fan trays are field replaceable and hot-swappable.</li> <li>• Each fan tray contains two fans.</li> </ul>	
<b>Physical Characteristics</b>	<b>Dimensions</b>	(H) 4.4 cm x (W) 44.2 cm x (D) 47.2 cm (1.73" x 17.4" x 18.6")
	<b>Weight</b>	7.75 kg (17.09 lbs)
<b>Additional Specifications</b>	<b>CPU</b>	Quad Core ARM Cortex™ A72 @ 1.8GHz
	<b>Memory and Flash</b>	8 GB DDR4 32 GB eMMC
	<b>Packet Buffer</b>	-
<b>Performance</b>	<b>Model switching capacity</b>	1760 Gbps
	<b>Model throughput capacity</b>	1310 Mpps
	<b>Average latency (LIFO, 64-byte packets)</b>	-
	<b>Stack size</b>	10 members
	<b>Max stacking distance</b>	Up to 10 kms with long range transceivers
	<b>Stacking bandwidth</b>	400 Gbps
	<b>Switched virtual interfaces (dual stack)</b>	1,024
	<b>IPv4 host table (ARP)</b>	49,152
	<b>IPv6 host table (ND)</b>	49,152
	<b>IPv4 unicast routes</b>	61,000
	<b>IPv6 unicast routes</b>	61,000
	<b>IPv4 multicast routes</b>	8,192
	<b>IPv6 multicast routes</b>	8,192
	<b>MAC table capacity</b>	32,768
	<b>IGMP groups</b>	4,096
	<b>MLD groups</b>	8,192
<b>IPv4/IPv6/MAC ACL entries (ingress)</b>	20,480/5,120/20,480	

## Technical Specifications

	<b>IPv4/IPv6/MAC ACL entries (engress)</b>	8,192/2,048/8,192
	<b>VFR</b>	256
<b>Environment</b>	<b>Operating temperature</b>	32°F to 113°F (0°C to 45°C) up to 5,000 ft. Derate -1 degree C for every 1,000 ft from 5,000 ft to 10,000 ft. Can support excursion to 131°F (55°C) for short periods <sup>1</sup> of time.
	<b>Operating relative humidity</b>	5% to 95% @ 104°F (40°C) non-condensing
	<b>Non-operating temperature</b>	-40°F to 158°F (-40°C to 70°C) up to 15,000 ft
	<b>Non-operating humidity</b>	5% to 90% @ 149°F (65°C) non-condensing
	<b>Max operating altitude</b>	10,000 feet (3.04 km) Max
	<b>Max non-operating altitude</b>	15,000 feet (4.6 km) Max
	<b>Acoustic</b>	Sound Power, LWAd = 5.8 Bel Sound Pressure, LpAm (Bystander) = 41.7 dB
	<b>Primary airflow</b>	Front and side-to-back
<b>Electrical Characteristics</b>	<b>Frequency</b>	50Hz/60Hz
	<b>AC voltage</b>	JL670A PSU: 110V-120V/200V/208V-240V; AC input JL086A PSU: 100V-240V; AC input JL087A PSU: 110V-240V; AC input JL758A PSU: 36-72VDC; DC input
	<b>Current (for voltages listed above)</b>	JL670A PSU: 11A/9A/8A JL086A PSU: 8A/3.5A JL087A PSU: 12A/5A JL758A PSU: 16.6 – 34.3A
	<b>Power consumption (230VAC)</b>	With single JL086A PSU: Idle: 207W 100% Traffic Rate: 283W With single JL087A PSU: Idle: 208W 100% Traffic Rate: 282W With single JL670A PSU: Idle: 211W 100% Traffic Rate: 283W
<b>Safety</b>	Include US, Canada, Europe, Worldwide	Europe: EN 62368-1:2014 +A11:2017 EN 62368-1:2020 +A11:2020 US: UL 62368-1 2nd Ed. CAN: CSA-C22.2 No. 62368-1-14 2nd Ed. Worldwide: IEC 62368-1:2014 (2nd Ed) IEC 62368-1:2018 (3rd Ed) Taiwan: CNS 15598-1:2020
<b>Emissions</b>	Include US, Canada, Europe, Worldwide	Europe: EN 55032:2015+A11:2020, Class A EN 55035:2017+A11:2020 EN IEC 61000-3-2:2019+A1:2021 EN 61000-3-3:2013+A2:2021 US: FCC 47 CFR part 15 subpart B, Class A CAN: ICES-003 Issue 7:2020, Class A Japan: VCCI-CISPR 32:2016, Class A Taiwan: CNS 15936:2016, Class A AUS/NZ: AS/NZS CISPR 32:2015+A1:2020, Class A Worldwide:

## Technical Specifications

		CISPR 32:2015/AMD1:2019, Class A CISPR 35:2016
<b>Lasers</b>	Include US, Canada, Europe, Worldwide	EN 60825-1:2014 +A11:2021 / IEC 60825-1:2014 Class 1 Laser Products / Laser Klasse 1 (Applicable for accessories – Optical Transceivers only)
<b>Immunity</b>	<b>Generic</b>	CISPR 35
	<b>EN</b>	EN 55035:2017
	<b>ESD</b>	IEC 61000-4-2
	<b>Radiated</b>	IEC 61000-4-3
	<b>EFT/Burst</b>	IEC 61000-4-4
	<b>Surge</b>	IEC 61000-4-5
	<b>Conducted</b>	IEC 61000-4-6
	<b>Power frequency magnetic field</b>	IEC 61000-4-8
	<b>Voltage dips and interruptions</b>	IEC 61000-4-11
	<b>Harmonics</b>	IEC 61000-3-2:2018+A1:2020; EN IEC 61000-3-2:2019+A1:2021
<b>Flicker</b>	IEC/EN 61000-3-3:2013+A2:2021	
<b>Mounting and Enclosure</b>	Mounts in an EIA standard 19 in. telco rack or equipment cabinet. Horizontal surface mounting only. 2-post rack kit included.	

### HPE Aruba Networking 6300M 24-port SFP+ and 4-port SFP56 Switch (R8S89A)

<b>Description</b>	<p>24x ports SmartRate 100M2/1G/2.5G/5G/10G BaseT Class 6 PoE ports supporting up to 60W per port (MACsec)  2x 10G/25G/50G1 SFP ports  2x 10G/25G SFP ports (MACsec)  Supports PoE Standards IEEE 802.3af, 802.3at and 802.3bt (up to 60W)  1x USB-C Console Port  1x RJ Console Port  1x OOBM port  1x USB Type A Host port</p> <p><b>Notes:</b> 150G capability is for use with 50G DACs for both interconnect and VSF stacking. 50G transceivers and DACs are not supported on S0E91A and S0X44A switch models, which requires QSFP to SFP56 DAC cable for VSF stacking with other CX 6300F and CX 6300M switch models only. VSF stacking not supported on 1G ports.</p>	
<b>Power Supplies</b>	<p>2 field-replaceable, hotswappable power supply slots 1 minimum power supply required (ordered separately)</p> <p>Supported PSUs  JL086A  JL087A  JL670A  JL758A  Max PoE Power: 2880W</p>	
<b>Fans</b>	<p>The switch has two fan tray slots and comes with two fan trays installed.  Min 2 fan trays required.  Fan trays are field replaceable and hotswappable.  Each fan tray contains two fans.</p>	
<b>Physical Characteristics</b>	<b>Dimensions</b>	(H) 4.4 cm x (W) 44.2 cm x (D) 38.5 cm (1.73" x 17.4" x 15.2")
	<b>Weight</b>	5.26 kg (11.60 lbs)



## Technical Specifications

<b>Mounting and Enclosure</b>	Mounts in an EIA- standard 19 in. telco rack or equipment cabinet. Horizontal surface mounting only. 2-post rack kit included.		
<b>Additional Specifications</b>	<b>CPU</b>	Quad Core ARM Cortex™ A72 @ 1.8GHz	
	<b>Memory and Flash</b>	8 GB DDR4 32 GB eMMC	
	<b>Packet Buffer</b>	16 MB	
<b>Performance</b>	<b>System switching capacity</b>	880 Gbps	
	<b>System throughput capacity</b>	660 Mpps	
	<b>Model switching capacity</b>	880 Gbps	
	<b>Model throughput capacity</b>	654 Mpps	
	<b>Average latency (LIFO, 64-byte packets)</b>	1Gbps: 4.24µSec 10Gbps: 1.50µSec 25Gbps: 2.91µSec 50Gbps <sup>1</sup> : 3.49µSec <b>Notes:</b> <sup>1</sup> 50G capability is for use with 50G DACs for both interconnect and VSF stacking. 50G SR transceivers have been added with a minimum software of 10.09.1010. VSF stacking not supported on 1G ports.	
	<b>Stack size</b>	10 members	
	<b>Max stacking distance</b>	Up to 10 kms with long range transceivers	
	<b>Stacking bandwidth</b>	200 Gbps	
	<b>Switched virtual interfaces (dual stack)</b>	1,024	
	<b>IPv4 host table (ARP)</b>	49,152	
	<b>IPv6 host table (ND)</b>	49,152	
	<b>IPv4 unicast routes</b>	61,000	
	<b>IPv6 unicast routes</b>	61,000	
	<b>IPv4 multicast routes</b>	8,192	
	<b>IPv6 multicast routes</b>	8,192	
	<b>MAC table capacity</b>	32,768	
	<b>IGMP groups</b>	4,096	
	<b>MLD groups</b>	8,192	
	<b>IPv4/IPv6/MAC ACL entries (ingress)</b>	20,480/5,120/20,480	
	<b>IPv4/IPv6/MAC ACL entries (egress)</b>	8,192/2,048/8,192	
	<b>VFR</b>	256	
	<b>Environment</b>	<b>Operating temperature</b>	32°F to 113°F (0°C to 45°C) up to 5,000 ft. Derate -1 degree C for every 1,000 ft from 5,000 ft to 10,000 ft. Can support excursion to 131°F (55°C) for short periods <sup>1</sup> of time. 55C excursion not supported when 10G LRM/LR/ER inserted: <ul style="list-style-type: none"> <li>When 10G BT and 10G LRM/LR/ER transceivers are installed together, fan redundancy is only supported up to 104°F (40°C), 5,000ft</li> </ul> <b>Notes:</b> <sup>1</sup> 50G capability is for use with 50G DACs for both interconnect and VSF stacking. 50G SR transceivers have been added with a minimum software of 10.09.1010. VSF stacking not supported on 1G ports.
		<b>Operating relative humidity</b>	15% to 95% @ 104°F (40°C) non-condensing
<b>Non-operating temperature</b>		-40°F to 158°F (-40°C to 70°C) up to 15,000 ft	
<b>Non-operating humidity</b>		15% to 90% @ 149°F (65°C) non-condensing	
<b>Max operating altitude</b>		10,000 feet (3.04 km) Max	

## Technical Specifications

	<b>Max non-operating altitude</b>	15,000 feet (4.6 km) Max
	<b>Acoustic</b>	Sound Power, LWAd = 4.9 Bel Sound Pressure, LpAm (Bystander) = 33.0 dB
	<b>Primary airflow</b>	Front and side-to-back
<b>Electrical Characteristics</b>	<b>Frequency</b>	50Hz/60Hz
	<b>AC voltage</b>	JL670A PSU: 110V-120V/208V-240V JL086A PSU: 100V-240V JL087A PSU: 110V-240V
	<b>Current (for voltages listed above)</b>	JL670A PSU: 11A/8A JL086A PSU: 8A/3.5A JL087A PSU: 12A/5A
	<b>Power consumption (230VAC)</b>	With JL086A PSU: Idle: 90W 100% Traffic Rate: 143W Idle: 90W 100% Traffic Rate: 140W With JL670A PSU: Idle: 101W 100% Traffic Rate: 152W
<b>Safety</b>	Include US, Canada, Europe, Worldwide	Europe: EN 62368-1:2014 +A11:2017 2nd Ed. EN 62368-1:2020 +A11:2020 3rd Ed. UK: BS EN 62368-1:2014 + A11:2017 2nd Ed BS EN 62368-1:2020 + A11:2020 3rd Ed US/Canada: UL 62368-1 2nd Ed. CAN/CSA-C22.2 No. 62368-1-14 2nd Ed. Worldwide: IEC 60950-1:2005 + Am1:2009 + Am2:2013 w/all known National Deviations IEC 62368-1:2014 2 <sup>nd</sup> Ed. w/all known National Deviations IEC 62368-1:2018 3 <sup>rd</sup> Ed. w/all known National Deviations
<b>Emissions</b>	Include US, Canada, Europe, Worldwide	Europe: EN 55032:2015 +A11:2020, Class A EN 55035:2017 +A11:2020 EN 61000-3-2:2014, Class A EN 61000-3-3:2013 US/Canada: FCC CFR47 Part 15:2014, Class A ICES-003 Class A Worldwide: VCCI Class A CISPR 32 Class A CISPR 35:2016
<b>Lasers</b>	Include US, Canada, Europe, Worldwide	EN 60825-1:2014 / IEC 60825-1:2014 Class 1 Class 1 Laser Products / Laser Klasse 1 (Applicable for accessories – Optical Transceivers only)



## Technical Specifications

<b>Immunity</b>	<b>Generic</b>	CISPR 35
	<b>EN</b>	EN 55035:2017
	<b>ESD</b>	IEC 61000-4-2
	<b>Radiated</b>	IEC 61000-4-3
	<b>EFT/Burst</b>	IEC 61000-4-4
	<b>Surge</b>	IEC 61000-4-5
	<b>Conducted</b>	IEC 61000-4-6
	<b>Power frequency magnetic field</b>	IEC 61000-4-8
	<b>Voltage dips and interruptions</b>	IEC 61000-4-11
	<b>Harmonics</b>	IEC 61000-3-2, EN 61000-3-2
	<b>Flicker</b>	IEC 61000-3-3, EN 61000-3-3
<b>Mounting and Enclosure</b>	Mounts in an EIA standard 19 in. telco rack or equipment cabinet. Horizontal surface mounting only. 2-post rack kit included.	

## HPE Aruba Networking 6300M 48p HPE Smart Rate 1G/2.5G/5G Class8 PoE and 2p 50G and 2p 25G Switch (R8S90A)

<b>Description</b>	<p>48x ports SmartRate 100M2/1G/2.5G/5G BaseT Class 8 PoE ports supporting up to 90W per port (MACsec)  2x 10G/25G/50G1 SFP ports  2x 10G/25G SFP ports (MACsec)  Supports PoE Standards IEEE 802.3af, 802.3at and 802.3bt (up to 90W)  1x USB-C Console Port  1x RJ Console Port  1x OOBM port  1x USB Type A Host port</p> <p><b>Notes:</b> 150G capability is for use with 50G DACs for both interconnect and VSF stacking. 50G transceivers and DACs are not supported on S0E91A and S0X44A switch models, which requires QSFP to SFP56 DAC cable for VSF stacking with other CX 6300F and CX 6300M switch models only. VSF stacking not supported on 1G ports.</p>	
<b>Power Supplies</b>	<p>2 field-replaceable, hotswappable power supply slots 1 minimum power supply required (ordered separately)</p> <p>Supported PSUs  JL086A  JL087A  JL670A  JL758A  Max PoE Power: 2880W</p>	
<b>Fans</b>	<p>The switch has two fan tray slots and comes with two fan trays installed.  Min 2 fan trays required.  Fan trays are field replaceable and hotswappable.  Each fan tray contains two fans.</p>	
<b>Physical Characteristics</b>	<b>Dimensions</b>	(H) 4.4 cm x (W) 44.2 cm x (D) 38.5 cm (1.73" x 17.4" x 15.2")
	<b>Weight</b>	5.48 kg (12.08 lbs)
<b>Mounting and Enclosure</b>	Mounts in an EIA- standard 19 in. telco rack or equipment cabinet. Horizontal surface mounting only. 2-post rack kit included.	
<b>Additional Specifications</b>	<b>CPU</b>	Quad Core ARM Cortex™ A72 @ 1.8GHz
	<b>Memory and Flash</b>	8 GB DDR4 32 GB eMMC
	<b>Packet Buffer</b>	16 MB



## Technical Specifications

Performance	<b>System switching capacity</b>	880 Gbps	
	<b>System throughput capacity</b>	660 Mpps	
	<b>Model switching capacity</b>	880 Gbps	
	<b>Model throughput capacity</b>	654 Mpps	
	<b>Average latency (LIFO, 64-byte packets)</b>	1Gbps: 4.24µSec 10Gbps: 1.50µSec 25Gbps: 2.91µSec 50Gbps <sup>1</sup> : 3.49µSec <b>Notes:</b> <sup>1</sup> 50G capability is for use with 50G DACs for both interconnect and VSF stacking. 50G SR transceivers have been added with a minimum software of 10.09.1010. VSF stacking not supported on 1G ports.	
	<b>Stack size</b>	10 members	
	<b>Max stacking distance</b>	Up to 10 kms with long range transceivers	
	<b>Stacking bandwidth</b>	200 Gbps	
	<b>Switched virtual interfaces (dual stack)</b>	1,024	
	<b>IPv4 host table (ARP)</b>	49,152	
	<b>IPv6 host table (ND)</b>	49,152	
	<b>IPv4 unicast routes</b>	61,000	
	<b>IPv6 unicast routes</b>	61,000	
	<b>IPv4 multicast routes</b>	8,192	
	<b>IPv6 multicast routes</b>	8,192	
	<b>MAC table capacity</b>	32,768	
	<b>IGMP groups</b>	4,096	
	<b>MLD groups</b>	8,192	
	<b>IPv4/IPv6/MAC ACL entries (ingress)</b>	20,480/5,120/20,480	
	<b>IPv4/IPv6/MAC ACL entries (egress)</b>	8,192/2,048/8,192	
	<b>VFR</b>	256	
	Environment	<b>Operating temperature</b>	32°F to 113°F (0°C to 45°C) up to 5,000 ft. Derate -1 degree C for every 1,000 ft from 5,000 ft to 10,000 ft. Can support excursion to 131°F (55°C) for short periods <sup>1</sup> of time. 55C excursion not supported when 10G LRM/LR/ER inserted: <ul style="list-style-type: none"> <li>When 10G BT and 10G LRM/LR/ER transceivers are installed together, fan redundancy is only supported up to 104°F (40°C), 5,000ft</li> </ul> <b>Notes:</b> <sup>1</sup> 50G capability is for use with 50G DACs for both interconnect and VSF stacking. 50G SR transceivers have been added with a minimum software of 10.09.1010. VSF stacking not supported on 1G ports.
		<b>Operating relative humidity</b>	15% to 95% @ 104°F (40°C) non-condensing
<b>Non-operating temperature</b>		-40°F to 158°F (-40°C to 70°C) up to 15,000 ft	
<b>Non-operating humidity</b>		15% to 90% @ 149°F (65°C) non-condensing	
<b>Max operating altitude</b>		10,000 feet (3.04 km) Max	
<b>Max non-operating altitude</b>		15,000 feet (4.6 km) Max	
<b>Acoustic</b>		Sound Power, LWAd = 5.0 Bel Sound Pressure, LpAm (Bystander) = 33.4 dB	
<b>Primary airflow</b>		Front and side-to-back	

## Technical Specifications

<b>Electrical Characteristics</b>	<b>Frequency</b>	50Hz/60 Hz
	<b>AC voltage</b>	JL670A PSU: 110V-120V/208V-240V JL086A PSU: 100V-240V JL087A PSU: 110V-240V
	<b>Current (for voltages listed above)</b>	JL670A PSU: 11A/8A JL086A PSU: 8A/3.5A JL087A PSU: 12A/5A
	<b>Power consumption (230VAC)</b>	With JL086A PSU: Idle: 90W 100% Traffic Rate: 143W Idle: 90W 100% Traffic Rate: 140W With JL670A PSU: Idle: 101W 100% Traffic Rate: 152W
<b>Safety</b>	Include US, Canada, Europe, Worldwide	Europe: EN 62368-1:2014 +A11:2017 2nd Ed. EN 62368-1:2020 +A11:2020 3rd Ed. UK: BS EN 62368-1:2014 + A11:2017 2nd Ed BS EN 62368-1:2020 + A11:2020 3rd Ed US/Canada: UL 62368-1 2nd Ed. CAN/CSA-C22.2 No. 62368-1-14 2nd Ed. Worldwide: IEC 60950-1:2005 + Am1:2009 + Am2:2013 w/all known National Deviations IEC 62368-1:2014 2 <sup>nd</sup> Ed. w/all known National Deviations IEC 62368-1:2018 3 <sup>rd</sup> Ed. w/all known National Deviations
<b>Emissions</b>	Include US, Canada, Europe, Worldwide	Europe: EN 55032:2015 +A11:2020, Class A EN 55035:2017 +A11:2020 EN 61000-3-2:2014, Class A EN 61000-3-3:2013 US/Canada: FCC CFR47 Part 15:2014, Class A ICES-003 Class A Worldwide: VCCI Class A CISPR 32 Class A CISPR 35:2016
<b>Lasers</b>	Include US, Canada, Europe, Worldwide	EN 60825-1:2014 / IEC 60825-1:2014 Class 1 Class 1 Laser Products / Laser Klasse 1 (Applicable for accessories – Optical Transceivers only)
<b>Immunity</b>	<b>Generic</b>	CISPR 35
	<b>EN</b>	EN 55035:2017
	<b>ESD</b>	IEC 61000-4-2
	<b>Radiated</b>	IEC 61000-4-3
	<b>EFT/Burst</b>	IEC 61000-4-4
	<b>Surge</b>	IEC 61000-4-5
	<b>Conducted</b>	IEC 61000-4-6
	<b>Power frequency magnetic field</b>	IEC 61000-4-8



## Technical Specifications

	<b>Voltage dips and interruptions</b>	IEC 61000-4-11
	<b>Harmonics</b>	IEC 61000-3-2, EN 61000-3-2
	<b>Flicker</b>	IEC 61000-3-3, EN 61000-3-3
<b>Mounting and Enclosure</b>	Mounts in an EIA standard 19 in. telco rack or equipment cabinet. Horizontal surface mounting only. 2-post rack kit included.	

### HPE Aruba Networking 6300M 48SR5 12p Class8 PoE and 36p Class6 PoE HPE Smart Rate 1G/2.5G/5G and 2p 50G and 2p 10G LRM support Switch (R8S91A)

<b>Description</b>	<p>48x ports SmartRate 100M/1G/2.5G/5G BaseT Class 8 PoE ports supporting up to 90W per port on ports 1-12, and up to 60W per port on ports 13-48 (MACsec)</p> <p>2x 10G/25G/50G<sup>1</sup> SFP ports</p> <p>2x 1G/10G SFP ports (LRM + MACsec)</p> <p>Supports PoE Standards IEEE 802.3af, 802.3at and 802.3bt (up to 90W)</p> <p>1x USB-C Console Port</p> <p>1x RJ Console Port</p> <p>1x OOBM port</p> <p>1x USB Type A Host port</p> <p><b>Notes:</b> <sup>1</sup>50G capability is for use with 50G DACs for both interconnect and VSF stacking. 50G SR transceivers have been added with a minimum software of 10.09.1010. VSF stacking not supported on 1G ports.</p>	
<b>Power Supplies</b>	<p>2 field-replaceable, hotswappable power supply slots 1 minimum power supply required (ordered separately)</p> <p>Supported PSUs</p> <p>JL086A</p> <p>JL087A</p> <p>JL670A</p> <p>JL758A</p> <p>Max PoE Power: 2880W</p>	
<b>Fans</b>	<p>The switch has two fan tray slots and comes with two fan trays installed.</p> <p>Min 2 fan trays required.</p> <p>Fan trays are field replaceable and hotswappable.</p> <p>Each fan tray contains two fans.</p>	
<b>Physical Characteristics</b>	<b>Dimensions</b>	(H) 4.4 cm x (W) 44.2 cm x (D) 38.5 cm (1.73" x 17.4" x 15.2")
	<b>Weight</b>	5.47 kg (12.06 lbs)
<b>Mounting and Enclosure</b>	Mounts in an EIA- standard 19 in. telco rack or equipment cabinet. Horizontal surface mounting only. 2-post rack kit included.	
<b>Additional Specifications</b>	<b>CPU</b>	Quad Core ARM Cortex™ A72 @ 1.8GHz
	<b>Memory and Flash</b>	8 GB DDR4 32 GB eMMC
	<b>Packet Buffer</b>	16 MB
<b>Performance</b>	<b>System switching capacity</b>	880 Gbps
	<b>System throughput capacity</b>	660 Mpps
	<b>Model switching capacity</b>	880 Gbps
	<b>Model throughput capacity</b>	654 Mpps
	<b>Average latency (LIFO, 64-byte packets)</b>	1Gbps: 4.24µSec 10Gbps: 1.50µSec 25Gbps: 2.91µSec 50Gbps <sup>1</sup> : 3.49µSec



## Technical Specifications

		<p><b>Notes:</b> <sup>1</sup>50G capability is for use with 50G DACs for both interconnect and VSF stacking. 50G SR transceivers have been added with a minimum software of 10.09.1010. VSF stacking not supported on 1G ports.</p>
	<b>Stack size</b>	10 members
	<b>Max stacking distance</b>	Up to 10 kms with long range transceivers
	<b>Stacking bandwidth</b>	200 Gbps
	<b>Switched virtual interfaces (dual stack)</b>	1,024
	<b>IPv4 host table (ARP)</b>	49,152
	<b>IPv6 host table (ND)</b>	49,152
	<b>IPv4 unicast routes</b>	61,000
	<b>IPv6 unicast routes</b>	61,000
	<b>IPv4 multicast routes</b>	8,192
	<b>IPv6 multicast routes</b>	8,192
	<b>MAC table capacity</b>	32,768
	<b>IGMP groups</b>	4,096
	<b>MLD groups</b>	8,192
	<b>IPv4/IPv6/MAC ACL entries (ingress)</b>	20,480/5,120/20,480
	<b>IPv4/IPv6/MAC ACL entries (egress)</b>	8,192/2,048/8,192
	<b>VFR</b>	256
<b>Environment</b>	<b>Operating temperature</b>	<p>32°F to 113°F (0°C to 45°C) up to 5,000 ft.          Derate -1 degree C for every 1,000 ft from 5,000 ft to 10,000 ft.          Can support excursion to 131°F (55°C) for short periods<sup>1</sup> of time.          55C excursion not supported when 10G LRM/LR/ER inserted:</p> <ul style="list-style-type: none"> <li>When 10G BT and 10G LRM/LR/ER transceivers are installed together, fan redundancy is only supported up to 104°F (40°C), 5,000ft</li> </ul> <p><b>Notes:</b> <sup>1</sup>50G capability is for use with 50G DACs for both interconnect and VSF stacking. 50G SR transceivers have been added with a minimum software of 10.09.1010. VSF stacking not supported on 1G ports.</p>
	<b>Operating relative humidity</b>	15% to 95% @ 104°F (40°C) non-condensing
	<b>Non-operating temperature</b>	-40°F to 158°F (-40°C to 70°C) up to 15,000 ft
	<b>Non-operating humidity</b>	15% to 90% @ 149°F (65°C) non-condensing
	<b>Max operating altitude</b>	10,000 feet (3.04 km) Max
	<b>Max non-operating altitude</b>	15,000 feet (4.6 km) Max
	<b>Acoustic</b>	<p>Sound Power, LWAd = 4.9 Bel          Sound Pressure, LpAm (Bystander) = 32.6 dB</p>
	<b>Primary airflow</b>	Front and side-to-back
<b>Electrical Characteristics</b>	<b>Frequency</b>	50Hz/60Hz
	<b>AC voltage</b>	<p>JL670A PSU:          110V-120V/208V-240V          JL086A PSU: 100V-240V          JL087A PSU: 110V-240V</p>
	<b>Current (for voltages listed above)</b>	<p>JL670A PSU: 11A/8A          JL086A PSU: 8A/3.5A          JL087A PSU: 12A/5A</p>
	<b>Power consumption (230VAC)</b>	<p>With JL086A PSU:          Idle: 90W          100% Traffic Rate: 143W</p>

## Technical Specifications

		<p>With JL087A PSU: Idle: 90W 100% Traffic Rate: 140W</p> <p>With JL670A PSU: Idle: 101W 100% Traffic Rate: 152W</p>
<b>Safety</b>	Include US, Canada, Europe, Worldwide	<p>Europe: EN 62368-1:2014 +A11:2017 2nd Ed. EN 62368-1:2020 +A11:2020 3rd Ed.</p> <p>UK: BS EN 62368-1:2014 + A11:2017 2nd Ed BS EN 62368-1:2020 + A11:2020 3rd Ed</p> <p>US/Canada: UL 62368-1 2nd Ed. CAN/CSA-C22.2 No. 62368-1-14 2nd Ed.</p> <p>Worldwide: IEC 60950-1:2005 + Am1:2009 + Am2:2013 w/all known National Deviations IEC 62368-1:2014 2<sup>nd</sup> Ed. w/all known National Deviations IEC 62368-1:2018 3<sup>rd</sup> Ed. w/all known National Deviations</p>
<b>Emissions</b>	Include US, Canada, Europe, Worldwide	<p>Europe: EN 55032:2015 +A11:2020, Class A EN 55035:2017 +A11:2020 EN 61000-3-2:2014, Class A EN 61000-3-3:2013</p> <p>US/Canada: FCC CFR47 Part 15:2014, Class A ICES-003 Class A</p> <p>Worldwide: VCCI Class A CISPR 32 Class A CISPR 35:2016</p>
<b>Lasers</b>	Include US, Canada, Europe, Worldwide	EN 60825-1:2014 / IEC 60825-1:2014 Class 1 Class 1 Laser Products / Laser Klasse 1 (Applicable for accessories – Optical Transceivers only)
<b>Immunity</b>	<b>Generic</b>	CISPR 35
	<b>EN</b>	EN 55035:2017
	<b>ESD</b>	IEC 61000-4-2
	<b>Radiated</b>	IEC 61000-4-3
	<b>EFT/Burst</b>	IEC 61000-4-4
	<b>Surge</b>	IEC 61000-4-5
	<b>Conducted</b>	IEC 61000-4-6
	<b>Power frequency magnetic field</b>	IEC 61000-4-8
	<b>Voltage dips and interruptions</b>	IEC 61000-4-11
	<b>Harmonics</b>	IEC 61000-3-2, EN 61000-3-2
	<b>Flicker</b>	IEC 61000-3-3, EN 61000-3-3
<b>Mounting and Enclosure</b>	Mounts in an EIA standard 19 in. telco rack or equipment cabinet. Horizontal surface mounting only. 2-post rack kit included.	



## Technical Specifications

HPE Aruba Networking 6300M 24p SFP+ LRM support and 2p 50G and 2p 25G MACsec Switch (R8S92A)																															
<b>Description</b>	24x 1G/10G SFP+ ports (LRM + MACsec) 2x 10G/25G/50G <sup>1</sup> SFP ports 2x 10G/25G SFP ports (MACsec) 1x USB-C Console Port 1x RJ Console Port 1x OOBM port 1x USB Type A Host port <b>Notes:</b> <sup>1</sup> 50G capability is for use with 50G DACs for both interconnect and VSF stacking. 50G SR transceivers have been added with a minimum software of 10.09.1010. VSF stacking not supported on 1G ports.																														
<b>Power Supplies</b>	2 field-replaceable, hotswappable power supply slots 1 minimum power supply required (ordered separately)  Supported PSUs JL085A JL757A PSU																														
<b>Fans</b>	The switch has two fan tray slots and comes with two fan trays installed. Min 2 fan trays required. Fan trays are field replaceable and hotswappable. Each fan tray contains two fans.																														
<b>Physical Characteristics</b>	<table border="1"> <tr> <td><b>Dimensions</b></td> <td>(H) 4.4 cm x (W) 44.2 cm x (D) 38.5 cm (1.73" x 17.4" x 15.2")</td> </tr> <tr> <td><b>Weight</b></td> <td>5.47 kg (12.06 lbs)</td> </tr> </table>	<b>Dimensions</b>	(H) 4.4 cm x (W) 44.2 cm x (D) 38.5 cm (1.73" x 17.4" x 15.2")	<b>Weight</b>	5.47 kg (12.06 lbs)																										
<b>Dimensions</b>	(H) 4.4 cm x (W) 44.2 cm x (D) 38.5 cm (1.73" x 17.4" x 15.2")																														
<b>Weight</b>	5.47 kg (12.06 lbs)																														
<b>Mounting and Enclosure</b>	Mounts in an EIA- standard 19 in. telco rack or equipment cabinet. Horizontal surface mounting only. 2-post rack kit included.																														
<b>Additional Specifications</b>	<table border="1"> <tr> <td><b>CPU</b></td> <td>Quad Core ARM Cortex™ A72 @ 1.8GHz</td> </tr> <tr> <td><b>Memory and Flash</b></td> <td>8 GB DDR4 32 GB eMMC</td> </tr> <tr> <td><b>Packet Buffer</b></td> <td>16 MB</td> </tr> </table>	<b>CPU</b>	Quad Core ARM Cortex™ A72 @ 1.8GHz	<b>Memory and Flash</b>	8 GB DDR4 32 GB eMMC	<b>Packet Buffer</b>	16 MB																								
<b>CPU</b>	Quad Core ARM Cortex™ A72 @ 1.8GHz																														
<b>Memory and Flash</b>	8 GB DDR4 32 GB eMMC																														
<b>Packet Buffer</b>	16 MB																														
<b>Performance</b>	<table border="1"> <tr> <td><b>System switching capacity</b></td> <td>880 Gbps</td> </tr> <tr> <td><b>System throughput capacity</b></td> <td>660 Mpps</td> </tr> <tr> <td><b>Model switching capacity</b></td> <td>880 Gbps</td> </tr> <tr> <td><b>Model throughput capacity</b></td> <td>654 Mpps</td> </tr> <tr> <td><b>Average latency (LIFO, 64-byte packets)</b></td> <td>           1Gbps: 4.24µSec            10Gbps: 1.50µSec            25Gbps: 2.91µSec            50Gbps<sup>1</sup>: 3.49µSec  <b>Notes:</b> <sup>1</sup>50G capability is for use with 50G DACs for both interconnect and VSF stacking. 50G SR transceivers have been added with a minimum software of 10.09.1010. VSF stacking not supported on 1G ports.         </td> </tr> <tr> <td><b>Stack size</b></td> <td>10 members</td> </tr> <tr> <td><b>Max stacking distance</b></td> <td>Up to 10 kms with long range transceivers</td> </tr> <tr> <td><b>Stacking bandwidth</b></td> <td>200 Gbps</td> </tr> <tr> <td><b>Switched virtual interfaces (dual stack)</b></td> <td>1,024</td> </tr> <tr> <td><b>IPv4 host table (ARP)</b></td> <td>49,152</td> </tr> <tr> <td><b>IPv6 host table (ND)</b></td> <td>49,152</td> </tr> <tr> <td><b>IPv4 unicast routes</b></td> <td>61,000</td> </tr> <tr> <td><b>IPv6 unicast routes</b></td> <td>61,000</td> </tr> <tr> <td><b>IPv4 multicast routes</b></td> <td>8,192</td> </tr> <tr> <td><b>IPv6 multicast routes</b></td> <td>8,192</td> </tr> </table>	<b>System switching capacity</b>	880 Gbps	<b>System throughput capacity</b>	660 Mpps	<b>Model switching capacity</b>	880 Gbps	<b>Model throughput capacity</b>	654 Mpps	<b>Average latency (LIFO, 64-byte packets)</b>	1Gbps: 4.24µSec 10Gbps: 1.50µSec 25Gbps: 2.91µSec 50Gbps <sup>1</sup> : 3.49µSec <b>Notes:</b> <sup>1</sup> 50G capability is for use with 50G DACs for both interconnect and VSF stacking. 50G SR transceivers have been added with a minimum software of 10.09.1010. VSF stacking not supported on 1G ports.	<b>Stack size</b>	10 members	<b>Max stacking distance</b>	Up to 10 kms with long range transceivers	<b>Stacking bandwidth</b>	200 Gbps	<b>Switched virtual interfaces (dual stack)</b>	1,024	<b>IPv4 host table (ARP)</b>	49,152	<b>IPv6 host table (ND)</b>	49,152	<b>IPv4 unicast routes</b>	61,000	<b>IPv6 unicast routes</b>	61,000	<b>IPv4 multicast routes</b>	8,192	<b>IPv6 multicast routes</b>	8,192
<b>System switching capacity</b>	880 Gbps																														
<b>System throughput capacity</b>	660 Mpps																														
<b>Model switching capacity</b>	880 Gbps																														
<b>Model throughput capacity</b>	654 Mpps																														
<b>Average latency (LIFO, 64-byte packets)</b>	1Gbps: 4.24µSec 10Gbps: 1.50µSec 25Gbps: 2.91µSec 50Gbps <sup>1</sup> : 3.49µSec <b>Notes:</b> <sup>1</sup> 50G capability is for use with 50G DACs for both interconnect and VSF stacking. 50G SR transceivers have been added with a minimum software of 10.09.1010. VSF stacking not supported on 1G ports.																														
<b>Stack size</b>	10 members																														
<b>Max stacking distance</b>	Up to 10 kms with long range transceivers																														
<b>Stacking bandwidth</b>	200 Gbps																														
<b>Switched virtual interfaces (dual stack)</b>	1,024																														
<b>IPv4 host table (ARP)</b>	49,152																														
<b>IPv6 host table (ND)</b>	49,152																														
<b>IPv4 unicast routes</b>	61,000																														
<b>IPv6 unicast routes</b>	61,000																														
<b>IPv4 multicast routes</b>	8,192																														
<b>IPv6 multicast routes</b>	8,192																														

## Technical Specifications

	<b>MAC table capacity</b>	32,768
	<b>IGMP groups</b>	4,096
	<b>MLD groups</b>	8,192
	<b>IPv4/IPv6/MAC ACL entries (ingress)</b>	20,480/5,120/20,480
	<b>IPv4/IPv6/MAC ACL entries (egress)</b>	8,192/2,048/8,192
	<b>VFR</b>	256
<b>Environment</b>	<b>Operating temperature</b>	32°F to 113°F (0°C to 45°C) up to 5,000 ft. Derate -1 degree C for every 1,000 ft from 5,000 ft to 10,000 ft. Can support excursion to 131°F (55°C) for short periods <sup>2</sup> of time. 55C excursion not supported when 10G LRM/LR/ER inserted: <ul style="list-style-type: none"> <li>When 10G BT and 10G LRM/LR/ER transceivers are installed together, fan redundancy is only supported up to 104°F (40°C), 5,000ft</li> </ul> <b>Notes:</b> <sup>2</sup> No more than 96 consecutive hours and no more than 360 hours total (15 days) in 1 year.
	<b>Operating relative humidity</b>	15% to 95% @ 104°F (40°C) non-condensing
	<b>Non-operating temperature</b>	-40°F to 158°F (-40°C to 70°C) up to 15,000 ft
	<b>Non-operating humidity</b>	15% to 90% @ 149°F (65°C) non-condensing
	<b>Max operating altitude</b>	10,000 feet (3.04 km) Max
	<b>Max non-operating altitude</b>	15,000 feet (4.6 km) Max
	<b>Acoustic</b>	Sound Power, LWAd = 4.6 Bel Sound Pressure, LpAm (Bystander) = 30.1 dB
	<b>Primary airflow</b>	Front and side-to-back
<b>Electrical Characteristics</b>	<b>Frequency</b>	50Hz/60Hz
	<b>AC voltage</b>	JL085A PSU: 100V-240V
	<b>Current (for voltages listed above)</b>	JL085A PSU: 3A/1.2A
	<b>Power consumption (230VAC)</b>	Idle: 87W 100% Traffic Rate: 131W
<b>Safety</b>	Include US, Canada, Europe, Worldwide	Europe: EN 62368-1:2014 +A11:2017 2nd Ed. EN 62368-1:2020 +A11:2020 3rd Ed. UK: BS EN 62368-1:2014 + A11:2017 2nd Ed BS EN 62368-1:2020 + A11:2020 3rd Ed US/Canada: UL 62368-1 2nd Ed. CAN/CSA-C22.2 No. 62368-1-14 2nd Ed. Worldwide: IEC 60950-1:2005 + Am1:2009 + Am2:2013 w/all known National Deviations IEC 62368-1:2014 2 <sup>nd</sup> Ed. w/all known National Deviations IEC 62368-1:2018 3 <sup>rd</sup> Ed. w/all known National Deviations
<b>Emissions</b>	Include US, Canada, Europe, Worldwide	Europe: EN 55032:2015 +A11:2020, Class A EN 55035:2017 +A11:2020 EN 61000-3-2:2014, Class A EN 61000-3-3:2013 US/Canada: FCC CFR47 Part 15:2014, Class A ICES-003 Class A Worldwide:

## Technical Specifications

		VCCI Class A CISPR 32 Class A CISPR 35:2016
<b>Lasers</b>	Include US, Canada, Europe, Worldwide	EN 60825-1:2014 / IEC 60825-1:2014 Class 1 Class 1 Laser Products / Laser Klasse 1 (Applicable for accessories – Optical Transceivers only)
<b>Immunity</b>	<b>Generic</b>	CISPR 35
	<b>EN</b>	EN 55035:2017
	<b>ESD</b>	IEC 61000-4-2
	<b>Radiated</b>	IEC 61000-4-3
	<b>EFT/Burst</b>	IEC 61000-4-4
	<b>Surge</b>	IEC 61000-4-5
	<b>Conducted</b>	IEC 61000-4-6
	<b>Power frequency magnetic field</b>	IEC 61000-4-8
	<b>Voltage dips and interruptions</b>	IEC 61000-4-11
	<b>Harmonics</b>	IEC 61000-3-2, EN 61000-3-2
<b>Flicker</b>	IEC 61000-3-3, EN 61000-3-3	
<b>Mounting and Enclosure</b>	Mounts in an EIA standard 19 in. telco rack or equipment cabinet. Horizontal surface mounting only. 2-post rack kit included.	

### HPE Aruba Networking 6300M 24-port SFP+ and 4-port SFP56 Switch (JL658A)

### HPE Aruba Networking 6300M 24p SFP+ 1G/10G 4p SFP56 50G TAA Switch (S0G03A)

<b>Description</b>	24x 1G/10G SFP+ ports 4x 1G/10G/25G SFP ports	
<b>Additional Ports and Slots</b>	1x USB-C console port 1x OOBM 1x USB Type A host port	
<b>Power Supplies</b>	2 field-replaceable, hot-swappable power supply slots. 1 minimum power supply required (ordered separately) Supports JL085A PSU	
<b>Fan Tray</b>	The switch has two fan tray slots and comes with two fan trays installed. Fan trays are field replaceable and hot-swappable. Minimum 2 fan trays required. Each fan tray is comprised of two fans.	
<b>Physical Characteristics</b>	<b>Dimensions</b>	17.4 (w) x 15.2 (d) x 1.73 (h) in (44.2 x 38.5 x 4.4 cm)
	<b>Weight</b>	12.78 lbs (5.8 Kg)
<b>Mounting and Enclosure</b>	Mounts in an EIA- standard 19 in. telco rack or equipment cabinet. Horizontal surface mounting only. 2-post rack kit included.	
<b>CPU</b>	Quad Core ARM Cortex™ A72 @ 1.8GHz	
<b>Memory and Flash</b>	8 GBytes DDR4 32 GBytes eMMC	
<b>Packet Buffer</b>	8 MB packet buffer memory	
<b>Performance</b>	<b>System switching capacity</b>	880 Gbps
	<b>System throughput capacity</b>	660 Mpps
	<b>Model switching capacity</b>	880 Gbps
	<b>Model throughput capacity</b>	654 Mpps
	<b>Average latency (LIFO, 64-byte packets)</b>	1Gbps: 1.99µSec 10Gbps: 1.49µSec 25Gbps: 2.85µSec





## Technical Specifications

		50Gbps: 2.82μSec
	<b>Stack size</b>	10 members
	<b>Max stacking distance</b>	Up to 10 kms with long range transceivers
	<b>Stacking bandwidth</b>	200 Gbps (400 Gbps at full duplex)
	<b>Switched virtual interfaces (dual stack)</b>	1,024
	<b>IPv4 host table (ARP)</b>	49,152
	<b>IPv6 host table (ND)</b>	49,152
	<b>IPv4 unicast routes</b>	61,000
	<b>IPv6 unicast routes</b>	61,000
	<b>IPv4 multicast routes</b>	8,192
	<b>IPv6 multicast routes</b>	8,192
	<b>MAC table capacity</b>	32,768
	<b>IGMP groups</b>	4,096
	<b>MLD groups</b>	8,192
	<b>IPv4/IPv6/MAC ACL entries (ingress)</b>	20,480/5,120/20,480
	<b>IPv4/IPv6/MAC ACL entries (egress)</b>	8,192/2,048/8,192
	<b>VFR</b>	256
<b>Environment</b>	<b>Operating temperature</b>	32°F to 113°F (0°C to 45°C), up to 5,000 feet 32°F to 104°F (0°C to 40°C), 5,001 to 10,000 feet 1°C de-rating per 1,000 feet above 5,000 feet Can support excursion to 131°F (55°C) for short periods <sup>1</sup> of time. Operating temperature is reduced to 32°F (0°C) to 104°F (40°C) up to 5000ft when 10G SFP+ LR or ER Transceivers are installed.
	<b>Operating relative humidity</b>	15% to 95% relative humidity at 104°F (40°C), non-condensing
	<b>Non-operating temperature</b>	-40°F to 158°F (-40°C to 70°C)
	<b>Non-operating humidity</b>	15% to 95% relative humidity at 149°F(65°C), non-condensing
	<b>Max operating altitude</b>	Up to 10,000ft (3.048 Km)
	<b>Max non-operating altitude</b>	Up to 15,000ft (3.048 Km)
	<b>Acoustic</b>	Sound power, LWAd = 4.9 Bel Sound pressure, LpAm (bystander) = 31.0 dB
	<b>Primary airflow</b>	Front and side-to-back
<b>Electrical Characteristics</b>	<b>Frequency</b>	50-60 Hz
	<b>AC voltage</b>	JL085A PSU: 100V-240V
	<b>Current (for voltages listed above)</b>	JL085A PSU: 3A/1.2A
	<b>Power consumption (230VAC)</b>	Idle: 51W 100% traffic rate: 85W
<b>Safety</b>	<b>Europe:</b> EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011 + A2:2013 <b>US:</b> UL 60950-1 2nd Ed <b>Canada:</b> CAN/CSA-C22.2 No. 60950-1-07 <b>Worldwide:</b> IEC 60950-1:2005 w/all known National Deviations	
<b>Emissions</b>	<b>Europe:</b> EN 55022:2010, Class A EN 55032:2012, Class A EN 55024:2010, EN 61000-3-2:2014, EN 61000-3-3:2013 <b>US:</b> FCC part 15 Class A <b>Canada:</b> ICES-003 Class A <b>Worldwide:</b> VCCI Class A, CISPR 22 Class A CISPR 32 Class A CISPR 24:2010	
<b>Lasers</b>	EN 60825-1:2007 / IEC 60825-1:2007 Class 1	

## Technical Specifications

<b>Immunity</b>	Class 1 Laser Products / Laser Klasse 1 (Applicable for accessories - Optical Transceivers only)	
	<b>Generic</b>	CISPR 24 / CISPR 35
	<b>EN</b>	EN 55024:2010 / EN 55035:2017
	<b>ESD</b>	IEC 61000-4-2
	<b>Radiated</b>	IEC 61000-4-3
	<b>EFT/Burst</b>	IEC 61000-4-4
	<b>Surge</b>	IEC 61000-4-5
	<b>Conducted</b>	IEC 61000-4-6
	<b>Power frequency magnetic field</b>	IEC 61000-4-8
	<b>Voltage dips and interruptions</b>	IEC 61000-4-11
	<b>Harmonics</b>	IEC 61000-3-2, EN 61000-3-2
<b>Flicker</b>	IEC 61000-3-3, EN 61000-3-3	
<b>Notes:</b> <sup>1</sup> Not more than 96 consecutive hours or 360 hours total or 15 occurrences in a 1-year period.		

### HPE Aruba Networking 6300M 48- port HPE Smart Rate 1/2.5/5GbE Class 6 PoE and 4-port SFP56 Switch (JL659A)

### HPE Aruba Networking 6300M 48p Smart Rate 1G/2.5G/5G Class6 PoE 4p SFP56 50G TAA Switch (SOG04A)

<b>Description</b>	48x ports SmartRate 100M/1G/2.5G/5G BASE-T Class 6 PoE ports supporting up to 60W per port 4x 1G/10G/25G SFP ports Supports PoE Standards IEEE 802.3af, 802.3at and 802.3bt (up to 60W)	
<b>Additional Ports and Slots</b>	1x USB-C console port 1x OOBM 1x USB Type A host port	
<b>Power Supplies</b>	2 field-replaceable, hot-swappable power supply slots 1 minimum power supply required (ordered separately) Supported PSUs: JL086A, JL087A, JL670A Max PoE power: 2880W	
<b>Fan Tray</b>	The switch has two fan tray slots and comes with two fan trays installed. Fan trays are field replaceable and hot-swappable. Minimum 2 fan trays required. Each fan tray is comprised of two fans.	
<b>Physical Characteristics</b>	<b>Dimensions</b>	17.4 (w) x 15.2 (d) x 1.73 (h) in (44.2 x 38.5 x 4.4 cm)
	<b>Weight</b>	14.8 lbs (6.71 kg)
<b>Mounting and Enclosure</b>	Mounts in an EIA- standard 19 in. telco rack or equipment cabinet. Horizontal surface mounting only. 2-post rack kit included.	
<b>CPU</b>	Quad Core ARM Cortex™ A72 @ 1.8GHz	
<b>Memory and Flash</b>	8 GBytes DDR4 32 GBytes eMMC	
<b>Packet Buffer</b>	8 MB packet buffer memory	
<b>Performance</b>	<b>System switching capacity</b>	880 Gbps
	<b>System throughput capacity</b>	660 Mpps
	<b>Model switching capacity</b>	880 Gbps
	<b>Model throughput capacity</b>	654 Mpps
	<b>Average latency (LIFO, 64-byte packets)</b>	1Gbps: 4.24µSec
		10Gbps: 1.50µSec
		25Gbps: 2.91µSec
<b>Stack size</b>	50Gbps: 3.49µSec	
	10 members	

## Technical Specifications

	<b>Max stacking distance</b>	Up to 10 kms with long range transceivers
	<b>Stacking bandwidth</b>	200 Gbps (400 Gbps at full duplex)
	<b>Switched virtual interfaces (dual stack)</b>	1,024
	<b>IPv4 host table (ARP)</b>	49,152
	<b>IPv6 host table (ND)</b>	49,152
	<b>IPv4 unicast routes</b>	61,000
	<b>IPv6 unicast routes</b>	61,000
	<b>IPv4 multicast routes</b>	8,192
	<b>IPv6 multicast routes</b>	8,192
	<b>MAC table capacity</b>	32,768
	<b>IGMP groups</b>	4,096
	<b>MLD groups</b>	8,192
	<b>IPv4/IPv6/MAC ACL entries (ingress)</b>	20,480/5,120/20,480
	<b>IPv4/IPv6/MAC ACL entries (egress)</b>	8,192/2,048/8,192
	<b>VRF</b>	256
<b>Environment</b>	<b>Operating temperature</b>	32°F to 113°F (0°C to 45°C), up to 5,000 feet 32°F to 104°F (0°C to 40°C), 5,001 to 10,000 feet 1°C de-rating per 1,000 feet above 5,000 feet
	<b>Operating humidity</b>	15% to 95% relative humidity at 104°F (40°C), non-condensing
	<b>Non-operating temperature</b>	-40°F to 158°F (-40°C to 70°C)
	<b>Non-operating humidity</b>	15% to 95% relative humidity at 149°F(65°C), non-condensing
	<b>Max operating altitude</b>	Up to 10,000ft (3.048 Km)
	<b>Max non-operating altitude</b>	Up to 15,000ft (3.048 Km)
	<b>Acoustic</b>	Sound power, LWAd = 4.8 Bel Sound pressure, LpAm (bystander) = 30.6 dB
	<b>Primary airflow</b>	Front and side-to-back
<b>Electrical Characteristics</b>	<b>Frequency</b>	50-60 Hz
	<b>AC voltage</b>	JL670A PSU: 110V-120V/208V-240V JL086A PSU: 100V-240V JL087A PSU: 110V-240V
	<b>Current (for voltages listed above)</b>	JL670A PSU: 11A/8A JL086A PSU: 8A/3.5A JL087A PSU: 12A/5A
	<b>Power consumption (230VAC)</b>	With JL086A PSU: Idle: 133W 100% traffic rate: 199W  With JL087A PSU: Idle: 138W 100% traffic rate: 193W  With JL670A PSU: Idle: 140W 100% traffic rate: 201W
<b>Safety</b>	<b>Europe:</b> EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011 + A2:2013 <b>US:</b> UL 60950-1 2nd Ed.. <b>Canada:</b> CAN/CSA-C22.2 No. 60950-1-07 <b>Worldwide:</b> IEC 60950-1:2005 w/all known National Deviations	

## Technical Specifications

<b>Emissions</b>	<b>Europe:</b> EN 55022:2010, Class A EN 55032:2012, Class A EN 55024:2010, EN 61000-3-2:2014, EN 61000-3-3:2013 <b>US:</b> FCC part 15 Class A <b>Canada:</b> ICES-003 Class A <b>Worldwide:</b> VCCI Class A, CISPR 22 Class A CISPR 32 Class A CISPR 24:2010	
<b>Lasers</b>	EN 60825-1:2007 / IEC 60825-1:2007 Class 1 Class 1 Laser Products / Laser Klasse 1 (Applicable for accessories - Optical Transceivers only)	
<b>Immunity</b>	<b>Generic</b>	CISPR 24 / CISPR 35
	<b>EN</b>	EN 55024:2010 / EN 55035:2017
	<b>ESD</b>	IEC 61000-4-2
	<b>Radiated</b>	IEC 61000-4-3
	<b>EFT/Burst</b>	IEC 61000-4-4
	<b>Surge</b>	IEC 61000-4-5
	<b>Conducted</b>	IEC 61000-4-6
	<b>Power frequency magnetic field</b>	IEC 61000-4-8
	<b>Voltage dips and interruptions</b>	IEC 61000-4-11
	<b>Harmonics</b>	IEC 61000-3-2, EN 61000-3-2
<b>Flicker</b>	IEC 61000-3-3, EN 61000-3-3	

### HPE Aruba Networking 6300M 24- port HPE Smart Rate 1/2.5/5GbE Class 6 PoE and 4-port SFP56 Switch (JL660A)

### HPE Aruba Networking 6300M 24p Smart Rate 1G/2.5G/5G Class6 PoE 4p SFP56 50G TAA Switch (SOG05A)

<b>Description</b>	24x ports SmartRate 100M/1G/2.5G/5G BASE-T Class 6 PoE ports supporting up to 60W per port 4x 1G/10G/25G SFP ports Supports PoE Standards IEEE 802.3af, 802.3at and 802.3bt (up to 60W)	
<b>Additional Ports and Slots</b>	1x USB-C console port 1x OOBM 1x USB Type A host port	
<b>Power Supplies</b>	2 field-replaceable, hot-swappable power supply slots 1 minimum power supply required (ordered separately) Supported PSUs: JL086A, JL087A, JL670A Max PoE power: 1440W	
<b>Fan Tray</b>	The switch has two fan tray slots and comes with one fan tray installed. Fan trays are field replaceable and hot-swappable. Minimum 1 fan tray required. Second fan tray ordered separately. Each fan tray is comprised of two fans.	
<b>Physical Characteristics</b>	<b>Dimensions</b>	17.4 (w) x 15.2 (d) x 1.73 (h) in (44.2 x 38.5 x 4.4 cm)
	<b>Weight</b>	13.36 lbs (6.06 kg)
<b>Mounting and Enclosure</b>	Mounts in an EIA- standard 19 in. telco rack or equipment cabinet. Horizontal surface mounting only. 2-post rack kit included.	
<b>CPU</b>	Quad Core ARM Cortex™ A72 @ 1.8GHz	
<b>Memory and Flash</b>	8 GBytes DDR4 32 GBytes eMMC	
<b>Packet Buffer</b>	8 MB packet buffer memory	
<b>Performance</b>	<b>System switching capacity</b>	880 Gbps
	<b>System throughput capacity</b>	660 Mpps
	<b>Model switching capacity</b>	640 Gbps
	<b>Model throughput capacity</b>	476 Mpps

## Technical Specifications

	<b>Average latency (LIFO, 64-byte packets)</b>	1Gbps: 4.24μSec 10Gbps: 1.50μSec 25Gbps: 2.91μSec 50Gbps: 3.49μSec
	<b>Stack size</b>	10 members
	<b>Max stacking distance</b>	Up to 10 kms with long range transceivers
	<b>Stacking bandwidth</b>	200 Gbps (400 Gbps at full duplex)
	<b>Switched virtual interfaces (dual stack)</b>	1,024
	<b>IPv4 host table (ARP)</b>	49,152
	<b>IPv6 host table (ND)</b>	49,152
	<b>IPv4 unicast routes</b>	61,000
	<b>IPv6 unicast routes</b>	61,000
	<b>IPv4 multicast routes</b>	8,192
	<b>IPv6 multicast routes</b>	8,192
	<b>MAC table capacity</b>	32,768
	<b>IGMP groups</b>	4,096
	<b>MLD groups</b>	8,192
	<b>IPv4/IPv6/MAC ACL entries (ingress)</b>	20,480/5,120/20,480
	<b>IPv4/IPv6/MAC ACL entries (egress)</b>	8,192/2,048/8,192
	<b>VRF</b>	256
<b>Environment</b>	<b>Operating temperature</b>	32°F to 113°F (0°C to 45°C), up to 5,000 feet 32°F to 104°F (0°C to 40°C), 5,001 to 10,000 feet 1°C de-rating per 1,000 feet above 5,000 feet Can support excursion to 131°F (55°C) for short periods <sup>1</sup> of time. Requires two fan trays to support excursion.
	<b>Operating humidity</b>	15% to 95% relative humidity at 104°F (40°C), non-condensing
	<b>Non-operating temperature</b>	-40°F to 158°F (-40°C to 70°C)
	<b>Non-operating humidity</b>	15% to 95% relative humidity at 149°F(65°C), non-condensing
	<b>Max operating altitude</b>	Up to 10,000ft (3.048 Km)
	<b>Max non-operating altitude</b>	Up to 15,000ft (3.048 Km)
	<b>Acoustic</b>	Sound power, LWAd = 5.2 Bel Sound pressure, LpAm (bystander) = 34.2 dB
	<b>Primary airflow</b>	Front and side-to-back
<b>Electrical Characteristics</b>	<b>Frequency</b>	50-60 Hz
	<b>AC voltage</b>	JL670A PSU: 110V-120V/208V-240V JL086A PSU: 100V-240V JL087A PSU: 110V-240V
	<b>Current (for voltages listed above)</b>	JL670A PSU: 11A/8A JL086A PSU: 8A/3.5A JL087A PSU: 12A/5A
	<b>Power consumption (230VAC)</b>	With JL086A PSU: Idle: 93W 100% traffic rate: 137W With JL087A PSU: Idle: 91W 100% traffic rate: 131W With JL670A PSU:

## Technical Specifications

		Idle: 98W 100% traffic rate: 139W
<b>Safety</b>	<b>Europe:</b> EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011 + A2:2013 <b>US:</b> UL 60950-1 2nd Ed.. <b>Canada:</b> CAN/CSA-C22.2 No. 60950-1-07 <b>Worldwide:</b> IEC 60950-1:2005 w/all known National Deviations	
<b>Emissions</b>	<b>Europe:</b> EN 55022:2010, Class A EN 55032:2012, Class A EN 55024:2010, EN 61000-3-2:2014 EN 61000-3-3:2013 <b>US:</b> FCC part 15 Class A <b>Canada:</b> ICES-003 Class A <b>Worldwide:</b> VCCI Class A, CISPR 22 Class A CISPR 32 Class A CISPR 24:2010	
<b>Lasers</b>	EN 60825-1:2007 / IEC 60825-1:2007 Class 1 Class 1 Laser Products / Laser Klasse 1 (Applicable for accessories - Optical Transceivers only)	
<b>Immunity</b>	<b>Generic</b>	CISPR 24 / CISPR 35
	<b>EN</b>	EN 55024:2010 / EN 55035:2017
	<b>ESD</b>	IEC 61000-4-2
	<b>Radiated</b>	IEC 61000-4-3
	<b>EFT/Burst</b>	IEC 61000-4-4
	<b>Surge</b>	IEC 61000-4-5
	<b>Conducted</b>	IEC 61000-4-6
	<b>Power frequency magnetic field</b>	IEC 61000-4-8
<b>Immunity</b>	<b>Voltage dips and interruptions</b>	IEC 61000-4-11
	<b>Harmonics</b>	IEC 61000-3-2, EN 61000-3-2
	<b>Flicker</b>	IEC 61000-3-3, EN 61000-3-3

**Notes:** <sup>1</sup> Not more than 96 consecutive hours or 360 hours total or 15 occurrences in a 1-year period.

### HPE Aruba Networking 6300M 48-port 1GbE Class 4 PoE and 4-port SFP56 Switch (JL661A)

### HPE Aruba Networking 6300M 48p 10M/100M/1G Class4 PoE 4p SFP56 50G TAA Switch (S0G06A)

<b>Description</b>	48x 10/100/1000 BASE-T PoE+ ports supporting up to 30W per port 4x 1G/10G/25G SFP ports Supports PoE Standards IEEE 802.3af, 802.3at	
<b>Additional Ports and Slots</b>	1x USB-C console port 1x OOBM 1x USB Type A host port	
<b>Power Supplies</b>	2 field-replaceable, hot-swappable power supply slots 1 minimum power supply required (ordered separately) Supported PSUs: JL086A, JL087A, JL670A Max PoE power: 1600W	
<b>Fan Tray</b>	The switch has two fan tray slots and comes with one fan tray installed. Fan trays are field replaceable and hot-swappable. Minimum 1 fan tray required. Second fan tray ordered separately. Each fan tray is comprised of two fans.	
<b>Physical Characteristics</b>	<b>Dimensions</b>	17.4 (w) x 15.2 (d) x 1.73 (h) in (44.2 x 38.5 x 4.4 cm)
	<b>Weight</b>	12.61 lbs (5.72 kg)
<b>Mounting and Enclosure</b>	Mounts in an EIA- standard 19 in. telco rack or equipment cabinet. Horizontal surface mounting only. 2-post rack kit included.	
<b>CPU</b>	Quad Core ARM Cortex™ A72 @ 1.8GHz	
<b>Memory and Flash</b>	8 GBytes DDR4 32 GBytes eMMC	
<b>Packet Buffer</b>	8 MB packet buffer memory	



## Technical Specifications

<b>Performance</b>	<b>System switching capacity</b>	880 Gbps	
	<b>System throughput capacity</b>	660 Mpps	
	<b>Model switching capacity</b>	496 Gbps	
	<b>Model throughput capacity</b>	369 Mpps	
	<b>Average latency (LIFO, 64-byte packets)</b>	1Gbps: 2.28µSec 10Gbps: 1.46µSec 25Gbps: 1.90µSec 50Gbps: 3.49µSec	
	<b>Stack size</b>	10 members	
	<b>Max stacking distance</b>	Up to 10 kms with long range transceivers	
	<b>Stacking bandwidth</b>	200 Gbps (400 Gbps at full duplex)	
	<b>Switched virtual interfaces (dual stack)</b>	1,024	
	<b>IPv4 host table (ARP)</b>	49,152	
	<b>IPv6 host table (ND)</b>	49,152	
	<b>IPv4 unicast routes</b>	61,000	
	<b>IPv6 unicast routes</b>	61,000	
	<b>IPv4 multicast routes</b>	8,192	
	<b>IPv6 multicast routes</b>	8,192	
	<b>MAC table capacity</b>	32,768	
	<b>IGMP groups</b>	4,096	
	<b>MLD groups</b>	8,192	
	<b>IPv4/IPv6/MAC ACL entries (ingress)</b>	20,480/5,120/20,480	
	<b>IPv4/IPv6/MAC ACL entries (egress)</b>	8,192/2,048/8,192	
	<b>VRF</b>	256	
	<b>Environment</b>	<b>Operating temperature</b>	32°F to 113°F (0°C to 45°C), up to 5,000 feet 32°F to 104°F (0°C to 40°C), 5,001 to 10,000 feet 1°C de-rating per 1,000 feet above 5,000 feet Can support excursion to 131°F (55°C) for short periods <sup>1</sup> of time.
		<b>Operating humidity</b>	15% to 95% relative humidity at 104°F (40°C), non-condensing
		<b>Non-operating temperature</b>	-40°F to 158°F (-40°C to 70°C)
		<b>Non-operating humidity</b>	15% to 95% relative humidity at 149°F(65°C), non-condensing
		<b>Max operating altitude</b>	Up to 10,000ft (3.048 Km)
<b>Max non-operating altitude</b>		Up to 15,000ft (3.048 Km)	
<b>Acoustic</b>		Sound power, LWAd = 4.7 Bel Sound pressure, LpAm (bystander) = 29.8 dB	
<b>Primary airflow</b>	Front and side-to-back		
<b>Electrical Characteristics</b>	<b>Frequency</b>	50-60 Hz	
	<b>AC voltage</b>	JL670A PSU: 110V-120V/208V-240V JL086A PSU: 100V-240V JL087A PSU: 110V-240V	
	<b>Current (for voltages listed above)</b>	JL670A PSU: 11A/8A JL086A PSU: 8A/3.5A JL087A PSU: 12A/5A	

## Technical Specifications

<b>Electrical Characteristics</b>	<b>Power consumption (230VAC)</b>	With JL086A PSU: Idle: 70W 100% traffic rate: 90W  With JL087A PSU: Idle: 71W 100% traffic rate: 88W  With JL670A PSU: Idle: 73W 100% traffic rate: 96W
<b>Safety</b>	<b>Europe:</b> EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011 + A2:2013 <b>US:</b> UL 60950-1 2nd Ed.. <b>Canada:</b> CAN/CSA-C22.2 No. 60950-1-07 <b>Worldwide:</b> IEC 60950-1:2005 w/all known National Deviations	
<b>Emissions</b>	<b>Europe:</b> EN 55022:2010, Class A EN 55032:2012, Class A EN 55024:2010, EN 61000-3-2:2014 EN 61000-3-3:2013 <b>US:</b> FCC part 15 Class A <b>Canada:</b> ICES-003 Class A <b>Worldwide:</b> VCCI Class A, CISPR 22 Class A CISPR 32 Class A CISPR 24:2010	
<b>Lasers</b>	EN 60825-1:2007 / IEC 60825-1:2007 Class 1 Class 1 Laser Products / Laser Klasse 1 (Applicable for accessories - Optical Transceivers only)	
<b>Immunity</b>	<b>Generic</b>	CISPR 24 / CISPR 35
	<b>EN</b>	EN 55024:2010 / EN 55035:2017
	<b>ESD</b>	IEC 61000-4-2
	<b>Radiated</b>	IEC 61000-4-3
	<b>EFT/Burst</b>	IEC 61000-4-4
<b>Immunity</b>	<b>Surge</b>	IEC 61000-4-5
	<b>Conducted</b>	IEC 61000-4-6
	<b>Power frequency magnetic field</b>	IEC 61000-4-8
	<b>Voltage dips and interruptions</b>	IEC 61000-4-11
	<b>Harmonics</b>	IEC 61000-3-2, EN 61000-3-2
	<b>Flicker</b>	IEC 61000-3-3, EN 61000-3-3
<b>Notes:</b> <sup>1</sup> Not more than 96 consecutive hours or 360 hours total or 15 occurrences in a 1-year period.		

### HPE Aruba Networking 6300M 24-port 1GbE Class 4 PoE and 4-port SFP56 Switch (JL662A)

### HPE Aruba Networking 6300M 24p 10M/100M/1G Class4 PoE 4p SFP56 50G TAA Switch (S0F99A)

<b>Description</b>	24x ports 10/100/1000 BaseT PoE+ ports supporting up to 30W per port 4x 1G/10G/25G/50G <sup>1</sup> SFP ports Supports PoE Standards IEEE 802.3af, 802.3at 1x USB-C Console Port 1x OOBM port 1x USB Type A Host port <b>Notes:</b> <sup>1</sup> 50G capability is for use with 50G DACs for both interconnect and VSF stacking. 50G SR transceivers have been added with a minimum software of 10.09.1010. VSF stacking not supported on 1G ports.
<b>Power Supplies</b>	2 field-replaceable, hot-swappable power supply slots 1 minimum power supply required (ordered separately) Supported PSUs: JL086A, JL087A, JL670A Max PoE power: 720W
<b>Fan Tray</b>	The switch has two fan tray slots and comes with one fan tray installed.



## Technical Specifications

	Fan trays are field replaceable and hot-swappable. Minimum 1 fan tray required. Second fan tray ordered separately. Each fan tray is comprised of two fans.	
<b>Physical Characteristics</b>	<b>Dimensions</b>	17.4 (w) x 15.2 (d) x 1.73 (h) in (44.2 x 38.5 x 4.4 cm)
	<b>Weight</b>	12.23 lbs (5.55 kg)
<b>Mounting and Enclosure</b>	Mounts in an EIA- standard 19 in. telco rack or equipment cabinet. Horizontal surface mounting only. 2-post rack kit included.	
<b>CPU</b>	Quad Core ARM Cortex™ A72 @ 1.8GHz	
<b>Memory and Flash</b>	8 GBytes DDR4 32 GBytes eMMC	
<b>Packet Buffer</b>	8 MB packet buffer memory	
<b>Performance</b>	<b>System switching capacity</b>	880 Gbps
	<b>System throughput capacity</b>	660 Mpps
	<b>Model switching capacity</b>	448 Gbps
	<b>Model throughput capacity</b>	334 Mpps
	<b>Average latency (LIFO, 64-byte packets)</b>	1Gbps: 2.28μSec
		10Gbps: 1.46μSec
		25Gbps: 1.90μSec
		50Gbps: 3.49μSec
	<b>Stack size</b>	10 members
	<b>Max stacking distance</b>	Up to 10 kms with long range transceivers
	<b>Stacking bandwidth</b>	200 Gbps (400 Gbps at full duplex)
	<b>Switched virtual interfaces (dual stack)</b>	1,024
	<b>IPv4 host table (ARP)</b>	49,152
	<b>IPv6 host table (ND)</b>	49,152
	<b>IPv4 unicast routes</b>	61,000
	<b>IPv6 unicast routes</b>	61,000
	<b>IPv4 multicast routes</b>	8,192
<b>IPv6 multicast routes</b>	8,192	
<b>VRF</b>	256	
<b>Performance</b>	<b>MAC table capacity</b>	32,768
	<b>IGMP Groups</b>	4,096
	<b>MLD Groups</b>	8,192
	<b>IPv4/IPv6/MAC ACL entries (ingress)</b>	20,480/5,120/20,480
	<b>IPv4/IPv6/MAC ACL entries (egress)</b>	8,192/2,048/8,192
<b>Environment</b>	<b>Operating temperature</b>	32°F to 113°F (0°C to 45°C), up to 5,000 feet
		32°F to 104°F (0°C to 40°C), 5,001 to 10,000 feet
		1°C de-rating per 1,000 feet above 5,000 feet Can support excursion to 131°F (55°C) for short periods <sup>1</sup> of time.
	<b>Operating humidity</b>	15% to 95% relative humidity at 104°F (40°C), non-condensing
	<b>Non-operating temperature</b>	-40°F to 158°F (-40°C to 70°C)
	<b>Non-operating humidity</b>	15% to 95% relative humidity at 149°F(65°C), non-condensing
<b>Max operating altitude</b>	Up to 10,000ft (3.048 Km)	
<b>Max non-operating altitude</b>	Up to 15,000ft (3.048 Km)	

## Technical Specifications

	<b>Acoustic</b>	Sound power, LWAd = 4.7 Bel Sound pressure, LpAm (bystander) = 29.4 dB
	<b>Primary airflow</b>	Front and side-to-back
<b>Electrical Characteristics</b>	<b>Frequency</b>	50-60 Hz
	<b>AC voltage</b>	JL670A PSU: 110V-120V/208V-240V JL086A PSU: 100V-240V JL087A PSU: 110V-240V
	<b>Current (for voltages listed above)</b>	JL670A PSU: 11A/8A JL086A PSU: 8A/3.5A JL087A PSU: 12A/5A
	<b>Power consumption (230VAC)</b>	With JL086A PSU: 100% traffic rate: 76W  With JL087A PSU: Idle: 59W 100% traffic rate: 74W  With JL670A PSU: Idle: 62W 100% traffic rate: 81W
<b>Safety</b>	<b>Europe:</b> EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011 + A2:2013 <b>US:</b> UL 60950-1 2nd Ed.. <b>Canada:</b> CAN/CSA-C22.2 No. 60950-1-07 <b>Worldwide:</b> IEC 60950-1:2005 w/all known National Deviations	
<b>Emissions</b>	<b>Europe:</b> EN 55022:2010, Class A EN 55032:2012, Class A EN 55024:2010, EN 61000-3-2:2014 EN 61000-3-3:2013 <b>US:</b> FCC part 15 Class A <b>Canada:</b> ICES-003 Class A <b>Worldwide:</b> VCCI Class A, CISPR 22 Class A CISPR 32 Class A CISPR 24:2010	
<b>Lasers</b>	EN 60825-1:2007 / IEC 60825-1:2007 Class 1 Class 1 Laser Products / Laser Klasse 1 (Applicable for accessories - Optical Transceivers only)	
<b>Immunity</b>	<b>Generic</b>	CISPR 24 / CISPR 35
	<b>EN</b>	EN 55024:2010 / EN 55035:2017
	<b>ESD</b>	IEC 61000-4-2
<b>Immunity</b>	<b>Radiated</b>	IEC 61000-4-3
	<b>EFT/Burst</b>	IEC 61000-4-4
	<b>Surge</b>	IEC 61000-4-5
	<b>Conducted</b>	IEC 61000-4-6
	<b>Power frequency magnetic field</b>	IEC 61000-4-8
	<b>Voltage dips and interruptions</b>	IEC 61000-4-11
	<b>Harmonics</b>	IEC 61000-3-2, EN 61000-3-2
<b>Flicker</b>	IEC 61000-3-3, EN 61000-3-3	
<b>Notes:</b> <sup>1</sup> Not more than 96 consecutive hours or 360 hours total or 15 occurrences in a 1-year period.		



## Technical Specifications

### HPE Aruba Networking 6300M 48-port 1GbE and 4-port SFP56 Switch (JL663A)

### HPE Aruba Networking 6300M 48p 10M/100M/1G 4p SFP56 50G TAA Switch (SOG00A)

<b>Description</b>	24x ports 10/100/1000 BaseT PoE+ ports supporting up to 30W per port 4x 1G/10G/25G/50G <sup>1</sup> SFP ports 1x USB-C Console Port 1x OOBM port 1x USB Type A Host port <b>Notes:</b> <sup>1</sup> 50G capability is for use with 50G DACs for both interconnect and VSF stacking. 50G SR transceivers have been added with a minimum software of 10.09.1010. VSF stacking not supported on 1G ports.		
<b>Power Supplies</b>	2 field-replaceable, hot-swappable power supply slots 1 minimum power supply required (ordered separately) Supports JL085A PSU		
<b>Fan Tray</b>	The switch has two fan tray slots and comes with one fan tray installed. Fan trays are field replaceable and hot-swappable. Minimum 1 fan tray required. The second fan tray ordered separately. Each fan tray is comprised of two fans.		
<b>Physical Characteristics</b>	<b>Dimensions</b>	17.4 (w) x 15.2 (d) x 1.73 (h) in (44.2 x 38.5 x 4.4 cm)	
	<b>Weight</b>	12.14 lbs (5.51 kg)	
<b>Mounting and Enclosure</b>	Mounts in an EIA- standard 19 in. telco rack or equipment cabinet. Horizontal surface mounting only. 2-post rack kit included.		
<b>CPU</b>	Quad Core ARM Cortex™ A72 @ 1.8GHz		
<b>Memory and Flash</b>	8 GBytes DDR4 32 GBytes eMMC		
<b>Packet Buffer</b>	8 MB packet buffer memory		
<b>Performance</b>	<b>System switching capacity</b>	880 Gbps	
	<b>System throughput capacity</b>	660 Mpps	
	<b>Model switching capacity</b>	496 Gbps	
	<b>Model throughput capacity</b>	369 Mpps	
	<b>Average latency (LIFO, 64-byte packets)</b>	1Gbps:	2.28µSec
		10Gbps:	1.46µSec
		25Gbps:	1.90µSec
		50Gbps:	3.49µSec
	<b>Stack size</b>	10 members	
	<b>Max stacking distance</b>	Up to 10 kms with long range transceivers	
	<b>Stacking bandwidth</b>	200 Gbps (400 Gbps at full duplex)	
	<b>Switched virtual interfaces (dual stack)</b>	1,024	
	<b>IPv4 host table (ARP)</b>	49,152	
	<b>IPv6 host table (ND)</b>	49,152	
	<b>IPv4 unicast routes</b>	61,000	
<b>IPv6 unicast routes</b>	61,000		
<b>IPv4 multicast routes</b>	8,192		
<b>IPv6 multicast routes</b>	8,192		
<b>Performance</b>	<b>MAC table capacity</b>	32,768	
	<b>IGMP groups</b>	4,096	
	<b>MLD groups</b>	8,192	
	<b>IPv4/IPv6/MAC ACL entries (ingress)</b>	20,480/5,120/20,480	

## Technical Specifications

	<b>IPv4/IPv6/MAC ACL entries (engress)</b>	8,192/2,048/8,192
	<b>VRF</b>	256
<b>Environment</b>	<b>Operating temperature</b>	32°F to 113°F (0°C to 45°C), up to 5,000 feet 32°F to 104°F (0°C to 40°C), 5,001 to 10,000 feet 1°C de-rating per 1,000 feet above 5,000 feet Can support excursion to 131°F (55°C) for short periods <sup>1</sup> of time.
	<b>Operating humidity</b>	15% to 95% relative humidity at 104°F (40°C), non-condensing
	<b>Non-operating temperature</b>	-40°F to 158°F (-40°C to 70°C)
	<b>Non-operating humidity</b>	15% to 95% relative humidity at 149°F(65°C), non-condensing
	<b>Max operating altitude</b>	Up to 10,000ft (3.048 Km)
	<b>Max non-operating altitude</b>	Up to 15,000ft (3.048 Km)
	<b>Acoustic</b>	Sound power, LWAd = 4.6 Bel Sound pressure, LpAm (bystander) = 28.7 dB
	<b>Primary airflow</b>	Front and side-to-back
<b>Electrical characteristics</b>	<b>Frequency</b>	50-60 Hz
	<b>AC voltage</b>	JL085A PSU: 100V-240V
	<b>Current (for voltages listed above)</b>	JL085A PSU: 3A/1.2A
	<b>Power Consumption (230VAC)</b>	Idle: 56W 100% traffic rate: 75W
<b>Safety</b>	<b>Europe:</b> EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011 + A2:2013 <b>US:</b> UL 60950-1 2nd Ed. <b>Canada:</b> CAN/CSA-C22.2 No. 60950-1-07 <b>Worldwide:</b> IEC 60950-1:2005 w/all known National Deviations	
<b>Emissions</b>	<b>Europe:</b> EN 55022:2010, Class A EN 55032:2012, Class A EN 55024:2010, EN 61000-3-2:2014 EN 61000-3-3:2013 <b>US:</b> FCC part 15 Class A <b>Canada:</b> ICES-003 Class A <b>Worldwide:</b> VCCI Class A, CISPR 22 Class A CISPR 32 Class A CISPR 24:2010	
<b>Lasers</b>	EN 60825-1:2007 / IEC 60825-1:2007 Class 1 Class 1 Laser Products / Laser Klasse 1 (Applicable for accessories - Optical Transceivers only)	
<b>Immunity</b>	<b>Generic</b>	CISPR 24 / CISPR 35
	<b>EN</b>	EN 55024:2010 / EN 55035:2017
	<b>ESD</b>	IEC 61000-4-2
	<b>Radiated</b>	IEC 61000-4-3
	<b>EFT/Burst</b>	IEC 61000-4-4
	<b>Surge</b>	IEC 61000-4-5
	<b>Conducted</b>	IEC 61000-4-6
	<b>Power frequency magnetic field</b>	IEC 61000-4-8
	<b>Voltage dips and interruptions</b>	IEC 61000-4-11
<b>Harmonics</b>	IEC 61000-3-2, EN 61000-3-2	
<b>Flicker</b>	IEC 61000-3-3, EN 61000-3-3	

**Notes:** <sup>1</sup> Not more than 96 consecutive hours or 360 hours total or 15 occurrences in a 1-year period.



## Technical Specifications

### HPE Aruba Networking 6300M 24-port 1GbE and 4-port SFP56 Switch (JL664A)

### HPE Aruba Networking 6300M 24p 10M/100M/1G 4p SFP56 50G TAA Switch (S0G01A)

<b>Description</b>	24x ports 10/100/1000 BaseT PoE+ ports supporting up to 30W per port 4x 1G/10G/25G/50G <sup>1</sup> SFP ports 1x USB-C Console Port 1x OOBM port 1x USB Type A Host port <b>Notes:</b> <sup>1</sup> 50G capability is for use with 50G DACs for both interconnect and VSF stacking. 50G SR transceivers have been added with a minimum software of 10.09.1010. VSF stacking not supported on 1G ports.		
<b>Power supplies</b>	2 field-replaceable, hot-swappable power supply slots 1 minimum power supply required (ordered separately) Supports JL085A PSU		
<b>Fan tray</b>	The switch has two fan tray slots and comes with one fan tray installed. Fan trays are field replaceable and hot-swappable. Minimum 1 fan tray required. Second fan tray ordered separately. Each fan tray is comprised of two fans.		
<b>Physical characteristics</b>	<b>Dimensions</b>	17.4 (w) x 15.2 (d) x 1.73 (h) in (44.2 x 38.5 x 4.4 cm)	
	<b>Weight</b>	11.97 lbs (5.43 kg)	
<b>Mounting and enclosure</b>	Mounts in an EIA- standard 19 in. telco rack or equipment cabinet. Horizontal surface mounting only. 2-post rack kit included.		
<b>CPU</b>	Quad Core ARM Cortex™ A72 @ 1.8GHz		
<b>Memory and Flash</b>	8 GBytes DDR4 32 GBytes eMMC		
<b>Packet Buffer</b>	8 MB packet buffer memory		
<b>Performance</b>	<b>System switching capacity</b>	880 Gbps	
	<b>System throughput capacity</b>	660 Mpps	
	<b>Model switching capacity</b>	448 Gbps	
	<b>Model throughput capacity</b>	334 Mpps	
	<b>Average latency (LIFO, 64-byte packets)</b>	1Gbps:	2.28µSec
		10Gbps:	1.46µSec
		25Gbps:	1.90µSec
		50Gbps:	3.49µSec
	<b>Stack size</b>	10 members	
	<b>Max stacking distance</b>	Up to 10 kms with long range transceivers	
	<b>Stacking bandwidth</b>	200 Gbps (400 Gbps at full duplex)	
	<b>Switched virtual interfaces (dual stack)</b>	1,024	
	<b>IPv4 host table (ARP)</b>	49,152	
	<b>IPv6 host table (ND)</b>	49,152	
	<b>IPv4 unicast routes</b>	61,000	
	<b>IPv6 unicast routes</b>	61,000	
	<b>IPv4 multicast routes</b>	8,192	
	<b>IPv6 multicast routes</b>	8,192	
	<b>MAC table capacity</b>	32,768	
	<b>IGMP groups</b>	4,096	
<b>MLD groups</b>	8,192		
<b>IPv4/IPv6/MAC ACL entries (ingress)</b>	20,480/5,120/20,480		

## Technical Specifications

	<b>IPv4/IPv6/MAC ACL entries (engress)</b>	8,192/2,048/8,192
	<b>VRF</b>	256
<b>Environment</b>	<b>Operating temperature</b>	32°F to 113°F (0°C to 45°C), up to 5,000 feet 32°F to 104°F (0°C to 40°C), 5,001 to 10,000 feet 1°C de-rating per 1,000 feet above 5,000 feet Can support excursion to 131°F (55°C) for short periods <sup>1</sup> of time.
	<b>Operating humidity</b>	15% to 95% relative humidity at 104°F (40°C), non-condensing
<b>Environment</b>	<b>Non-operating temperature</b>	-40°F to 158°F (-40°C to 70°C)
	<b>Non-operating humidity</b>	15% to 95% relative humidity at 149°F(65°C), non-condensing
	<b>Max operating altitude</b>	Up to 10,000ft (3.048 Km)
	<b>Max non-operating altitude</b>	Up to 15,000ft (3.048 Km)
	<b>Acoustic</b>	Sound power, LWAd = 4.6 Bel Sound pressure, LpAm (bystander) = 28.6 dB
	<b>Primary airflow</b>	Front and side-to-back
<b>Electrical Characteristics</b>	<b>Frequency</b>	50-60 Hz
	<b>AC voltage</b>	JL085A PSU: 100V-240V
	<b>Current (for voltages listed above)</b>	JL085A PSU: 3A/1.2A
	<b>Power Consumption (230VAC)</b>	Idle: 49W 100% traffic rate: 64W
<b>Safety</b>	<b>Europe:</b> EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011 + A2:2013 <b>US:</b> UL 60950-1 2nd Ed. <b>Canada:</b> CAN/CSA-C22.2 No. 60950-1-07 <b>Worldwide:</b> IEC 60950-1:2005 w/all known National Deviations	
<b>Emissions</b>	<b>Europe:</b> EN 55022:2010, Class A EN 55032:2012, Class A EN 55024:2010, EN 61000-3-2:2014 EN 61000-3-3:2013 <b>US:</b> FCC part 15 Class A <b>Canada:</b> ICES-003 Class A <b>Worldwide:</b> VCCI Class A, CISPR 22 Class A CISPR 32 Class A CISPR 24:2010	
<b>Lasers</b>	EN 60825-1:2007 / IEC 60825-1:2007 Class 1 Class 1 Laser Products / Laser Klasse 1 (Applicable for accessories - Optical Transceivers only)	
<b>Immunity</b>	<b>Generic</b>	CISPR 24 / CISPR 35
	<b>EN</b>	EN 55024:2010 / EN 55035:2017
	<b>ESD</b>	IEC 61000-4-2
	<b>Radiated</b>	IEC 61000-4-3
	<b>EFT/Burst</b>	IEC 61000-4-4
	<b>Surge</b>	IEC 61000-4-5
	<b>Conducted</b>	IEC 61000-4-6
	<b>Power frequency magnetic field</b>	IEC 61000-4-8
	<b>Voltage dips and interruptions</b>	IEC 61000-4-11
	<b>Harmonics</b>	IEC 61000-3-2, EN 61000-3-2
	<b>Flicker</b>	IEC 61000-3-3, EN 61000-3-3

**Notes:** <sup>1</sup> Not more than 96 consecutive hours or 360 hours total or 15 occurrences in a 1-year period.



## Technical Specifications

### HPE Aruba Networking 6300M 48-port 1GbE and 4-port SFP56 Power-to-Port 2 Fan Trays 1 PSU Bundle (JL762A)

### HPE Aruba Networking 6300M 48p 10M/100M/1G 4p SFP56 50G Power-to-Port 2xFan PSU TAA Bundle (S0G02A)

<b>Description</b>	<p>24x ports 10/100/1000 BaseT PoE+ ports supporting up to 30W per port          4x 1G/10G/25G/50G<sup>1</sup> SFP ports          1x USB-C Console Port          1x OOBM port          1x USB Type A Host port</p> <p><b>Notes:</b> <sup>1</sup>50G capability is for use with 50G DACs for both interconnect and VSF stacking. 50G SR transceivers have been added with a minimum software of 10.09.1010. VSF stacking not supported on 1G ports.</p>	
<b>Additional ports and slots</b>	<p>1x USB-C console port          1x OOBM          1x USB Type A host port</p>	
<b>Power supplies</b>	<p>2 field-replaceable, hot-swappable power supply slots          Comes with 1 power-to-port power supply pre-installed          Additional power-to-port power supply can be ordered separately          Supports JL760A HPE Aruba Networking X371 12VDC 250W 100-240VAC Power-to-Port Power Supply only</p>	
<b>Fan tray</b>	<p>Switch has two fan tray slots and comes with two fan trays installed          Fan trays are field replaceable and hot-swappable. Minimum 2 fan trays required. Second fan tray ordered separately          Each fan tray is comprised of two fans          Supports JL761A HPE Aruba Networking CX 6300M Power-to-Port Fan Tray only</p>	
<b>Physical characteristics</b>	<b>Dimensions</b>	17.4 (w) x 15.2 (d) x 1.73 (h) in (44.2 x 38.5 x 4.4 cm)
	<b>Weight</b>	12.5 lbs (5.7 kg), with 1 PSU 13.8 lbs (6.27kg), with 2 PSUs
<b>Mounting and enclosure</b>	<p>Mounts in an EIA- standard 19 in. telco rack or equipment cabinet.          Horizontal surface mounting only. 2-post rack kit included.</p>	
<b>CPU</b>	Quad Core ARM Cortex™ A72 @ 1.8GHz	
<b>Memory and Flash</b>	<p>8 GBytes DDR4          32 GBytes eMMC</p>	
<b>Packet Buffer</b>	8 MB shared packet buffer memory	
<b>Performance</b>	<b>System switching capacity</b>	880 Gbps
	<b>System throughput capacity</b>	660 Mpps
	<b>Model switching capacity</b>	496 Gbps
	<b>Model throughput capacity</b>	369 Mpps
	<b>Average latency (LIFO, 64-byte packets)</b>	1Gbps: 2.28μSec 10Gbps: 1.46μSec 25Gbps: 1.90μSec 50Gbps: 3.49μSec
	<b>Stack size</b>	10 members
	<b>Max stacking distance</b>	Up to 10 kms with long range transceivers
	<b>Stacking bandwidth</b>	200 Gbps (400 Gbps at full duplex)
	<b>Switched virtual interfaces (dual stack)</b>	1,024
	<b>IPv4 host table (ARP)</b>	49,152
	<b>IPv6 host table (ND)</b>	49,152
	<b>IPv4 unicast routes</b>	61,000

## Technical Specifications

	<b>IPv6 unicast routes</b>	61,000
	<b>IPv4 multicast routes</b>	8,192
	<b>IPv6 multicast routes</b>	8,192
	<b>MAC table capacity</b>	32,768
	<b>IGMP groups</b>	4,096
	<b>MLD groups</b>	8,192
	<b>IPv4/IPv6/MAC ACL entries (ingress)</b>	20,480/5,120/20,480
	<b>IPv4/IPv6/MAC ACL entries (egress)</b>	8,192/2,048/8,192
	<b>VRF</b>	256
<b>Environment</b>	<b>Operating temperature</b>	32°F to 113°F (0°C to 45°C), up to 5,000 feet 32°F to 104°F (0°C to 40°C), 5,001 to 10,000 feet 1°C de-rating per 1,000 feet above 5,000 feet Can support excursion to 131°F (55°C) for short periods <sup>1</sup> of time.
	<b>Operating humidity</b>	15% to 95% relative humidity at 104°F (40°C), non-condensing
	<b>Non-operating temperature</b>	-40°F to 158°F (-40°C to 70°C)
	<b>Non-operating humidity</b>	15% to 90% relative humidity at 149°F(65°C), non-condensing
	<b>Max operating altitude</b>	Up to 10,000ft (3.048 Km)
	<b>Max non-operating altitude</b>	Up to 15,000ft (3.048 Km)
	<b>Acoustic</b>	Sound power, LWAd = 4.6 Bel Sound pressure, LpAm (bystander) = 28.7 dB
	<b>Primary airflow</b>	Back-to-front and side
<b>Electrical Characteristics</b>	<b>Frequency</b>	50-60 Hz
	<b>AC voltage</b>	JL760A PSU: 100V-240V
	<b>Current (for voltages listed above)</b>	JL760A PSU: 3A/1.2A
	<b>80plus.org certification</b>	TBA for JL760A PS.
	<b>Power Consumption (230VAC)</b>	Idle: 56W 100% traffic rate: 75W
<b>Safety</b>	<b>Europe:</b> EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011 + A2:2013, EN 62368-1:2014 +A11:2017 <b>US:</b> UL 60950-1 2nd Ed.. <b>Canada:</b> CAN/CSA-C22.2 No. 60950-1-07 <b>Worldwide:</b> IEC 60950-1:2005 w/all known National Deviations <b>Taiwan:</b> CNS-14336-1	
<b>Emissions</b>	<b>Europe:</b> EN 55032:2015 +AC:2016, Class A, EN 55035:2017, EN 61000-3-2:2014, EN 61000-3-3:2013 <b>US:</b> FCC 47 CFR part 15B, Class A <b>Canada:</b> ICES-003 Class A <b>Worldwide:</b> VCCI Class A, CISPR 32 Ed 2.0: 2015 + COR1:2016, Class A, CISPR 35:2016	
<b>Lasers</b>	EN 60825-1:2007 / IEC 60825-1:2007 Class 1 Class 1 Laser Products / Laser Klasse 1 (Applicable for accessories - Optical Transceivers only)	
<b>Immunity</b>	<b>Generic</b>	CISPR 35
	<b>EN</b>	EN 55035:2017
	<b>ESD</b>	IEC 61000-4-2
	<b>Radiated</b>	IEC 61000-4-3
	<b>EFT/Burst</b>	IEC 61000-4-4



## Technical Specifications

	<b>Surge</b>	IEC 61000-4-5
	<b>Conducted</b>	IEC 61000-4-6
	<b>Power frequency magnetic field</b>	IEC 61000-4-8
	<b>Voltage dips and interruptions</b>	IEC 61000-4-11
	<b>Harmonics</b>	IEC 61000-3-2, EN 61000-3-2
	<b>Flicker</b>	IEC 61000-3-3, EN 61000-3-3

**Notes:** <sup>1</sup> Not more than 96 consecutive hours or 360 hours total or 15 occurrences in a 1-year period.

### HPE Aruba Networking 48-port 1GbE Class 4 PoE and 4-port SFP56 Switch (JL665A)

### HPE Aruba Networking 6300F 48p 10M/100M/1G Class4 PoE 4p SFP56 50G TAA Switch (SOG95A)

<b>Description</b>	48x ports 10/100/1000 BaseT PoE+ ports supporting up to 30W per port 1G/10G/25G/50G <sup>1</sup> SFP ports Supports PoE Standards IEEE 802.3af, 802.3at 1x USB-C Console Port 1x OOBM port 1x USB Type A Host port <b>Notes:</b> <sup>1</sup> 50G capability is for use with 50G DACs for both interconnect and VSF stacking. 50G SR transceivers have been added with a minimum software of 10.09.1010. VSF stacking not supported on 1G ports.		
<b>Power Supplies</b>	Internal (fixed) power supply (950W) Max PoE power: 740W		
<b>Fan Tray</b>	Fixed fans		
<b>Physical Characteristics</b>	<b>Dimensions</b>	17.4 (w) x 12.9 (d) x 1.73 (h) in (44.2 cm x 32.7 x 4.39 cm))	
	<b>Weight</b>	11.24 lbs (5.10 kg)	
<b>Mounting And Enclosure</b>	Mounts in an EIA- standard 19 in. telco rack or equipment cabinet. Horizontal surface mounting only. 2-post rack kit included.		
<b>CPU</b>	Quad Core ARM Cortex™ A72 @ 1.8GHz		
<b>Memory And Flash</b>	8 GBytes DDR4 32 GBytes eMMC		
<b>Packet Buffer</b>	8 MB packet buffer memory		
<b>Performance</b>	<b>System switching capacity</b>	880 Gbps	
	<b>System throughput capacity</b>	660 Mpps	
	<b>Model switching capacity</b>	496 Gbps	
	<b>Model throughput capacity</b>	369 Mpps	
	<b>Average latency (LIFO, 64-byte packets)</b>	1Gbps:	2.28μSec
		10Gbps:	1.46μSec
		25Gbps:	1.90μSec
		50Gbps:	3.49μSec
	<b>Stack size</b>	10 members	
	<b>Max stacking distance</b>	Up to 10 kms with long range transceivers	
	<b>Stacking bandwidth</b>	200 Gbps (400 Gbps at full duplex)	
	<b>Switched virtual interfaces (dual stack)</b>	1,024	
	<b>IPv4 host table (ARP)</b>	49,152	
	<b>IPv6 host table (ND)</b>	49,152	
<b>IPv4 unicast routes</b>	61,000		
<b>IPv6 unicast routes</b>	61,000		
<b>IPv4 multicast routes</b>	8,192		



## Technical Specifications

	<b>IPv6 multicast routes</b>	8,192
	<b>MAC table capacity</b>	32,768
	<b>IGMP groups</b>	4,096
	<b>MLD groups</b>	8,192
	<b>IPv4/IPv6/MAC ACL entries (ingress)</b>	20,480/5,120/20,480
	<b>IPv4/IPv6/MAC ACL entries (egress)</b>	8,192/2,048/8,192
	<b>VRF</b>	256
<b>Environment</b>	<b>Operating temperature</b>	32°F to 113°F (0°C to 45°C), up to 5,000 feet 32°F to 104°F (0°C to 40°C), 5,001 to 10,000 feet 1°C de-rating per 1,000 feet above 5,000 feet Can support excursion to 131°F (55°C) for short periods <sup>1</sup> of time.
	<b>Operating</b>	15% to 95% relative humidity at 104°F (40°C), non-condensing
	<b>Non-operating temperature</b>	40°F to 158°F (-40°C to 70°C)
	<b>Non-operating humidity</b>	15% to 95% relative humidity at 149°F(65°C), non-condensing
	<b>Max operating altitude</b>	Up to 10,000ft (3.048 Km)
	<b>Max non-operating altitude</b>	Up to 15,000ft (3.048 Km)
	<b>Acoustic</b>	Sound power, LWAd = 5.2 Bel Sound pressure, LpAm (bystander) = 34.9 dB
	<b>Primary airflow</b>	Front and side-to-back
<b>Electrical Characteristics</b>	<b>Frequency</b>	50-60 Hz
	<b>AC voltage</b>	Fixed PSU: 100V-120V/200V-240V
	<b>Current (for voltages listed above)</b>	Fixed PSU: 11A/6A
	<b>Power Consumption (230VAC)</b>	Hibernation (0 rpm fan): 12W Idle: 63W 100% traffic rate: 86W
<b>Safety</b>	<b>Europe:</b> EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011 + A2:2013 <b>US:</b> UL 60950-1 2nd Ed. <b>Canada:</b> CAN/CSA-C22.2 No. 60950-1-07 <b>Worldwide:</b> IEC 60950-1:2005 w/all known National Deviations	
<b>Emissions</b>	<b>Europe:</b> EN 55022:2010, Class A EN 55032:2012, Class A EN 55024:2010, EN 61000-3-2:2014 EN 61000-3-3:2013 <b>US:</b> FCC part 15 Class A <b>Canada:</b> ICES-003 Class A <b>Worldwide:</b> VCCI Class A, CISPR 22 Class A CISPR 32 Class A CISPR 24:2010	
<b>Lasers</b>	EN 60825-1:2007 / IEC 60825-1:2007 Class 1 Class 1 Laser Products / Laser Klasse 1 (Applicable for accessories - Optical Transceivers only)	
<b>Immunity</b>	<b>Generic</b>	CISPR 24 / CISPR 35
	<b>EN</b>	EN 55024:2010 / EN 55035:2017
	<b>ESD</b>	IEC 61000-4-2
	<b>Radiated</b>	IEC 61000-4-3
	<b>EFT/Burst</b>	IEC 61000-4-4
	<b>Surge</b>	IEC 61000-4-5
	<b>Conducted</b>	IEC 61000-4-6
	<b>Power frequency magnetic field</b>	IEC 61000-4-8

## Technical Specifications

	<b>Voltage dips and interruptions</b>	IEC 61000-4-11
	<b>Harmonics</b>	IEC 61000-3-2, EN 61000-3-2
	<b>Flicker</b>	IEC 61000-3-3, EN 61000-3-3

**Notes:** <sup>1</sup> Not more than 96 consecutive hours or 360 hours total or 15 occurrences in a 1-year period.

### HPE Aruba Networking 6300F 24-port 1GbE Class 4 PoE and 4-port SFP56 Switch (JL666A)

### HPE Aruba Networking 6300F 24p 10M/100M/1G Class4 PoE 4p SFP56 50G TAA Switch (SOG96A)

<b>Description</b>	24x ports 10/100/1000 BaseT PoE+ ports supporting up to 30W per port 1G/10G/25G/50G <sup>1</sup> SFP ports 1x USB-C Console Port 1x OOBM port 1x USB Type A Host port <b>Notes:</b> <sup>1</sup> 50G capability is for use with 50G DACs for both interconnect and VSF stacking. 50G SR transceivers have been added with a minimum software of 10.09.1010. VSF stacking not supported on 1G ports.	
<b>Power Supplies</b>	Internal (fixed) power supply (950W) Max PoE power: 370W	
<b>Fan Tray</b>	Fixed fans	
<b>Physical Characteristics</b>	<b>Dimensions</b>	17.4 (w) x 12.9 (d) x 1.73 (h) in (44.2 cm x 32.7 x 4.39 cm))
	<b>Weight</b>	10.91 lbs (4.95 kg)
<b>Mounting And Enclosure</b>	Mounts in an EIA- standard 19 in. telco rack or equipment cabinet. Horizontal surface mounting only. 2-post rack kit included.	
<b>CPU</b>	Quad Core ARM Cortex™ A72 @ 1.8GHz	
<b>Memory And Flash</b>	8 GBytes DDR4 32 GBytes eMMC	
<b>Packet Buffer</b>	8 MB packet buffer memory	
<b>Performance</b>	<b>System switching capacity</b>	880 Gbps
	<b>System throughput capacity</b>	660 Mpps
	<b>Model switching capacity</b>	448 Gbps
	<b>Model throughput capacity</b>	334 Mpps
	<b>Average latency (LIFO, 64-byte packets)</b>	1Gbps: 2.28μSec
		10Gbps: 1.46μSec
		25Gbps: 1.90μSec
		50Gbps: 3.49μSec
	<b>Stack size</b>	10 members
	<b>Max stacking distance</b>	Up to 10 kms with long range transceivers
	<b>Stacking bandwidth</b>	200 Gbps (400 Gbps at full duplex)
	<b>Switched virtual interfaces (dual stack)</b>	1,024
	<b>IPv4 host table (ARP)</b>	49,152
	<b>IPv6 host table (ND)</b>	49,152
	<b>IPv4 unicast routes</b>	61,000
	<b>IPv6 unicast routes</b>	61,000
<b>IPv4 multicast routes</b>	8,192	
<b>IPv6 multicast routes</b>	8,192	
<b>MAC table capacity</b>	32,768	
<b>IGMP groups</b>	4,096	
<b>MLD groups</b>	8,192	



## Technical Specifications

	<b>IPv4/IPv6/MAC ACL entries (ingress)</b>	20,480/5,120/20,480
	<b>IPv4/IPv6/MAC ACL entries (egress)</b>	8,192/2,048/8,192
	<b>VRF</b>	256
<b>Environment</b>	<b>Operating temperature</b>	32°F to 113°F (0°C to 45°C), up to 5,000 feet 32°F to 104°F (0°C to 40°C), 5,001 to 10,000 feet 1°C de-rating per 1,000 feet above 5,000 feet Can support excursion to 131°F (55°C) for short periods <sup>1</sup> of time.
	<b>Operating humidity</b>	15% to 95% relative humidity at 104°F (40°C), non-condensing
	<b>Non-operating temperature</b>	-40°F to 158°F (-40°C to 70°C)
	<b>Non-operating humidity</b>	15% to 95% relative humidity at 149°F(65°C), non-condensing
	<b>Max operating altitude</b>	Up to 10,000ft (3.048 Km)
	<b>Max non-operating altitude</b>	Up to 15,000ft (3.048 Km)
	<b>Acoustic</b>	Sound power, LWAd = 5.0 Bel Sound pressure, LpAm (bystander) = 32.3 dB
	<b>Primary airflow</b>	Front and side-to-back
<b>Electrical Characteristics</b>	<b>Frequency</b>	50-60 Hz
	<b>AC voltage</b>	Fixed PSU: 100V-120V/200V-240V
	<b>Current (for voltages listed above)</b>	Fixed PSU: 11A/6A
	<b>Power Consumption (230VAC)</b>	Idle: 52W 100% traffic rate: 67W
<b>Safety</b>	<b>Europe:</b> EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011 + A2:2013 <b>US:</b> UL 60950-1 2nd Ed <b>Canada:</b> CAN/CSA-C22.2 No. 60950-1-07 <b>Worldwide:</b> IEC 60950-1:2005 w/all known National Deviations	
<b>Emissions</b>	<b>Europe:</b> EN 55022:2010, Class A EN 55032:2012, Class A EN 55024:2010, EN 61000-3-2:2014 EN 61000-3-3:2013 <b>US:</b> FCC part 15 Class A <b>Canada:</b> ICES-003 Class A <b>Worldwide:</b> VCCI Class A, CISPR 22 Class A CISPR 32 Class A CISPR 24:2010	
<b>Lasers</b>	EN 60825-1:2007 / IEC 60825-1:2007 Class 1 Class 1 Laser Products / Laser Klasse 1 (Applicable for accessories - Optical Transceivers only)	
<b>Immunity</b>	<b>Generic</b>	CISPR 24 / CISPR 35
	<b>EN</b>	EN 55024:2010 / EN 55035:2017
	<b>ESD</b>	IEC 61000-4-2
	<b>Radiated</b>	IEC 61000-4-3
	<b>EFT/Burst</b>	IEC 61000-4-4
	<b>Surge</b>	IEC 61000-4-5
	<b>Conducted</b>	IEC 61000-4-6
	<b>Power frequency magnetic field</b>	IEC 61000-4-8
	<b>Voltage dips and interruptions</b>	IEC 61000-4-11

## Technical Specifications

	<b>Harmonics</b>	IEC 61000-3-2, EN 61000-3-2
	<b>Flicker</b>	IEC 61000-3-3, EN 61000-3-3

**Notes:** <sup>1</sup> Not more than 96 consecutive hours or 360 hours total or 15 occurrences in a 1-year period.

### HPE Aruba Networking 6300F 48-port 1GbE and 4-port SFP56 Switch (JL667A)

### HPE Aruba Networking 6300F 48p 10M/100M/1G 4p SFP56 50G TAA Switch (S0G97A)

<b>Description</b>	48x ports 10/100/1000 BaseT PoE+ ports supporting up to 30W per port 1G/10G/25G/50G <sup>1</sup> SFP ports 1x USB-C Console Port 1x OOBM port 1x USB Type A Host port <b>Notes:</b> <sup>1</sup> 50G capability is for use with 50G DACs for both interconnect and VSF stacking. 50G SR transceivers have been added with a minimum software of 10.09.1010. VSF stacking not supported on 1G ports.	
<b>Power Supplies</b>	Internal (fixed) power supply (200W)	
<b>Fan Tray</b>	Fixed fans	
<b>Physical Characteristics</b>	<b>Dimensions</b>	17.4 (w) x 12.9 (d) x 1.73 (h) in (44.2 cm x 32.7 x 4.39 cm))
	<b>Weight</b>	9.83 lbs (4.46 kg)
<b>Mounting And Enclosure</b>	Mounts in an EIA- standard 19 in. telco rack or equipment cabinet. Horizontal surface mounting only. 2-post rack kit included.	
<b>CPU</b>	Quad Core ARM Cortex™ A72 @ 1.8GHz	
<b>Memory And Flash</b>	8 GBytes DDR4 32 GBytes eMMC	
<b>Packet Buffer</b>	8 MB packet buffer memory	
<b>Performance</b>	<b>System switching capacity</b>	880 Gbps
	<b>System throughput capacity</b>	660 Mpps
	<b>Model switching capacity</b>	496 Gbps
	<b>Model throughput capacity</b>	369 Mpps
	<b>Average latency (LIFO, 64-byte packets)</b>	1Gbps: 2.28μSec
		10Gbps: 1.46μSec
		25Gbps: 1.90μSec
		50Gbps: 3.49μSec
	<b>Stack size</b>	10 members
	<b>Max stacking distance</b>	Up to 10 kms with long range transceivers
	<b>Stacking bandwidth</b>	200 Gbps (400 Gbps at full duplex)
	<b>Switched virtual interfaces (dual stack)</b>	1,024
	<b>IPv4 host table (ARP)</b>	49,152
	<b>IPv6 host table (ND)</b>	49,152
	<b>IPv4 unicast routes</b>	61,000
	<b>IPv6 unicast routes</b>	61,000
	<b>IPv4 multicast routes</b>	8,192
	<b>IPv6 multicast routes</b>	8,192
	<b>MAC table capacity</b>	32,768
	<b>IGMP groups</b>	4,096
<b>MLD groups</b>	8,192	
<b>IPv4/IPv6/MAC ACL entries (ingress)</b>	20,480/5,120/20,480	
<b>IPv4/IPv6/MAC ACL entries (egress)</b>	8,192/2,048/8,192	

## Technical Specifications

	<b>VRF</b>	256
<b>Environment</b>	<b>Operating temperature</b>	32°F to 113°F (0°C to 45°C), up to 5,000 feet 32°F to 104°F (0°C to 40°C), 5,001 to 10,000 feet 1°C de-rating per 1,000 feet above 5,000 feet Can support excursion to 131°F (55°C) for short periods <sup>1</sup> of time.
	<b>Operating humidity</b>	15% to 95% relative humidity at 104°F (40°C), non-condensing
	<b>Non-operating temperature</b>	-40°F to 158°F (-40°C to 70°C)
	<b>Non-operating humidity</b>	15% to 95% relative humidity at 149°F(65°C), non-condensing
	<b>Max operating altitude</b>	Up to 10,000ft (3.048 Km)
	<b>Max non-operating altitude</b>	Up to 15,000ft (3.048 Km)
	<b>Acoustic</b>	Sound power, LWAd = 4.9 Bel Sound pressure, LpAm (bystander) = 31.5 dB
	<b>Primary airflow</b>	Front and side-to-back
<b>Electrical Characteristics</b>	<b>Frequency</b>	50-60 Hz
	<b>AC voltage</b>	Fixed PSU: 100V-120V/200V-240V
	<b>Current (for voltages listed above)</b>	Fixed PSU: 2.5A/1.4A
	<b>Power Consumption (230VAC)</b>	Idle: 52W 100% traffic rate: 74W
<b>Safety</b>	<b>Europe:</b> EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011 + A2:2013 <b>US:</b> UL 60950-1 2nd Ed. <b>Canada:</b> CAN/CSA-C22.2 No. 60950-1-07 <b>Worldwide:</b> IEC 60950-1:2005 w/all known National Deviations	
<b>Emissions</b>	<b>Europe:</b> EN 55022:2010, Class A EN 55032:2012, Class A EN 55024:2010, EN 61000-3-2:2014 EN 61000-3-3:2013 <b>US:</b> FCC part 15 Class A <b>Canada:</b> ICES-003 Class A <b>Worldwide:</b> VCCI Class A, CISPR 22 Class A CISPR 32 Class A CISPR 24:2010	
<b>Lasers</b>	EN 60825-1:2007 / IEC 60825-1:2007 Class 1 Class 1 Laser Products / Laser Klasse 1 (Applicable for accessories - Optical Transceivers only)	
<b>Immunity</b>	<b>Generic</b>	CISPR 24 / CISPR 35
	<b>EN</b>	EN 55024:2010 / EN 55035:2017
	<b>ESD</b>	IEC 61000-4-2
	<b>Radiated</b>	IEC 61000-4-3
	<b>EFT/Burst</b>	IEC 61000-4-4
	<b>Surge</b>	IEC 61000-4-5
	<b>Conducted</b>	IEC 61000-4-6
	<b>Power frequency magnetic field</b>	IEC 61000-4-8
	<b>Voltage dips and interruptions</b>	IEC 61000-4-11
	<b>Harmonics</b>	IEC 61000-3-2, EN 61000-3-2
<b>Flicker</b>	IEC 61000-3-3, EN 61000-3-3	

**Notes:** <sup>1</sup> Not more than 96 consecutive hours or 360 hours total or 15 occurrences in a 1-year period.



## Technical Specifications

### HPE Aruba Networking 6300F 24-port 1GbE and 4-port SFP56 Switch (JL668A)

### HPE Aruba Networking 6300F 24p 10M/100M/1G 4p SFP56 50G TAA Switch (S0G98A)

<b>Description</b>	24x ports 10/100/1000 BaseT PoE+ ports supporting up to 30W per port 1G/10G/25G/50G <sup>1</sup> SFP ports 1x USB-C Console Port 1x OOBM port 1x USB Type A Host port <b>Notes:</b> <sup>1</sup> 50G capability is for use with 50G DACs for both interconnect and VSF stacking. 50G SR transceivers have been added with a minimum software of 10.09.1010. VSF stacking not supported on 1G ports.		
<b>Additional Ports And Slots</b>	1x USB-C console port 1x OOBM 1x USB Type A host port		
<b>Power Supplies</b>	Internal (fixed) power supply (200W)		
<b>Fan Tray</b>	Fixed fans		
<b>Physical Characteristics</b>	<b>Dimensions</b>	17.4 (w) x 12.9 (d) x 1.73 (h) in (44.2 cm x 32.7 x 4.39 cm))	
	<b>Weight</b>	9.61 lbs (4.36 kg)	
<b>Mounting And Enclosure</b>	Mounts in an EIA- standard 19 in. telco rack or equipment cabinet. Horizontal surface mounting only. 2-post rack kit included.		
<b>CPU</b>	Quad Core ARM Cortex™ A72 @ 1.8GHz		
<b>Memory And Flash</b>	8 GBytes DDR4 32 GBytes eMMC		
<b>Packet Buffer</b>	8 MB packet buffer memory		
<b>Performance</b>	<b>System switching capacity</b>	880 Gbps	
	<b>System throughput capacity</b>	660 Mpps	
	<b>Model switching capacity</b>	448 Gbps	
	<b>Model throughput capacity</b>	334 Mpps	
	<b>Average latency (LIFO, 64-byte packets)</b>	1Gbps:	2.28μSec
		10Gbps:	1.46μSec
		25Gbps:	1.90μSec
		50Gbps:	3.49μSec
	<b>Stack size</b>	10 members	
	<b>Max stacking distance</b>	Up to 10 kms with long range transceivers	
	<b>Stacking bandwidth</b>	200 Gbps (400 Gbps at full duplex)	
	<b>Switched virtual interfaces (dual stack)</b>	1,024	
	<b>IPv4 host table (ARP)</b>	49,152	
	<b>IPv6 host table (ND)</b>	49,152	
	<b>IPv4 unicast routes</b>	61,000	
	<b>IPv6 unicast routes</b>	61,000	
	<b>IPv4 multicast routes</b>	8,192	
	<b>IPv6 multicast routes</b>	8,192	
	<b>MAC table capacity</b>	32,768	
	<b>IGMP groups</b>	4,096	
	<b>MLD groups</b>	8,192	
	<b>IPv4/IPv6/MAC ACL entries (ingress)</b>	20,480/5,120/20,480	
	<b>IPv4/IPv6/MAC ACL entries (egress)</b>	<b>ACL</b>	8,192/2,048/8,192
<b>VRF</b>	256		

## Technical Specifications

<b>Environment</b>	<b>Operating temperature</b>	32°F to 113°F (0°C to 45°C), up to 5,000 feet 32°F to 104°F (0°C to 40°C), 5,001 to 10,000 feet 1°C de-rating per 1,000 feet above 5,000 feet Can support excursion to 131°F (55°C) for short periods <sup>1</sup> of time.
	<b>Operating humidity</b>	15% to 95% relative humidity at 104°F (40°C), non-condensing
	<b>Non-operating temperature</b>	-40°F to 158°F (-40°C to 70°C)
	<b>Non-operating humidity</b>	15% to 95% relative humidity at 149°F(65°C), non-condensing
	<b>Max operating altitude</b>	Up to 10,000ft (3.048 Km)
	<b>Max non-operating altitude</b>	Up to 15,000ft (3.048 Km)
	<b>Acoustic</b>	Sound power, LWAd = 4.9 Bel Sound pressure, LpAm (bystander) = 31.6 dB
	<b>Primary airflow</b>	Front and side-to-back
<b>Electrical Characteristics</b>	<b>Frequency</b>	50-60 Hz
	<b>AC voltage</b>	Fixed PSU: 100V-120V/200V-240V
	<b>Current (for voltages listed above)</b>	Fixed PSU: 2.5A/1.4A
	<b>Power Consumption (230VAC)</b>	Idle: 49W 100% traffic rate: 63W
<b>Safety</b>	<b>Europe:</b> EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011 + A2:2013 <b>US:</b> UL 60950-1 2nd Ed.. <b>Canada:</b> CAN/CSA-C22.2 No. 60950-1-07 <b>Worldwide:</b> IEC 60950-1:2005 w/all known National Deviations	
<b>Emissions</b>	<b>Europe:</b> EN 55022:2010, Class A EN 55032:2012, Class A EN 55024:2010, EN 61000-3-2:2014 EN 61000-3-3:2013 <b>US:</b> FCC part 15 Class A <b>Canada:</b> ICES-003 Class A <b>Worldwide:</b> VCCI Class A, CISPR 22 Class A CISPR 32 Class A CISPR 24:2010	
<b>Lasers</b>	EN 60825-1:2007 / IEC 60825-1:2007 Class 1 Class 1 Laser Products / Laser Klasse 1 (Applicable for accessories - Optical Transceivers only)	
<b>Immunity</b>	<b>Generic</b>	CISPR 24 / CISPR 35
	<b>EN</b>	EN 55024:2010 / EN 55035:2017
	<b>ESD</b>	IEC 61000-4-2
	<b>Radiated</b>	IEC 61000-4-3
	<b>EFT/Burst</b>	IEC 61000-4-4
	<b>Surge</b>	IEC 61000-4-5
	<b>Conducted</b>	IEC 61000-4-6
	<b>Power frequency magnetic field</b>	IEC 61000-4-8
	<b>Voltage dips and interruptions</b>	IEC 61000-4-11
	<b>Harmonics</b>	IEC 61000-3-2, EN 61000-3-2
<b>Flicker</b>	IEC 61000-3-3, EN 61000-3-3	

**Notes:** <sup>1</sup> Not more than 96 consecutive hours or 360 hours total or 15 occurrences in a 1-year period.





## Technical Specifications

### Standards and Protocols

Applies to all products in series

- ANSI/TIA-1057 LLDP Media Endpoint Discovery (LLDP-MED)
- CPU DoS Protection
- Bootstrap Router (BSR) Mechanism for PIM, PIM WG
- Draft-ietf-savi-mix
- IEEE 802.1AB-2005
- IEEE 802.1ak-2007
- IEEE 802.1AX-2008 Link Aggregation
- IEEE 802.1D MAC Bridges
- IEEE 802.1p Priority
- IEEE 802.1Q VLANs
- IEEE 802.1s Multiple Spanning Trees
- IEEE 802.1t-2001
- IEEE 802.1v VLAN classification by Protocol and Port
- IEEE 802.1w Rapid Reconfiguration of Spanning Tree
- IEEE 802.3ab 1000BASE-T
- IEEE 802.3ad Link Aggregation Control Protocol (LACP)
- IEEE 802.3ae 10-Gigabit Ethernet
- IEEE 802.3af Power over Ethernet
- IEEE 802.3at Power over Ethernet
- IEEE 802.3bt Power over Ethernet
- IEEE 802.3az Energy Efficient Ethernet (EEE)
- IEEE 802.3x Flow Control
- IEEE 802.3z 1000BASE-X
- RFC 783 TFTP Protocol (revision 2)
- RFC 791 IP
- RFC 792 ICMP
- RFC 793 TCP
- RFC 813 Window and Acknowledgement Strategy in TCP
- RFC 815 IP datagram reassembly algorithms
- RFC 826 ARP
- RFC 879 TCP maximum segment size and related topics
- RFC 896 Congestion control in IP/TCP internetworks
- RFC 917 Internet subnets
- RFC 919 Broadcasting Internet Datagrams
- RFC 922 Broadcasting Internet Datagrams in the Presence of Subnets (IP\_BROAD)
- RFC 925 Multi-LAN address resolution
- RFC 951 BOOTP
- RFC 1027 Proxy ARP
- RFC 1122 Requirements for Internet Hosts - Communications Layers
- RFC 1215 Convention for defining traps for use with the SNMP
- RFC 1256 ICMP Router Discovery Messages
- RFC 1350 TFTP Protocol (revision 2)
- RFC 1393 Traceroute Using an IP Option
- RFC 1403 BGP OSPF Interaction
- RFC 1519 CIDR
- RFC 1542 BOOTP Extensions
- RFC 1583 OSPF Version 2
- RFC 1591 Domain Name System Structure and Delegation

## Technical Specifications

- RFC 1657 Definitions of Managed Objects for BGP-4 using SMIv2
- RFC 1772 Application of the Border Gateway Protocol on the Internet
- RFC 1757 Remote Network Monitoring Management Information Base
- RFC 1812 Requirements for IP Version 4 Router
- RFC 1918 Address Allocation for Private Internet
- RFC 1997 BGP Communities Attribute
- RFC 1998 An Application of the BGP Community Attribute in Multi-home Routing
- RFC 2131 DHCP
- RFC 2132 DHCP Options and BOOTP Vendor Extensions
- RFC 2236 IGMP
- RFC 2328 OSPF Version 2
- RFC 2375 IPv6 Multicast Address Assignments
- RFC 2385 Protection of BGP Sessions via the TCP MD5 Signature Option
- RFC 2401 Security Architecture for the Internet Protocol
- RFC 2402 IP Authentication Header
- RFC 2439 BGP Route Flap Damping
- RFC 2460 Internet Protocol, Version 6 (IPv6) Specification
- RFC 2464 Transmission of IPv6 over Ethernet Networks
- RFC 2545 Use of BGP-4 Multiprotocol Extensions for IPv6 Inter-Domain Routing
- RFC 2576 (Coexistence between SNMP V1, V2, V3)
- RFC 2579 (SMIv2 Text Conventions)
- RFC 2580 (SMIv2 Conformance)
- RFC 2710 Multicast Listener Discovery (MLD) for IPv6
- RFC 2711 IPv6 Router Alert Option
- RFC 2787 Definitions of Managed Objects for the Virtual Router Redundancy Protocol
- RFC 2918 Route Refresh Capability for BGP-4
- RFC 2925 Definitions of Managed Objects for Remote Ping, Traceroute, and Lookup Operations (Ping only)
- RFC 2934 Protocol Independent Multicast MIB for IPv4
- RFC 3019 MLDv1 MIB
- RFC 3046 DHCP Relay Agent Information Option
- RFC 3056 Connection of IPv6 Domains via IPv4 Clouds
- RFC 3065 Autonomous System Confederation for BGP
- RFC 3068 An Anycast prefix for 6to4 Relay Route
- RFC 3101 OSPF Not-so-stubby-area option
- RFC 3137 OSPF Stub Router Advertisement sFlow
- RFC 3376 IGMPv3
- RFC 3416 (SNMP Protocol Operations v2)
- RFC 3417 (SNMP Transport Mappings)
- RFC 3418 Management Information Base (MIB) for the Simple Network Management Protocol (SNMP)
- RFC 3484 Default Address Selection for IPv6
- RFC 3509 Alternative Implementations of OSPF Area Border Routers
- RFC 3575 IANA Considerations for RADIUS
- RFC 3623 Graceful OSPF Restart
- RFC 3768 VRRP
- RFC 3810 Multicast Listener Discovery Version 2 (MLDv2) for IPv6
- RFC 3973 PIM Dense Mode
- RFC 4022 MIB for TCP
- RFC 4113 MIB for UDP
- RFC 4213 Basic Transition Mechanisms for IPv6 Hosts and Routers
- RFC 4251 The Secure Shell (SSH) Protocol

## Technical Specifications

- RFC 4252 SSHv6 Authentication
- RFC 4253 SSHv6 Transport Layer
- RFC 4254 SSHv6 Connection
- RFC 4271 A Border Gateway Protocol 4 (BGP-4)
- RFC 4273 Definitions of Managed Objects for BGP-4
- RFC 4291 IP Version 6 Addressing Architecture
- RFC 4292 IP Forwarding Table MIB
- RFC 4293 Management Information Base for the Internet Protocol (IP)
- RFC 4360 BGP Extended Communities Attribute
- RFC 4419 Key Exchange for SSH
- RFC 4443 ICMPv6
- RFC 4456 BGP Route Reflection: An Alternative to Full Mesh Internal BGP (IBGP)
- RFC 4486 Subcodes for BGP Cease Notification Message
- RFC 4541 IGMP & MLD Snooping Switch
- RFC 4552 Authentication/Confidentiality for OSPFv3
- RFC 4601 PIM Sparse Mode
- RFC 4607 Source-Specific Multicast for IP
- RFC 4675 RADIUS VLAN & Priority
- RFC 4724 Graceful Restart Mechanism for BGP
- RFC 4750 OSPFv2 MIB partial support no SetMIB
- RFC 4760 Multiprotocol Extensions for BGP-4
- RFC 4861 IPv6 Neighbor Discovery
- RFC 4862 IPv6 Stateless Address Auto-configuration
- RFC 4940 IANA Considerations for OSPF
- RFC 5065 Autonomous System Confederation for BGP
- RFC 5095 Deprecation of Type 0 Routing Headers in IPv6
- RFC 5187 OSPFv3 Graceful Restart
- RFC 5340 OSPFv3 for IPv6
- RFC 5424 Syslog Protocol
- RFC 5492 Capabilities Advertisement with BGP-4
- RFC 5519 Multicast Group Membership Discovery MIB (MLDv2 only)
- RFC 5701 IPv6 Address Specific BGP Extended Community Attribute
- RFC 5722 Handling of Overlapping IPv6 Fragments
- RFC 5798 VRRP (exclude Accept Mode and sub-sec timer)
- RFC 5880 Bidirectional Forwarding Detection
- RFC 5905 Network Time Protocol Version 4: Protocol and Algorithms Specification
- RFC 6620 FCFS SAVI
- RFC 6987 OSPF Stub Router Advertisement
- RFC 7047 The Open vSwitch Database Management Protocol
- RFC 7313 Enhanced Route Refresh Capability for BGP-4
- RFC 8201 Path MTU Discovery for IP version 6
- SNMPv1/v2c/v3
- ITU-T Rec G.8032/Y.1344 Mar. 2010
- 2.5G/5GBASE-T (IEEE 802.3bz-2016), 2.5G/5G NBASE-T
- 10GBASE-T (IEEE 802.3an-2006)
- 25-Gigabit Ethernet (IEEE 802.3by-2016, 802.3cc-2017)
- 40-Gigabit Ethernet (IEEE 802.3ba-2010)
- 50-Gigabit Ethernet (IEEE 802.3cd-2018)
- 100-Gigabit Ethernet (IEEE 802.3ba-2010, 802.3bj-2014, 802.3bm-2014)

## HPE Aruba Networking Data Center Solution

### New HPE Aruba Networking Data Center Solution SKUs

HPE and HPE Aruba Networking offer customers highly differentiated pre-engineered IT infrastructure solutions that span a wide variety HPE compute, HPE storage, HPE Aruba Networking that span virtualization, vSAN, HCI, HPC, MCS, Microsoft, SAP HANA, VMware, Nutanix application and IaaS service offerings. HPE Aruba Networking 10/25 and 40/100G CX switches can be deployed as part of these solutions and is often designed into these integrated solutions along with HPE ProLiant DL/DX servers, SimpliVity, Nimble, Synergy, Cray Shasta, Cray ClusterStor, Superdome Flex and HPE GreenLake. These ready-to-deploy, integrated IT data center solutions help simplify and speed IT service delivery while reducing the time, risk, and expertise needed to deploy complex solutions.

To ensure that these HPE and HPE Aruba Networking integrated solutions receive simplified ordering and the highest-level of customer service and support, HPE Aruba Networking has created a special tracking HPE Aruba Networking Data Center SKUs for HPE deployments that identifies these integrated solutions to ensure they receive rapid support triage and streamlines escalation through HPE Services. Please use these new tracking SKUs when HPE Aruba Networking CX switches are included in HPE integrated and mixed HPE compute, HPE storage and HPE Aruba Networking configuration and deployments.

**Notes:** Current HPE Aruba Networking “J#” SKUs should still be used for all data center network centric (HPE Aruba Networking “only”, Non HPE environments). Please contact your sales representative for additional information and ordering guidance.

### HPE Aruba Networking CX 6300 DC Switch Series

#### BTO Models

Rule #	Description	SKU
1, 2, 3, 4, 5, 6	HPE Aruba Networking CX 6300M 48G Power-to-Port Airflow 2 Fans 1 Power Supply Unit Bundle <ul style="list-style-type: none"> <li>HPE Aruba Networking 6300M 48-port 1GbE and 4-port SFP56 Power-to-Port 2 Fan Trays 1 PSU Bundle</li> <li>Includes 1 Pwr2Prt PSU, can select Min0 / Max1 (250W R9F61A)</li> <li>Includes 2 Pwr2Prt Fan trays (R9F62A), with no open slots</li> <li>Min=0 \ Max = 4 SFP/SFP+/SFP28/SFP56 1/10/25/50G Transceiver</li> <li>1U - Height</li> </ul>	R9F63A
	HPE Aruba Networking CX 6300M 48G Power-to-Port Airflow 2 Fans 1 Power Supply Unit Bundle PDU <ul style="list-style-type: none"> <li>C15 PDU Jumper Cord (NA/MEX/TW/JP) (J9943A)</li> </ul>	R9F63A#B2B
	HPE Aruba Networking CX 6300M 48G Power-to-Port Airflow 2 Fans 1 Power Supply Unit Bundle PDU <ul style="list-style-type: none"> <li>C15 PDU Jumper Cord (ROW) (J9944A)</li> </ul>	R9F63A#B2C
	HPE Aruba Networking CX 6300M 48G Power-to-Port Airflow 2 Fans 1 Power Supply Unit Bundle 220v <ul style="list-style-type: none"> <li>HPE 2.5m C15 to NEMA 6-20P Pwr Cord (JL336A)</li> </ul>	R9F63A#B2E
	HPE Aruba Networking CX 6300M 48G Power-to-Port Airflow 2 Fans 1 Power Supply Unit Bundle NoLoc <ul style="list-style-type: none"> <li>No Localized Power Cord Selected. Use J9955A to obtain a Locking Plug Power Cord (L6-20P)</li> </ul>	R9F63A#AC3

#### Configuration Rules

Rule #	Description	
1	<b>The following Transceivers install into this Switch: (Use BTO only when adding to switch)</b> Aruba 1G SFP LC SX 500m OM2 MMF Transceiver for HPE HPE Aruba Networking 1G SFP LC LX 10km SMF Transceiver HPE Aruba Networking 1G SFP LC LH 70km SMF Transceiver HPE Aruba Networking 1G SFP RJ45 T 100m Cat5e Transceiver Aruba 1G SFP LC SX 500m MMF TAA Transceiver for HPE HPE Aruba Networking 1G SFP LC LX 10km SMF TAA Transceiver HPE Aruba Networking 1G SFP RJ45 T 100m Cat5e TAA Transceiver	R9F86A J4859D J4860D R9F87A R9Q43A R9Q44A R9Q45A
2	<b>The following Transceivers install into this Switch: (Use BTO only when adding to switch)</b> Aruba 10GBASE-T SFP+ RJ45 30m Cat6A Transceiver for HPE HPE Aruba Networking 10G SFP+ LC SR 300m OM3 MMF Transceiver	R9F85A R9F82A

## HPE Aruba Networking Data Center Solution

	HPE Aruba Networking 10G SFP+ LC LR 10km SMF Transceiver	J9151E
	HPE Aruba Networking 10G SFP+ LC ER 40km SMF Transceiver	J9153D
	HPE Aruba Networking 10G SFP+ LC SR 300m MMF TAA Transceiver	R9Q46A
	Aruba 10G SFP+ LC LR 10km SMF TAA Transceiver for HPE	R9Q47A
	HPE Aruba Networking 10G SFP+ to SFP+ 1m Direct Attach Copper Cable	R9F83A
	HPE Aruba Networking 10G SFP+ to SFP+ 3m Direct Attach Copper Cable	R9F84A
3	<b>The following Transceivers install into this Switch: (Use BTO only when adding to switch)</b>	
	HPE Aruba Networking 25G SFP28 LC SR 100m MMF Transceiver	R9F89A
	HPE Aruba Networking 25G SFP28 LC eSR 400m MMF Transceiver	R9F90A
	HPE Aruba Networking 25G SFP28 LC LR 10km SMF Transceiver	JL486A
	HPE Aruba Networking 25G SFP28 to SFP28 0.65m Direct Attach Copper Cable	R9F91A
	HPE Aruba Networking 25G SFP28 to SFP28 3m Direct Attach Copper Cable	R9F92A
	HPE Aruba Networking 25G SFP28 to SFP28 5m Direct Attach Copper Cable	R9F93A
4	<b>The following Transceivers install into this Switch: (Use BTO only when adding to switch)</b>	
	HPE Aruba Networking 50G SFP56 to SFP56 0.65m Direct Attach Copper Cable	R9G06A
	HPE Aruba Networking 50G SFP56 to SFP56 3m Direct Attach Copper Cable	R9G07A
5	<b>Localization required on orders without B2B, B2C, B2E or AC3 options.</b>	
6	<b>The following Transceivers install into this Switch: (Use BTO only when adding to switch)</b>	
	Aruba 100M SFP LC FX 2km MMF Transceiver for HPE	R9F88A

### Notes:

- Drop down under power supply should offer the following options and results:
  - Switch/Router/Power Supply to PDU Power Cord - B2B in North America, Mexico, Taiwan, and Japan or B2C ROW. (Watson Default B2B or B2C for Rack Level CTO)
  - Switch/Router/Power Supply to Wall Power Cord - Localized Option (Watson Default for BTO and Box Level CTO)
- High Volt Switch/Router/Power Supply to Wall Power Cord - B2E Option. (Offered only in North America, Mexico, Taiwan, and Japan)
- No Power Cord - AC3 Option
- Locking Power Cord (J9955A) L6-20P is available through the OCA Accessories tab
- OCA Only Model Selection Form - HPE Offering > HPE Aruba Networking > DC Solutions Switches for HPE > AOS-CX: HPE Aruba Networking 6300 DC Switch Series

### Rack Level Integration CTO Models

Rule #	Description	SKU
1, 2, 3, 4, 5, 6, 7	HPE Aruba Networking CX 6300M 48G Power-to-Port Airflow 2 Fans 1 Power Supply Unit Bundle	R9F63A
	<ul style="list-style-type: none"> <li>• HPE Aruba Networking 6300M 48-port 1GbE and 4-port SFP56 Power-to-Port 2 Fan Trays 1 PSU Bundle</li> <li>• Includes 1 Pwr2Prt PSU, can select Min0 / Max1 (250W R9F61A)</li> <li>• Includes 2 Pwr2Prt Fan trays (R9F62A), with no open slots</li> <li>• Min=0 \ Max = 4 SFP/SFP+/SFP28/SFP56 1/10/25/50G Transceiver</li> <li>• 1U - Height</li> </ul>	
	HPE Aruba Networking CX 6300M 48G Power-to-Port Airflow 2 Fans 1 Power Supply Unit Bundle PDU	R9F63A#B2B
	<ul style="list-style-type: none"> <li>• C15 PDU Jumper Cord (NA/MEX/TW/JP) (J9943A)</li> </ul>	
	HPE Aruba Networking CX 6300M 48G Power-to-Port Airflow 2 Fans 1 Power Supply Unit Bundle PDU	R9F63A#B2C
	<ul style="list-style-type: none"> <li>• C15 PDU Jumper Cord (ROW) (J9944A)</li> </ul>	
	HPE Aruba Networking CX 6300M 48G Power-to-Port Airflow 2 Fans 1 Power Supply Unit Bundle 220v	R9F63A#B2E
	<ul style="list-style-type: none"> <li>• HPE 2.5m C15 to NEMA 6-20P Pwr Cord (JL336A)</li> </ul>	
	HPE Aruba Networking CX 6300M 48G Power-to-Port Airflow 2 Fans 1 Power Supply Unit Bundle NoLoc	R9F63A#AC3
	<ul style="list-style-type: none"> <li>• No Localized Power Cord Selected. Use J9955A to obtain a Locking Plug Power Cord (L6-20P)</li> </ul>	

### Configuration Rules



## HPE Aruba Networking Data Center Solution

Rule #	Description	
1	<b>The following Transceivers install into this Switch: (Use OD1 or B01 quoted to switch if switch is CTO) - if applicable:</b> Aruba 1G SFP LC SX 500m OM2 MMF Transceiver for HPE HPE Aruba Networking 1G SFP LC LX 10km SMF Transceiver HPE Aruba Networking 1G SFP LC LH 70km SMF Transceiver HPE Aruba Networking 1G SFP RJ45 T 100m Cat5e Transceiver Aruba 1G SFP LC SX 500m MMF TAA Transceiver for HPE HPE Aruba Networking 1G SFP LC LX 10km SMF TAA Transceiver HPE Aruba Networking 1G SFP RJ45 T 100m Cat5e TAA Transceiver	R9F86A J4859D J4860D R9F87A R9Q43A R9Q44A R9Q45A
2	<b>The following Transceivers install into this Switch: (Use OD1 quoted to switch if switch is CTO) - if applicable:</b> Aruba 10GBASE-T SFP+ RJ45 30m Cat6A Transceiver for HPE HPE Aruba Networking 10G SFP+ LC SR 300m OM3 MMF Transceiver HPE Aruba Networking 10G SFP+ LC LR 10km SMF Transceiver HPE Aruba Networking 10G SFP+ LC ER 40km SMF Transceiver HPE Aruba Networking 10G SFP+ LC SR 300m MMF TAA Transceiver Aruba 10G SFP+ LC LR 10km SMF TAA Transceiver for HPE HPE Aruba Networking 10G SFP+ to SFP+ 1m Direct Attach Copper Cable HPE Aruba Networking 10G SFP+ to SFP+ 3m Direct Attach Copper Cable	R9F85A R9F82A J9151E J9153D R9Q46A R9Q47A R9F83A R9F84A
3	<b>The following Transceivers install into this Switch: (Use OD1 or B01 quoted to switch if switch is CTO) - if applicable:</b> HPE Aruba Networking 25G SFP28 LC SR 100m MMF Transceiver HPE Aruba Networking 25G SFP28 LC eSR 400m MMF Transceiver HPE Aruba Networking 25G SFP28 LC LR 10km SMF Transceiver HPE Aruba Networking 25G SFP28 to SFP28 0.65m Direct Attach Copper Cable HPE Aruba Networking 25G SFP28 to SFP28 3m Direct Attach Copper Cable HPE Aruba Networking 25G SFP28 to SFP28 5m Direct Attach Copper Cable	R9F89A R9F90A JL486A R9F91A R9F92A R9F93A
4	<b>The following Transceivers install into this Switch: (Use OD1 or B01 quoted to switch if switch is CTO) - if applicable:</b> HPE Aruba Networking 50G SFP56 to SFP56 0.65m Direct Attach Copper Cable HPE Aruba Networking 50G SFP56 to SFP56 3m Direct Attach Copper Cable	R9G06A R9G07A
5	Localization required on orders without B2B, B2C, B2E or AC3 options.	
6	If the CTO Switch Chassis needs to be racked, Then the CTO Base Model needs to integrate (with OD1) to the HPE Network Rack.	
7	When Switches are Factory Racked with this power supply, Then B2B, or B2C should be the Defaulted Power Cable option on the Power Supplies. (See Drop down remark in "Power Supplies" section.)	
8	The following Transceivers install into this Switch: (Use BTO only when adding to switch) R9F88A - Aruba 100M SFP LC FX 2km MMF Transceiver for HPE Aruba 100M SFP LC FX 2km MMF Transceiver for HPE	R9F88A
<b>Notes:</b>	<ul style="list-style-type: none"> <li>- Drop down under power supply should offer the following options and results: <ul style="list-style-type: none"> <li>o Switch/Router/Power Supply to PDU Power Cord - B2B in North America, Mexico, Taiwan, and Japan or B2C ROW. (OCA Default B2B or B2C for Rack Level CTO)</li> <li>o Switch/Router/Power Supply to Wall Power Cord - Localized Option (OCA Default for BTO)</li> </ul> </li> <li>- High Volt Switch/Router/Power Supply to Wall Power Cord - B2E Option. (Offered only in North America, Mexico, Taiwan, and Japan)</li> <li>- No Power Cord - AC3 Option</li> <li>- Locking Power Cord (J9955A) L6-20P is available through the OCA Accessories tab</li> </ul>	

## HPE Aruba Networking Data Center Solution

### Transceivers

<b>SFP Transceivers</b>		
Rule #	Description	SKU
	Aruba 100M SFP LC FX 2km MMF Transceiver for HPE	R9F88A
<b>Notes:</b>	<b>Not supported in the SFP56 Ports</b>	
	Aruba 1G SFP LC SX 500m OM2 MMF Transceiver for HPE	R9F86A
	HPE Aruba Networking 1G SFP LC LX 10km SMF Transceiver	J4859D
	HPE Aruba Networking 1G SFP LC LH 70km SMF Transceiver	J4860D
	HPE Aruba Networking 1G SFP RJ45 T 100m Cat5e Transceiver	R9F87A
	Aruba 1G SFP LC SX 500m MMF TAA Transceiver for HPE	R9Q43A
	HPE Aruba Networking 1G SFP LC LX 10km SMF TAA Transceiver	R9Q44A
	HPE Aruba Networking 1G SFP RJ45 T 100m Cat5e TAA Transceiver	R9Q45A
<b>SFP+ Transceivers</b>		
Rule #	Description	SKU
1	Aruba 10GBASE-T SFP+ RJ45 30m Cat6A Transceiver for HPE	R9F85A
	HPE Aruba Networking 10G SFP+ LC SR 300m OM3 MMF Transceiver	R9F82A
	HPE Aruba Networking 10G SFP+ LC LR 10km SMF Transceiver	J9151E
	HPE Aruba Networking 10G SFP+ LC ER 40km SMF Transceiver	J9153D
	HPE Aruba Networking 10G SFP+ LC SR 300m MMF TAA Transceiver	R9Q46A
	Aruba 10G SFP+ LC LR 10km SMF TAA Transceiver for HPE	R9Q47A
	HPE Aruba Networking 10G SFP+ to SFP+ 1m Direct Attach Copper Cable	R9F83A
	HPE Aruba Networking 10G SFP+ to SFP+ 3m Direct Attach Copper Cable	R9F84A
<b>SFP28 Transceivers</b>		
Rule #	Description	SKU
	HPE Aruba Networking 25G SFP28 LC SR 100m MMF Transceiver	R9F89A
	HPE Aruba Networking 25G SFP28 LC eSR 400m MMF Transceiver	R9F90A
	HPE Aruba Networking 25G SFP28 LC LR 10km SMF Transceiver	JL486A
	HPE Aruba Networking 25G SFP28 to SFP28 0.65m Direct Attach Copper Cable	R9F91A
	HPE Aruba Networking 25G SFP28 to SFP28 3m Direct Attach Copper Cable	R9F92A
	HPE Aruba Networking 25G SFP28 to SFP28 5m Direct Attach Copper Cable	R9F93A
<b>SFP56 Transceivers</b>		
Rule #	Description	SKU
	HPE Aruba Networking 50G SFP56 to SFP56 0.65m Direct Attach Copper Cable	R9G06A
	HPE Aruba Networking 50G SFP56 to SFP56 3m Direct Attach Copper Cable	R9G07A

### Switch Options

<b>Fan Trays</b>		
Rule #	Description	SKU
1	R9F63A System (std 2 // max 2) User Selection (min 0 // max 0) per enclosure	
	HPE Aruba Networking CX 6300M Power-to-Port Airflow Fan Tray	R9F62A
<b>Notes:</b>	<b>Spare only</b>	
<b>Configuration Rules</b>		
Rule #	Description	SKU
1	<b>The Following Switch is only compatible with this Power to Port FanTray;</b>	
	HPE Aruba Networking CX 6300M 48G Power-to-Port Airflow 2 Fans 1 Power Supply Unit Bundle	R9F63A
<b>Notes:</b>	<b>This switch includes 2 Fan Trays. No additional Fan Trays necessary"</b>	
<b>Rack Mount Kits</b>		
	System (std 0 // max 1) User Selection (min 0 // max 1) per enclosure	
	HPE Aruba Networking 1U Universal 4-post Rack Mount Kit	R9F57A
<b>Notes:</b>	<b>If the switch will be factory racked into an HPE Universal Rack, then (Min 1) of the 4 Post Rack Mount kit is required and should nest to Rack.</b>	

## HPE Aruba Networking Data Center Solution

	<b>Air Duct Kit</b>	
	For System (std 0 // max 1) User Selection (min 0 // max 1) per Switch	
1, 2, 3	HPE Aruba Networking Universal 4-post Duct Kit	R9F60A
<b>Notes:</b>	Only for Power to Port Bundles	
	<b>Configuration Rules</b>	
<b>Rule #</b>	<b>Description</b>	
1	The Following Switch is only compatible with this Power to Port FanTray;	
	HPE Aruba Networking CX 6300M 48G Power-to-Port Airflow 2 Fans 1 Power Supply Unit Bundle	R9F63A
2	For optimal performance, it is recommended that the user select the Duct Kit for Power to Port Switch Bundles	
3	If this Air Duct Kit is selected, then the following 4 Post Rack Mount kit must be selected:	
	HPE Aruba Networking 1U Universal 4-post Rack Mount Kit	R9F57A
	<b>India PDU Cable</b>	
	For R9F63A (std 0 // max 1) User Selection (min 0 // max 1) per enclosure	
1	HPE Networking 2.0m C13 to C14 PDU India Power Cord	JL671A
	<ul style="list-style-type: none"> <li>C13 India PDU Cable for Factory Racked Systems Only</li> </ul>	
1	HPE Networking 2.5m C15 to C14 PDU India Power Cord	JL672A
	<ul style="list-style-type: none"> <li>C15 India PDU Cable for Factory Racked Systems Only</li> </ul>	
	<b>Configuration Rules</b>	
<b>Rule #</b>	<b>Description</b>	
1	This Power Cord is only valid when the #AC3 option is selected for the supported Switch Enclosure	
<b>Notes:</b>	This PDU cable is for Solutions shipping to India.	

## Power Supplies

	<b>Power Supply Units</b>	
	R9F63A System (std 1 // max 2) User Selection (min 0 // max 1) per enclosure	
1, 2	HPE Aruba Networking CX 6300M 12VDC 250W 100-240VAC Power-to-Port Airflow Power Supply Unit	R9F61A
	<ul style="list-style-type: none"> <li>Uses 1 x C13, 250w</li> </ul>	
	HPE Aruba Networking CX 6300M 12VDC 250W 100-240VAC Power-to-Port Airflow Power Supply Unit PDU	R9F61A#B2B
	<ul style="list-style-type: none"> <li>C13 PDU Jumper Cord (NA/MEX/TW/JP) (J9943A)</li> </ul>	
	HPE Aruba Networking CX 6300M 12VDC 250W 100-240VAC Power-to-Port Airflow Power Supply Unit PDU	R9F61A#B2C
	<ul style="list-style-type: none"> <li>C13 PDU Jumper Cord (ROW) (J9944A)</li> </ul>	
	HPE Aruba Networking CX 6300M 12VDC 250W 100-240VAC Power-to-Port Airflow Power Supply Unit 220v	R9F61A#B2E
	<ul style="list-style-type: none"> <li>HPE 2.5m C13 to NEMA 6-20P Pwr Cord (JL336A)</li> </ul>	
	HPE Aruba Networking CX 6300M 12VDC 250W 100-240VAC Power-to-Port Airflow Power Supply Unit NoLoc	R9F61A#AC3
	<ul style="list-style-type: none"> <li>No Localized Power Cord Selected. Use J9955A to obtain a Locking Plug Power Cord (L6-20P)</li> </ul>	
	<b>Configuration Rules</b>	
<b>Rule #</b>	<b>Description</b>	
1	Localization (Wall Power Cord) required on orders without B2B, B2C, (PDU Power Cord) or B2E. (See Localization Menu)	
2	The Following Switch is only compatible with this Power to Port PSU:	
	HPE Aruba Networking CX 6300M 48G Power-to-Port Airflow 2 Fans 1 Power Supply Unit Bundle	R9F63A
<b>Notes:</b>	<ul style="list-style-type: none"> <li>Drop down under power supply should offer the following options and results: <ul style="list-style-type: none"> <li>Switch/Router to PDU Power Cord - B2B in NA, Mexico, Taiwan, and Japan or B2C ROW. (OCA Default B2B or B2C for Rack Level CTO)</li> <li>Switch/Router/Power Supply to Wall Power Cord - Localized Option (OCA Default for BTO and Box Level CTO)</li> </ul> </li> </ul>	



## HPE Aruba Networking Data Center Solution

- High Volt Switch/Router/Power Supply to Wall Power Cord - B2E Option. (Offered only in North America, Mexico, Taiwan, and Japan)
- No Localized Power Cord Selected - AC3 Option
- If you want the Locking Power Cord (J9955A) L6-20P, then you must order this power cord through the Accessories tab

### PSU Options

For R9F61A (std 0 // max 1) User Selection (min 0 // max 1) per PSU

HPE Networking 2.0m C13 to C14 PDU India Power Cord JL671A

- C13 India PDU Cable for Factory Racked Systems Only

HPE Networking 2.5m C15 to C14 PDU India Power Cord JL672A

- C15 India PDU Cable for Factory Racked Systems Only

### Notes:

- This Power Cord is only valid when the #AC3 option is selected for the supported Power Supply
- This PDU cable is for Solutions shipping to India.

## Software

### HPE Aruba Networking Net Edit

#### Single Node Subscription for Data Center Solutions

Aruba NetEdit Single Node 1 year Subscription E-STU for HPE R9G36AAE

Aruba NetEdit Single Node 3 year Subscription E-STU for HPE R9G37AAE

### HPE Aruba Networking Fabric Composer

#### Single Node Subscription for Data Center Solutions

HPE Aruba Networking Fabric Composer Device Management Service Tier 3 Switch 1y Subscription E-STU R9G31AAE

HPE Aruba Networking Fabric Composer Device Management Service Tier 3 Switch 3y Subscription E-STU R9G32AAE

HPE Aruba Networking Fabric Composer Device Management Service Tier 3 Switch 5y Subscription E-STU R9G33AAE

## Technical Specifications

### HPE Aruba Networking 6300M 48-port 1GbE and 4-port SFP56 Power-to-Port 2 Fan Trays 1 PSU Bundle

(R9F63A)

<b>Description</b>	48x 10/100/1000 BASE-T PoE+ ports 1G/10G/25G <sup>1</sup> SFP ports <b>Notes:</b> <sup>1</sup> 50G capability is for use with 50G DACs for both interconnect and VSF stacking.	
<b>Additional ports and slots</b>	1x USB-C console port 1x OOBM 1x USB Type A host portJL	
<b>Power supplies</b>	2 field-replaceable, hot-swappable power supply slots Comes with 1 power-to-port power supply pre-installed Additional power-to-port power supply can be ordered separately Supports R9F61A HPE Aruba Networking X371 12VDC 250W 100-240VAC Power-to-Port Power Supply only	
<b>Fan tray</b>	Switch has two fan tray slots and comes with two fan trays installed Fan trays are field replaceable and hot-swappable. Minimum 2 fan trays required. Second fan tray ordered separately Each fan tray is comprised of two fans Supports R9F62A HPE Aruba Networking CX 6300M Power-to-Port Fan Tray only	
<b>Physical characteristics</b>	<b>Dimensions</b>	17.4 (w) x 15.2 (d) x 1.73 (h) in (44.2 x 38.5 x 4.4 cm)
	<b>Weight</b>	12.5 lbs (5.7 kg), with 1 PSU 13.8 lbs (6.27kg), with 2 PSUs

## HPE Aruba Networking Data Center Solution

<b>Mounting and enclosure</b>	Mounts in an EIA- standard 19 in. telco rack or equipment cabinet. Horizontal surface mounting only. 2-post rack kit included.		
<b>CPU</b>	Quad Core ARM Cortex™ A72 @ 1.8GHz		
<b>Memory and Flash</b>	8 GBytes DDR4 32 GBytes eMMC		
<b>Packet Buffer</b>	8 MB shared packet buffer memory		
<b>Performance</b>	<b>System switching capacity</b>	880 Gbps	
	<b>System throughput capacity</b>	660 Mpps	
	<b>Model switching capacity</b>	496 Gbps	
	<b>Model throughput capacity</b>	369 Mpps	
	<b>Average latency (LIFO, 64-byte packets)</b>	1Gbps:	2.28µSec
		10Gbps:	1.46µSec
		25Gbps:	1.90µSec
		50Gbps:	3.49µSec
	<b>Stack size</b>	10 members	
	<b>Max stacking distance</b>	Up to 10 kms with long range transceivers	
	<b>Stacking bandwidth</b>	200 Gbps (400 Gbps at full duplex)	
	<b>Switched virtual interfaces (dual stack)</b>	1,024	
	<b>IPv4 host table (ARP)</b>	49,152	
	<b>IPv6 host table (ND)</b>	49,152	
	<b>IPv4 unicast routes</b>	61,000	
	<b>IPv6 unicast routes</b>	61,000	
	<b>IPv4 multicast routes</b>	8,192	
	<b>IPv6 multicast routes</b>	8,192	
	<b>MAC table capacity</b>	32,768	
	<b>IGMP groups</b>	4,096	
<b>MLD groups</b>	8,192		
<b>IPv4/IPv6/MAC ACL entries (ingress)</b>	20,480/5,120/20,480		
<b>IPv4/IPv6/MAC ACL entries (egress)</b>	8,192/2,048/8,192		
<b>VRF</b>	256		
<b>Environment</b>	<b>Operating temperature</b>	32°F to 113°F (0°C to 45°C), up to 5,000 feet 32°F to 104°F (0°C to 40°C), 5,001 to 10,000 feet 1°C de-rating per 1,000 feet above 5,000 feet Can support excursion to 131°F (55°C) for short periods <sup>1</sup> of time.	
	<b>Operating humidity</b>	15% to 95% relative humidity at 104°F (40°C), non-condensing	
	<b>Non-operating temperature</b>	-40°F to 158°F (-40°C to 70°C)	
	<b>Non-operating humidity</b>	15% to 90% relative humidity at 149°F (65°C), non-condensing	
	<b>Max operating altitude</b>	Up to 10,000ft (3.048 Km)	
	<b>Max non-operating altitude</b>	Up to 15,000ft (3.048 Km)	
	<b>Acoustic</b>	Sound power, LWAd = 4.6 Bel Sound pressure, LpAm (bystander) = 28.7 dB	
	<b>Primary airflow</b>	Back-to-front and side	

## HPE Aruba Networking Data Center Solution

<b>Electrical Characteristics</b>	<b>Frequency</b>	50-60 Hz
	<b>AC voltage</b>	R9F61A PSU: 100V-240V
	<b>Current (for voltages listed above)</b>	R9F61A PSU: 3A/1.2A
	<b>Power Consumption (230VAC)</b>	Hibernation (0 rpm fan): 9W Idle: 56W 100% traffic rate: 75W
<b>Safety</b>	<b>Europe:</b> EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011 + A2:2013, EN 62368-1:2014 +A11:2017 <b>US:</b> UL 60950-1 2nd Ed.. <b>Canada:</b> CAN/CSA-C22.2 No. 60950-1-07 <b>Worldwide:</b> IEC 60950-1:2005 w/all known National Deviations <b>Taiwan:</b> CNS-14336-1	
<b>Emissions</b>	<b>Europe:</b> EN 55032:2015 +AC:2016, Class A, EN 55035:2017, EN 61000-3-2:2014, EN 61000-3-3:2013 <b>US:</b> FCC 47 CFR part 15B, Class A <b>Canada:</b> ICES-003 Class A <b>Worldwide:</b> VCCI Class A, CISPR 32 Ed 2.0: 2015 + COR1:2016, Class A, CISPR 35:2016	
<b>Lasers</b>	EN 60825-1:2007 / IEC 60825-1:2007 Class 1 Class 1 Laser Products / Laser Klasse 1 (Applicable for accessories - Optical Transceivers only)	
<b>Immunity</b>	<b>Generic</b>	CISPR 35
	<b>EN</b>	EN 55035:2017
	<b>ESD</b>	IEC 61000-4-2
	<b>Radiated</b>	IEC 61000-4-3
	<b>EFT/Burst</b>	IEC 61000-4-4
	<b>Surge</b>	IEC 61000-4-5
	<b>Conducted</b>	IEC 61000-4-6
	<b>Power frequency magnetic field</b>	IEC 61000-4-8
	<b>Voltage dips and interruptions</b>	IEC 61000-4-11
	<b>Harmonics</b>	IEC 61000-3-2, EN 61000-3-2
<b>Flicker</b>	IEC 61000-3-3, EN 61000-3-3	





## Summary of Changes

Date	Version History	Action	Description of Change
03-Sep-2024	Version 33	Changed	Configuration Information section was updated.
03-Jun-2024	Version 32	Changed	Configuration Information section was updated.
01-Apr-2024	Version 31	Changed	Configuration Information section was updated.
04-Dec-2023	Version 30	Changed	Obsolete SKU was removed. Configuration Information section was updated. Series name was updated.
06-Nov-2023	Version 29	Changed	Overview, Standard Features, Configuration Information, Technical Specifications sections were updated
07-Aug-2023	Version 28	Changed	Configuration Information section was updated.
10-Jul-2023	Version 27	Changed	Configuration Information section was updated.
15-May-2023	Version 26	Changed	Configuration Information section was updated.
13-Mar-2023	Version 25	Changed	Configuration Information section was updated.
06-Feb-2023	Version 24	Changed	Standard Features, Configuration Information and Technical Specifications sections were updated.
05-Dec-2022	Version 23	Changed	Configuration Information section was updated, and new SKUs were added.
07-Nov-2022	Version 22	Changed	Standard Features, Configuration Information, Technical Specifications sections were updated.
10-Oct-2022	Version 21	Changed	Configuration Information section was updated.
03-Oct-2022	Version 20	Changed	Configuration Information and Aruba Data Center Networking Solution for HPE sections were updated.
15-Aug-2022	Version 19	Changed	Overview, Standard Features, Configuration Information, and Technical Specifications sections were updated.
06-Jun-2022	Version 18	Changed	Standard Features, Configuration Information, Technical Specifications sections were updated.
02-May-2022	Version 17	Changed	Overview, Standard Features, Configuration Information, Technical Specifications and Aruba Data Center Networking Solution for HPE sections were updated.
04-Apr-2022	Version 16	Changed	Configuration Information section was updated.
07-Feb-2022	Version 15	Changed	Configuration Information section was updated.
06-Dec-2021	Version 14	Changed	New Aruba Data Center Networking Solution for HPE section was added to QuickSpecs
02-Aug-2021	Version 13	Changed	Standard Features, Configuration Information, and Technical Specifications section were updated. SKUs added as well.
07-Jun-2021	Version 12	Changed	Overview, Standard Features, and Configuration Information sections were updated.
04-May-2021	Version 11	Changed	Standard Features, Configuration Information, and Technical Specifications sections were updated.
08-Mar-2021	Version 10	Changed	SKUs were added in Configuration Information section.
14-Dec-2020	Version 9	Changed	Overview Standard Features, Configuration information and Technical Specifications sections were updated.
07-Dec-2020	Version 8	Changed	Standard Features, Configuration information and Technical Specifications sections were updated.
08-Sep-2020	Version 7	Changed	Configuration Information section was updated.
10-Aug-2020	Version 6	Changed	Standard Features and Configuration information sections were updated.
06-Jul-2020	Version 5	Changed	Overview Standard Features, Configuration information and Technical Specifications sections were updated.
03-Feb-2020	Version 4	Changed	Configuration information section was updated.
20-Jan-2020	Version 3	Changed	Configuration information and Technical Specifications sections were updated.
06-Jan-2020	Version 2	Changed	Standard Features, Configuration information and Technical Specifications sections were updated.
01-Nov-2019	Version 1	New	New QuickSpecs

## Copyright

Make the right purchase decision.  
Contact our presales specialists.



---

© Copyright 2024 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

To learn more, visit: <http://www.hpe.com/networking>

a00073540enw - 16489 - Worldwide - V33 - 03-September-2024