



DC2000B PCIe 4.0 NVMe M.2 SSD

Enterprise Class for Server Applications

Kingston DC2000B is a high-performance PCIe 4.0 NVMe M.2 SSD using the latest Gen 4x4 PCIe interface with 112-layer 3D TLC NAND. Ideally suited for use in high-volume rack-mount servers as an internal boot drive(s) to preserve valuable front-loading drive bays, as well as for use in purpose-built systems where a high-performance M.2 SSD is needed that includes hardware-based on-board power loss protection (PLP). New for DC2000B is an integrated aluminum heatsink that offers broader thermal compatibility for a wide range of systems. DC2000B delivers low latency and excellent IO consistency to handle various workloads from boot drive applications to high-speed application caching. DC2000B is rated at 0.4 DWPD write endurance and carries a 5-year warranty.

- PCIe 4.0 NVMe Gen 4x4 performance
- Hardware-based power loss protection

Key Features

- **PCIe 4.0 NVMe Performance**
Utilizes PCIe Gen 4x4 lanes for high-performance speeds.
- **On-board Power Loss Protection (PLP)**
Reduce the possibility of data loss and/or corruption due to unexpected power-off.

Specifications

Form Factor	M.2 2280
Interface	PCIe 4.0 x4 NVMe
Capacities ¹	240GB, 480GB, 960GB
NAND	3D TLC
Sequential Read/Write	240GB – 4500/400 MBs 480GB – 7000/800 MBs 960GB – 7000/1300 MBs
Steady-State 4k Read/Write ²	240GB – 260000/18000 IOPS 480GB – 530000/32000 IOPS 960GB – 540000/47000 IOPS
Total Bytes Written (TBW) ³	240GB – 175.2 TBW 480GB – 350.4 TBW 960GB – 700.8 TBW
Latency Read (Avg)	240GB-960GB: 70µs
Latency Write (Avg)	240GB – 53µs 480GB – 29µs 960GB – 20µs
Power Loss Protection (Power Caps)	Yes
Enterprise SMART tools	Reliability tracking, usage statistics, SSD life remaining, wear leveling, temperature

Endurance	240GB — (0.4 DWPD/5yrs) ⁴ 480GB — (0.4 DWPD/5yrs) ⁴ 960GB — (0.4 DWPD/5yrs) ⁴
Power Consumption	240GB: Average Read: 2.97W Average Write: 4.02W Max Read: 3.01W Max Write: 4.09W 480GB: Average Read: 3.22W Average Write: 5.60W Max Read: 3.29W Max Write: 5.77W 960GB: Average Read: 3.26W Average Write: 7.36W Max Read: 3.36W Max Write: 7.80W
Storage temperature	-40°C ~ 85°C
Operating temperature	0°C ~ 70°C
Dimensions	80mm x 22mm x 8.3mm
Weight	240GB – 9g 480GB – 10g 960GB – 11g
Vibration non-operating	20G Peak (10–2000Hz)
MTBF	2 million hours
Warranty/support ⁵	Limited 5-year warranty with free technical support

Part Numbers

SEDC2000BM8

SEDC2000BM8/240G

SEDC2000BM8/480G

SEDC2000BM8/960G

Product Image



1. Some of the listed capacity on a Flash storage device is used for formatting and other functions and thus is not available for data storage. As such, the actual available capacity for data storage is less than what is listed on the product. For more information go to [Kingston's Flash Memory Guide](#).
2. Measurement taken once the workload has reached steady state but including all background activities required for normal operation and data reliability.
3. [Total Bytes Written](#) (TBW) is derived from the JEDEC Client Workload (JESD219A).
4. Drives Writes Per Day (DWPD) derived from the JEDEC Enterprise Workload (JESD219A).
5. Limited warranty based on 5 years or "SSD Life Remaining" which can be found using the [Kingston SSD Manager](#). A new, unused product will show a wear indicator value of one hundred (100), whereas a product that has reached its endurance limit of program erase cycles will show a wear indicator value of one (1). See [Kingston.com/wa](#) for details.



THIS DOCUMENT SUBJECT TO CHANGE WITHOUT NOTICE.

©2024 Kingston Technology Corporation, 17600 Newhope Street, Fountain Valley, CA 92708 USA. All rights reserved. All trademarks and registered trademarks are the property of their respective owners. MKD-07242024