

TD-2D range

Labelling solutions built for real work

Brother's range of TD professional label printers offer the ability to print high quality labels on demand while bridging the gap between full desktop and portable printing.

Brother's range of TD professional label printers offer the ability to print high quality labels on demand to meet your organisation's needs. Printing labels up to 4 inches in width, and with direct thermal and thermal transfer print technology, they fit the requirements of a large range of vertical market applications.

The desktop printer range at a glance...

2 inch desktop label, receipt and wristband printer



Direct thermal print technology
Print width of up to 59mm
Print speeds up to 152mm/sec (6ips)
203dpi print resolution
USB (Type C) and Serial* connectivity
P-touch Template, ESC/P, Raster and ZPL 2, EPL 2, DPL, CPCL emulations supported

TD-2310D203

2 inch desktop label, receipt and wristband printer with customisation options



Direct thermal print technology
Print width of up to 59mm
Print speeds up to 152mm/sec (6ips)
203dpi print resolution
USB (Type C), USB Host, Serial* and Wired LAN connectivity
P-touch Template, ESC/P, Raster and ZPL 2, EPL 2, DPL, CPCL emulations supported
Rechargeable battery base unit available

TD-2320D203

High resolution 2 inch desktop label, receipt and wristband printer with customisation options



Direct thermal print technology
Print width of up to 59mm
Print speeds up to 152mm/sec (6ips)
300dpi print resolution
USB (Type C), USB Host, Serial* and Wired LAN connectivity
P-touch Template, ESC/P, Raster and ZPL 2, EPL 2, DPL, CPCL emulations supported
Rechargeable battery base unit available

TD-2320D300

2 inch desktop label, receipt and wristband printer with full connectivity and customisation



Direct thermal print technology
Print width of up to 59mm
Print speeds up to 152mm/sec (6ips)
203dpi print resolution
USB (Type C), USB Host, Serial* Bluetooth, Wired LAN and WiFi connectivity
P-touch Template, ESC/P, Raster and ZPL 2, EPL 2, DPL, CPCL emulations supported
Rechargeable battery base unit available

TD-2350D203

TD-2D range continued

High resolution 2 inch desktop label, receipt and wristband printer with full connectivity and customisation



Direct thermal print technology

Print width of up to 59mm

Print speeds up to 152mm/sec (6ips)

300dpi print resolution

USB (Type C), USB Host, Serial* Bluetooth, Wired LAN and WiFi connectivity

P-touch Template, ESC/P, Raster and ZPL 2, EPL 2, DPL, CPCL emulations supported

Rechargeable battery base unit available

TD-2350D300

2 inch desktop label, receipt and wristband printer with touch screen display



Direct thermal print technology

Print width of up to 59mm

Print speeds up to 152mm/sec (6ips)

203dpi print resolution

USB (Type C), USB Host, Serial* and Wired LAN connectivity

P-touch Template, ESC/P, Raster and ZPL 2, EPL 2, DPL, CPCL emulations supported

Rechargeable battery base unit available

TD-2320DSA203

High resolution 2 inch desktop label, receipt and wristband printer with touch screen display



Direct thermal print technology

Print width of up to 59mm

Print speeds up to 152mm/sec (6ips)

300dpi print resolution

USB (Type C), USB Host, Serial* and Wired LAN connectivity

P-touch Template, ESC/P, Raster and ZPL 2, EPL 2, DPL, CPCL emulations supported

Rechargeable battery base unit available

TD-2320DSA300

2 inch desktop label, receipt and wristband printer with full connectivity and touch screen display



Direct thermal print technology

Print width of up to 59mm

Print speeds up to 152mm/sec (6ips)

203dpi print resolution

USB (Type C), USB Host, Serial* Bluetooth, Wired LAN and WiFi connectivity

P-touch Template, ESC/P, Raster and ZPL 2, EPL 2, DPL, CPCL emulations supported

Rechargeable battery base unit available

TD-2350DSA203

High resolution 2 inch desktop label, receipt and wristband printer with full connectivity, touch screen display and carry handle



Direct thermal print technology

Print width of up to 59mm

Print speeds up to 152mm/sec (6ips)

300dpi print resolution

USB (Type C), USB Host, Serial* Bluetooth, Wired LAN and WiFi connectivity

P-touch Template, ESC/P, Raster and ZPL 2, EPL 2, DPL, CPCL emulations supported

Rechargeable battery base unit available

TD-2350SAH300

TD-4D range

Versatile, high-resolution desktop printers for professional label printing.

4 inch direct thermal desktop printer



Direct thermal print technology
Print width of up to 104.1mm
Print speeds up to 127mm/sec (5ips)
203dpi print resolution
USB and Serial connectivity
P-touch Template, ESC/P, CPCL ZPL 2, EPL 2 and DPL emulations supported

TD-4210D

4 inch direct thermal desktop printer with fast print speeds



Direct thermal print technology
Print width of up to 104.1mm
Print speeds up to 203.2mm/sec (8ips)
203dpi print resolution
USB and Serial connectivity
P-touch Template, ESC/P, CPCL ZPL 2, EPL 2 and DPL emulations supported

TD-4410D

4 inch direct thermal desktop printer with fast print speeds and wired LAN



Direct thermal print technology
Print width of up to 104.1mm
Print speeds up to 203.2mm/sec (8ips)
203dpi print resolution
USB, Serial and Wired LAN connectivity
P-touch Template, ESC/P, CPCL ZPL 2, EPL 2 and DPL emulations supported

TD-4420DN

High resolution 4 inch direct thermal desktop printer with wired LAN



Direct thermal print technology
Print width of up to 108.4mm
Print speeds up to 152mm/sec (6ips)
300dpi print resolution
USB, Serial and Wired LAN connectivity
P-touch Template, ESC/P, CPCL ZPL 2, EPL 2 and DPL emulations supported

TD-4520DN

High resolution 4 inch direct thermal desktop printer with full connectivity



Direct thermal print technology
Print width of up to 108.4mm
Print speeds up to 152mm/sec (6ips)
300dpi print resolution
USB, Serial, Wired LAN, Bluetooth and WiFi connectivity
Mono backlit LCD display
P-touch Template, ESC/P, CPCL ZPL 2, EPL 2 and DPL emulations supported

TD-4550DNWB

TD-4D linerless

Optimised for efficiency with sustainability in mind - linerless label printers.

4 inch direct thermal linerless desktop label printer with cutter



Direct thermal print technology

Print width of up to 108.4mm

Print speeds up to 203.2mm/sec (8ips)

203dpi print resolution

USB, Serial, Wired LAN connectivity

P-touch Template, ESC/P, Raster and ZPL 2, EPL 2, CPCL and DPL emulations supported

Pre-installed cutter with label-taken sensor

TD-4420DNFC

4 inch direct thermal linerless desktop label printer with full connectivity and cutter



Direct thermal print technology

Print width of up to 104.1mm

Print speeds up to 152.4mm/sec (6ips)

300dpi print resolution

USB, USB Host, Serial Bluetooth, Wired LAN and WiFi connectivity

P-touch Template, ESC/P, Raster and ZPL 2, EPL 2, CPCL and DPL emulation supported

Pre-installed cutter with label-taken sensor

TD-4550DNWBFC



TD-4T range

High performance, thermal desktop printing for ultimate productivity.

4 inch thermal transfer desktop printer



Direct thermal and thermal transfer print technology

Print width of up to 108mm

Print speeds up to 152mm/sec

203dpi print resolution

USB, USB Host, Serial and Wired LAN connectivity

FBPL-EZD (EPL 2, ZPL 2, DPL) emulations supported

TD-4420TN

High resolution 4 inch thermal transfer desktop printer



Direct thermal and thermal transfer print technology

Print width of up to 105.7mm

Print speeds up to 127mm/sec

300dpi print resolution

USB, USB Host, Serial and Wired LAN connectivity

FBPL-EZD (EPL 2, ZPL 2, DPL) emulations supported

TD-4520TN

4 inch thermal transfer desktop printer with fast print speeds, Bluetooth and WiFi



Direct thermal and thermal transfer print technology

Print width of up to 108mm

Print speeds up to 203.2mm/sec

203dpi print resolution

USB, USB Host, Serial, Wired LAN, Bluetooth and WiFi connectivity

LCD display

FBPL-EZD (EPL 2, ZPL 2, DPL) emulations supported

TD-4650TNWB

High resolution 4 inch thermal transfer desktop printer with Bluetooth and WiFi



Direct thermal and thermal transfer print technology

Print width of up to 105.7mm

Print speeds up to 152.4mm/sec

300dpi print resolution

USB, USB Host, Serial, Wired LAN, Bluetooth and WiFi connectivity

LCD display

FBPL-EZD (EPL 2, ZPL 2, DPL) emulations supported

TD-4750TNWB

4 inch thermal transfer desktop printer with fast print speeds, Bluetooth, WiFi and RFID support



Direct thermal and thermal transfer print technology

Print width of up to 108mm

Print speeds up to 203.2mm/sec

203dpi print resolution

USB, USB Host, Serial, Wired LAN, Bluetooth and WiFi connectivity

LCD display

FBPL-EZD (EPL 2, ZPL 2, DPL) emulations supported

RFID media supported

TD-4650TNWBR

High resolution 4 inch thermal transfer desktop printer with Bluetooth, WiFi and RFID support



Direct thermal and thermal transfer print technology

Print width of up to 105.7mm

Print speeds up to 152.4mm/sec

300dpi print resolution

USB, USB Host, Serial, Wired LAN, Bluetooth and WiFi connectivity

LCD display

FBPL-EZD (EPL 2, ZPL 2, DPL) emulations supported

RFID media supported

TD-4750TNWBR

TD-2D accessories

Power and additional options

PA-LP-008 Label peeler

TD-2320D203
TD-2320D300
TD-2350D203
TD-2350D300
TD-2320DSA203
TD-2320DSA300
TD-2350DSA203
TD-2350DSAH300



PA-CU-007 Cutter

TD-2320D203
TD-2320D300
TD-2350D203
TD-2350D300
TD-2320DSA203
TD-2320DSA300
TD-2350DSA203
TD-2350DSAH300



PA-KU-001 Keyboard unit

TD-2320DSA203
TD-2320DSA300
TD-2350DSA203
TD-2350DSAH300



PA-BB-004 Battery base*

TD-2320D203
TD-2320D300
TD-2350D203
TD-2350D300
TD-2320DSA203
TD-2320DSA300
TD-2350DSA203
TD-2350DSAH300

* Requires PA-BT-004



PA-HU2-002 Thermal print head (203dpi)

TD-2310D203
TD-2320D203
TD-2320D300
TD-2350D203
TD-2350D300
TD-2320DSA203
TD-2320DSA300
TD-2350DSA203
TD-2350DSAH300



PA-HU3-002 Thermal print head (300dpi)

TD-2310D203
TD-2320D203
TD-2320D300
TD-2350D203
TD-2350D300
TD-2320DSA203
TD-2320DSA300
TD-2350DSA203
TD-2350DSAH300



PA-PR2-002 Platen roller (203dpi)

TD-2310D203
TD-2320D203
TD-2320D300
TD-2350D203
TD-2350D300
TD-2320DSA203
TD-2320DSA300
TD-2350DSA203
TD-2350DSAH300



PA-PR3-002 Platen roller (300dpi)

TD-2310D203
TD-2320D203
TD-2320D300
TD-2350D203
TD-2350D300
TD-2320DSA203
TD-2320DSA300
TD-2350DSA203
TD-2350DSAH300



PA-BC-004 Battery charger

TD-2320D203
TD-2320D300
TD-2350D203
TD-2350D300
TD-2320DSA203
TD-2320DSA300
TD-2350DSA203
TD-2350DSAH300



PA-SCA-002 Serial cable

TD-2310D203
TD-2320D203
TD-2320D300
TD-2350D203
TD-2350D300
TD-2320DSA203
TD-2320DSA300
TD-2350DSA203
TD-2350DSAH300



PA-BT-004 Li-ion rechargeable battery*

TD-2310D203
TD-2320D203
TD-2320D300
TD-2350D203
TD-2350D300
TD-2320DSA203
TD-2320DSA300
TD-2350DSA203
TD-2350DSAH300



* Requires PA-BB-004

PA-AD-005(EU) Standard AC adapter

TD-2310D203
TD-2320D203
TD-2320D300
TD-2350D203
TD-2350D300
TD-2320DSA203
TD-2320DSA300
TD-2350DSA203
TD-2350DSAH300



PA-AD-006(EU) Healthcare AC adapter

TD-2310D203
TD-2320D203
TD-2320D300
TD-2350D203
TD-2350D300
TD-2320DSA203
TD-2320DSA300
TD-2350DSA203
TD-2350DSAH300



TD-4D accessories

TD-4D Additional Options

PA-LP-002
Label peeler

TD-4210D
TD-4410D
TD-4420DN
TD-4520DN
TD-4550DNWB



PA-CU-001
Cutter

TD-4210D
TD-4410D
TD-4420DN
TD-4520DN
TD-4550DNWB



PA-HU2-001
Thermal print head (203dpi)

TD-4210D
TD-4410D
TD-4420DN



PA-HU3-001
Thermal print head (300dpi)

TD-4520DN
TD-4550DNWB



PA-PR2-001
Platen roller (203dpi)

TD-4210D
TD-4410D
TD-4420DN



PA-PR3-001
Platen roller (300dpi)

TD-4520DN
TD-4550DNWB



PA-LCU-002
Linerless cutter

TD-4420DNFC
TD-4550DNWBFC



PA-LPR2-002
Linerless platen roller (203dpi)

TD-4420DNFC



PA-LPR3-002
Linerless platen roller (300dpi)

TD-4550DNWBFC



PA-AD-006 (EU)
Healthcare AC adapter

TD-4210D
TD-4410D
TD-4420DN
TD-4520DN
TD-4550DNWB
TD-4420DNFC
TD-4550DNWBFC



Why choose Brother?

3 years return-to-base warranty

We feel it's extremely important to make sure expert help is at hand when things go wrong. That's why we offer a three-year return-to-base warranty as standard with all of our thermal printers.

"At your side"

Our award-winning specialist support team is on standby to offer support and advice for any integration needs. We also have Brother sales representatives across Europe and the rest of the world who are easy to contact and happy to help.

The print experts

From our versatile range of multifunction printers, scanners and label printers, to our business solutions that help personalise your technology to suit your business needs, we pride ourselves on being "the print experts" and having a print solution for any application.

TD-2D range

brief summary

TD-2310D203

TD-2320D203

TD-2320D300

TD-2350D203

TD-2350D300

2 Inch

Printing

Print technology	Direct thermal				
Print resolution	203dpi	203dpi	300dpi	203dpi	300dpi
Print speed	152.4mm/sec (6ips)				
Max print width	59mm				
Min print length	6.4mm				
Max print length	1000mm				
Media sensor type	Gap (Transmissive), Black mark (Reflective)				
Media sensor location	Gap (fixed), Reflective (adjustable)				
Release mode	Continuous, tear off	Continuous, tear off / Optional: peel, cut			

Connectivity

USB	USB Ver.2.0 (Full Speed) (Type C)				
USB Host Port	—	Yes			
Serial	Original serial cable (option: PA-SCA-002)				
Bluetooth	—	—	—	Yes. Bluetooth Ver 5.2 (BR/EDR: Class1, BLE: Class1.5) / MFi	
Wireless LAN	—	—	—	IEEE802.11 a/b/g/n (Infrastructure Mode) IEEE802.11 g/n (Wireless Direct mode)	
Wired LAN	—	10/100BASE-TX			

General

Dimensions (mm)	119 (w) x 224 (d) x 158 (h)				
Weight	1.46kg	1.50kg	1.50kg	1.53kg	1.53kg
Control panel	3 button / 3 LED			7 button / 3 LED / Monochrome LCD	
Operating system support	Microsoft Windows 10,11 Microsoft Windows Server 2016,2019,2022 Linux				
Supported commands	Raster ESC/P P-touch Template / ZPL 2 emulation CPCL emulation / EPL 2 emulation / DPL emulation				
Mobile OS	Android 9 or later			Android 9 or later, iOS 15 or later	

TD-2D range

brief summary

TD-2320DSA203

TD-2320DSA300

TD-2350DSA203

TD-2350DSAH300

2 Inch

Printing

Print technology	Direct thermal			
Print resolution	203dpi	300dpi	203dpi	300dpi
Print speed	152.4mm/sec (6ips)			
Max print width	59mm			
Min print length	6.4mm			
Max print length	1000mm			
Media sensor type	Gap (Transmissive), Black mark (Reflective)			
Media sensor location	Gap (fixed), Reflective (adjustable)			
Release mode	Continuous, tear off / Optional: peel, cut			

Connectivity

USB	USB Ver.2.0 (Full Speed) (Type C)			
USB Host Port	Yes			
Serial	Original serial cable (option: PA-SCA-002)			
Bluetooth	—	—	Yes. Bluetooth Ver 5.2 (BR/EDR: Class1, BLE: Class1.5) / MFi	
Wireless LAN	—	—	IEEE802.11 a/b/g/n (Infrastructure Mode) IEEE802.11 g/n (Wireless Direct mode)	
Wired LAN	10/100BASE-TX			

General

Dimensions (mm)	119 (w) x 224 (d) x 176 (h)			153 (w) x 280 (d) x 176 (h)
Weight	1.77kg	1.77kg	1.77kg	1.94kg
Control panel	24 button / 3.5" colour touch screen			
Operating system support	Microsoft Windows 10,11 Microsoft Windows Server 2016,2019,2022 Linux			
Supported commands	Raster ESC/P P-touch Template / ZPL 2 emulation CPCL emulation / EPL 2 emulation / DPL emulation			
Mobile OS	Android 9 or later		Android 9 or later, iOS 15 or later	

TD-4D range

brief summary

TD-4210D	TD-4410D	TD-4420DN	TD-4520DN	TD-4550DNWB	TD-4420DNFC	TD-4550DNWBFC
4 Inch						

Printing

Print technology	Direct thermal						
Print resolution	203dpi	203dpi	203dpi	300dpi	300dpi	203dpi	300dpi
Print speed	127mm/sec (5ips)	203mm/sec (8ips)		152mm/sec (6ips)		203.2 mm/sec (8ips)	152.4 mm/sec (6ips)
Max print width	104.1mm			108.4mm		104.1mm	108.4mm
Min print length	6.4mm						
Max print length	3,000mm						
Media sensor type	Gap (transmissive), Bar (reflective)					Gap (Transmissive), Black mark (Reflective)	
Media sensor location	Gap (fixed), Reflective (adjustable)						
Release mode	Continuous, tear off / Optional: peel, cut					Standard: Cut	

Connectivity

USB	USB Ver.2.0 (Full Speed) (Type B)						
USB Host Port	—	—	—	—	Yes	—	Yes
Serial	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Bluetooth	—	—	—	—	Yes	—	Yes
Wireless LAN	—	—	—	—	Yes	—	Yes
Wired LAN	—	—	Yes	Yes	Yes	Yes	Yes

General

Dimensions (mm)	180 (w) x 224 (d) x 155 (h)				180 (w) x 255 (d) x 155 (h)		
Weight	2.08kg				2.49kg		
Control panel	3 button 3 LED				7 button 3 LED	3 button 3 LED	7 button 3 LED
Operating system support	Windows 7/8/8.1/10/11, Linux		Windows 7/8/8.1/10/11, Windows Server 2008/2008R2/2012/2012R2/2016/2019/2022, Linux			Microsoft Windows10,11 Microsoft Windows Server 2016/2019/2022, Linux	
Supported commands	Raster ESC/P P-touch Template ZPL 2 emulation CPCL emulation EPL 2 emulation DPL emulation						

TD-4T range

brief summary

TD-4420TN

TD-4520TN

TD-4650TNWB

TD-4750TNWB

TD-4650TNWBR

TD-4750TNWBR

4 Inch

Printing

Print technology	Thermal Transfer/Direct Thermal					
Print speed	152mm/sec	127mm/sec	203.2mm/sec	152.4mm/sec	203.2mm/sec	152.4mm/sec
Resolution	203dpi	300dpi	203dpi	300dpi	203dpi	300dpi
Max print width	108mm	105.7mm	108mm	105.7mm	108mm	105.7mm
Min print length	Peeler: 25.4mm, Cutter: 25.4mm Tear: 50mm		Continuous: 5mm Tear mode: Media width less than 2 inch: 25.4mm Media width greater than 2 inch: 50mm Peeler mode: 25.4mm Cutter mode: 25.4mm			
Max print length	25,400mm	11,430mm	25,400mm	11,430mm	25,400mm	11,430mm
Media sensor type	Gap (transmissive), Bar (reflective)					
Media sensor location	Gap (fixed), Reflective (adjustable)					
Tear off release mode	Standard: Continuous, Tear off Optional: Peeler, Cutter				Standard: Continuous, tear off	

Connectivity

USB	Yes	Yes	Yes	Yes	Yes	Yes
Serial	Yes	Yes	Yes	Yes	Yes	Yes
Wired LAN	Yes	Yes	Yes	Yes	Yes	Yes
USB Host Port	Yes	Yes	Yes	Yes	Yes	Yes
Bluetooth	—	—	Yes	Yes	Yes	Yes
Wireless LAN	—	—	Yes	Yes	Yes	Yes

Connectivity

Dimensions (mm)	204 (w) x 280 (d) x 164 (h)	219 (w) x 284 (d) x 191 (h)
Weight	2.5kg	2.5kg
Control panel	1 button 1 LED with 3 colours	1 LED with 3 colors. 6 buttons for Navigation
LCD	—	Yes Yes Yes Yes
Operating system support	Windows 7/8/8.1/10/11 Windows Server 2008/2008R2/ 2012/2012R2/2016 OS X 10.10.x,10.11.x macOS 10.12.x, 10.13.x, 10.14.x, 11 Linux	Windows 7 Windows 8 Windows 8.1 Windows 10 Windows 11 Windows Server 2008, 2008 R2, 2012, 2012 R2, 2016, 2019 Linux Mac OS v10.6-11
Supported commands	FBPL-EZD (EPL 2, ZPL 2, DPL) emulation	



Certified by
**Brother
International
Europe**

TD-2D desktop printing supplies

Supply type	Part code	Description	Size	Quantity	Rolls/Box
Receipt	BDL-7J000058-102	Continuous receipt roll	58mm x 101.6m	n/a	8
Labels	BDE-1J026051-102	Die-cut labels roll	51mm x 26mm	1,900 labels	16

TD-4D desktop printing supplies

Supply type	Part code	Description	Size	Quantity	Rolls/Box
Receipt	BDL-7J000102-058	Continuous receipt roll	101.6mm x 32.2m	n/a	20
	BDL-7J000076-066	Continuous receipt roll	76mm x 42m	n/a	8
	BDL-7J000058-102	Continuous receipt roll	58mm x 101.6m	n/a	8
	BDL-7J000058-040	Continuous receipt roll	58mm x 13.8m	n/a	24
Labels	BDE-1J000102-102	Continuous label roll	102mm x 58m	n/a	8
	BDE-1J050102-102	Die-cut label roll	102mm x 50mm	1,050 labels	8
	BDE-1J152102-058	Die-cut label roll	102mm x 152mm	85 labels	20
	BDE-1J152102-102	Die-cut label roll	102mm x 152mm	350 labels	8
	BDE-1J026076-102	Die-cut label roll	76mm x 26mm	1,900 labels	8
	BDE-1J044076-066	Die-cut label roll	76mm x 44mm	400 labels	8
	BDE-1J026051-102	Die-cut label roll	51mm x 26mm	1,900 labels	16
	BDE-1J026051-060	Die-cut label roll	51mm x 26mm	500 labels	12
Linerless Labels*	BFA-272039-102	Continuous linerless roll	39mm x 82.3mm	N/A	12
	BFA-274058-080	Continuous linerless roll	58mm x 51.8mm	N/A	32
	BFA-274080-080	Continuous linerless roll	80mm x 51.8mm	N/A	32
	BFA-274106-080	Continuous linerless roll	106mm x 51.8mm	N/A	9

* Linerless Labels only compatible with TD-4420DNFC & TD-4550DNWBFC - Available soon

TD-4T desktop printing supplies

Supply type	Part code	Description	Size	Quantity	Rolls/Box
Labels	BUS-1J074102-121	Uncoated thermal transfer die cut labels	102mm x 74mm	1,100 labels	6
	BUS-1J150102-121	Uncoated thermal transfer die cut labels	102mm x 150mm	550 labels	6
	BCS-1J074102-121	Coated thermal transfer die cut labels	102mm x 74mm	1,100 labels	6
	BCS-1J150102-121	Coated thermal transfer die cut labels	102mm x 150mm	550 labels	6
Ribbons	BWS-1D300-060	Standard wax ribbon	60mm x 300m	n/a	12
	BWS-1D300-080	Standard wax ribbon	80mm x 300m	n/a	12
	BWS-1D300-110	Standard wax ribbon	110mm x 300m	n/a	12
	BWP-1D300-060	Premium wax ribbon	60mm x 300m	n/a	12
	BWP-1D300-080	Premium wax ribbon	80mm x 300m	n/a	12
	BWP-1D300-110	Premium wax ribbon	110mm x 300m	n/a	12
	BSS-1D300-060	Standard wax/resin ribbon	60mm x 300m	n/a	12
	BSS-1D300-080	Standard wax/resin ribbon	80mm x 300m	n/a	12
	BSS-1D300-110	Standard wax/resin ribbon	110mm x 300m	n/a	12
	BSP-1D300-060	Premium wax/resin ribbon	60mm x 300m	n/a	12
	BSP-1D300-080	Premium wax/resin ribbon	80mm x 300m	n/a	12
	BSP-1D300-110	Premium wax/resin ribbon	110mm x 300m	n/a	12
	BRS-1D300-060	Standard resin ribbon	60mm x 300m	n/a	12
	BRS-1D300-080	Standard resin ribbon	80mm x 300m	n/a	12
	BRS-1D300-110	Standard resin ribbon	110mm x 300m	n/a	12
	BRP-1D300-060	Premium resin ribbon	60mm x 300m	n/a	12
	BRP-1D300-080	Premium resin ribbon	80mm x 300m	n/a	12
	BRP-1D300-110	Premium resin ribbon	110mm x 300m	n/a	12

For additional consumable options please contact your local Brother office.

