




EloPOS Pack 2

High Performance Compute



Connectivity-Rich



Compact Form-Factor



3-Year Warranty

Product Overview

The EloPOS Pack 2 delivers a high performance enterprise-grade computing solution in a sleek, compact form factor. Backed by the security and infrastructure of an Intel-based system with the speed of 14th gen Raptor Lake processors, the EloPOS Pack 2 provides the power you need to run your business. With versatile connectivity options, plug in anything from Elo's latest monitor via single cable USB-C to a legacy printer requiring a 12V powered-USB. The system provides flexibility to make upgrades as your business requirements change.

Whether you want Windows 10 or a no-OS model to run Linux, the enterprise-ready EloPOS Pack 2 provides the freedom to adapt to your infrastructure. To get you up and running quicker, the no-OS models have been pretested with Linux SuSE, Ubuntu and Red Hat operating systems.

i5 Models Offer: TPM 2.0, Intel AMT, Intel Standard Manageability & Intel vPro

Pair with a monitor to create the perfect solution for your self-checkout and point-of-sale lanes

Easily secures into place with the mounting bracket and for extra security, use the included Kensington locks

EloPOS Pack 2

Specifications		
Processor	Intel Core™ i3- 14100T Processor (12M Cache, up to 4.4 GHz by Intel® Turbo Boost Technology 2.0)	Intel Core i5- 14500T Processor (24M Smart Cache, up to 4.8 GHz by Intel® Turbo Boost Technology 2.0) Intel® vPro Support
Chipset	Intel Q670 Express	
Video	Intel UHD Graphics 730	Intel UHD Graphics 770
BIOS	AMI	
Memory	8GB 5600MHz DDR5 SO-DIMM on 1 of 2 slots (Expandable to 64GB maximum ¹ on 2 slots) ²	8GB or 16GB 5600MHz DDR5 SO-DIMM on 1 of 2 slots (Expandable to 64GB max ¹ on 2 slots) ²
	¹ Maximum memory using 2 slots. Expandable up to 64GB maximum, SO-DIMM DDR5-5600. ² Check brand of the memory included in your unit before purchasing the memory kit.	
Storage	256GB M.2 PCIe (NVMe) SSD ³ , 160 TBW	256GB M.2 PCIe (NVMe) SSD ³ , 160 TBW or 512GB M.2 PCIe (NVMe) SSD ³ , 320 TBW
	³ GB equals one billion bytes when referring to storage capacity. Accessible capacity may be less.	
Operating Systems	No Operating System, Microsoft Windows 11 IoT Enterprise LTSC 64-bit	
Languages	Windows 10 - 36 Language groups	
Control Buttons	Power	
I/O Ports	1x HDMI port, 1x LAN RJ45 (Gigabit), 2x USB 3.0 (Front side), 4x USB 3.0 (Rear side), 1x 24V & 5x 12V Powered USB, 1x 12V/24V Cash Drawer Port on I/O (EPSON Pinout, 24V default; selectable by internal switch), 1x Full-function USB-C (Power up to 27W, USB 3.0, Display Port), 1x 3.5 mm headset jack	
Wireless	802.11 a/b/g/n/ac/ax 2.4GHz, 5GHz and 6GHz	
Antenna	2T2R design with External SMA connector	
Bluetooth	Bluetooth 5.3	
RAID	Intel Volume Management Device (VMD) technology for select SKUs	
TPM	TPM 2.0	
AMT	N/A	Intel Active Management Technology (AMT)
Real Time Clock	Replaceable CR2450 lithium metal battery for clock	
Power Supply	External 24VDC universal-type power supply brick, AC input voltage: 100-240 VAC, Input frequency: 50-60 Hz, Maximum output power: 180W	
Power Consumption	ON i3: 63W (8GB DIMM/256GB SSD). Don't exceed 117W for all peripherals load. ON i5: 62W (8GB DIMM/512GB SSD). Don't exceed 118W for all peripherals load. SLEEP: <3W; OFF BIOS EUP Disable: <2.5W; OFF BIOS EUP Enabled: < 0.5W	
Mounting Options	Bracket mounts to table with screws, System slides forward to engage hooks on bracket	
Other Features	Serviceable internal components. Kensington Nano Security Slot. Kensington lock slot (Standard Size).	
Upgrade Options	8GB 5600MHz DDR5 SO-DIMM - E466053, 16GB 5600MHz DDR5 SO-DIMM - E466237 , 32GB 5600MHz DDR5 SO-DIMM - E466430, M.2 PCIe (NVMe) 128GB SSD - E466613, M.2 PCIe (NVMe) 256GB SSD - E466803	
Dimensions	10.9" x 1.4" x 9.4" / 276 mm x 37 mm x 237.5 mm	
Shipping Box Dimensions	14.3" x 6.1" x 13.3" / 365 mm x 156 mm x 338 mm	
Weight	Unpackaged: 5.76 lbs / 2.6 kg; Packaged: 10.14 lbs / 4.6 kg	
Temperature	Operating: 0°C to 40°C (32°F to 104°F); Storage: -20°C to 60°C (-4°F to 140°F)	
Humidity (non-condensing)	Operating: 10% to 90%; Storage: 0% to 95% (38.7°C max wet bulb temperature)	
Agency Approvals	United State UL, FCC; Canada cUL, IC; Germany, TUV; Europe CE; Australia RCM ; United Kingdom UKCA; International CB; Japan VCCI, MIC; China CCC, SRRC; Mexico NOM; RoHS CoC	
Compliance	Energy Star 8.0 certified configurations available	
Warranty	3 years	
Extended Warranty	4 year coverage - Elo P/N: E896120 ; 5 year coverage - Elo P/N: E896322 3 year coverage + AUR - Elo P/N: E896699; 4 year coverage + AUR - Elo P/N: E896903; 5 year coverage + AUR - Elo P/N: E897104	
MTBF	50,000 hours demonstrated	
What's in the box	EloPOS Pack 2, North America Power Cord (1800+/-50mm), (6 ft +/- 1 inch), EU Power Cord (1800+/-50mm), Power Adapter - 180W, USB Type-C cable (1800+/-50mm), (6 ft +/- 1 inch), HDMI cable (1800+/-50mm), (6 ft +/- 1 inch), USB cable (1800+/-50mm), (6 ft +/- 1 inch), 2x SMA Antenna, QIG	

Ordering Information

Part Numbers	OS	Processor	Storage	Memory (RAM)
E262004	Windows 11	i3-14100T	256GB SSD	8GB RAM
E262189	No OS	i5-14500T	256GB SSD	8GB RAM
E262377	Windows 11	i5-14500T	256GB SSD	8GB RAM

Learn more about Elo at [EloTouch.com](https://www.elotouch.com).

Americas

Tel +1 408 597 8000
elosales.na@elotouch.com

Europe (EMEA)

Tel +32 16 930 136
EMEA.Sales@elotouch.com

Asia Pacific

Tel +86 (21) 3329 1385
www.elotouch.com.cn

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo, the Elo logo and EloPOS are either trademarks or registered trademarks of Elo Touch Solutions, Inc. All other trademarks are the property of their respective owners.
© 2025 Elo Touch Solutions, Inc. All rights reserved. 25031AUS00196

