

Product data sheet

Specifications



APC Step-Down Transformer RM 2U 208V IN 120V OUT; w/5-20 Receptacles



AP9626

Overview

Presentation	The Step-Down Transformer converts high voltage (208 or 200 VAC) output into low voltage (120 or 100 VAC) output for powering low voltage AC equipment.
Lead time	Usually in Stock

Main

Main Input Voltage	208 V
Product or Component Type	Accessory
Main Output Voltage	120 V
Input Connection Type	NEMA L6-30P
number of rack unit	2U
Number of cables	1
Provided Equipment	User Manual Rack Mounting brackets

Physical

Color	Black
Height	3.5 in (8.9 cm)
Width	17.5 in (44.5 cm)
Depth	24.02 in (61 cm)
Net Weight	95.20 lb(US) (43.18 kg)
mounting location	Front
Mounting preference	No preference
Mounting Mode	Rack-mounted

Input

Acceptable Input Voltage	208 V
Max line current	24 A
Input current limits	30 A
Load Capacity	5000 VA

Output

Maximum Total Current Draw per Phase	24 A
Number of power socket outlets	12

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Efficiency	90 %
------------	------

Number of power socket outlets	12 NEMA 5-20R
--------------------------------	---------------

Conformance

Product Certifications	CSA
------------------------	-----

Standards	OSHPD UL 1778
-----------	------------------

Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
---------------------------------------	-------------------------

Relative Humidity	0...95 %
-------------------	----------

Operating altitude	0...10000 ft
--------------------	--------------

Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
-------------------------------------	--------------------------

Storage Relative Humidity	0...95 %
---------------------------	----------

Storage altitude	0...50000 ft (0.0000000000...15240.0000000000 m)
------------------	--

Ordering and shipping details

GTIN	731304249139
------	--------------

Country of origin	PH
-------------------	----

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	10.0000000000 in (25.4 cm)
------------------	----------------------------

Package 1 Width	37.5 in (95.3 cm)
-----------------	-------------------

Package 1 Length	24.5 in (62.2 cm)
------------------	-------------------

Package 1 Weight	110.2 lb(US) (50 kg)
------------------	----------------------

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Energy Efficient Take-back Transparency RoHS/REACH


Resource performance


 Energy Efficient Product

 Take-Back Program Available

Well-being performance

 Lead Free

 Mercury Free

 Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)