

Overview

Help avoid job interruptions with the HP Staple Cartridge Refill that holds up to 5,000 staples.

The HP Staple Cartridge Refill is easy to install and use, ensuring accurate stapling for professional-looking documents.

Know if staples are running low before you start your print job. You'll see a message when the stapler is low so that, if needed, you can add another refill cartridge before the job starts.

With 5,000 staples, the HP Staple Cartridge Refill offers great value and the reliability you've come to expect from HP.

Specifications

Minimum dimensions (W x D x H)	94 x 40 x 42 mm
Minimum dimensions (W \times D \times H)	3.7 x 1.57 x 1.65 in (Replacement parts only; no shipping material)
Weight	0.208 kg
Weight	0.46 lb
Package dimensions (W x D x H)	200 x 200 x 200 mm
Package weight	0.45 kg
UPC number	190780619261
Manufacturer Warranty	90 Day HP Dealer Exchange; Warranty and support options vary by product, country and local legal requirements. Go to hp.com/support to learn about HP award winning service and support options in your region.
What's in the box	Staple refill pack; Install guide

Additional specifications

Accessory type	Other
Additive metric depth	0
Additive metric height	0
Additive metric width	0
Business filter	cMPS
Color yield	500000
Compatibility	HP Color LaserJet Enterprise Flow MFP M681z J8A13A, HP Color LaserJet Enterprise Flow MFP M682z J8A17A, HP LaserJet Enterprise MFP M631z J8J65A, HP LaserJet Enterprise Flow MFP M632z J8J72A, HP LaserJet Enterprise Flow MFP M633z J8J78A, HP Color LaserJet Managed Flow MFP E67560z L3U70A, HP LaserJet Managed MFP E62565hs J8J73A, HP LaserJet Managed Flow MFP E62565z J8J79A
Component type	LLC
Country of origin	Made in China
Electromagnetic compatibility	CISPR 22:2008 (International) - Class A, CISPR 32:2012 (International) - Class A, EN 55032: 2012 (EU) - Class A, EN 61000-3-2: 2014 (EU), EN 61000-3-3: 2013 (EU), EN 55024: 2010 (EU), EMC Directive 2014/30/EU, FCC CFR 47 Part 15 Class A / ICES-003, Issue 6 Class A (US/Canada). Other EMC approvals as required by individual countries
Maximum additive metric depth	0
Maximum additive metric height	0
Maximum additive metric width	0
Metric depth	40
Metric height	42
Metric width	94
Mono yield	500000
Non-Operating Humidity Range	35 to 85% RH
Office color yield	500000
Operating humidity range	10 to 80% RH
Operating temperature range	59 to 86°F
Operating temperature range	15 to 30ºC
Orderable product number	J8J96A
Package dimensions (W x D x H)	8.0 x 8.0 x 8.0 in
Package weight	1.0 lb
Page yield (black and white)	Cartridge contains 5,000 staples
Page yield (color)	Cartridge contains 5,000 staples

Safety	IEC 60950-1:2005 +A1:2009 +A2:2013 (International); EN60950-1:2006 +A11:2009 +A1:2010 +A12:2011 +A2:2013 (EU); Low Voltage Directive 2014/35/EU with CE Mark (Europe). Other safety approvals as required by individual countries
Storage temperature range	32 to 95°F
Storage temperature range	0 to 35ºC
Tariff numbers	8305200000 (AM-Base-HTS); 8305200000 (EU-Base-HTS); 83052000 (AP-Base-HTS)
UNSPSC code	44101707
Warranty	90 Day HP Dealer Exchange; Warranty and support options vary by product, country and local legal requirements. Go to hp.com/support to learn about HP award winning service and support options in your region.

Disclaimer — Copyright

© Copyright 2024 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Generated by Dynamic Collateral Tool – (ww-en) – Sep 23, 2024 9:51 AM UTC+0000