

# Xerox® VersaLink® C9000 Color Printer



The VersaLink® C9000 Color Printer is built on Xerox® ConnectKey® Technology. For more information, go to [www.ConnectKey.com](http://www.ConnectKey.com).

SYSTEM SPECIFICATIONS	VERSALINK® C9000DT
<b>One-Sided Speed<sup>1</sup></b> 8.5 x 11 in./A4 8.5 x 11 in./A4 SEF 8.5 x 14 in./216 x 356 mm 11 x 17 in./A3/297 x 420 mm/ 12 x 18 in/SRA3/320 x 450 mm	Up to 55 ppm (pages per minute) long edge feed (LEF) Up to 40 ppm Up to 32 ppm Up to 27 ppm
<b>Two-Sided Speed<sup>1</sup></b> 8.5 x 11 in./A4 8.5 x 11 in./A4 SEF 8.5 x 14 in./216 x 356 mm 11 x 17 in./A3/297 x 420 mm/ 12 x 18 in/SRA3/320 x 450 mm	Up to 55 ppm LEF Up to 40 ppm Up to 21 ppm Up to 19 ppm
<b>Monthly Duty Cycle<sup>2</sup></b>	Up to 270,000 pages/month
<b>Recommended Average Monthly Print Volume<sup>3</sup></b>	Up to 30,000 pages per month
<b>Hard Drive</b>	320 GB HDD
<b>Processor</b>	1.6 GHz Dual-Core
<b>Memory</b>	4 GB
<b>Connectivity</b>	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n/g/b/a and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair
<b>Controller Features</b>	Configuration Cloning, Xerox Extensible Interface Platform®, Xerox App Gallery App, Xerox® Standard Accounting Tool, Role Based Permissions, Convenience Authentication Enabled
<b>User Interface Languages</b>	English, French, Italian, German, Spanish, Brazilian Portuguese, Russian, Dutch, Swedish, Danish, Finnish, Norwegian, Greek, Turkish, Polish, Czech, Hungarian, Romanian, Catalan

# Xerox® VersaLink® C9000 Color Printer

DEVICE SPECIFICATIONS				
ELECTRICAL REQUIREMENTS				
North America	Voltage: 110-127V +/-10% Frequency: 50/60 Hz +/-3%, 12A			
Europe and Other Geographies	Voltage: 220-240V +/-10% Frequency: 50/60 Hz +/-3%, 10A			
POWER CONSUMPTION				
Printing <sup>4</sup>	For 110V: 2.85 kWh For 220V: 2.82 kWh			
Standby Mode <sup>4</sup>	110V: 75.3 Watts or less 220V: 73.8 Watts or less			
Sleep Mode <sup>4</sup>	0.71 watts or less			
OPERATING ENVIRONMENT				
Required Temperature Range(Storage)	Below 48° C, and in compliance with MN2-810.13			
Required Temperature Range(Operating)	50° to 83° F (10° to 28° C) Must be 28° C or below if humidity is at 85 %			
Required Relative Humidity	15% to 85%; must be 62.5% or below at 32° C			
Sound Power Levels	Printing: 6.83 B(A) or less Standby: 3.24 B(A) or less  Full System (including finisher) Printing: 7.64 B(A) Standby: 3.38 B(A)			
Sound Pressure Levels	Printing: 58.2 dB or less Standby: 15.1 dB or less  Full System (including finisher) Printing: 58.1 dB Standby: 15.3 dB			
Boot Time (from Off to UI Ready)	Less than 60 seconds			
Warm-up Time (from Sleep to UI Ready)	Less than 16 seconds			
DIMENSIONS AND WEIGHT (UNPACKAGED)	WIDTH	DEPTH	HEIGHT	WEIGHT
VersaLink® C9000/DT	24.4 in./620 mm	28.5 in./723 mm	31.9 in./809.3 mm	178 lb./80.8 kg
Two Tray Module	26.3 in./668.5 mm	28.5 in./723 mm	10.3 in./261.2 mm	60.0 lb./27.2 kg
Tandem Tray Module	26.3 in./668.5 mm	28.5 in./723 mm	10.3 in./261.2 mm	74.5 lb./33.8 kg
High-Capacity Feeder	15.3 in./389 mm	23.7 in./602.9 mm	15.0 in./380.01 mm	63.9 lb./29.0 kg
Office Finisher LX	22 in./559.8 mm	21.7 in./552 mm	39.8 in./1012 mm	61.7 lb./28.0 kg
Office Finisher with Booklet Maker attached	59.5 in./1513 mm	28.4 in./723 mm	42.3 in./1076 mm	334.2 lb./151.6 kg
BR Booklet Maker Finisher	30.28 in./769.2 mm	28.5 in./723 mm	41.5 in./1055.1 mm	134.3 lb./60.9 kg

# Xerox® VersaLink® C9000 Color Printer

<b>DIMENSIONS AND WEIGHT (PACKAGED)</b>	<b>WIDTH</b>	<b>DEPTH</b>	<b>HEIGHT</b>	<b>WEIGHT</b>
VersaLink® C9000/DT	32.8 in./833 mm	28.2 in./717 mm	33.4 in./852 mm	209.4 lb./95 kg
High-Capacity Feeder	20.7 in./526 mm	29.8 in./756 mm	19.3 in./491 mm	74.3 lb./33.7 kg
Two Tray Module	32.7 in./830 mm	33.5 in./850 mm	15.75 in./400 mm	72.7 lb./33 kg
Tandem Tray Module	32.7 in./830 mm	33.5 in./850 mm	15.75 in./400 mm	86 lb./39 kg
Office Finishers	27.2 in./690 mm	40.2 in./1021 mm	25.7 in./654 mm	82 lb./37 kg
Booklet Maker Finisher	20 in./507 mm	30 in./761 mm	17.2 in./437 mm	31 lb./14 kg
BR Booklet Maker Finisher	30 in./764 mm	30.5 in./774 mm	47.4 in./1203 mm	169.7 lb./77 kg
Horizontal Transport for BR BookletMaker Finisher	21 in./533 mm	23.1 in./589 mm	12.6 in./319 mm	14.3 lb./6.5 kg
<b>CERTIFICATIONS</b>				
To view the latest list of certifications, go to <a href="http://www.xerox.com/OfficeCertifications">www.xerox.com/OfficeCertifications</a> .				
<b>PRINT</b>				
<b>First-Print-Out Time</b>	As fast as 10.5 seconds color			
	As fast as 10 seconds black			
<b>Print Resolution</b>	Up to 1200 x 2400 dpi			
<b>Page Description Languages</b>	Adobe® PostScript® 3™ PCL® 5c, 6 PDF XPS TIFF JPEG HP-GL			
<b>Color Management</b>	Embedded spot color table with the ability to swap out PANTONE® approved color table, Custom spot color editor, Xerox® Precise Color Management System software			
<b>Maximum Print Area</b>	4 mm from lead edge of paper, 2 mm from Side and Trail edges of paper			

# Xerox® VersaLink® C9000 Color Printer

<p><b>Print Features</b></p>	<p>Application Defaults            Banner Pages Enable/Disable            Bi-directional Real-time Status            Booklet Layout            Color Adjustments (lightness, contrast, saturation, color balance)            Color Correction            Draft Mode            Finishing (requires finishing)            Fit to New Paper Size            Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages)            Job Monitoring (Client or Local User Interface)            N-up Page Layout (up to 16 pages per sheet)            Paper Selection by Attribute            Personal Print            Print Around Enable/Disable            Print from USB            Run Black            Sample Set            Saved Job            Scaling            Secure Print            Skip Blank Pages            Special Pages (exception page programming: covers, inserts, exceptions pages)            Store and Recall Driver Settings            Stored Jobs Deletion            Two-sided Printing (as default)            Watermark (predefined and custom)            Xerox® Earth Smart Driver Settings</p>
<p><b>Print from USB</b></p>	<p>Allows walk-up printing from Type A USB port            Supports direct printing from computer via Type B USB port            Supported file formats: PDF, JPEG, TIFF, XPS, PDF/A</p>
<p><b>Operating Systems</b></p>	<p>Windows® 7, 8, 8.1, 10            Windows Server 2008 SP2, Server 2008 R2 SP1, Server 2012, Server 2012 R2,            Server 2016, Server 2019            macOS® 10.11, 10.12, 10.13            Citrix®            Redhat® Enterprise Linux®            Fedora Core            IBM® AIX®            HP-UX®            Oracle® Solaris            SUSE®            SAP®            UNIX®            Note: For information about supported versions for the above operating systems, please visit our Drivers &amp; Downloads page and specify your device at <a href="http://www.support.xerox.com">www.support.xerox.com</a>.</p>
<p><b>Fonts</b></p>	<p>PostScript fonts: 136            PCL fonts: 83</p>
<p><b>Xerox® Global Print Driver®</b></p>	<p>A truly universal print driver that lets IT administrators install, upgrade, and manage Xerox® and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.</p>
<p><b>Xerox® Pull Print Driver</b></p>	<p>Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.</p>

<b>MOBILE SOLUTIONS AND MOBILE DEVICE APPS</b>	
<b>Apple® AirPrint®</b>	Print email, photos, and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.
<b>Mopria® Certified</b>	ConnectKey® Technology-enabled print devices are Mopria® certified. Mopria certification ensures you can print wirelessly from your Mopria supported (Android™) smartphone, tablet, and other mobile devices instantly and easily.
<b>Xerox® @printbyXerox App</b>	@printbyXerox App is a free service that allows secure printing from any email-enabled device (computer, phone, tablet, iOS, Android™, Google® Chromebook™ and more) to a Xerox® printer or MFP using a single email address with no IT intervention. No training is needed. End-users simply send attachments to the email address and release them at the MFP panel.
<b>Xerox® Print Services plug-in for Android™</b>	The Xerox® Print Services plug-in for Android KitKat (4.4 or greater) devices streamline mobile printing without third-party apps or additional print drivers. You can easily print photos, Web pages and documents when your mobile device is connected to printers using a wireless network. A robust print option set includes two-sided printing, stapling, and secure code release. A free download is available from the Google Play™ store.
<b>Xerox® Workplace Suite and Xerox® Workplace Cloud</b>	<p>Xerox® Workplace Solutions boost productivity and reduce costs with a modular print management and mobility solution. Control and manage your printer fleet while enabling mobile productivity with simplified workflows, convenience, and security—for any brand printer, anywhere. Xerox® Workplace Solutions offer flexible license options to suit any size business with the ability to scale as you grow.</p> <ul style="list-style-type: none"> <li>• Xerox® Workplace Suite: On-site, your server</li> <li>• Xerox® Workplace Cloud: Simple setup, cloud administration</li> </ul> <p>To learn more about the Xerox® Workplace Suite and Xerox® Workplace Cloud, visit <a href="http://www.xerox.com/Mobility">www.xerox.com/Mobility</a>.</p>
<b>SOFTWARE SOLUTIONS</b>	
<b>Xerox® ConnectKey® Apps (Found at the Xerox App Gallery App)</b>	Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey® Apps do not require a dedicated server, PC, or IT resource. Instead, simply download these lightweight, serverless ConnectKey® Apps to the device.

SECURITY	
<b>Security Features</b>	Access Controls AES 256-bit Encryption Audit Log Certificate Path Validation Certificate Revocation List (CRL)/Status Protocol (OCSP) Detection of external program falsification (XCP Plug-in) Cisco® Identity Services Engine (ISE) Integration Domain Filtering FIPS 140-2 Firmware Verification Immediate Disk Overwrite IP Address Filtering IPsec Network Authentication Port Filtering Pre-installed Self-Signed Certificates Role Based Permissions Secure Print Security Certificate Management Smart Card Enablement (CAC/PIV/.NET) SNMPv3 Status Protocol (OCSP) TLS/SSL Trusted Platform Module (TPM)
ACCOUNTING	
XEROX® STANDARD ACCOUNTING/NETWORK ACCOUNTING (STANDARD)	
<b>Tracking</b>	Print usage
<b>Accounting</b>	Xerox® Standard Accounting Tool Up to 9,999 User Accounts Up to 500 General Accounts  Network Accounting (Job Based Accounting) Up to 60,000 User IDs; Up to 60,000 Account IDs Up to 14,000 Accounting Records (transactions)
<b>Features</b>	Administrator can manage the feature via the Embedded Web Server.
ACCOUNTING OPTIONS – NETWORK ACCOUNTING (ALLOWS CENTRAL SERVER TO MANAGE ALL ACCOUNTING)	
	<ul style="list-style-type: none"> <li>Enhanced network accounting with up to the minute data on how the system is being used</li> <li>Comprehensive management and enterprise scale tracking and reporting of device print usage</li> <li>Numerous solutions are available through Xerox Alliance Partners. For details visit <a href="http://www.xerox.com">www.xerox.com</a></li> <li>Security enhancements include simultaneous support for HTTP/HTTPS protocols</li> <li>Device requests account authentication from third party server enabling larger databases of users and accounts</li> <li>Accept Authentication Login at control panel and pass to third party Networking Account</li> </ul>
PAPER HANDLING	
BYPASS TRAY	
<b>Capacity<sup>5</sup></b>	100 sheets
<b>Sizes</b>	Custom sizes: 3.5 x 3.9 in. to 12.6 x 19 in./88.9 x 98.4 mm to 320 x 482.6 mm Banners: 3.5 x 3.9 in. to 12.6 x 52 in./88.9 x 98.4 mm to 320 x 1320.8 mm
<b>Weights</b>	Simplex: 18 lb. bond to 130 lb. cover/64 to 350 gsm Duplex: 18 lb. bond to 110 lb. cover/64 to 300 gsm

Xerox® VersaLink® C9000 Color Printer

<b>Types</b>	Bond Plain Paper Cardstock Custom Envelopes Extra Heavyweight Cardstock Extra Heavyweight Glossy Cardstock	Glossy Cardstock Hole Punched Labels Heavyweight Cardstock Heavyweight Glossy Cardstock Letterhead	Lightweight Cardstock Lightweight Glossy Cardstock Pre-Printed Postcards Recycled
<b>TRAY 1 AND 2</b>			
<b>Capacity<sup>5</sup></b>	520 sheets each		
<b>Sizes</b>	Tray 1: 3.9 x 5.8 in. to 11.7 x 17 in./100 x 148 mm to 297 x 431.8 mm Tray 2: 3.9 x 5.8 in. to 12.6 x 18 in./100 x 148 mm to 320 x 457.2 mm		
<b>Weights</b>	18 lb. bond to 110 lb. cover/64 to 300 gsm		
<b>Types</b>	Bond Plain Paper Cardstock Custom Glossy Cardstock	Hole Punched Labels Heavyweight Cardstock Heavyweight Glossy Cardstock Letterhead	Lightweight Cardstock Lightweight Glossy Cardstock Pre-Printed Recycled
<b>TWO TRAY MODULE</b>			
<b>Capacity<sup>5</sup></b>	1,040 sheets		
<b>Sizes</b>	Custom sizes: 3.9 x 5.8 in. to 12.6 x 18 in./100 x 148 mm to 320 x 457.2 mm		
<b>Weights</b>	18 lb. bond to 110 lb. cover/64 to 300 gsm		
<b>Types</b>	Bond Plain Paper Cardstock Custom Glossy Cardstock	Hole Punched Labels Heavyweight Cardstock Heavyweight Glossy Cardstock Letterhead	Lightweight Cardstock Lightweight Glossy Cardstock Pre-Printed Recycled
<b>TANDEM TRAY MODULE</b>			
<b>Capacity<sup>5</sup></b>	2,000 sheets		
<b>Sizes</b>	8.5 x 11 in., 7.25 x 10.5 in./A4, B5		
<b>Weights</b>	18 lb. bond to 110 lb. cover/64 to 300 gsm		
<b>Types</b>	Bond Plain Paper Cardstock Custom Glossy Cardstock	Hole Punched Labels Heavyweight Cardstock Heavyweight Glossy Cardstock Letterhead	Lightweight Cardstock Lightweight Glossy Cardstock Pre-Printed Recycled
<b>HIGH-CAPACITY FEEDER</b>			
<b>Capacity<sup>5</sup></b>	2,000 sheets		
<b>Sizes</b>	8.5 x 11 in., 7.25 x 10.5 in./A4, B5		
<b>Weights</b>	18 lb. bond to 80 lb. cover/64 to 216 gsm		
<b>Types</b>	Bond Plain Paper Cardstock Custom	Glossy Cardstock Hole Punched Letterhead Lightweight Cardstock	Lightweight Glossy Cardstock Recycled

# Xerox® VersaLink® C9000 Color Printer

<b>ENVELOPE TRAY – REPLACES TRAY 1 (OPTIONAL)</b>	
Capacity <sup>5</sup>	Up to 50 envelopes
Sizes	#10 commercial, Monarch, DL, C4, C5, C6 Custom sizes: 3.5 x 3.85 in. to 9.5 x 13.1 in./90 x 98 mm to 241 x 332 mm
<b>TOTAL CAPACITY</b>	
VersaLink® C9000/DT Capacity <sup>5</sup>	1,140 sheets
Maximum Capacity <sup>5</sup>	5,140 sheets
<b>FINISHING</b>	
<b>OUTPUT TRAYS</b>	
Catch Tray	500 sheets (without center tray) 2x 250 sheets (with center tray when offset is off) 2x 125 sheets (with center tray when offset is on)
<b>OFFICE FINISHERS (OPTIONAL)</b>	
Capacity <sup>5</sup>	Stacking Tray: 2,000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in./A4) (dual stapling only with optional booklet maker) Offset available for collated sets of standard size paper (8.5 x 11 in./A4 to 11 x 17 in./A3)
Sizes	
Office Finisher LX:	8.3 x 7.2 in. to 11.7 x 17 in./210 x 182 mm to 297 x 432 mm
Office Finisher:	5.8 to 11.7 in. x 5.8 to 17 in./148.0 to 297.0 mm x 148.0 to 432.0 mm
Weights	
Office Finisher LX:	16 lb. bond to 80 lb. cover/60 to 220 gsm
Office Finisher:	16 lb. bond to 95 lb. cover/60 to 256 gsm
Multiposition Stapling	50 sheets of 24 lb. bond/90 gsm
Hole Punch (Optional)	Office Finisher LX: up to 65 lb. cover (200 gsm)/Office Finisher: up to 80 lb. cover (220 gsm)
North America:	2/3 hole punch
Europe:	2/4 hole punch
<b>BOOKLET MAKER FOR OFFICE FINISHERS (SCORE/CREASE, SADDLE-STITCH STAPLE) (OPTIONAL)</b>	
Capacity <sup>5</sup>	40 booklets (2-15 sheets per booklet – 20 lb./80 gsm or less)
Sizes	Letter – 8.5 x 11 in./A4 SEF Legal – 8.5 x 14 in./B4 SEF Ledger – 11 x 17 in./A3 SEF
Saddle-stitch Stapling	2-15 sheets/8-60 page booklet 16 lb. bond to 24 lb. bond/60 to 90 gsm
Score/Crease	1-15 sheets/unstapled/60-105 gsm only
<b>OPTIONAL BR BOOKLET MAKER FINISHER (REQUIRES HORIZONTAL TRANSPORT KIT)</b>	
Capacity <sup>5</sup>	Offsetting Top Tray: 500 sheets of 8.5 x 11 in./A4 unstapled Stacking Stapling Tray: 1,500 sheets of 8.5 x 11 in./11 x 17 in./A4/A3 unstapled or 200 stapled sets of 8.5 x 11 in./A4 (single-position stapling or dual or 4-position stapling) or 100 stapled sets of 11 x 17 in./A3
Sizes	4 x 6 in. to 11 x 17 in./A6 to A3 for stacking 7.25 x 10.5 in. to 11 x 17 in./B5 to A3 for stapling
Weights	16 lb. bond to 110 lb. cover/60 to 300 gsm (coated and uncoated)
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb./90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported



# Xerox® VersaLink® C9000 Color Printer

<b>Hole Punch</b> North America Europe	2/3 hole punch 2/4 hole punch 4 hole “Swedish” punch (optional)
<b>Booklet Maker</b>	Saddle-stitch 2 to 16 sheets (7 sheets at 106 to 176 gsm coated or 5 sheets at 177 to 220 gsm coated) Bi-fold up to 5 sheets Letter, Legal, Tabloid, A3, A4 supported
<b>DEVICE MANAGEMENT</b>	
<b>Network Protocols</b>	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour®/AirPrint™ Most protocols not in use can be disabled
<b>Administrative Protocols</b>	DHCP, SNMP, WINS, HTTP, HTTPS, TLS, SNTP, MDNS
<b>REMOTE CONTROL PANEL</b>	
	<ul style="list-style-type: none"> <li>• Enables faster, more convenient technical support and user training</li> <li>• IT administrators and other authorized users can control the device remotely from a web page on any PC</li> <li>• Remote user experience is identical to performing tasks directly at the device</li> </ul>
<b>XEROX® CENTREWARE® WEB</b>	
	<ul style="list-style-type: none"> <li>• A Web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system</li> <li>• Works with any SNMP-managed printer from any manufacturer</li> <li>• Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management</li> </ul>
<b>XEROX® EMBEDDED WEB SERVER – INTEGRATED DEVICE WEB PAGE</b>	
<b>Device Status</b>	<ul style="list-style-type: none"> <li>• Tray status/contents</li> <li>• Consumables status</li> <li>• Billing/Usage</li> <li>• Quick Links</li> <li>• Online Support</li> </ul>
<b>Print Queue Viewing</b>	Job print queue management—view and delete
<b>Job Submission</b>	Print-ready files (PS, PCL, PDF, XPS, JPEG, TXT, PRN, TIF)
<b>Device Administration</b>	Allows simple, remote installation setting of configuration options and management of the device
<b>Browsers</b>	Microsoft® Internet Explorer® Microsoft Edge™ Mozilla™ Firefox® Apple® Safari® Google Chrome™
<b>REMOTE SERVICES</b>	
<b>Automated Meter Readings (AMR)</b>	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.
<b>Automatic Supplies Replenishment (ASR)</b>	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.

# Xerox® VersaLink® C9000 Color Printer

WHAT'S IN THE BOX		
	<ul style="list-style-type: none"> <li>• VersaLink® C9000 Color Printer</li> <li>• Starter Capacity Print Cartridge: One of each (Cyan, Magenta, Yellow: 12,000 print capacity<sup>6</sup>, Black:18,000 print capacity<sup>6</sup>)</li> <li>• Drum Cartridge – One of each (Cyan, Magenta, Yellow, and Black 190,000 print capacity)<sup>6</sup></li> <li>• Quick Use Guide</li> <li>• Install Guide</li> <li>• Software and Documentation CD (with Drivers, Warranty Statement and Safety Regulatory Recycle Disposal Guide)</li> <li>• Power Cord</li> </ul>	
SUPPLIES AND ACCESSORIES	QUANTITY	PART NUMBER
<b>SUPPLIES</b>		
Standard Capacity Toner Cartridges	Cyan: 12,300 standard pages <sup>5</sup> Magenta: 12,300 standard pages <sup>5</sup> Yellow: 12,300 standard pages <sup>5</sup> Black: 18,900 standard pages <sup>5</sup>	106R04062 106R04063 106R04064 106R04065
High Capacity Toner Cartridges	Cyan: 26,500 standard pages <sup>6</sup> Magenta: 26,500 standard pages <sup>6</sup> Yellow: 26,500 standard pages <sup>6</sup> Black: 31,400 standard pages <sup>6</sup>	106R04074 106R04075 106R04076 106R04077
Drum Cartridge	Cyan: 190,000 standard pages <sup>6</sup> Magenta: 190,000 standard pages <sup>6</sup> Yellow: 190,000 standard pages <sup>6</sup> Black: 190,000 standard pages <sup>6</sup>	101R00602
Waste Cartridge	47,000 standard pages <sup>7</sup>	108R01504
IBT Cleaner	160,000 standard pages <sup>7</sup>	104R00256
Transfer Roller	200,000 standard pages <sup>7</sup>	116R00015
Office Finisher Booklet Maker Cartridge (8 cartridges per container)	16,000 staples (2,000 each cartridge)	008R12897
Staple Refills for Office Finisher(3 refills per container)	15,000 staples (5,000 each refill)	008R12941
Staple Cartridges for BR Finisher and Office Finisher (1 cartridge per carton)	5,000 staples (5,000 each cartridge)	008R12964
Staple Cartridges for BR Booklet Maker (1 cartridge per carton)	5,000 staples (5,000 each cartridge)	008R13177
<b>ACCESSORIES / OPTIONS</b>		
Two Tray Module		097S04969
Tandem Tray Module		097S04970
High-Capacity Feeder		097S04845
Envelope Tray (Replaces Tray 1)		497K17880
Office Finisher LX (includes Gap Filler)		097S04848
Office Finisher		097S05019
2/3 Hole Punch for Office Finisher LX (available in Western Hemisphere)		497K03860
2/3 Hole Punch for Office Finisher (available in Western Hemisphere)		497K20600
2/4 Hole Punch for Office Finisher LX (available in Eastern Hemisphere)		497K03870

# Xerox® VersaLink® C9000 Color Printer

2/4 Hole Punch for Office Finisher (available in Eastern Hemisphere)	497K20610
Booklet Maker for Office Finisher LX	497K03852
Booklet Maker for Office Finisher	497K20590
BR Booklet Maker Finisher with 2/3 Hole Punch (comes with Horizontal Transport)	497K21000
BR Booklet Maker finisher with 2/4 Hole Punch	097S04982
Swedish 4 Hole Punch for BR Finisher	497K14370
Wireless Network Adapter Kit	497K16750
Xerox Precise Color Management System	097S04974
Internal Card Reader/RFID Kit	497K18120 (Western Hemisphere) 497K18140 (Eastern Hemisphere)

<sup>1</sup> Declared print speed in accordance with ISO/IEC 24734.

<sup>2</sup> Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

<sup>3</sup> Recommended average throughput is not a minimum but is intended to cover a range of volumes for different environments.

<sup>4</sup> Power states defined per ENERGY STAR® Program requirements for Imaging Equipment.

<sup>5</sup> Paper capacities are based on 20 lb. 75 gsm stock; capacities will vary with different weight stocks.

<sup>6</sup> Average standard pages. Declared Yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print mode.

<sup>7</sup> Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed. For more information visit: <http://www.office.xerox.com/Latest/SUPGL-01.pdf>.

Return spent imaging supplies through the Xerox® Green World Alliance® collection/reuse/recycling program.

For more information, visit [www.xerox.com/About-Xerox/Recycling](http://www.xerox.com/About-Xerox/Recycling).

For more information, visit us at [www.xerox.com/Office](http://www.xerox.com/Office).

Configurations vary by geography.