

H273-Z82 (rev. AAW1) | (rev.AAN1)


High Density Server – AMD EPYC™ 9004 DP 2U 4-Node Server 8 x Gen4 NVMe/SATA 3000W | Application: **HCI & Hybrid/Private Cloud Server**

- 2U 4-node rear access server system
- AMD EPYC™ 9004 series processor family
- Dual processor per node, 5nm technology
- 12-Channel RDIMM DDR5 per processor, 96 x DIMMs
- Dual ROM Architecture supported
- 8 x 1Gb/s LAN ports (Intel® I350-AM2)
- 4 x Dedicated management ports
- 8 x 2.5" Gen4 NVMe/SATA hot-swappable bays
- 4 x M.2 with PCIe Gen4 x4 interface **(optional)**
- 4 x LP PCIe Gen5 x16 expansion slots
- 4 x OCP 3.0 Gen5 x16 mezzanine slots
- Dual 3000W (240V) 80 PLUS Titanium redundant power supply



[Request a Quote](#)

Compare



OVERVIEW **SPECIFICATIONS** SUPPORT RESOURCES BUY

Dimensions (WxHxD, mm)

2U 4-Node - Rear access
440 x 87.5 x 877

Motherboard

MZB3-HD0

CPU

AMD EPYC™ 9004 series processor family
Dual processor, 5nm technology
Up to 96-core, 192 threads per processor
Supports CPU 400W at ambient 25°C
Supports CPU 400W at ambient 20°C if using OCP 3.0

Socket

Per Node:
2 x LGA 6096

Total:
8 x LGA 6096

Socket SP5

Chipset

System on Chip

Memory

Per node:
24 x DIMM slots

Total:
96 x DIMM slots
DDR5 memory supported only
12-Channel memory architecture
RDIMM modules up to 128GB supported
3DS RDIMM modules up to 256GB supported
Memory speed: Up to 4800 MHz

LAN

Per node:
2 x 1GbE LAN ports (1 x Intel® I350-AM2)
Support NCSI function
1 x Dedicated management port

Total:
8 x 1GbE LAN ports (4 x Intel® I350-AM2)
Support NCSI function
4 x Dedicated management ports

Video

Integrated in Aspeed® AST2600
2D Video Graphic Adapter with PCIe bus interface
1920x1200@60Hz 32bpp, DDR4 SDRAM

Management chip on CMC board:
Integrated in Aspeed® AST2520A2-GP

Storage

Per node:
2 x 2.5" Gen4 NVMe/SATA/SAS hot-swappable bays

Total:
8 x 2.5" Gen4 NVMe/SATA/SAS hot-swappable bays

SAS card is required for SAS devices support

SAS

Supported via add-on SAS Card

RAID

N/A

Expansion Slots

Per node:

Riser Card CRSH01R:
- 1 x PCIe x16 (Gen5 x16) low-profile slot, from CPU_0

1 x OCP 3.0 mezzanine slot with PCIe Gen5 x16 bandwidth, from CPU_0
Supports NCSI function

*1 x M.2 slot:
- M-key
- PCIe Gen4 x4, from CPU_0
- Supports NGFF-2280/22110 cards

Total:
Riser Card CRSH01R x 4:
- 4 x PCIe x16 (Gen5 x16) low-profile slots, from CPU_0

4 x OCP 3.0 mezzanine slots with PCIe Gen5 x16 bandwidth, from CPU_0
Support NCSI function

*4 x M.2 slots:
- M-key
- PCIe Gen4 x4, from CPU_0
- Support NGFF-2280/22110 cards

***Optional kit for M.2 extension riser card**
PN: 9CMTF192NR-00

Internal I/O

Per node:
1 x TPM header

Front I/O

Per node:
1 x Power button with LED
1 x ID button with LED
1 x Status LED
1 x System reset button

Total:
4 x Power buttons with LED
4 x ID buttons with LED
4 x Status LEDs
4 x System reset buttons
*1 x CMC status LED
*1 x CMC reset button

***Only one CMC status LED and reset button per system**

Rear I/O

Per node:
2 x USB 3.2 Gen1
1 x Mini-DP
2 x RJ45
1 x RJ45 MLAN
1 x Node Status LED

Total:
8 x USB 3.2 Gen1
4 x Mini-DP
8 x RJ45
4 x RJ45 MLAN
4 x Node Status LEDs

***Spanning Tree Protocol (STP) must be enabled in LAN switch function if using ring topology**

Backplane I/O

Backplane P/N: 9CBPH081NR-00
PCIe Gen4 x4 or SATA 6Gb/s or SAS 12Gb/s

TPM

1 x TPM header with SPI interface
Optional TPM2.0 kit: **CTM010**

Power Supply

Dual 3000W (240V) 80 PLUS Titanium redundant power supply

AC Input:
- 100-127V~/ 16A, 50-60Hz
- 200-240V~/ 16A, 50-60Hz

DC Input:
- 240Vdc/ 16A

DC Output:
- Max 1200W/ 100-127V~
+ 12.2V/ 98.36A
+ 12.2Vsb/ 3A
- Max 2600W/ 200-207V~
+ 12.2V/ 213A
+ 12.2Vsb/ 3A
- Max 3000W/ 208-240V~
+ 12.2V/ 245.9A
+ 12.2Vsb/ 3A

NOTE: The system power supply requires C19 power cord

System Management

Aspeed® AST2600 management controller
GIGABYTE Management Console (AMI MegaRAC SP-X) web interface

Dashboard
HTML5 KVM
Sensor Monitor (Voltage, RPM, Temperature, CPU Status ...etc.)
Sensor Reading History Data
FRU Information
SEL Log in Linear Storage / Circular Storage Policy
Hardware Inventory
Fan Profile
System Firewall
Power Consumption
Power Control
LDAP / AD / RADIUS Support
Backup & Restore Configuration
Remote BIOS / BMC / CPLD Update
Event Log Filter
User Management
Media Redirection Settings
PAM Order Settings
SSL Settings
SMTP Settings

OS Compatibility

Please refer to OS compatibility table in support page

[Ubuntu 22.04 LTS](#)

System Fans

4 x 80x80x80mm (16,500rpm)

Operating Properties

Operating temperature: 10°C to 35°C
Operating humidity: 8-80% (non-condensing)
Non-operating temperature: -40°C to 60°C
Non-operating humidity: 20%-95% (non-condensing)

Packaging Dimensions

1179 x 700 x 380 mm

Packaging Content

1 x H273-Z82
8 x CPU heatsinks
1 x Rail Kit

Part Numbers

- Barebone package: 6NH273Z82DR000AAW1*
- Motherboard: 9MZ83HD0UR-000
- Rail kit: 25HB2-A66125-K0R
- CPU heatsink: 25ST1-25320P-M1R/25ST1-25320Q-M1R
- M.2 extension riser card: 9CMTF192NR-00 **(optional)**
- Backplane board: 9CBPH081NR-00
- Fan module: 25ST2-888020-S1R
- Riser card - CRSH01R: 9CRSH01RNR-00
- Rear IO board (incl. LAN chip): 9CLBH160NR-00
- Mini-DP to D-Sub cable: 25CRN-200801-K1R
- Power Supply: 25EP0-230009-L0S
- C19 power cord 125V/15A (US): 25CP1-018000-Q0R **(optional)**
- C19 power cord 250V/16A (EU): 25CP3-01830H-Q0R **(optional)**

* The entire materials provided herein are for reference only. GIGABYTE reserves the right to modify or revise the content at anytime without prior notice.
* Advertised performance is based on maximum theoretical interface values from respective Chipset vendors or organization who defined the interface specification. Actual performance may vary by system configuration.
* All trademarks and logos are the properties of their respective holders.
* Due to standard PC architecture, a certain amount of memory is reserved for system usage and therefore the actual memory size is less than the stated amount.

DISCOVER	COMPANY	CONSUMER	ENTERPRISE	SOLUTION	SERVICE / SUPPORT
Join Us	About Us	Motherboard	Server Motherboard	Application Solutions	Product Support
Customer Care	CSR	Graphics Card	Rack Server	Industry Solutions	Online Support
GIGABYTE Stable Models (GSM)	News	Laptop	GPU Server		FAQ
Business Center	Career	Monitor	High Density Server	RESOURCE	Warranty
	Investor	Desktop PC	Advanced Cooling	Insight	
	Contact Us	PC Peripherals	ARM Server	Success Case	
		PC Components	Storage Server	Awards	
			Edge Server	News	
			Tower Server / Workstation	Events	
			Embedded Computing		

FOLLOW US

