

Overview

Simple, powerful, portable

Unlock 8K[2] with one connection. The HP USB-C to DisplayPort Adapter G2 supports stunning displays with an easy-to-use plugand-play[1] design. Gain the power of broad compatibility for an unrestricted workflow, anywhere you go.



Plug-and-play. On-the-go.

Level up the way you work with an adapter that connects to 8K[2] displays. Featuring top-tier DisplayPort™ 1.4, simply plug in for high-performance connection up and downstream — no SW downloads or drivers needed[1].



Ultra lightweight and ready to work

Choose travel-ready tech. The single-side USB-C® to DisplayPort™ 1.4 supports total connection from almost anywhere. Plus, it's ultra lightweight at just 32.5g, meaning you've got the gear for work on the go.



The ultimate team player

Get ready to break brand barriers with the power of multi-OS support. Move between Windows®, Linux®, Chrome, MacOS, iPadOS, or Android, even non-HP devices, for an unstoppable workflow.



Built for a better tomorrow

The better choice for a brighter tomorrow, this adapter is made with at least 80% post-consumer recycled plastics[4] and FSC®-certified packaging.

- [1] Host PC USB-C® port must support DP Alt mode.
- [2] Supports up to 8K (7680x4320@60Hz) with Display Stream Compression.
- [4] Recycled plastic is expressed as a percentage of the total weight plastic. Post-consumer recycled is based on the definition set in the EPEAT® standard for computers, IEEE 1680.1-2018 standard.

Specifications

Minimum dimensions (W x D x H)	180 x 23.7 x 15.3 mm
Minimum dimensions (W \times D \times H)	7.09 x 0.93 x 0.60 in
Weight	32.5 g
Weight	0.07 lb
Video connectors	1 DisplayPort™ 1.4
Package dimensions (W \times D \times H)	160 x 140 x 17.6 mm
Package weight	51 g
Sustainable impact specifications	80% post-consumer recycled plastic; Packaging is recyclable
Minimum System Requirements	USB Type-C® with Alt Mode DisplayPort™; Thunderbolt™ 4; Thunderbolt™ 3
Manufacturer Warranty	HP standard one-year limited warranty
What's in the box	Dongle; Warranty card

Additional specifications

Cable length	12 cm
Cable length (imperial)	4.72 in
Cartons per layer	7
Cartons per pallet	42
Color	Black
Compatible Operating Systems	Windows 10; Windows 11; macOS; Chrome OS™; iPadOS; Android™
Country of origin	Product of China
Datasheet photo 1	AHID/e0595848e6dac5c6ffb9d5c22227873c8177e4bc
Datasheet photo 2	AHID/4270f3ee83433c5e1f9fa4be79f8ee0b0845b871
Datasheet photo 3	AHID/7696a642cae0ccf537347ea46b4675ef59d50db1
Datasheet photo 4	AHID/8440e7f7e269d8cb625a2a05659d31f47d35f95e
Displays supported	Single monitor
Package dimensions (W x D x H)	6.30 x 5.51 x 0.70 in
Package weight	0.11 lb
Pallet (layers)	6
Pallet weight	62.53 kg
Pallet weight	137.57 lb
Product type	AC adapters
Products per pallet	3360
Products per pallet layer	560
Resolution (maximum)	7680 x 4320 @ 60 Hz
UNSPSC code	26121630

Disclaimer — Copyright

iPad® and MacOS are trademarks of Apple Computer, Inc., registered in the U.S. and other countries. Linux® is the registered trademark of Linus Torvalds in the U.S. and other countries. Microsoft, Encarta, MSN, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. © 2024 Google LLC All rights reserved. Chrome and Android are trademarks of Google LLC. USB Type-C® and USB-C® are registered trademarks of USB Implementers Forum. DisplayPort™ and the DisplayPort™ logo are trademarks owned by the Video Electronics Standards Association (VESA®) in the United States and other countries.

Actual product may vary from image shown.

© Copyright 2024 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Generated by Dynamic Collateral Tool – (ww-en) – Aug 16, 2024 8:02 AM UTC+0000