Overview

HP Fortis Flip G1i 11 inch Notebook PC



- 1 Internal microphones (2)
- 2 Webcam LED
- 3 Webcam

- 4 HP Privacy Camera
- 5 Pen garage (Optional)
- 6 Clickpad

Overview



Sides

- 1 Power Connector
- **2** RJ-45 Ethernet port
- 3 HDMI port (Cable not included)
- 4 USB Type-A 5Gbps signaling rate (Powered)
- 5 USB Type-C[®] 5Gbps signaling rate (USB Power Delivery, DisplayPort[™] 1.2)
- 6 Headphone/mic combo jack
- 7 USB Type-A 5Gbps signaling rate (Powered)
- **8** Security lock slot (nano lock sold separately)

PRODUCT NAME

HP Fortis Flip G1i 11 inch Notebook PC

OPERATING SYSTEM

Preinstalled Windows 11 Pro

Windows 11 Pro Education

Windows 11 Home - HP recommends Windows 11 Pro for Business

Windows 11 Home Single Language - HP recommends Windows 11 Pro for Business Windows 11 Pro (Windows 11 Enterprise available with a Volume Licensing Agreement)

FreeDOS

PROCESSORS

					Max	Base	Intel SIPP/vPro®	Intel® Turbo
Processor ^{1,2}	Cores	Number of	Threads	L3 Cache	Frequency	Frequency	Enterprise	Boost
110003301	Cores	E-cores	Tilleaus	LJ Cache	E-cores	E-cores		Technology 2.0
Intel® N250	4	4	4	6 MB	3.8 GHz	1 3 GHz	Х	Yes
Intel® N150	4	4	4	6 MB	3.6 GHz	0.8GHz	Х	Yes

Processor Family

Intel® Processor N-series

- 1. Multicore is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. Performance and clock frequency will vary depending on application workload and your hardware and software configurations. Intel's numbering, branding and/or naming is not a measurement of higher performance.
- 2. In accordance with Microsoft's support policy, HP does not support the Windows 8 or Windows 7 operating system on products configured with Intel and AMD 7th generation and forward processors or provide any Windows 8 or Windows 7 drivers on http://www.support.hp.com

CHIPSET

Chipset is integrated with processor



Technical Specifications

GRAPHICS

Integrated

Intel® UHD Graphics

Supports

Support HD decode, DX12, HDMI 2.1b³

3. HD content required to view HD images.

DISPLAY

Availability may vary by country.

Actual brightness will be lower with touchscreen or HP Sure View.

Touch

29.46 cm (11.6") diagonal, HD (1366 x 768), LCD, Touch, Corning® Gorilla® Glass 3, SVA, BrightView, WLED, 250 nits, NTSC 45%

29.46 cm (11.6") diagonal, HD (1366 x 768), LCD, Touch, Corning® Gorilla® Glass 3, UWVA, BrightView, WLED, 250 nits, NTSC 50%

Display Size (Diagonal)

29.46 cm (11.6") diagonal

STORAGE AND DRIVES

Primary Storage

256 GB PCIe[®] NVMe[™] SSD Value ⁴ 128 GB UFS ⁴

4. For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 30 GB (for Windows 10 and 11) is reserved for system recovery software.



Technical Specifications

MEMORY

Maximum Memory

16 GB LPDDR5-6400 MT/s 5

Memory

16 GB LPDDR5-6400 MT/s 5 8 GB LPDDR5-6400 MT/s 5 4 GB LPDDR5-6400 MT/s 5

Memory Slots

No memory slots Memory soldered on board System runs at 4800 MT/s The memory is non-accessible / non-upgradeable

5. Due to the non-industry standard nature of some third-party memory modules, we recommend HP branded memory to ensure compatibility. If you mix memory speeds, the system will perform at the lower memory speed.



NETWORKING/COMMUNICATIONS

WLAN

Intel® Wi-Fi 6E AX211 Bluetooth® 5.3 wireless card, non-vPro 6

WWAN

Qualcomm® Snapdragon™ X12 4G LTE Advanced CAT 6 7

Miracast

Native Miracast Support 8

Ethernet

Realtek RTL8111HSH 10/100/1000 Integrated NIC 9

- 6. Wi-Fi 6E requires a Wi-Fi 6E router, sold separately to function in the 6GHz band. Availability of public wireless access points limited. Wi-Fi 6E is backwards compatible with prior 802.11 specs. And available in countries where Wi-Fi 6E is supported.
- 7. 4G LTE module is optional, must be configured at the factory, requires activation and separately purchased service contract. Check with service provider for coverage and availability in your area. Connection, upload and download speeds will vary due to network, location, environment, network conditions, and other factors. 4G LTE not available on all products, in all regions.
- 8. Miracast is a wireless technology your PC can use to project your screen to TVs, projectors, and streaming.
- 9. The term "10/100/1000" or "Gigabit" Ethernet indicates compatibility with IEEE standard 802.3ab for Gigabit Ethernet, and does not connote actual operating speed of 1 Gb/s. For high-speed transmission, connection to a Gigabit Ethernet server and network infrastructure is required.

AUDIO/MULTIMEDIA

Select product only (Privacy panel SKU).

Audio

2 Integrated stereo speakers Integrated dual array microphone

Speaker Power

2W/4ohm per speaker

Camera

720p HD camera HP Privacy Camera

World-facing Wide Field of View 80 5MP auto-focus secondary camera (Optional)



Technical Specifications

KEYBOARDS/POINTING DEVICES/BUTTONS & FUNCTION KEYS

Keyboard

Full-sized keyboard, spill and pick resistant keyboard

Pointing Device

Clickpad with multi-touch gesture support, taps enabled as default

Function Keys

Copilot+ in Windows requires Windows 11. Some features require an NPU. Timing of feature delivery and availability varies by market and device. Requires Microsoft account to log in. Where Microsoft in Windows is not available, the Copilot key will lead to the Bing search engine. See aka.ms/copilotpluspcs.

- F1 Display Switching
- F2 Brightness Down
- F3 Brightness Up
- F4 Audio Mute/Unmute
- F5 Volume Down
- F6 Volume Up
- F7 Mic Mute/Unmute
- F8 Blank
- F9 Blank
- F10 Insert
- F11 Wireless On/Off
- F12 HP Programmable Key

Pen

Pen garage (optional)

HP Slim Rechargeable pen (optional)



SOFTWARE AND SECURITY

Preinstalled Software

Software

HP PC Hardware Diagnostics Windows

mvHP

HP Smart Support 10

HP Services Scan 11

HP Connection Optimizer

HP Hotkey Support

HP Support Assistant 12 (download)

HP Notifications

HP Privacy Settings

Buy Microsoft Office (Sold separately)

Manageability Features

HP Connect for Microsoft Endpoint Manager 13

HP Image Assistant Gen5 (download)

HP Manageability Integration Kit (download) 14

HP Client Management Script Library (download)

HP Patch Assistant (download) 15

HP Driver Packs (download)

HP Client Catalog (download)

NOTE: To enhance brightness, level go to the Intel® Graphics Command Center app, click on System and turn off the Display Power Savings function.

Security Management

Secured-Core PC Enable (require memory 8GB and above) 16

HP Wolf Security for Business ¹⁷ includes:

HP Sure Sense 18

HP Sure Start Gen7 19

BIOS

HP BIOSphere Gen6²⁰

HP Secure Erase 21

Absolute Persistence Module 22

HP DriveLock & Automatic DriveLock

BIOS Update via Network

HP Wake on WLAN

TPM 2.0 Embedded Security Chip (Common Criteria EAL4+ Certified) (FIPS 140-2 Level 2 Certified)

Security

TPM

Model: Nuvoton NPCT760HABYX

Version: 7.2.3.1 Revision: TPM 2.0

FIPS 140-2 Compliant: Yes

IPv6 Support

Yes



Technical Specifications

FirstNet Certified

Yes

The BIOS on this notebook implements ISO/IEC 19678:2015 guidelines (formerly NIST 800-147).

UEFI version: 2.7 Class: Class 3

10. HP Smart Support requires the HP Insights agent to be installed. For more information about how to enable or to download HP Smart Support, please visit http://www.hp.com/smart-support. HP Services Scan is preinstalled and/or provided thru Windows Update and will check entitlement on each hardware device to determine if an HP Insights agent-enabled service has been purchased, and will download applicable software automatically. HP Insights agent is a telemetry and analytics platform that provides critical data around devices and applications and is not sold as a standalone service. HP follows stringent GDPR privacy regulations and is ISO27001, ISO27701, ISO27017 and SOC2 Type2 certified for Information Security. Internet access is required. For full system requirements or to disable this feature, please visit https://www.hpdaas.com/requirements.

11. HP Services Scan is provided thru Windows Update and will check entitlement on each hardware device to determine if an HP TechPulse-enabled service has been purchased, and will download applicable software automatically. To disable this feature, please follow the instructions at http://www.hpdaas.com/requirements. HP TechPulse is a telemetry and analytics platform that provides critical data around devices and applications and is not sold as a standalone service. HP TechPulse follows stringent GDPR privacy regulations and is ISO27001, ISO27701, ISO27017 and SOC2 Type2 certified for Information Security. Internet access with connection to TechPulse portal is required. For full system requirements, please visit http://www.hpdaas.com/requirements. Not available in China.

- 12. HP Support Assistant requires Windows and Internet Access
- 13. HP Connect for Microsoft Endpoint Manager is available from the Azure Market Place for HP Pro, Elite, Z and Point-of-Sale PCs managed with Microsoft Endpoint Manager. Subscription to Microsoft Endpoint Manager required and sold separately. Network connection required.
- 14. HP Manageability Integration Kit can be downloaded from http://www.hp.com/go/clientmanagement.
- 15. HP Patch Assistant available on select HP PCs with the HP Manageability Kit that are managed through Microsoft System Center Configuration Manager. HP Manageability Integration Kit can be downloaded from https://www.hp.com/us-en/solutions/client-management-solutions.html#tab=manageability-tools
- 16. Secured-Core PC Enable requires 8 GB or more system memory. Secured-core PC is enabled from the factory.
- 17. HP Wolf Security for Business requires Windows 10 or higher, includes various HP security features and is available on HP Pro, Elite, RPOS and Workstation products. See product details for included security features and OS requirement.
- 18. HP Sure Sense is available on select HP PCs with Windows 10 Pro, Windows 10 Enterprise, Windows 11 Pro, or Windows 11 Enterprise OS.
- 19. HP Sure Start Gen7 is available on select HP PCs and requires Windows 10 and higher
- 20. HP BIOSphere Gen6 features may vary depending on the platform and configuration.
- 21. For the methods outlined in the National Institute of Standards and Technology Special Publication 800-88 "Clear" sanitation method. HP Secure Erase does not support platforms with Intel® Optane™.
- 22. Absolute firmware module is shipped turned off and can only be activated with the purchase a license subscription and full activation of the software agent. License subscriptions can be purchased for terms ranging multiple years. Service is limited, check with Absolute for availability outside the U.S. Certain conditions apply. For full details visit: https://www.absolute.com/about/legal/agreements/absolute/.



Technical Specifications

POWER

Availability may vary by country.

Battery is internal and not replaceable by customer. Serviceable by warranty.

Power Supply

HP Smart 65 W EM External AC power adapter ²³
HP Smart 45 W External AC power adapter ²³
Smart 45 W USB Type-C[®] adapter ²³
HP 65W Standard USB Type-C[®] Halogen Free AC power adapter²³

Battery

HP Long Life 3-cell, 42 Whr Polymer²⁴

Power Cord

2-wire plug - 1m 3-wire plug - 1m

Battery life

Up to 10 hours with 42whr battery (HP long life 3-cell, 42 Whr polymer, UMA graphic, Intel U9, display set to 250 nits, 8GB memory, 256GB) ²⁵

Battery Weight

HP Long Life 3-cell - 42 Wh Polymer - .49 lb HP Long Life 3-cell - 42 Wh Polymer - 225g

23.0nly available for selected regions and selected configurations.

24.Recharges your battery up to 50% within 30 minutes when the system is off or in standby mode. Power adapter minimum of 65 watts required for battery capacities 56Whr or less. Power adapter minimum of 100 watts required for battery capacities greater than 56Whr and less than 83Whr. Power adapter minimum of 120 watts required for battery capacities greater than 83Whr and less than 100Whr. After charging has reached 50% capacity, charging will return to normal. Charging time may vary +/-10% due to System tolerance.

25.MobileMark 25 battery life will vary depending on various factors including product model, configuration, loaded applications, features, use, wireless functionality, and power management settings. The maximum capacity of the battery will naturally decrease with time and usage. See www.bapco.com for additional details.



WEIGHTS & DIMENSIONS

Weight will vary by configuration. Does not include power adapter.

Product Weight

Starting at 3.24 lb Starting at 1.47 kg

Product Dimensions (W x D x H)

297 x 203.7 x 21.2 mm ²⁶ 11.7 x 8.02 x 0.84 in ²⁶

Pallet Dimensions (W x D x H)

11" boxes (260 mm height): 1200mm x 1000mm x 1200mm²⁷

26. Front height measurement is near the front edge where the mechanical chassis taper begins. Back height measurement is near the rear edge where the mechanical chassis taper ends.

27.Product packaging size varies based on options chosen. Please contact your HP representative for your packaging size details. For detailed packaging information, access the HP Commercial Notebooks Packaging Guide. https://h20195.www2.hp.com/v2/GetPDF.aspx/c08960410.pdf

PORTS/SLOTS

1 x USB Type-C[®] 5Gbps signaling rate (USB Power Delivery, DisplayPort™ 1.2) ²⁸

2 x USB Type-A 5Gbps signaling rate (Powered) ²⁹

1 x Headphone/mic combo jack

1 x HDMI 2.1

1 x AC power

1 x RJ-45

Expansion Slots

1 internal on-board Nano SIM slot for WWAN (optional) 42

28. USB 20Gbps signaling rate is not available with Thunderbolt™ 4. Actual throughput may vary.



Technical Specifications

ENVIRONMENTAL DATA

Eco-Label Certifications & declarations	This product has received or is and may be labeled with one or		fied to the following approvals	
	 EPEAT® Gold registered registration status in y TCO Certified China Energy Conserva China State Environme Taiwan Green Mark Korea Eco-label Japan PC Green label* 	tion Program (CECP) ental Protection Administratio		
Sustainable Impact	 Product Carbon Footpr 			
Specifications	 At least 30% ocean bound plastic in the (Speaker)¹ At least (0.6%) ITE-Derived closed loop plastic² At least (20%) post-consumer recycled plastic² Low Halogen⁴ 100% of HP paper-based packaging is from recycled or certified sustainable sources⁵ 			
System Configuration	 Bulk packaging available. The configuration used for the Energy Consumption and Declared Noise Emissions data for the Notebook model is based on a "Typically Configured Notebook". 			
Energy Consumption (in accordance with US ENERGY STAR® test method)	115VAC, 60Hz	230VAC, 50Hz	100VAC, 50Hz	
Normal Operation (Short idle)	3.91 W	4.03 W	4.13 W	
Normal Operation (Long idle)	N/A	N/A	N/A	
Sleep	0.54 W	0.63 W	0.59 W	
Off	0.30 W	0.33 W	0.29 W	
	NOTE: Energy efficiency data liste model family. HP computers mark U.S. Environmental Protection Age family does not offer ENERGY STA for a typically configured PC fea Microsoft Windows® operating syst	ed with the ENERGY STAR® Logo ency (EPA) ENERGY STAR® specifi IR® compliant configurations, the turing a hard disk drive, a high	are compliant with the applicable ications for computers. If a model en energy efficiency data listed is	
Heat Dissipation*	115VAC, 60Hz	230VAC, 50Hz	100VAC, 50Hz	
Normal Operation (Short idle)	13 BTU/hr	14 BTU/hr	14 BTU/hr	
Normal Operation (Long idle)	N/A	N/A	N/A	
Sleep	2 BTU/hr	2 BTU/hr	2 BTU/hr	



Off	1 RT	'U/hr	1 BTU/hr	1.1	BTU/hr
		•	ulated based on the m		
	level is attained	•		,	,
Declared Noise Emissions		Sound Power		Sound Pressu	ıre
(in accordance with ISO 7779 and ISO 9296)	(L _{WAd} , bels)			(L _{pAm} , decibels) 15.6	
Typically Configured – Idle	2.6				
Fixed Disk – Random writes		2.6		14.3	
Optical Drive – Sequential reads		2.6		14.2	
Longevity and Upgrading	Upgradeable fe	eatures and/or co	oossibly extending its un mponents contained in ghout the warranty per	n the	
Additional Information	(RoHS) This H Equipr This pi Safe D This pi level,) directive - 2011 P product is desiment (WEEE) Direction roduct is in comporinking Water and composee www.epeat.rcs parts weighing 469 and ISO1043	gned to comply with the ective – 2002/96/EC. bliance with California P ad Toxic Enforcement A bliance with the IEEE 16 net g over 25 grams used in	e Waste Electrical an Proposition 65 (State ct of 1986). 80 (EPEAT) standard In the product are man	nd Electronic of California; I at the Gold ked per
Packaging Materials	External:	PAPER/Corrug	ated		235 g
		PAPER/Paper			2 g
		PAPER/Molded	d Pulp		84 g
	Internal: PLASTIC/Polyethylene low densi		ethylene low density – I	LDPE	13 g
	The plastic packaging material contains at least 0.0% recycled content.				
RoHS Compliance	The corrugated paper packaging materials contains at least 48.2% recycled content. HP Inc. complies fully with materials regulations. We were among the first companies to extend the restrictions in the European Union (EU) Restriction of Hazardous Substances (RoHS) Directive to our products worldwide through the HP GSE. HP has contributed to the development of related legislation in Europe, as well as China, India, and Vietnam. We believe the RoHS directive and similar laws play an important role in promoting industry-wide elimination of substances of concern. We have supported the inclusion of additional substances—including PVC, BFRs, and certain phthalates—in future RoHS legislation that pertains to electrical and electronics products. We met our voluntary objective to achieve worldwide compliance with the new EU RoHS requirements for virtually all relevant products by July 2013, and we will continue to extend the scope of the commitment to include further restricted substances as regulations continue to evolve. To obtain a copy of the HP RoHS Compliance Statement, see HP RoHS position statement.				



Material Usage	This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at https://h20195.www2.hp.com/v2/GetDocument.aspx?docname=c05998906):
	 Asbestos Certain Azo Colorants Certain Brominated Flame Retardants – may not be used as flame retardants in plastics Cadmium Chlorinated Hydrocarbons Chlorinated Paraffins Bis(2-Ethylhexyl) phthalate (DEHP) Benzyl butyl phthalate (BBP) Dibutyl phthalate (DBP) Diisobutyl phthalate (DIBP) Formaldehyde Halogenated Diphenyl Methanes Lead carbonates and sulfates Lead and Lead compounds Mercuric Oxide Batteries Nickel – finishes must not be used on the external surface designed to be frequently handled or carried by the user. Ozone Depleting Substances Polybrominated Biphenyls (PBBs) Polybrominated Biphenyl Oxides (PBBOs) Polychlorinated Biphenyl (PCB) Polychlorinated Biphenyls (PCT) Polychlorinated Terphenyls (PCT) Polychlorinated (PVC) – except for wires and cables, and certain retail packaging has been voluntarily removed from most applications. Radioactive Substances Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)
Packaging Usage	 HP follows these guidelines to decrease the environmental impact of product packaging: Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials. Eliminate the use of ozone-depleting substances (ODS) in packaging materials. Design packaging materials for ease of disassembly. Maximize the use of post-consumer recycled content materials in packaging materials. Use readily recyclable packaging materials such as paper and corrugated materials. Reduce size and weight of packages to improve transportation fuel efficiency. Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.
End-of-life Management and Recycling	HP offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: https://h20195.www2.hp.com/V2/GetDocument.aspx?docname=c05403198 or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.



	The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: HP Product Disassembly Instruction Website. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.
HP, Inc. Corporate Environmental Information	 Sustainable Impact Report https://h20195.www2.hp.com/v2/GetDocument.aspx?docname=c06040 843 Eco-label certifications https://www.hp.com/us-en/sustainable-impact/document-reports.html#filters_documents_reports-=document_type-type_energy_star,type_epeat,type_tcolS0 ISO 14001 certificates https://h20195.www2.hp.com/v2/GetDocument.aspx?docname=c04777 932
footnotes	 Percentage of ocean-bound plastic contained in each component varies by product. Ocean Bound plastic is expressed as a percentage of the total weight plastic. Ocean Bound plastic is based on the definition set by the UL2809 standard. Recycled plastic is expressed as a percentage of the total weight plastic. Post-consumer recycled is based on the definition set in the EPEAT standard for computers, IEEE 1680.1-2018 standard. External power supplies, WWAN modules, power cords, cables and peripherals excluded. Service parts obtained after purchase may not be Low Halogen. HP paper and fiber-based packaging for PCs, displays, home and office print, and supplies is reported by suppliers as recycled or certified, with a minimum of 97% by volume verified by HP. Packaging is the box that comes with the product and all paper-based materials inside the box. Packaging for personal systems accessories and spare parts is not included. Plastic cushions are made from >90% recycled plastic.

Technical Specifications

SERVICE AND SUPPORT

HP Services offers 1-year limited warranties and 90 day software limited warranty options depending on country. Batteries have a default one year limited warranty. Refer to http://www.hp.com/support/batterywarranty/ for additional battery information. On-site service and extended coverage is also available. HP Care Pack Services are optional extended service contracts that go beyond the standard limited warranties. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at: http://www.hp.com/go/cpc²⁹

29. HP Care Packs are sold separately. Service levels and response times for HP Care Packs may vary depending on your geographic location. Service starts on date of hardware purchase. Restrictions and limitations apply. For details, visit http://www.hp.com/go/cpc. HP services are governed by the applicable HP terms and conditions of service provided or indicated to Customer at the time of purchase. Customer may have additional statutory rights according to applicable local laws, and such rights are not in any way affected by the HP terms and conditions of service or the HP Limited Warranty provided with your HP Product.



SYSTEM UNIT

Stand-Alone Power Requirements (AC Power)

Nominal Operating Voltage 19V Average Operating Power 11.7W

Integrated graphics Intel UHD Graphics

Discrete Graphics N/A
Max Operating Power UMA<45W

Temperature

Operating 41° to 95° F (5° to 35° C) Non-operating -4° to 140° F (-20° to 60° C)

Relative Humidity

Operating 10% to 90% Non-operating 5% to 95%

Shock

Operating 40 G, 2 ms, half-sine Non-operating 240 G, 2 ms, half-sine

Random Vibration

Operating 0.75 grams Non-operating 1.50 grams

Altitude (unpressurized)

Operating -50 to 10,000 ft (-15.24 to 3,048 m) Non-operating -50 to 40,000 ft (-15.24 to 12,192 m)

Planned Industry Standard Certifications

Regulatory Model Number HSN-I57C CSA/UL 62368-1 Yes FCC/ICES/CISPR/VCCI Yes ENERGY STAR® Yes 30

EPEAT® Registered Gold in United States 31

FCC/ICES/CISPR/VCCI Yes **CE MARKING** Yes **GS Mark** Yes Related commodity should comply with ISO 9241 Standards. China CCC/SRRC Yes Taiwan BSMI/NCC Yes Korea KCC/KC/KES Yes Ukraine NSoC/TEC Yes TCO Yes **WW RoHS** Yes Low Blue Light No

30. Configurations that are ENERGY STAR® qualified are identified as ENERGY STAR on HP websites and on http://www.energystar.gov

31. Based on US EPEAT® registration according to IEEE 1680.1-2018 EPEAT®. EPEAT® status varies by country. Visit http://www.epeat.net for more information.

DISPLAYS

NOTE: All specifications represent the typical specifications provided by hp's component manufacturers; actual performance may vary either higher or lower.

1. Actual brightness will be lower with touchscreen or HP Sure View. Touchscreen support 10 finger touches & SPT (Simultaneous Pen and Touch)

11.6 in HD (1366x768) Anti-Glare SVA NTSC 250 eDP 45 flat LCD Panel

Outline Dimensions (W x H) 268.5 x 168.5 max. (w/ PCB)

Active Area 256.125 x 144.0 mm

Weight 210g max. **Diagonal Size** 11.6 inch **Surface Treatment** Anti-Glare **Touch Enabled** Yes1

Contrast Ratio 400:1 (typ) 60Hz **Refresh Rate** 250nits **Brightness**

Pixel Resolution - Format 1366 x 768 (HD)

Backlight WLED Pixel Resolution RGB Color Gamut Coverage 45%NTSC **Color Depth** 6bits

40/40/15/30 **Viewing Angle**

Low Blue Light No

Power Consumption (W, EBL@ 150nits max/ 200nits max)

2.08W (max)/NA

11.6 in HD (1366x768) Anti-Glare UWVA NTSC 250 eDP 50 flat LCD **Panel**

Outline Dimensions (W x H) 278.5 x 168.5 max (w/ PCB)

Active Area 256.125 x 144.0 Weight 200g max. **Diagonal Size** 11.6 inch **Surface Treatment** Anti-Glare **Touch Enabled** Yes1

Contrast Ratio 600:1 (typ) Refresh Rate 60Hz 250nits **Brightness**

Pixel Resolution - Format 1366 x 768 (HD)

Backlight WLED **Pixel Resolution RGB Color Gamut Coverage** 50%NTSC **Color Depth** 6bits

Viewing Angle 85/85/85/85

Low Blue Light No

Power Consumption (W, EBL@ 1.94W (max)/NA

150nits max/ 200nits max)

STORAGE AND DRIVES

For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 30 GB (for Windows 10 and 11) is reserved for system recovery software.

128GB UFS

Form Factor UFS 3.1
Capacity 128GB
NAND Type TLC
Interface SCSI

Minimum Sequential Read 300MB/s (TWL support UFS 2.1 only)

Minimum Sequential Write 150MB/s

Logical Blocks Logical Block: 128GB(127,984,992,256 Bytes)

SSD 256GB 2230 PCIe NVMe Value

Form Factor M.2 2230
Capacity 256 GB
NAND Type 2230 Value

Interface PCIe NVMe Gen3X4 or Gen4X4

Minimum Sequential Read $2000 \text{ MB/s} \pm 10\%$ Minimum Sequential Write $900 \text{ MB/s} \pm 10\%$ Logical Blocks500,118,192

Features Pyritec, Pyritec2.0; TRIM; L1.2



NETWORKING/COMMUNICATIONS

Intel® AX211 Wi-Fi 6E +Bluetooth® 5.3 M.2 160MHz CNVi World-wide WLAN non-vPro 1

Wireless LAN Standards IEEE 802.11a IEEE 802.11b

IEEE 802.11a IEEE 802.11n IEEE 802.11ac IFFF 802.11ax IEEE 802.11d IEEE 802.11e IEEE 802.11h IEEE 802.11i IEEE 802.11k IEEE 802.11r IEEE 802.11v

Wi-Fi certified

Interoperability

Frequency Band •802.11b/g/n/ax

> 2.402 - 2.482 GHz •802.11a/n/ac/ax 4.9 – 4.95 GHz (Japan) 5.15 - 5.25 GHz 5.25 - 5.35 GHz 5.47 - 5.725 GHz 5.825 - 5.850 GHz 5.955 - 6.415 GHz 6.435 - 6.515 GHz

6.535 - 6.875 GHz 6.895 - 7.115 GHz

Data Rates • 802.11b: 1, 2, 5.5, 11 Mbps

> • 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps • 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps

• 802.11n: max 300Mbps 802.11ac: 1733Mbps • 802.11ax : max 2.4Gbps

Modulation **Direct Sequence Spread Spectrum**

OFDM, BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM, 1024QAM

• IEEE and WiFi compliant 64 / 128 bit WEP encryption for a/b/g mode only

• AES-CCMP: 128 bit in hardware

• 802.1x authentication

• WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES.

 WPA2 certification WPA3 certification • IEEE 802.11i WAPI

Network Architecture

Security³

Ad-hoc (Peer to Peer)

Models Infrastructure (Access Point Required)

Roaming IEEE 802.11 compliant roaming between access points

Output Power² • 802.11b: +17dBm minimum

• 802.11g: +16dBm minimum



• 802.11a: +17dBm minimum

802.11n HT20(2.4GHz): +14dBm minimum
802.11n HT40(2.4GHz): +13dBm minimum
802.11n HT20(5GHz): +14dBm minimum
802.11n HT40(5GHz): +13dBm minimum
802.11ac VHT80(5GHz): +10dBm minimum

802.11ac VHT160(5GHz): +10dBm minimum
 802.11ax HE40(2.4GHz): +12dBm minimum

802.11ax HE80(5GHz): +10dBm minimum
 802.11ax HE160(5GHz): +10dBm minimum

Power Consumption

• Transmit mode 2.0 W

• Receive mode 1.6 W

Idle mode (PSP) 180 mW (WLAN Associated)
Idle mode 50 mW (WLAN unassociated)

Connected Standby 10mW

• Radio disabled 8 mW

Power Management

ACPI and PCI Express compliant power management

802.11 compliant power saving mode

Receiver Sensitivity⁴

High efficiency antenna with spatial diversity, mounted in the display

enclosure

Two embedded dual band 2.4/5 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications

Antenna type

802.11b, 1Mbps: -93.5dBm maximum
 802.11b, 11Mbps: -84dBm maximum

802.11a/g, 6Mbps: -86dBm maximum
802.11a/g, 54Mbps: -72dBm maximum

802.11n, MCS07: -67dBm maximum
 802.11n, MCS15: -64dBm maximum

802.11ac, MCS0(VHT80): -84dBm maximum
802.11ac, MCS9(VHT80): -59dBm maximum
802.11ac, MCS9(VHT160): -58.5dBm maximum
802.11ax, MCS11(HE40): -57dBm maximum
802.11ax, MCS11(HE80): -54dBm maximum

• 802.11ax, MCS11(HE160): -53.5dBm maximum

Form Factor PCI-Express M.2 MiniCard

Dimensions Type 2230: 2.3 x 22.0 x 30.0 mm

 Weight
 Type 2230: 2.8g

 Operating Voltage
 3.3v +/- 9%

Temperature Operating 14° to 158° F (–10° to 70° C)

Non-operating -40° to 176° F (-40° to 80° C)

Humidity Operating 10% to 90% (non-condensing)

Non-operating 5% to 95% (non-condensing)

Operating 0 to 10,000 ft (3,048 m)

Non-operating 0 to 50,000 ft (15,240 m)

LED Activity LED Amber – Radio OFF; LED Off – Radio ON



HP Integrated Module with Bluetooth 4.0/4.1/4.2/5.0/5.1/5.2/5.3 Wireless Technology

Bluetooth Specification 4.0/4.1/4.2/5.0/5.1/5.2/5.3 Compliant

Frequency Band 2402 to 2480 MHz

Number of Available Legacy: 0~79 (1 MHz/CH) **Channels** BLE: 0~39 (2 MHz/CH)

Data Rates andLegacy: 3 Mbps data rate; throughput up to 2.17 Mbps **Throughput**BLE: 1 Mbps data rate; throughput up to 0.2 Mbps

Legacy: Synchronous Connection Oriented links up to 3, 64 kbps, voice

channels

Legacy: Asynchronous Connection Less links 2178.1 kbps/177.1 kbps

asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)

Transmit Power The Bluetooth component shall operate as a Class II Bluetooth device with

a maximum transmit power of + 9.5 dBm for BR and EDR.

Power Consumption Peak (Tx): 330 mW

Peak (Rx): 230 mW

Selective Suspend: 17 mW

Bluetooth Software
Supported Link Topology

Microsoft Windows Bluetooth Software

Power Management Microsoft Windows ACPI, and USB Bus Support

Certifications FCC (47 CFR) Part 15C, Section 15.247 & 15.249

Power Management Certifications

ETS 300 328, ETS 300 826 Low Voltage Directive IEC950

UL, CSA, and CE Mark

Bluetooth Profiles
Supported

BT4.1-ESR 5/6/7 Compliance

LE Link Layer Ping LE Dual Mode LE Link Layer

LE Low Duty Cycle Directed Advertising LE L2CAP Connection Oriented Channels

Train Nudging & Interlaced Scan

BT4.2 ESR08 Compliance

LE Secure Connection- Basic/Full LE Privacy 1.2 -Link Layer Privacy

LE Privacy 1.2 – Extended Scanner Filter Policies

LE Data Packet Length Extension

FAX Profile (FAX)

Basic Imaging Profile (BIP)2 Headset Profile (HSP) Hands Free Profile (HFP)

Advanced Audio Distribution Profile (A2DP)

BT5.2

ESR9/10 Compliance

LE Advertisement Extensions Channel Selection Algo

Limited High Duty Cycle Non-Connectable Advertising

2Mbps LE LE Long Range



- 1. Wi-Fi 6E requires a Wi-Fi 6E router, sold separately, to function in the 6GHz band. Availability of public wireless access points limited. Wi-Fi 6E is backwards compatible with prior 802.11 specs. And available in countries where Wi-Fi 6E is supported. Wi-Fi 6E is designed to support gigabit data rate when transferring files between two devices connected to the same router. Requires a wireless router, sold separately, that supports 80MHz and higher channels.
- 2. The FCC has declared as of September 1, 2014 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels.
- 3. Check latest software/driver release for updates on supported security features.
- 4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).



Qualcomm®

Snapdragon™ X12 4G LTE Advanced CAT 61

Technology/Operating FDD-LTE:

bands 1.2.3.4.5.7.8.12.13.14.17.18.19.20.25.26.28.29.30.66.71

TDD-LTE:

38.39.40(1).41.42(1).43(1).48(2)UMTS/HSPA+:

1,2,4,5,6,8,19

(1)Not support B40/42/43 in FCC/IC

(2)Not support B48 in IC (3)Not support HPUE in Japan

Wireless protocol

LTE Modulation 3GPP Release 12 LTE Specification DL-CAT.6, DL 64QAM standards

BW throughput up to 300Mbps; UL-CAT.4 16QAM throughput up to

50Mbps

UMTS Modulation 3GPP Release 9

GPS Standalone GPS/GLONASS/Galileo/BDS, A-GNSS

GPS bands GPS L1: 1575.42MHz ± 1.023MHz

> GLONASS L1: 1602.5625MHz ± 4MHz BDS: 1561.098MHz ± 2.046MHz Galileo: 1575.42MHz ± 1.023MHz

Maximum data rates LTE: 300 Mbps (Download), 50 Mbps (Upload)

DC-HSPA+: 42 Mbps (Download), 5.76 Mbps (Upload)

UMTS: 384Kbps (Download), 384Kbps (Upload)

Maximum output

LTE: 23/24dBm WCDMA: 23.5dBm power Maximum power 2.5A maximum

consumption

Form Factor M.2, 3042-S3 Key B

Weight 5.8 g

Dimensions

(Length x Width x

Thickness)

embedded eSIM Support

1. Mobile Broadband is an optional feature. Connection requires wireless data service contract, network support, and is not available in all areas. Contact service provider to determine the coverage area and availability. Connection speeds will vary due to location, environment, network conditions, and other factors. 4G LTE not available on all products or in all countries.

42 x 30 x 2.3 mm



Realtek RTL8111HSH 10/100/1000 Integrated NIC Connector
System Interface
Data rates supported

RJ-45 PCle + SMBus

10 Mbit/s operation (10BASE-T; IEEE 802.3i; IEEE 802.3 clauses 13-14) 100 Mbit/s operation (100BASE-TX; IEEE 802.3u; IEEE 802.3 clauses 21-

30)

1000 Mbit/s operation (1000BASE-T; IEEE 802.3ab; IEEE 8023 clauses

40)

Auto-Negotiation (Automatic Speed Selection)

Full Duplex Operation at all Speeds, Half Duplex operation at 10 and

100 Mbit/s

IEEE Compliance IEEE 802.1p QoS (Quality of Service) Support

IEEE 802.1q VLAN support

IEEE 802.3x Flow Control (IEEE 802.3 clauses 31-32; configurable)

IEEE 802.3az EEE (Energy Efficient Ethernet)

Performance TCP/IP/UDP Checksum Offload (configurable)

Protocol Offload (ARP & NS)

Large send offload and Giant send offload

Receiving Side Scaling Jumbo Frame 9K

Power consumption Cable Disconnetion: 25mW

100Mbps Full Run: 450mW 1000bp Full Run: 1000mW WoL Enable(S3/S4/S5): 50mW WoL Disable(S3/S4/S5): 25mW

Power ACPI compliant – multiple power modes

Management Situation-sensitive features reduce power consumption

Advanced link down power saving for reducing link down power

consumption

Management Interface Auto MDI/MDIX Crossover cable detection

IT Manageability Wake-on-LAN from modern standby or sleep state (Magic Packet and

Microsoft Wake-Up Frame); Wake-on-LAN from off (Magic Packet only)

PXE 2.1 Remote Boot

Statistics Gathering (SNMP MIB II, Ethernet-like MIB, Ethernet MIB

(802.3x, clause 30))

Comprehensive diagnostic and configuration software suite

Virtual Cable Doctor for Ethernet cable status.



POWER

HP 45W Smart AC adapter

Weight 0.44 lb (200 g) max (Not including power cord. Power cord varies by

country.)

Input 100 ~ 240VAC

Input Efficiency 87.74% at 115Vac and 88.4% at 230Vac

Input frequency range 47 to 63 Hz

Input AC current Max. 1.4 A at 90 VAC

Output

Output power 45W DC output 19.5V

Hold-up time 100% load 5ms at 115 Vac input/80% load 10ms at 115 Vac input

Output current limit <8.0A

Connector 4.5mm Barrel Type.

Environmental Design

Operating temperature 32° to 95° F (0° to 35° C)

Non-operating (storage)

temperature

Altitude 0 to 16,400 ft (0 to 5,000 m)

20% to 95% **Humidity Storage Humidity** 10% to 95%

EMI and Safety CE Mark - full compliance with LVD and EMC directives Certifications

-4° to 185° F (-20° to 85° C)

EN62368-1:2014+A11, UL62368-1

Agency approvals - C-UL-US, TUV/GS, TUV/PSE, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC and CECP, CU(EAC), EAEU, KCC(Safety+EMC) and K-MEPS, NOM-001 and 029 NYCE, NRcan. NRCS, ISC, SEC, PSB, Argentina S-mark, Australia GEMS and RCM, BIS,

Worldwide safety standards - IEC60950-1 and IEC62368-1: 2018,

BSMI, UAE, UKCA DoC

HP 65W EM Smart AC adapter

0.58 lb (265 g) max (Not including power cord. Power cord varies by Weight

country.)

Input 100 ~ 240VAC

Input Efficiency 88 % at 115 Vac and 89 % at 230Vac

Input frequency range 47 to 63 Hz

Input AC current Max. 1.7 A at 90 Vac

Output

65W **Output power** DC output 19.5V

Hold-up time 100% load 5ms at 115 Vac input/80% load 10ms at 115 Vac input

Output current limit < 11.0A

4.5/7.4mm Barrel Type Connector

Environmental Design

Operating temperature 32°F to 95°F (0° to 35°C) Non-operating (storage) -4°F to 185°F (-20° to 85°C)

temperature

Altitude 0 to 16,400 ft (0 to 5000m)

Humidity20% to 95%Storage Humidity10% to 95%

EMI and Safety CE Mark - full compliance with LVD and EMC directives

Certifications Worldwide safety standards - IEC60950-1 and IEC62368-1: 2018,

EN62368-1:2014+A11, UL62368-1

Agency approvals - C-UL-US, TUV/GS, EN55032 Class B, FCC Class B,

CISPR32 Class B, CCC and CECP, BIS, UKCA DoC

HP 45W USB type C Straight 1.8m AC Adapter **Weight** 0.44 lb (200 g) max

(Not including power cord. Power cord varies by country.)

Input 100 ~ 240VAC

Input Efficiency Average Efficiency of 25%, 50%, 75%, 100% load condition with

115Vac/230Vac Spec:

5V:81.5% 9V:86.7% 12V:87.4% 15V:87.8%

Input frequency range 47 ~ 63Hz

Input AC current

Max. 1.4 A at 90 Vac

Output

Output power 5V/15W

9V/27W 12V/36W 15V/45W

DC output 5V/9V/12V/15V

Hold-up time 100% load 5ms at 115 Vac input

Output current limit <5.0A

Connector

Connector USB Type-C

Environmental Design

Operating temperature 32°F to 95°F (0° to 35°C)

Non-operating (storage)

-4°F to 185°F (-20° to 85°C)

temperature

Altitude 0 to 16,400 ft (0 to 5000m)

Humidity20% to 95%Storage Humidity10% to 95%

EMI and Safety Certifications "CE Mark - full compliance with LVD and EMC directives

Worldwide safety standards - IEC60950-1 and IEC62368-1: 2018,

EN62368-1:2014+A11, UL62368-1

Agency approvals - C-UL-US, TUV/GS, TUV/PSE, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC and CECP, CU(EAC), EAEU, KCC(Safety+EMC) and K-MEPS, NOM-001 and 029 NYCE, NRcan, NRCS, ISC, SEC, PSB, Argentina S-mark, Australia RCM, BIS, BSMI, UAE,

UKCA DoC, USB-IF, Ukraine (CoC+DoC+RoHS+ECO)

HP 65W Standard USB-C Straight AC Power Adapter
 Weight
 240g ± 10g

 Input
 100 ~ 240VAC

Input Efficiency 81.50% min at 115 Vac/ 230 Vac @5.00V

86.70% min at 115 Vac/ 230 Vac @9.00V 88.00% min at 115 Vac/ 230 Vac @12.00V 89.00% min at 115 Vac/ 230 Vac @15.00V 89.00% min at 115 Vac/ 230 Vac @20.00V

Input frequency range 47 ~ 63Hz

Input AC current Max. 1.6 A at 90 Vac

Output

Output power 5V/15W

9V/27W 12V/60W 15V/65W 20V/65W

DC output 5V/9V/12V/15V/20V

Hold-up time 100% load 5ms at 115 Vac input

Output current limit <8.0A AC Inlet Type C6

DC Cable Connector DC Cable MaterialUSB type C
Halogen Free

Connector

Connector C6

Environmental Design

Operating temperature 32°F to 95°F (0°to 35°C)

Non-operating (storage)

temperature

Altitude 0 to 16,400 ft (0 to 5000m)

Humidity 20% to 95% **Storage Humidity** 10% to 95%

EMI and Safety CE Mark - full compliance with LVD and EMC directives

Certifications Worldwide safety standards - IEC60950-1 and IEC62368-1 : 2018,

-4°F to 185°F (-20° to 85°C)

EN62368-1:2014+A11, UL 62368-1

Agency approvals - C-UL-US, TUV/GS, TUV/PSE, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC and CECP, CU(EAC), EAEU, KCC(Safety+EMC) and K-MEPS, NOM-001 and 029 NYCE, NRcan, NRCS, ISC, SEC, PSB, Argentina S-mark, Australia RCM, BIS, BSMI, UAE,

UKCA DoC

AN 42Whr¹ Long Life Polymer Fast Charge² 3 cell Battery Cells/Type Energy 3cell Lithium-Ion Polymer cell / 545974

Voltage 11.4V Amp-hour capacity 3.752Ah Watt-hour capacity 42.75Wh

Temperature

Operating (Charging) 32° to 113° F (0° to 45° C)
Operating (Discharging) 14° to 122° F (-10° to 60° C)

Optional Travel Battery No

Available

1. Actual battery Watt-hours (Wh) will vary from design capacity. Battery capacity will naturally decrease with shelf life, time, usage, environment, temperature, system configuration, loaded apps, features, power management settings and other factors.

2. Recharges your battery up to 50% within 30 minutes when the system is off or in standby mode. Power adapter with a minimum capacity of 65 watts is required. After charging has reached 50% capacity, charging will return to normal. Charging time may vary +/-10% due to System tolerance.

AUDIO

HD Stereo Codec Realtek ALC3247

Audio I/O Ports Headset connector supports a CTIA style headset and is re-taskable as a Microphone-in or

Headphone-out port

Internal Speaker AmplifierCodec internal AmplifierMulti-streaming CapableSupport multi-streaming

Sampling Streaming Educate Support Multi-Streaming

Sampling Streams to be sent to/from headset or integrated speaker.

Wavetable Syntheses N/A
Analog Audio N/A
of Channels on Line-Out N/A
Internal Speaker Yes



ENVIRONMENTAL D	ATA					
Eco-Label	This product has received	This product has received or is in the process of being certified to the following approvals and may				
Certifications &	be labeled with one or more of these marks:					
declarations	IT ECO declaration					
	• US ENERGY STAR®					
	 US Federal Energy 	y Management Program (FEN	1P)			
	 EPEAT® Gold regi 	stered in the United States. S	See http://www.epeat.net for registration			
	status in your cou	ıntry.				
	 TCO Certified 					
	 China Energy Con 	servation Program (CECP)				
	China State Envir	onmental Protection Adminis	stration (SEPA)			
	 Taiwan Green Ma 	rk				
	 Korea Eco-label 					
	 Japan PC Green la 	ıbel*				
Sustainable Impact	Ocean-bound plastic in C	PU Fan and Speaker				
Specifications	• 20% post-consumer recy	cled plastic				
	 Low halogen 					
			inably sourced and recyclable			
	-		nably sourced and recyclable			
	Bulk packaging available The first state of the sta					
System Configuration	_	- -	and Declared Noise Emissions data for the			
	Notebook model is based	on a "Typically Configured No	otedook".			
Energy Consumption						
Linergy consumption						
(in accordance with US						
(in accordance with US ENERGY STAR® test						
(in accordance with US ENERGY STAR® test method)	115VAC, 60Hz	230VAC, 50Hz	100VAC, 50Hz			
ENERGY STAR® test	115VAC, 60Hz 3.91 W	230VAC, 50Hz 4.04 W	100VAC, 50Hz 4.13 W			
ENERGY STAR® test method)						
ENERGY STAR® test method) Normal Operation (Sort			· · · · · · · · · · · · · · · · · · ·			
ENERGY STAR® test method) Normal Operation (Sort idle) Normal Operation (Long idle)	3.91 W 0.54 W	4.04 W 0.63 W	4.13 W 0.59 W			
ENERGY STAR® test method) Normal Operation (Sort idle) Normal Operation (Long idle) Sleep	3.91 W 0.54 W 0.54 W	4.04 W 0.63 W 0.63 W	4.13 W 0.59 W 0.59 W			
ENERGY STAR® test method) Normal Operation (Sort idle) Normal Operation (Long idle)	3.91 W 0.54 W	4.04 W 0.63 W	4.13 W 0.59 W			
ENERGY STAR® test method) Normal Operation (Sort idle) Normal Operation (Long idle) Sleep	3.91 W 0.54 W 0.54 W 0.3 W	4.04 W 0.63 W 0.63 W	4.13 W 0.59 W 0.59 W			
ENERGY STAR® test method) Normal Operation (Sort idle) Normal Operation (Long idle) Sleep	3.91 W 0.54 W 0.54 W 0.3 W	4.04 W 0.63 W 0.63 W 0.33 W	4.13 W 0.59 W 0.59 W 0.29 W			
ENERGY STAR® test method) Normal Operation (Sort idle) Normal Operation (Long idle) Sleep	3.91 W 0.54 W 0.54 W 0.3 W NOTE: Energy efficiency data list	4.04 W 0.63 W 0.63 W 0.33 W sed is for an ENERGY STAR®	4.13 W 0.59 W 0.59 W 0.29 W compliant product if offered within the model			
ENERGY STAR® test method) Normal Operation (Sort idle) Normal Operation (Long idle) Sleep	3.91 W 0.54 W 0.54 W 0.3 W NOTE: Energy efficiency data list family. HP computers ma	4.04 W 0.63 W 0.33 W eed is for an ENERGY STAR®	4.13 W 0.59 W 0.29 W compliant product if offered within the model Logo are compliant with the applicable U.S.			
ENERGY STAR® test method) Normal Operation (Sort idle) Normal Operation (Long idle) Sleep	3.91 W 0.54 W 0.54 W 0.3 W NOTE: Energy efficiency data list family. HP computers ma Environmental Protection	4.04 W 0.63 W 0.33 W ed is for an ENERGY STAR® rked with the ENERGY STAR	4.13 W 0.59 W 0.59 W 0.29 W compliant product if offered within the model Logo are compliant with the applicable U.S. AR® specifications for computers. If a model			
ENERGY STAR® test method) Normal Operation (Sort idle) Normal Operation (Long idle) Sleep	3.91 W 0.54 W 0.54 W 0.3 W NOTE: Energy efficiency data list family. HP computers ma Environmental Protection family does not offer ENE	4.04 W 0.63 W 0.33 W 0.84 Steel is for an ENERGY STAR® or an ENERGY STAR® or an ENERGY STAR or an E	4.13 W 0.59 W 0.29 W compliant product if offered within the model Logo are compliant with the applicable U.S. AR® specifications for computers. If a model gurations, then energy efficiency data listed is			
ENERGY STAR® test method) Normal Operation (Sort idle) Normal Operation (Long idle) Sleep	3.91 W 0.54 W 0.54 W 0.3 W NOTE: Energy efficiency data list family. HP computers ma Environmental Protection family does not offer ENE for a typically configured	4.04 W 0.63 W 0.33 W ed is for an ENERGY STAR® rked with the ENERGY STAR Agency (EPA) ENERGY STAR RGY STAR® compliant config	4.13 W 0.59 W 0.59 W 0.29 W compliant product if offered within the model Logo are compliant with the applicable U.S. AR® specifications for computers. If a model			
ENERGY STAR® test method) Normal Operation (Sort idle) Normal Operation (Long idle) Sleep	3.91 W 0.54 W 0.54 W 0.3 W NOTE: Energy efficiency data list family. HP computers ma Environmental Protection family does not offer ENE	4.04 W 0.63 W 0.33 W ed is for an ENERGY STAR® rked with the ENERGY STAR Agency (EPA) ENERGY STAR RGY STAR® compliant config	4.13 W 0.59 W 0.29 W compliant product if offered within the model Logo are compliant with the applicable U.S. AR® specifications for computers. If a model gurations, then energy efficiency data listed is			
ENERGY STAR® test method) Normal Operation (Sort idle) Normal Operation (Long idle) Sleep	3.91 W 0.54 W 0.54 W 0.3 W NOTE: Energy efficiency data list family. HP computers ma Environmental Protection family does not offer ENE for a typically configured	4.04 W 0.63 W 0.33 W ed is for an ENERGY STAR® rked with the ENERGY STAR Agency (EPA) ENERGY STAR RGY STAR® compliant config	4.13 W 0.59 W 0.29 W compliant product if offered within the model Logo are compliant with the applicable U.S. AR® specifications for computers. If a model gurations, then energy efficiency data listed is			
ENERGY STAR® test method) Normal Operation (Sort idle) Normal Operation (Long idle) Sleep Off	3.91 W 0.54 W 0.54 W 0.3 W NOTE: Energy efficiency data list family. HP computers ma Environmental Protection family does not offer ENE for a typically configured Microsoft Windows® operation	4.04 W 0.63 W 0.33 W ed is for an ENERGY STAR® rked with the ENERGY STAR Agency (EPA) ENERGY STAR RGY STAR® compliant configured for the system.	4.13 W 0.59 W 0.29 W compliant product if offered within the model Logo are compliant with the applicable U.S. AR® specifications for computers. If a model gurations, then energy efficiency data listed is drive, a high efficiency power supply, and a			
ENERGY STAR® test method) Normal Operation (Sort idle) Normal Operation (Long idle) Sleep Off Heat Dissipation*	3.91 W 0.54 W 0.54 W 0.3 W NOTE: Energy efficiency data list family. HP computers ma Environmental Protection family does not offer ENE for a typically configured Microsoft Windows® operation	4.04 W 0.63 W 0.33 W ed is for an ENERGY STAR® rked with the ENERGY STAR Agency (EPA) ENERGY STAR RGY STAR® compliant configured for the system.	4.13 W 0.59 W 0.29 W compliant product if offered within the model Logo are compliant with the applicable U.S. AR® specifications for computers. If a model gurations, then energy efficiency data listed is drive, a high efficiency power supply, and a			
ENERGY STAR® test method) Normal Operation (Sort idle) Normal Operation (Long idle) Sleep Off Heat Dissipation* Normal Operation	3.91 W 0.54 W 0.54 W 0.3 W NOTE: Energy efficiency data list family. HP computers ma Environmental Protection family does not offer ENE for a typically configured Microsoft Windows® operations.	4.04 W 0.63 W 0.33 W eed is for an ENERGY STAR® rked with the ENERGY STAR Agency (EPA) ENERGY STAR RGY STAR® compliant configured by the complement of th	4.13 W 0.59 W 0.29 W compliant product if offered within the model Logo are compliant with the applicable U.S. AR® specifications for computers. If a model gurations, then energy efficiency data listed is drive, a high efficiency power supply, and a			
ENERGY STAR® test method) Normal Operation (Sort idle) Normal Operation (Long idle) Sleep Off Heat Dissipation* Normal Operation (Short idle)	3.91 W 0.54 W 0.54 W 0.3 W NOTE: Energy efficiency data list family. HP computers ma Environmental Protection family does not offer ENE for a typically configured Microsoft Windows® operations.	4.04 W 0.63 W 0.33 W eed is for an ENERGY STAR® rked with the ENERGY STAR Agency (EPA) ENERGY STAR RGY STAR® compliant configured by the complement of th	4.13 W 0.59 W 0.29 W compliant product if offered within the model Logo are compliant with the applicable U.S. AR® specifications for computers. If a model gurations, then energy efficiency data listed is drive, a high efficiency power supply, and a			



Off

1.1 BTU/hr

1.0 BTU/hr

1.0 BTU/hr



	*NOTE: Heat attained for	dissipation is calculated base one hour.	d on the measured watts,	assuming the service level is
Declared Noise		Sound Power	Sound F	Pressure
Emissions		(L _{WAd} , bels)		ecibels)
(in accordance with		(=ima, = ===,	(- -	,
ISO 7779 and ISO 9296)				
Typically Configured — Idle		1.3	1!	5.6
Fixed Disk – Random writes		1.3	14	4.2
Optical Drive – Sequential reads		1.3	14	4.3
Longevity and	This product	can be upgraded, possibly exte	nding its useful life by seve	ral years. Upgradeable
Upgrading	features and	or components contained in th	е	
	production.	re available throughout the wa		
Additional Information	dire This (WE This Drin This www Plas	product is in compliance with to ctive - 2011/65/EC. HP product is designed to compliance with Compliance with Compliance with Compliance with Compliance with Compliance with the compli	oly with the Waste Electrica alifornia Proposition 65 (St ent Act of 1986). he IEEE 1680 (EPEAT) stand	al and Electronic Equipment sate of California; Safe dard at the Gold level, see marked per ISO11469 and
Packaging Materials	External:	PAPER/Corrugated		191 g
		PAPER/Corrugated		44 g
		PAPER/Molded Pulp		42 g
		PAPER/Paper		2 g
	Internal:	PLASTIC/Polyethylene low de	ensity - LDPE	13 g
	The plastic	packaging material contains at l	east 0.0% recycled content	t.
	The corrugated paper packaging materials contains at least 53.6% recycled content.			
RoHS Compliance	HP Inc. complies fully with materials regulations. We were among the first companies to extend the			
	restrictions in the European Union (EU) Restriction of Hazardous Substances (RoHS) Directive to our			
	products worldwide through the HP GSE. HP has contributed to the development of related			
	_	Europe, as well as China, India,		
			ws play an important role in promoting industry-wide	
		f substances of concern. We ha		
	including PVC, BFRs, and certain phthalates—in future RoHS legislation that pertains to electrical			
	and electronics products.			
	We met our \	oluntary objective to achieve w	orldwide compliance with t	the new EU RoHS



	requirements for virtually all relevant products by July 2013, and we will continue to extend the scope of the commitment to include further restricted substances as regulations continue to evolve. To obtain a copy of the HP RoHS Compliance Statement, see HP RoHS position statement.
Material Usage	This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at http://www.hp.com/hpinfo/globalcitizenship/environment/supplychain/gen_specifications.html): • Asbestos • Certain Azo Colorants • Certain Brominated Flame Retardants – may not be used as flame retardants in plastics • Cadmium • Chlorinated Hydrocarbons • Chlorinated Paraffins • Bis(2-Ethylhexyl) phthalate (DEHP) • Benzyl butyl phthalate (DBP) • Dibutyl phthalate (DBP) • Diisobutyl phthalate (DBP) • Diisobutyl phthalate (DBP) • Formaldehyde • Halogenated Diphenyl Methanes • Lead carbonates and sulfates • Lead and Lead compounds • Mercuric Oxide Batteries • Nickel – finishes must not be used on the external surface designed to be frequently handled or carried by the user. • Ozone Depleting Substances • Polybrominated Biphenyls (PBBs) • Polybrominated Biphenyls (PBBs) • Polybrominated Biphenyl (PCB) • Polychlorinated Biphenyl (PCB) • Polychlorinated Biphenyl (PCB) • Polychlorinated Terphenyls (PCT) • Polyvinyl Chloride (PVC) – except for wires and cables, and certain retail packaging has been voluntarily removed from most applications. • Radioactive Substances • Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)
Packaging Usage	 HP follows these guidelines to decrease the environmental impact of product packaging: Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials. Eliminate the use of ozone-depleting substances (ODS) in packaging materials. Design packaging materials for ease of disassembly. Maximize the use of post-consumer recycled content materials in packaging materials. Use readily recyclable packaging materials such as paper and corrugated materials. Reduce size and weight of packages to improve transportation fuel efficiency. Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.

End-of-life	HP offers end-of-life HP product return and recycling programs in many geographic areas. To recycle			
Management and	your product, please go to: http://www.hp.com/go/reuse-recycle or contact your nearest HP sales			
Recycling	office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.			
	The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: http://www.hp.com/go/recyclers . These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.			
HP, Inc. Corporate	For more information about HP's commitment to the environment:			
Environmental				
Information	Global Citizenship Report			
	http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html			
	Eco-label certifications			
	http://www8.hp.com/us/en/hp-information/environment/ecolabels.html			
	ISO 14001 certificates:			
	http://h20195.www2.hp.com/V2/GetDocument.aspx?docname=c04755842 and			
	http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf			
footnotes	 Percentage of ocean-bound plastic contained in each component varies by product Recycled plastic content percentage is based on the definition set in the IEEE 1680.1-2018 standard. 			
	 External power supplies, WWAN modules, power cords, cables and peripherals excluded. 100% outer box packaging and corrugated cushions made from sustainably sourced certified and recycled fibers. 			
	 Fiber cushions made from 100% recycled wood fiber and organic materials. Plastic cushions are made from >90% recycled plastic. 			



Options and Accessories (sold separately and availability may vary by country)

DOCKING (Sold Separately)

Docking station model #1 HP USB-C Dock G5

Total number of supported displays

(incl. the notebook display)

Max. resolutions supported Dual 5K@ 30Hz + 4K UHD (multi-function mode)

3

Dock Connectors 1xHDMI, 2xDP

Technical limitations Maximum resolution and display support is dependent on the maximum

capability of the notebook.

Highest resolution with dual displays is two 8K@ 60Hz host in High Resolution

mode

3

Three maximum displays supported are two 5K@ 30 Hz on DP ports plus one

4K UHD@ 30 Hz on HDMI in Multi-function mode

The highest resolution for a non-Thunderbolt host in Multi-function mode is a

single 5K dual cable (using both DP ports) + (1) 4K on HDMI port.

Docking station model #2 HP USB-C/A Universal Dock G2

Total number of supported displays

(incl. the notebook display)

Max. resolutions supported Triple 4K UHD@ 60Hz

Dock Connectors 1xHDMI, 2xDP

Technical limitations Maximum resolution and display support is dependent on the maximum

capability of the notebook.

The best resolution for dual or triple displays is 4K UHD@ 60Hz.

For use with the USB-A adapter that comes in the box the maximum number of displays supported is (2) 4k x 60 Hz on the Type-A Gen 1 connection from

the host.

3

Docking station model #3 HP USB-C G5 Essential Dock

Total number of supported displays

(incl. the notebook display)
Max. resolutions supported

For hosts that support DisplayPort 1.4 with Display Stream Compression:

3x FHD @ 60 Hz 3x QHD @ 60 Hz 3x 4K @ 60 Hz

For hosts that support DisplayPort 1.3/1.4:

3x FHD @ 60 Hz 3x QHD @ 60 Hz 2x 4K @ 60 Hz

Dock Connectors 1 x HDMI, 2 x DP

Technical limitations Video resolution depends on the capability of the host machine. This dock

provides up to 65W of power delivery to the host machine.

Category	Description	Part Number
Audio	HP Wired USB-A Stereo Headset	428K6AA,428K6PT#ACJ
	Poly Voyager Free 60 Carbon Black Earbuds +Basic Charge Case	7Y8M2AA
	Poly Voyager Free 60 UC Black Earbuds +BT700 USB-C Adapter +Basic Charge	
	Case	7Y8M0AA
	Poly Voyager Free 60 UC Carbon Black Earbuds +BT700 USB-C Adapter +Basic	71/01/444
	Charge Case Poly Voyager Free 60 UC M Carbon Black Farbuds (BT700 UCB C Adaptor	7Y8H4AA
	Poly Voyager Free 60 UC M Carbon Black Earbuds +BT700 USB-C Adapter +Basic Charge Case	7Y8L8AA
	Poly Voyager Free 60+ UC Carbon Black Earbuds +BT700 USB-C Adapter	/ TOLONA
	+Touchscreen Charge Case	7Y8G4AA,7Y8H2AA
	Poly Voyager Free 60+ UC M Carbon Black Earbuds +BT700 USB-C Adapter	,
	+Touchscreen Charge Case	7Y8H0AA
	Poly Blackwire 3210 Monaural USB-C Headset +USB-C/A Adapter	8X214AA
	Poly Blackwire 3215 Monaural USB-C Headset +3.5mm Plug +USB-C/A	
	Adapter	8X227AA
	Poly Blackwire 3220 Stereo USB-C Headset +USB-C/A Adapter	93S87AA,8X228AA
	Poly Blackwire 3310 Monaural Microsoft Teams Certified USB-C Headset	01/24.54.4
	+USB-C/A Adapter	8X216AA
	Poly Blackwire 3310 Monaural USB-C Headset +USB-C/A Adapter	8X215AA
	Poly Blackwire 3315 Monaural Microsoft Teams Certified USB-C Headset +3.5mm Plug +USB-C/A Adapter	8X218AA
	Poly Blackwire 3315 Monaural USB-C Headset +3.5mm Plug +USB-C/A	ONZTORA
	Adapter	8X217AA
	Poly Blackwire 3320 Stereo Microsoft Teams Certified USB-C Headset +USB-	
	C/A Adapter	8X220AA
	Poly Blackwire 3320 Stereo USB-C Headset +USB-C/A Adapter	8X219AA
	Poly Blackwire 3325 Stereo Microsoft Teams Certified USB-C Headset	
	+3.5mm Plug +USB-C/A Adapter	8X222AA
	Poly Blackwire 3325 Stereo USB-C Headset +3.5mm Plug +USB-C/A Adapter	8X221AA
	Poly Blackwire 5210 Monaural USB-C Headset +3.5mm Plug +USB-C/A	
	Adapter	8X230AA
	Poly Blackwire 5220 Stereo USB-C Headset +3.5mm Plug +USB-C/A Adapter	8X231AA,93S88AA
	Poly Blackwire 8225 Stereo Microsoft Teams Certified USB-C Headset +USB-	8X225AA
	C/A Adapter Poly Blackwire 8225 Stereo USB-C Headset +USB-C/A Adapter	8X223AA
	Poly EncorePro 310 Monaural USB-A Headset	767G1AA
	•	77T43AA
	Poly EncorePro 310 Monoaural with Quick Disconnect Headset Poly EncorePro 310 USB-C Monoaural Headset	
	•	760Q8AA 767G0AA
	Poly EncorePro 320 Stereo USB-A Headset	
	Poly EncorePro 320 Stereo USB-C Headset	767F9AA
	Poly EncorePro 320 with Quick Disconnect Binaural Headset	77T26AA
	Poly EncorePro 510 Monaural Headset +Quick Disconnect Poly EncorePro 515 Microsoft Teams Certified Monoaural with USB-A	783Q2AA
	Headset	783R1AA
	Poly EncorePro 515 Monoaural with USB-A Headset	783R0AA
	Poly EncorePro 520 Binaural Headset +Quick Disconnect	783P7AA
	Poly EncorePro 525 Microsoft Teams Certified Stereo with USB-A Headset	783R2AA
	roty Encorer to 323 microsoft reams certified Stereo with 030-A fieduset	/OSRZAA



Poly EncorePro 525 USB-A Stereo Headset	783R3AA
Poly EncorePro 530 Headset +Quick Disconnect	783P3AA
Poly EncorePro 540 Convertible Headset +Quick Disconnect	783P1AA
Poly EncorePro 715 USB-A Monoaural Headset	783N5AA
Poly EncorePro 720 Binaural Headset +Quick Disconnect	8R707AA
Poly EncorePro 725 USB-A Stereo Headset	783M6AA
Poly EncorePro HW710 Single Ear Headset +Carry Case +Quick Disconnect	8R708AA
Poly Savi 7210 Office DECT 1880-1900 MHz Single Ear Headset (EMEA + APJ)	8D3G9AA
Poly Savi 7210 Office DECT 1920-1930 MHz Single Ear Headset (NA)	7W6D4AA
Poly Savi 7220 Office Binaural DECT 1880-1900 MHz Headset (EMEA + APJ)	8D3G8AA
Poly Savi 7220 Office Binaural DECT 1920-1930 MHz Headset (NA)	7W6D5AA
Poly Savi 7310 Office DECT 1880-1900 MHz Single Ear Headset (EMEA + APJ)	8D3G3AA
Poly Savi 7310 Office DECT 1910-1920 MHz Single Ear Headset (NA)	8D3G5AA
Poly Savi 7310 Office Monaural DECT 1920-1930 MHz Headset (NA)	7S430AA
Poly Savi 7310 UC Monaural DECT 1880-1900 MHz Headset (EMEA + APJ)	8L561AA
Poly Savi 7310 UC Monaural DECT 1893-1906 MHz Headset (Japan)	8L565AA
Poly Savi 7310 UC Monaural DECT 1910-1920 MHz Headset (NA)	8L566AA
Poly Savi 7310 UC Monaural DECT 1920-1930 MHz Headset (NA)	8L570AA
Poly Savi 7310 UC Monaural Microsoft Teams Certified DECT 1880-1900 MHz	0237 07171
Headset (EMEA + APJ)	8L575AA
Poly Savi 7310 UC Monaural Microsoft Teams Certified DECT 1893-1906 MHz	
Headset (Japan)	8L578AA
Poly Savi 7310 UC Monaural Microsoft Teams Certified DECT 1910-1920 MHz	
Headset (NA)	8L581AA
Poly Savi 7310 UC Monaural Microsoft Teams Certified DECT 1920-1930 MHz	
Headset (NA) Poly Savi 7310-M Office DECT 1880-1900 MHz Single Ear Headset (EMEA +	8L585AA
APJ)	8D3K7AA
Poly Savi 7310-M Office DECT 1893-1906 MHz Single Ear Headset (Japan)	8D3K9AA
Poly Savi 7310-M Office DECT 1910-1920 MHz Single Ear Headset (NA)	8D3L0AA
Poly Savi 7310-M Office DECT 1920-1930 MHz Single Ear Headset (NA)	7S439AA
Poly Savi 7320 Office Stereo DECT 1880-1900 MHz Headset (EMEA + APJ)	8D3F7AA
Poly Savi 7320 Office Stereo DECT 1893-1906 MHz Headset (Japan)	8D3F8AA
Poly Savi 7320 Office Stereo DECT 1910-1920 MHz Headset (NA)	8D3G0AA
Poly Savi 7320 Office Stereo DECT 1920-1930 MHz Headset (NA)	7S429AA
Poly Savi 7320 UC Stereo DECT 1880-1900 MHz Headset (EMEA + APJ)	8L545AA
Poly Savi 7320 UC Stereo DECT 1893-1906 MHz Headset (Japan)	8L546AA
Poly Savi 7320 UC Stereo DECT 1910-1920 MHz Headset (NA)	8L548AA
Poly Savi 7320 UC Stereo DECT 1920-1930 MHz Headset (NA)	8L549AA
Poly Savi 7320 UC Stereo Microsoft Teams Certified DECT 1880-1900 MHz	OLJ4JAA
Headset (EMEA + APJ)	8L553AA
Poly Savi 7320 UC Stereo Microsoft Teams Certified DECT 1893-1906 MHz	
Headset (Japan)	8L555AA
Poly Savi 7320 UC Stereo Microsoft Teams Certified DECT 1910-1920 MHz	
Headset (NA)	8L557AA
Poly Savi 7320 UC Stereo Microsoft Teams Certified DECT 1920-1930 MHz	01 === : :
Headset (NA)	8L559AA



Poly Savi 7320-M Office Stereo DECT 1880-1900 MHz Headset (EMEA + APJ)	8D3J6AA
Poly Savi 7320-M Office Stereo DECT 1893-1906 MHz Headset (Japan)	8D3K2AA
Poly Savi 7320-M Office Stereo DECT 1910-1920 MHz Headset (NA)	8D3K0AA
Poly Savi 7320-M Office Stereo DECT 1920-1930 MHz Headset (NA)	7S435AA
Poly Savi 7410 Office Monaural DECT 1880-1900 MHz Headset (EMEA + APJ)	8L589AA
Poly Savi 7410 Office Monaural DECT 1893-1906 MHz Headset (Japan)	8L591AA
Poly Savi 7410 Office Monaural DECT 1910-1920 MHz Headset (NA)	8L592AA
Poly Savi 7410 Office Monaural DECT 1920-1930 MHz Headset (NA)	8L7D5AA
Poly Savi 7410 Office Monaural Microsoft Teams Certified DECT 1880-1900	
MHz Headset (EMEA + APJ)	8L593AA
Poly Savi 7410 Office Monaural Microsoft Teams Certified DECT 1893-1906	01.50.44.4
MHz Headset (Japan)	8L594AA
Poly Savi 7410 Office Monaural Microsoft Teams Certified DECT 1910-1920 MHz Headset (NA)	8L597AA
Poly Savi 7410 Office Monaural Microsoft Teams Certified DECT 1920-1930	OLJSTAA
MHz Headset (NA)	8L7D7AA
Poly Savi 7420 Office Stereo DECT 1880-1900 MHz Headset (EMEA + APJ)	8L560AA
Poly Savi 7420 Office Stereo DECT 1893-1906 MHz Headset (Japan)	8L563AA
Poly Savi 7420 Office Stereo DECT 1910-1920 MHz Headset (NA)	8L564AA
Poly Savi 7420 Office Stereo DECT 1920-1930 MHz Headset (NA)	8L567AA
Poly Savi 7420 Office Stereo Microsoft Teams Certified DECT 1880-1900 MHz	olsonin'
Headset (EMEA + APJ)	8L574AA
Poly Savi 7420 Office Stereo Microsoft Teams Certified DECT 1893-1906 MHz	
Headset (Japan)	8L576AA
Poly Savi 7420 Office Stereo Microsoft Teams Certified DECT 1910-1920 MHz	
Headset (NA)	8L579AA
Poly Savi 7420 Office Stereo Microsoft Teams Certified DECT 1920-1930 MHz	01.502.4.4
Headset (NA)	8L583AA
Poly Savi 8210 Office DECT 1880-1890 MHz Single Ear Headset (EMEA + APJ)	8D3K3AA
Poly Savi 8210 Office DECT 1880-1900 MHz Single Ear Headset (EMEA + APJ)	8D3K5AA
Poly Savi 8210 Office DECT 1910-1920 MHz Single Ear Headset (NA)	8D3K6AA
Poly Savi 8210 Office DECT 1920-1930 MHz Single Ear Headset (NA)	7S445AA
Poly Savi 8210 UC DECT 1880-1900 MHz USB-A Headset (EMEA + APJ)	8D3E9AA
Poly Savi 8210 UC DECT 1920-1930 MHz USB-A Headset (NA)	77T29AA
Poly Savi 8210 UC Microsoft Teams Certified DECT 1880-1900 MHz USB-A	0025144
Headset (EMEA + APJ) Poly Savi 8210 UC Microsoft Teams Certified DECT 1920-1930 MHz USB-A	8D3F1AA
Headset (NA)	77T31AA
Poly Savi 8210-M Office DECT 1880-1900 MHz Single Ear Headset (EMEA +	// IJIM
APJ)	8D3J8AA
Poly Savi 8210-M Office DECT 1910-1920 MHz Single Ear Headset (NA)	8D3K1AA
Poly Savi 8210-M Office DECT 1920-1930 MHz Single Ear Headset (NA)	7S447AA
Poly Savi 8220 Office Stereo DECT 1880-1890 MHz Headset (EMEA + APJ)	8D3J1AA
Poly Savi 8220 Office Stereo DECT 1880-1900 MHz Headset (EMEA + APJ)	8D3J2AA
Poly Savi 8220 Office Stereo DECT 1910-1920 MHz Headset (NA)	8D3J4AA
Poly Savi 8220 Office Stereo DECT 1920-1930 MHz Headset (NA)	7S4B5AA
Poly Savi 8220 Stereo DECT 1880-1900 MHz Top +Charging Cradle (EMEA +	8Y9C4AA
Toty Javi Deed Stered Deet 1000-1300 mile top "Charging Craute (LMEA *	OTECHA



Options and Accessories (sold separately and availability may vary by country)

APJ) Poly Savi 8220 UC DECT 1880-1900 MHz USB-A Headset (EMEA + APJ) 8D3F2AA Poly Savi 8220 UC DECT 1920-1930 MHz USB-A Headset (NA) 77T33AA Poly Savi 8220 UC Microsoft Teams Certified DECT 1880-1900 MHz USB-A Headset (EMEA + APJ) 8D3F5AA Poly Savi 8220 UC Microsoft Teams Certified DECT 1920-1930 MHz USB-A Headset (NA) 77Y82AA Poly Savi 8220-M Office Stereo DECT 1880-1900 MHz Headset (EMEA + APJ) 8D3H8AA Poly Savi 8220-M Office Stereo DECT 1910-1920 MHz Headset (NA) 8D3J0AA Poly Savi 8220-M Office Stereo DECT 1920-1930 MHz Headset (NA) 7S4B6AA Poly Savi 8245 DECT 1880-1900 MHz Headset +USB-A to USB-C Cable +D400 (EMEA + APJ) 8D3H2AA Poly Savi 8245 Office DECT 1880-1900 MHz USB-A Headset (EMEA + APJ) 8D3H1AA Poly Savi 8245 Office DECT 1910-1920 MHz USB-A Headset (NA) 8Q005AA Polv Savi 8245 Office DECT 1920-1930 MHz USB-A Headset (NA) 7W6D1AA Poly Savi 8245-M Microsoft Teams Certified DECT 1880-1900 MHz USB-A Headset +D200 (EMEA + APJ) 8D3F4AA Poly Savi 8245-M Office Microsoft Teams Certified DECT 1880-1900 MHz USB-A Headset (EMEA + APJ) 8D3H7AA Poly Savi 8245-M Office Microsoft Teams Certified DECT 1910-1920 MHz **USB-A Headset (NA)** 8Q006AA Poly Savi 8245-M Office Microsoft Teams Certified DECT 1920-1930 MHz **USB-A Headset (NA)** 7W069AA Poly Savi 8410 Office Monaural DECT 1880-1900 MHz Headset (EMEA + APJ) **8L5A7AA** Poly Savi 8410 Office Monaural DECT 1920-1930 MHz Headset (NA) 8L7E6AA Poly Savi 8410 Office Monaural Microsoft Teams Certified DECT 1880-1900 MHz Headset (EMEA + APJ) 8L5A9AA Poly Savi 8410 Office Monaural Microsoft Teams Certified DECT 1920-1930 MHz Headset (NA) 8L7E9AA Poly Savi 8420 Office Stereo DECT 1880-1900 MHz Headset (EMEA + APJ) 8L5B2AA Poly Savi 8420 Office Stereo DECT 1920-1930 MHz Headset (NA) 8L7F2AA Poly Savi 8420 Office Stereo Microsoft Teams Certified DECT 1880-1900 MHz Headset (EMEA + APJ) 8L5B3AA Poly Savi 8420 Office Stereo Microsoft Teams Certified DECT 1920-1930 MHz Headset (NA) 8L7F5AA Poly Savi 8445 Office DECT 1880-1900 MHz Convertible Headset (EMEA + APJ) 8L5B4AA Poly Savi 8445 Office DECT 1910-1920 MHz Convertible Headset (NA) 8L5B5AA Poly Savi 8445 Office DECT 1920-1930 MHz Convertible Headset (NA) 8L7F8AA Poly Savi 8445 Office Microsoft Teams Certified DECT 1880-1890 MHz Convertible Headset (EMEA + APJ) 8L5B7AA Poly Savi 8445 Office Microsoft Teams Certified DECT 1880-1900 MHz Convertible Headset (EMEA + APJ) 8L5B6AA Poly Savi 8445 Office Microsoft Teams Certified DECT 1910-1920 MHz Convertible Headset (NA) 8L5B8AA Poly Savi 8445 Office Microsoft Teams Certified DECT 1920-1930 MHz Convertible Headset (NA) 8L7F1AA



Poly Voyager 4310 Microsoft Teams Certified Headset +BT700 dongle

77Y93AA

Options and Accessories (sold separately and availability may vary by country)

Accessories (Solu Separalely and availability may v	ary by country)
+Charging Stand	
Poly Voyager 4310 Microsoft Teams Certified USB-A Headset +BT700 dongle	77Y91AA
Poly Voyager 4310 Microsoft Teams Certified USB-C Headset +BT700 dongle	77Y95AA
Poly Voyager 4310 UC Monaural Headset +BT700 USB-A Adapter +Charging	
Stand	77Y92AA
Poly Voyager 4310 USB-A Headset +BT700 dongle	76U48AA
Poly Voyager 4310 USB-C Headset +BT700 dongle +Charging Stand	77Y96AA
Poly Voyager 4310 USB-C Headset +BT700 dongle	77Y94AA
Poly Voyager 4310-M Microsoft Teams Certified USB-C Headset +BT700	771/07 4 4
dongle +Charging Stand	77Y97AA
Poly Voyager 4310-M UC Headset +USB-A to USB-C Cable +BT700 dongle Poly Voyager 4320 Microsoft Teams Certified Headset +BT700 dongle	7Y210AA
+Charging Stand	77Z00AA
Poly Voyager 4320 Microsoft Teams Certified USB-A Headset +BT700 dongle	77299AA 77Y98AA
Poly Voyager 4320 Microsoft Teams Certified USB-C Headset +BT700 dongle	77730AA 77Z30AA
Poly Voyager 4320 UC Stereo USB-A Headset +BT700 USB-A Adapter	77230AA
+Charging Stand	77Y99AA
Poly Voyager 4320 USB-A Headset +BT700 dongle	76U49AA
Poly Voyager 4320 USB-C Headset +BT700 dongle +Charging Stand	77Z31AA
Poly Voyager 4320 USB-C Headset +BT700 dongle	76U50AA
Poly Voyager 4320-M +USB-A to USB-C Cable +BT700 dongle	7Y211AA
Poly Voyager 4320-M Microsoft Teams Certified Headset +BT700 dongle	
+Charging Stand	77Z32AA
Poly Voyager Focus 2 Microsoft Teams Certified USB-C-C Headset +USB-C/A	
Adapter +Charging Stand	9T9J6AA
Poly Voyager Focus 2 USB-C-C Headset +USB-C/A Adapter	9T9J3AA
Poly Voyager Focus 2 USB-C-C Headset +USB-C/A Adapter +Charging Stand	9T9J5AA
Poly Voyager Surround 80 UC Microsoft Teams Certified USB-C Black Headset	00.45344
+USB-C/A Adapter Poly Voyager Surround 80 UC Microsoft Teams Certified USB-C Headset	9D452AA
+USB-C/A Adapter	8H2G3AA,8G7U0AA
Poly Voyager Surround 80 UC Microsoft Teams Certified USB-C Headset	OHZOSAN,OOT OOAN
+USB-C/A Adapter Demo	9C6W5AA
Poly Voyager Surround 80 UC USB-C Headset +USB-C/A Adapter	8G7T9AA
Poly Voyager Surround 85 UC Microsoft Teams Certified USB-C Headset	
+USB-C/A Adapter +Charging Stand	8G7T8AA
Poly Voyager Surround 85 UC USB-C Headset +USB-C/A Adapter +Charging	
Stand	8G7T7AA
Poly Sync 10 Microsoft Teams Certified Speakerphone	77P34AA
Poly Sync 10 Speakerphone +USB-A to USB-C Cable	7S4M6AA
Poly Sync 10 USB-A USB-C Speakerphone	772C3AA
Poly Sync 20 Microsoft Teams Certified USB-A Speakerphone	772C8AA
Poly Sync 20 USB-A Speakerphone	772D2AA
Poly Sync 20 USB-C Speakerphone	7F0J7AA
Poly Sync 20+ Microsoft Teams Certified USB-A Speakerphone	772C9AA
Poly Sync 20+ Microsoft Teams Certified USB-C Speakerphone	772D1AA
	7776644



Poly Sync 20+ USB-A Speakerphone

772C6AA

- p	, , , , , , , , , , , , , , , , , , ,	, , ,		
	Poly Sync 20+ USB-C Speakerphone	772D0AA		
	Poly Sync 20+M Speakerphone +USB-A to USB-C Cable +BT700 dongle +Pouch	7Y215AA		
	Poly Sync 20-M Microsoft Teams Certified USB-C Speakerphone	7FOJ8AA		
		754M1AA		
	Poly Sync 20-M Speakerphone +USB-A to USB-C Cable			
	Poly Sync 40 Microsoft Teams Certified Speakerphone Poly Sync 40 USB-A USB-C Speakerphone	77P35AA 772C4AA		
	Poly Sync 40+ Microsoft Teams Certified USB-A USB-C Speakerphone +BT700	772C4AA		
	USB-A Adapter	77P36AA		
	Poly Sync 40+ USB-A USB-C Speakerphone +BT700 USB-A Adapter	772C5AA		
	Poly Sync 60 Microsoft Teams Certified Speakerphone	77P41AA		
	Poly Sync 60 Speakerphone	772C2AA		
Video	HP 325 FHD USB-A Webcam	53X27AA		
	HP 625 FHD Webcam	6Y7L1AA		
Cases	HP 14 Convertible Laptop Backpack Tote	9C2H1AA		
	HP 14 Modular Laptop Sleeve	9J499AA		
	HP 15.6 Modular Laptop Backpack	9J496AA		
	HP 15.6 Modular Laptop Bag	9J497AA		
	HP 15.6 Modular Laptop Sleeve	9J498AA		
	HP Convertible Laptop Stand	9C2H2AA		
	HP Mobility 14 Laptop Case	4U9G9AA		
	HP Prelude 15.6 Top Load	1E7D7AA,50P31AA		
	HP Prelude 15.6 Backpack	1E7D6AA,1E7D6UT,50P32AA		
	HP Prelude Pro Recycled 15.6 Backpack	1X644AA		
	HP Prelude Pro Recycled 15.6 Top Load	1X645AA		
	HP Renew Business 14.1 Laptop Bag	3E5F9AA		
	HP Renew Business 14.1 Laptop Sleeve	3E2U7AA		
	HP Renew Business 15.6 Laptop Bag	3E5F8AA		
	HP Renew Business 17.3 Laptop Backpack	3E2U5AA		
	HP Renew Business 17.3 Laptop Bag	3E2U6AA		
	HP Renew Executive 14.1 Laptop Sleeve	6B8Y3AA		
	HP Renew Executive 16 Laptop Backpack	6B8Y2AA		
	HP Renew Executive 16 Laptop Bag	6B8Y1AA,6B8Y1UT		
	HP Travel 18L 15.6 Iron Gray Laptop Backpack	6H2D9AA		
	HP Travel 25L 15.6 Iron Gray Laptop Backpack	6H2D8AA		
Docking	UD USD 6420W SS D. J.	mm1.14 c		
Docking	HP USB-C 120W G5 Dock	5TW10AA		
	HP USB-C/A 120W G2 Universal Dock	5TW13AA		
Digital Pen	HP 705 RECHBL Multi Pen	93Z28AA		
-	HP Slim RECHBL Pen	630W7AA		



Options and Accessories (sold separately and availability may vary by country)

Pen Accessory HP Rechargeable Slim Pen Charger 4X491AA

Hub HP 4K USB-C Multiport Hub 6G842AA,6G843UT

HP Universal USB-C Multiport Hub 50H55UT, 50H55PT#ACJ

HP USB-C to USB-A Hub Z6A00AA

HP USB-C Travel Hub G3 86S97AA,86S97UT

HP Universal USB-C Hub and Laptop Charger Combo 9HOH9AA

Adapter HP USB-C to RJ45 Adapter G2 4Z527AA

HP USB 3.0 to Gigabit RJ45 Adapter G2 4Z7Z7AA

HP HDMI to VGA Adapter

HP USB-C to DisplayPort Adapter G2

8Y8Y1AA

HP USB-C to HDMI 2.0 Adapter 1WC36AA
HP USB-C to USB 3.0 Adapter N2Z63AA

HP USB-C to VGA Adapter N9K76AA

Keyboard/Combo HP 125 Wired USB Keyboard 266C9AA

HP 225 Wireless Keyboard 805T1AA, 805T1UT
HP 320K WD USB Keyboard 9SR37AA, 9SR37UT
HP 325 Chrome BT Keyboard 45U14AA

HP 355 Compact Multi-Device BT Keyboard 692S9AA

HP 405 Multi-Device Wired Backlit Keyboard 7N7C1AA, 7N7C1UT

HP 435 Programmable BT Keypad 7N7C3AA

HP 455 Wireless Programmable USB Keyboard 4R177AA

HP 475 Dual-Mode Keyboard 7N7B9AA, 7N7B9UT
HP 225 Antimicrobial Wired Mouse and Keyboard Combo 286K3AA

HP 225 Wired Mouse and Keyboard Combo 286J4AA

HP 225 Wired Mouse and Keyboard Combo Cashmere White 86J24AA

HP 235 Wireless Mouse and Keyboard Combo 1Y4D0UT

HP 655 Wireless Keyboard and Mouse Combo

4R009AA, 4R009UT

HP Wired Desktop 320MK Mouse and Keyboard

9SR36AA, 9SR36UT

MouseHP 105 Sanitizable Mouse Pad8X595AAHP 125 USB-A Wired Mouse265A9AT,265A9UT

HP 128 USB Laser Wired Mouse 265D9AA
HP 205 Sanitizable Desk Mat 8X597AA
HP 320M USB-A Wired Mouse 9VA80AA

HP 425 Programmable Bluetooth Wireless Mouse 7M1D5AA

HP 695 Qi-Charging Bluetooth Wireless Mouse 8F1Y4AA

HP 715 Rechargeable Multi-Device Bluetooth 5.0 + Wireless 2.4GHz Bluetooth Mouse

Power HP 65W 4.5 mm Smart AC Power Adapter H6Y89AA

HP 65W USB-C Laptop Charger 671R3UT
HP 65W USB-C LC AC Power Adapter 1P3K6AA

6E6F0AA

Z01AA
Y15AA
A62AA
A63AA
V42AA
B56AA



HP Fortis Flip G1i 11 inch Notebook PC

Summary of Changes

Date of change:	Version History:	Updated	Description of change:
January 22, 2025	V1 to V2	Added	Environmental Section
February 6, 2025	V2 to V3	Added	Display Section

© Copyright 2025 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Intel, Celeron, Pentium and Intel vPro are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries. Bluetooth is a trademark owned by its proprietor and used by HP Inc. under license. USB Type-C® and USB-C® are registered trademarks of USB Implementers Forum. ENERGY STAR is a registered trademark of the U.S. Environmental Protection Agency. © 2023 Google LLC All rights reserved. Google and the Google Logo are registered trademarks of Google LLC.

