Hewlett Packard
Enterprise

# HPE StoreFabric SN3600B Fibre Channel Switch - Product Information Reference

Part Number:
Published:
Edition:

# HPE StoreFabric SN3600B Fibre Channel Switch - Product Information Reference

## Abstract

Part Number:
Published:
Edition:

© Copyright –

## Notices

The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

Confidential computer software. Valid license from Hewlett Packard Enterprise required for possession, use, or copying. Consistent with FAR 12.211 and 12.212, Commercial Computer Software, Computer Software Documentation, and Technical Data for Commercial Items are licensed to the U.S. Government under vendor's standard commercial license.

Links to third-party websites take you outside the Hewlett Packard Enterprise website. Hewlett Packard Enterprise has no control over and is not responsible for information outside the Hewlett Packard Enterprise website.

## Acknowledgments

Intel®, Itanium®, Optane™, Pentium®, Xeon®, Intel Inside®, and the Intel Inside logo are trademarks of Intel Corporation in the U.S. and other countries.

AMD and the AMD EPYC™ and combinations thereof are trademarks of Advanced Micro Devices, Inc.

Microsoft® and Windows® are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.

Adobe® and Acrobat® are trademarks of Adobe Systems Incorporated.

Java® and Oracle® are registered trademarks of Oracle and/or its affiliates.

UNIX® is a registered trademark of The Open Group.

All third-party marks are property of their respective owners.

## Revision history

| Part number | Publication date | Edition | Summary of changes |
|---|---|---|---|

## Table of contents


- Overview
  - Summary
    - Product description
  - Standard Models
    - New RoHS compliant part numbers
    - Standard models
  - Product features
- Specifications
  - Specifications
    - Physical specifications
    - System specifications
    - Electrical specifications
    - Environmental specifications
- Compatibility/Supportability
  - Spare Parts
    - New model specific parts list
    - Switch
    - Drive
    - Transceiver
    - Adapter
    - Cable
    - Power cord
    - Hardware
    - Miscellaneous
  - Option Parts
    - New model specific parts list
    - Transceivers
    - Accessories
    - Cables
    - Software
  - OS Compatibility
- Useful Links

## Summary

**Subtopics**

Product description

## Product description



**The HPE SN3600B Fibre Channel Switch meets the demands of hyper-scale virtualization, larger cloud infrastructures, and growing all-flash-based storage environments by delivering market-leading 32 GB Fibre Channel technology and capabilities. It provides a high-density building block for increased scalability, designed to support growth, demanding workloads, and data center consolidation in small to large-scale enterprise infrastructures. It is built for maximum affordability and flexibility, performance, and ease of use. The HPE SN3600B is an affordable entry-level 8-24-port 32 GB Fibre Channel switch that doesn't compromise on 32 GB functionality offering 24 x 32 Gigabyte per second (Gb/s) SFP+ ports in a 1U form-factor. You can start small with as little as 8-ports and select 16 GB FC or 32 GB FC optics to meet your budget requirements. And for low cost deployments, it is available preconfigured with 8 Short Wave 16 GB SFP+ for customers transitioning to next gen IT technology. Each of the twenty-four (24) SFP+ ports supports 4, 8, 16 and 32 Gb/s Fibre Channel speeds. The HPE SN3600B is designed to support the SAN requirements of a small to medium-sized workgroup as well as customers who demand enterprise SAN switch capabilities. With industry leading highest FC port density in a slim 1U height, the HPE SN3600B enables the creation of very dense fabrics in a relatively small space for tighter budgets.**

## Standard Models

**Subtopics**

New RoHS compliant part numbers
Standard models

## New RoHS compliant part numbers

To find the latest RoHS compliance information, please use the HPE PartSurfer ( **click here to visit HPE PartSurfer website** ) and click on one of the linked model numbers. When locating RoHS information in PartSurfer, you can use the Options part number for the components, the sales order number for a system that the component is used in, or the Spare part number for a specific part. You can find the sales order numbers and Option part numbers in the Product QuickSpecs.

## Standard models

| Description | Model Number |
|---|---|
| HPE StoreFabric SN3600B 32Gb 24/8 fibre channel switch | Q1H70B<br>Click here to obtain parts list for this model . |
| HPE StoreFabric SN3600B 32Gb 24/8 8-port short wave SFP+ fibre channel switch | R4G55A<br>Click here to obtain parts list for this model . |
| HPE SN3600B 32Gb 24/8 8-port 32Gb short wave SFP28 fibre channel switch | R7R97A<br>Click here to obtain parts list for this model . |
| HPE StoreFabric SN3600B 32Gb 24/24 fibre channel switch | Q1H71B<br>Click here to obtain parts list for this model . |
| HPE StoreFabric SN3600B 32Gb 24/24 power pack+ fibre channel switch | Q1H72B<br>Click here to obtain parts list for this model . |

## Product features

| Feature | Description |
|---|---|
| Integrated design | • Component consolidation<br>• Shared power and cooling<br>• Zero foot print |
| Fibre channel connections between the servers and switch reside within BladeSystem chassis | • No need for Fibre Channel cables and SFPs<br>• Faster time to deploy<br>• Minimal external cabling<br>• Compatible with StorageWorks B-series switches |
| 4Gb SAN facing ports | • High speed bandwidth capability<br>• Supports Brocade trunking<br>• Auto-sensing recognizes 2Gb & 1Gb fabric devices |
| Broad range of management tools | • Supports all Brocade Fabric OS based applications<br>• SMI compliant for server based SAN management |
| Redundant switches | • Each server blade has redundant path to the fabric<br>• Enables use of multipathing software |
| Same technology as standalone Brocade switches | • Leverages same hardware and firmware |
| Available in Base, Full Fabric, or Power Pack models | • Choice of features and management options |

# Specifications

**Subtopics**


- Physical specifications
- System specifications
- Electrical specifications
- Environmental specifications


## Physical specifications

| Specification | Description |
|---|---|
| Dimensions (W x H x D) | 42.88 x 4.29 x 30.66 mm (16.88 x 1.69 x 12.07 in) |
| System weight | 5.76 kg (12.65 lb) With one integrated power supply, without transceivers |

## System specifications

| Specification | Description |
|---|---|
| Targeted environment | • Workgroups<br>• Departments |
| Fibre channel port bandwidth | 32 Gb/s |
| Aggregate device bandwidth | 768Gb end-to-end full duplex |
| Storage system support | • HPE Primera<br>• 3PAR StoreServ<br>• Nimble<br>• StoreVirtual 4000<br>• P9000/XP7<br>• MSA 2050/1050 |
| FC Ports | • 8 or 24 Enabled<br>• 24 Max |
| Scalability | Full-Fabric architecture with a maximum of 239 switches |
| Certified maximum | 9,000 active nodes; 56 switches, 19 hops in Fabric OS fabrics; larger fabrics certified as required |

| Specification | Description |
|---|---|
| Performance | Fibre Channel:<br>• 8.5 Gb/s line speed, full duplex<br>• 14.025 Gb/s line speed an 28.05 Gb/s line speed, full duplex<br>• Auto-Sensing of 4, 8, 16 and 32 Gb/s port speeds |
| ISL Trunking | Frame-Based trunking with:<br>• Up to eight 32 Gb/s ports per ISL trunk<br>• Up to 256 Gb/s per ISL trunk<br>• Exchange-Based load balancing across ISLs with DPS included in Fabric OS |
| Maximum fabric latency | Latency for locally switch ports is 900 ns (including FEC) |
| Maximum frame size | 2,112-byte Payload |
| Classes of service | Class 2, Class 3, Class F (Inter-Switch frames) |
| Port types | F_Port, E_Port, M_Port, D_Port (ClearLink Diagnostic Port) on 24 SFP+ ports<br>Access Gateway mode: F_Port and NPIV-enabled N_Port |
| Data traffic types | Fabric switches supporting unicast |
| Media types | • 32 Gb/s: HPE SN3600B requires HPE hot-pluggable SFP+, LC connector; 32 Gb/s SWL, LWL<br>• 16 Gb/s: HPE SN3600B requires HPE hot-pluggable SFP+, LC connector; 16 Gb/s SWL, LWL, ELWL<br>Fibre Channel distance subject to fiber-optic cable and port speed |
| USB | One USB port for system log file downloads or firmware upgrades |
| Frame buffers | 2,000 Dynamically allocated |
| SFP | B-Series |
| Advanced trunking | Included with Power Pack+ or Optional Upgrade |
| Adaptive networking | Adaptive Networking |
| Form factor | 1U |
| Zoning software | Yes (Included) |
| Hot plug, redundant power supplies | No |
| Hot plug fans | Yes (Integrated with power supply) |

## Electrical specifications

| Specification | Description |
|---|---|
| Power supply | Base switch includes a single, fixed power supply with four integrated system cooling fans |
| AC Input | 90 to 264 V |
| Maximum input current | 2.2 A |
| Input line frequency | 47 to 63 Hz |
| Power consumption | • 76.52 W With all 24 ports populated with 32 Gb/s SWL optics<br>• 55.83 W For idle configuration (All Optics Loaded but Not Initialized) |

## Environmental specifications

| Specification | Description |
|---|---|
| **Temperature** | |
| Operating | 0° to 40°C (32° to 104°F) |
| Non-Operating | ( -25°) to 70°C (-13° to 158°F) |
| **Humidity** | |
| Operating | 10% to 85% (Non-Condensing) |
| Non-Operating | 10% to 90% (Non-Condensing) |
| **Altitude** | |
| Operating | Up to 3,000 m (9,842 ft) |
| Storage | Up to 12 km (39,370 ft) |
| **Shock** | |
| Operating | Up to 20 G, 6 ms half sine |
| Non-operating | Half sine, 33Gb 11 ms, 3Gb axis |
| **Vibration** | |
| Operating | 0.5 g sine, 0.4 grms. random, 5 to 500 Hz |
| Non-Operating | 2.0 g sine, 1.1 grms. random, 5 to 500 Hz |
| **Heat dissipation** | |
| Heat dissipation | 24 Ports at:<br>• 215 BTU/hr 100 V ac (Typical)<br>• 209.56 BTU/hr 200 V ac (Typical) |

# Spare Parts

**Subtopics**


- New model specific parts list
- Switch
- Drive
- Transceiver
- Adapter
- Cable
- Power cord
- Hardware
- Miscellaneous


## New model specific parts list

**IMPORTANT:** To obtain current part number information for a specific product model, use the Standard Models page for this product family.

- The product Standard Models page now links the model SKU numbers to the spare parts list for each model found on the HPE PartSurfer web site. (To report missing or incorrect parts information in PartSurfer, please use the "Contact us" and "Missing or incorrect data" links within the PartSurfer web site utility.)
- To look up RoHS-compliant information in PartSurfer, use the component?s option part number or the sales order number for a system in which the component is used (available in the QuickSpecs or Standard Models page).

## Switch

| Description | Spare Part Number |
|---|---|
| SN3600B 32Gb 24-ports Fibre Channel (FC) switch with 8 active ports - Support 32Gb, 16 and 8 FC Small Form Factor Pluggable + (SFP+), Virtual Machine Identity (VMID) support via VM Insight, support for Smart SAN for 3PAR -Automated SAN | 874533-001 |
| SN3600B 32Gb 24-ports FC switch with 24 active ports - Supports 32Gb, 16 and 8 FC SFP+, VMID support via VM Insight, support for Smart SAN for 3PAR -Automated SAN | 874534-001 |
| SN3600B 32Gb 24-port FC switch with 24 active - Support 32Gb, 16 and 8 FC SFP+, VMID support , support for Smart SAN for 3PAR, Power Pack+ Software of Fabric Vision | 874535-001 |
| SN3600B 32GB FC SWITCH | P45391-001 |

## Drive

| Description | Spare Part Number |
|---|---|
| B-series 4GB USB Drive | P10794-001 |

## Transceiver

| Description | Spare Part Number |
|---|---|
| 16GB Brocade SFP+ transceiver | 874536-001 |
| B-Series 32Gb SFP+ Long Wave (LW) transceiver | 855070-001 |
| HP B-series 16Gb SFP+ LC SW transceiver - SFP+ 16Gb SW transceiver, with 850nm laser that provides 14.025GBd connectivity up to 125 m (410 ft) on 50um OM4 multi-mode fiber - Has one LC 16Gb port | 656435-001 |
| HP B-series 16Gb SFP+ LC LW transceiver - SFP+ 18Gb LW transceiver, with 1310nm laser that provides 16Gb connectivity up to 10 km (6.2 miles) on single-mode fiber - Has one LC 16-Gb port | 656436-001 |
| 32G SFP+ SWL 1Pk | P29141-001 |

## Adapter

| Description | Spare Part Number |
|---|---|
| B-series 16Gb LW 25-km FC Adapter | 741204-001 |

## Cable

| Description | Spare Part Number |
|---|---|
| Cable - JMP CRD C13/C14 India 2.0 m blank | P10794-001 |
| Premier Flex Multimode OM4 LC/LC Fiber Optic cable, 1.0 m (3.28 ft) long - Duplex zipcord graded index 50/125um multimode bendable fiber optic cable with LC/MPO connectors on each end (Blue color) - Optical performance: 4700 MHz/km | 656427-001 |
| Premier Flex Multimode OM4 LC/LC Fiber Optic cable, 2.0m (6.56 ft) long - Duplex zipcord graded index 50/125um multimode bendable fiber optic cable with LC/MPO connectors on each end (Blue color) - Optical performance: 4700 MHz/km | 656428-001 |
| Premier Flex Multimode OM4 LC/LC Fiber Optic cable, 5.0 m (16.4 ft) long - Duplex zipcord graded index 50/125um multimode bendable fiber optic cable with LC/MPO connectors on each end (Blue color) - Optical performance: 4700 MHz/km | 656429-001 |
| Premier Flex Multimode OM4 LC/LC Fiber Optic cable, 15 m (49.2 ft) long - Duplex zipcord graded index 50/125um multimode bendable fiber optic cable with LC/MPO connectors on each end (Blue color) - Optical performance: 4700 MHz/km | 656430-001 |

| Description | Spare Part Number |
|---|---|
| Premier Flex Multimode OM4 LC/LC Fiber Optic cable, 30 m (98.4 ft) long - Duplex zipcord graded index 50/125um multimode bendable fiber optic cable with LC/MPO connectors on each end (Blue color) - Optical performance: 4700 MHz/km | 656431-001 |
| Premier Flex Multimode OM4 LC/LC Fiber Optic cable, 50 m (164 ft) long - Duplex zipcord graded index 50/125um multimode bendable fiber optic cable with LC/MPO connectors on each end (Blue color) - Optical performance: 4700 MHz/km | 656432-001 |
| Premier flex Multi-fiber Push On (MPO) MPO/MPO (Optical mode) OM4, 12f, 1 m (3.28 ft) long fiber cable | 873182-001 |
| Premier flex MPO/MPO (Optical mode) OM4 12f 2 m (6.56 ft) long fiber cable | 873183-001 |
| Premier flex MPO/MPO (Optical mode) OM4, 12f, 4 m (13.12 ft) long fiber cable | 873184-001 |
| Premier Flex Multimode OM4 MPO/MPO Fiber Optic cable, 8-fibre, 10 m (32 ft) long - Duplex graded index 50/125um multimode 'bendable fiber optic cable with MPO connectors on each end (Blue color) | 656433-001 |
| Premier flex MPO/MPO (Optical mode) OM4, 12f, 15 m (49.21 ft) long fiber cable | 873185-001 |
| Premier flex MPO MPO/MPO (Optical mode) OM4, 12f, 30 m (98.42 ft) long fiber cable | 873186-001 |
| Premier Flex Multimode OM4 MPO/MPO Fiber Optic cable, 8-fibre, 50 m (164 ft) long - Duplex graded index 50/125um multimode 'bendable' fiber optic cable with MPO connectors on each end (Blue color) | 656434-001 |
| Premier Flex MPO to 4x LC Fiber Optic cables assembly, 5 m (16.4 ft) long - bendable fiber optic cable assembly with (M) MPO connector on one end to four fiber optic cables with (M) LC connectors on the other | 800867-001 |
| Premier Flex MPO (Multiple-Fiber Push-On/Pull-off) to 4 x LC Fiber Optic cables assembly, 15m (49.2ft) long - 'Bendable' fiber optic cable assembly with (M) MPO connector on one end to four fiber optic cables with (M) LC connectors on the other | 800868-001 |
| Premier Flex MPO to 4xLucent Connector (LC) 30 m (98.42 ft) long | 873187-001 |
| Multimode OM3 LC/LC Fiber Optic cable, 0.5 m (1.64 ft) long - Duplex zipcord graded index 50/125um multimode fiber optic cable with LC connectors on each end (Aqua color) - Optical performance: 2000 MHz/km | 491023-001 |
| Multimode OM3 LC/LC Fiber Optic cable, 1.0 m (3.28 ft) long - Duplex zipcord graded index 50/125um multimode fiber optic cable with LC connectors on each end (Aqua color) - Optical performance: 2000 MHz/km | 491024-001 |
| Multimode OM3 LC/LC Fiber Optic cable, 2.0 m (6.56 ft) long - Duplex zipcord graded index 50/125um multimode fiber optic cable with LC connectors on each end (Aqua color) - Optical performance: 2000 MHz/km | 491025-001 |

| Description | Spare Part Number |
|---|---|
| Multimode OM3 LC/LC Fiber Optic cable, 5.0 m (16.4 ft) long - Duplex zipcord graded index 50/125um multimode fiber optic cable with LC connectors on each end (Aqua color) - Optical performance: 2000 MHz/km | 491026-001 |
| Multimode OM3 LC/LC Fiber Optic cable, 30 m (98.4 ft) long - Duplex zipcord graded index 50/125um multimode fiber optic cable with LC connectors on each end (Aqua color) - Optical performance: 2000 MHz/km | 491028-001 |
| Multimode OM3 LC/LC Fiber Optic cable, 50 m (164 ft) long - Duplex zipcord graded index 50/125um multimode fiber optic cable with LC connectors on each end (Aqua color) - Optical performance: 2000 MHz/km | 491029-001 |
| Cable Jumper cord C13/C14 India 2.0 m Blank | P10794-001 |

## Power cord

| Description | Spare Part Number |
|---|---|
| AC Power Distribution Unit (PDU) power cord (Black) - 250 V ac, 16 AWG, 2.0 m (6.6 ft) long - Includes IEC-320 C14 (M) connector to IEC 320 C13 (F) connector | 142258-003 |

## Hardware

| Description | Spare Part Number |
|---|---|
| 16G SFP+ SWL 1Pk | P29143-001 |

## Miscellaneous

| Description | Spare Part Number |
|---|---|
| SFP+,ELWL,32G,25KM,1-PK SECURE | P42554-001 |

## Option Parts

**Subtopics**


- New model specific parts list
- Transceivers
- Accessories
- Cables

## New model specific parts list

**IMPORTANT:** To obtain current part number information for a specific product model, use the Standard Models page for this product family.

- The product Standard Models page now links the model SKU numbers to the spare parts list for each model found on the HPE PartSurfer web site. (To report missing or incorrect parts information in PartSurfer, please use the "Contact us" and "Missing or incorrect data" links within the PartSurfer web site utility.)
- To look up RoHS-compliant information in PartSurfer, use the component?s option part number or the sales order number for a system in which the component is used (available in the QuickSpecs or Standard Models page).

## Transceivers

| Description | Option Part Number |
|---|---|
| HPE B-series 32Gb SFP+ Long Wave (LW) 1-pack transceiver | P9H29A |
| HPE B-series 16Gb SFP+ SW Transceiver | QK724A |
| HPE B-series 16Gb LW 25-km FC SFP 1-pack Transceiver | H6Z29A |
| HPE B-series 16Gb SFP+ LW 10-km Transceiver | QK725A |
| HPE SN3600B 16Gb 8-port Short Wave SFP+ Fibre Channel Upgrade License with Transceiver Kit | R7M10A |
| HPE SN3600B 32Gb 8-port Short Wave SFP28 Fibre Channel Upgrade License with Transceiver Kit | R7M09A |
| HPE B-series 32Gb SFP28 Short Wave 1-pack Secure Transceiver | R6B12A |
| HPE B-series 32Gb SFP28 Short Wave 8-pack Secure Transceiver | R6W26A |
| HPE B-series 32Gb SFP28 Long Wave 10km 1-pack Secure Transceiver | R6B13A |
| HPE B-series 32Gb SFP Extended Long Wave 25km 1-pack Secure Transceiver | R7M17A |
| HPE B-series 16Gb SFP+ Short Wave 1-pack Secure Transceiver | R6B10A |
| HPE B-series 16Gb SFP+ Short Wave 8-pack Secure Transceiver | R6W28A |
| HPE B-series 16Gb SFP+ Long Wave 10km 1-pack Secure Transceiver | R6B11A |
| HPE B-series 16Gb SFP+ Extended Long Wave 25km 1-pack Secure Transceiver | R6B21A |

**NOTE**

The above POD Kits are available as a physical upgrade package only, these are not available as an e-license becausethey include the optics. POD Kits include Secure optics.

## Accessories

| Description | Option Part Number |
| --- | --- |
| HPE B-series 4 Gb USB Drive | N9Y63A |

## Cables

| Description | Option Part Number |
|---|---|
| HPE PremierFlex OM4+ fiber optic cables | |
| HPE PremierFlex LC/LC multi-mode OM4 2 fiber 1 m cable | QK732A |
| HPE PremierFlex LC/LC multi-mode OM4 2 fiber 2 m cable | QK733A |
| HPE PremierFlex LC/LC multi-mode OM4 2 fiber 5 m cable | QK734A |
| HPE PremierFlex LC/LC multi-mode OM4 2 fiber 15 m cable | QK735A |
| HPE PremierFlex LC/LC multi-mode OM4 2 fiber 30 m cable | QK736A |
| HPE PremierFlex LC/LC multi-mode OM4 2 fiber 50 m cable | QK737A |
| HPE PremierFlex OM4+ QSFP fiber optic cables | |
| HPE PremierFlex MPO/MPO multi-mode OM4 12 fiber 1 m cable | Q1H63A |
| HPE PremierFlex MPO/MPO multi-mode OM4 12 fiber 2 m cable | Q1H64A |
| HPE PremierFlex MPO/MPO multi-mode OM4 12 fiber 5 m cable | Q1H65A |
| HPE PremierFlex MPO/MPO multi-mode OM4 12 fiber 10 m cable | QK729A |
| HPE PremierFlex MPO/MPO OM4 12f 15 m cable | Q1H66A |
| HPE PremierFlex MPO/MPO multi-mode OM4 12 fiber 30 m cable | Q1H67A |
| HPE PremierFlex MPO/MPO multi-mode OM4 8 fiber 50 m cable | QK731A |
| HPE PremierFlex MPO/MPO OM4 100 m (12 ft) cable | H6Z30A |
| HPE PremierFlex MPO to 4xLC OM4 splitter cables | |
| HPE Multi Fiber Push On (MPO) to 4 x Lucent Connector (LC) 5 m cable | K2Q46A |
| HPE MPO to 4 x LC 15 m cable | K2Q47A |
| HPE PremierFlex MPO to 4 x LC 30 m cable | Q1H68A |
| HPE OM3 LC-LC Optical cables | |
| HPE LC to LC Multi-Mode OM3 2-fiber 0.5 m 1-pack fiber optic cable | AJ833A |
| HPE LC to LC Multi-Mode OM3 2-fiber 1 m 1-pack fiber optic cable | AJ834A |
| HPE LC to LC Multi-Mode OM3 2-fiber 2 m 1-pack fiber optic cable | AJ835A |
| HPE LC to LC Multi-Mode OM3 2-fiber 5 m 1-pack fiber optic cable | AJ836A |
| HPE LC to LC Multi-Mode OM3 2-fiber 15 m 1-pack fiber optic cable | AJ837A |
| HPE LC to LC Multi-Mode OM3 2-fiber 30 m 1-pack fiber optic cable | AJ838A |
| HPE LC to LC Multi-Mode OM3 2-fiber 50 m 1-pack fiber optic cable | AJ839A |

## Software

| Description | Option Part Number |
|---|---|
| Optional software | |
| HPE Smart SAN for HPE 3PAR StoreServ 8200/8400/8440/8450 E-LTU | L7D49AAE |
| HPE StoreFabric SN3600B power pack+ upgrade E-LTU | Q1Z11BAE |
| HPE SANnav Management Portal Base 1yr E-LTU | R3P45AAE |
| HPE SANnav Management Portal Enterprise 1yr E-LTU | R3P46AAE |
| HPE SANnav Global View 1yr E-LTU | R3P47AAE |
| HPE SANnav Management Portal Base 3yr E-LTU | R3P48AAE |
| HPE SANnav Management Portal Enterprise 3yr E-LTU | R3P49AAE |
| HPE SANnav Global View 3yr E-LTU | R3P50AAE |
| HPE SANnav Management Portal Base 5yr E-LTU | R4P29AAE |
| HPE SANnav Management Portal Enterprise 5yr E-LTU | R4P30AAE |
| HPE SANnav Global View 5yr E-LTU | R4P31AAE |
| HPE Network Orchestrator E-LTU | Q9Y41AAE |
| HPE Network Orchestrator Enterprise E-LTU | R0H75AAE |
| HPE Network Orchestrator Enterprise Upgrade E-LTU | R0H76AAE |
| **SANnav Renewal Software Licenses** | |
| HPE SANnav Management Portal Base 1-year Renewal E-LTU | S1S52AAE |
| HPE SANnav Management Portal Enterprise 1-year Renewal E-LTU | S1S55AAE |
| HPE SANnav Global View 1-year Renewal E-LTU | S1S58AAE |
| **License** | |
| HPE StoreFabric SN3600B 8-port Fibre Channel (FC) upgrade E-LTU | Q1Z10AAE |
| 8-Port upgrade license for - SN3600B 32 Gb 24/8 FC switch | Q1H70B |

**NOTE**

The Base edition of HPE SANnav Management Portal does not support management of director class switches.

HPE SANnav Management Software License-to-Use (LTU/E-LTU) includes maintenance and support for the duration ofthe license. At the end of the license period, customer will need to purchase a new license to continue using the software.Software renewal via HPE PointNext is not allowed/supported.

A 90-day, full-featured trial license for SANnav Management Portal and SANnav Global View is available.

## OS Compatibility

| Feature | Description |
|---|---|
| **Supported software** | • HTTP<br>• SNMP v1/v3 (FE MIB, FC Management MIB)<br>• SSH<br>• Auditing<br>• Syslog<br>• Advanced web tools<br>• Network Advisor SAN Enterprise or Network Advisor SAN Professional/Professional Plus<br>• Command Line Interface(CLI)<br>• SMI-S compliant<br>• Trial licenses for add-on capabilities |
| **Software components** | Standard, base models:<br>• Frame filtering<br>• Advanced zoning<br>• We tools<br>• Adaptive Networking (AN) |
| | Optional:SN3600B 32 GB Switch power pack+ software bundle |
| **Software components, optional** | SN3600B 32 Gb Switch Power Pack+ software bundle<br>• Fabric vision<br>• Extended fabric<br>• ISL Trunking<br>• HPE SANnav management software<br>• HPE Smart SAN for 3PAR<br>• HPE Network orchestrator |

## Useful Links

| Description | Direct links |
| --- | --- |
| Alerts | Click here to view " Advisories, Alerts and Bulletins and Notices of HPE StoreFabric SN3600B Fibre Channel Switch". |
| Drivers and Software | Click here to view "Drivers and software of HPE StoreFabric SN3600B Fibre Channel Switch". |
| Knowledge article | Click here to view" Knowledge articles, Troubleshooting, FAQ, How to , Information document of HPE StoreFabric SN3600B Fibre Channel Switch". |
| Manuals | Click here to view "Manuals, Guides,Release notes, Troubleshooting articles and other related document of HPE StoreFabric SN3600B Fibre Channel Switch". |
| Videos | Click here to access " Videos of Remove/Replace, Setup/Installation, Troubleshooting, Management/Operations of HPE StoreFabric SN3600B Fibre Channel Switch". |