


# **OVERVIEW**



1. Power button	5. USB-C (USB 10Gbps), with USB PD 3.0 & DP 2.1
2. Headphone / microphone combo jack (3.5mm)	6. Pogo pin connector (8-point)
3. Thunderbolt 4	7. Kensington Nano Security Slot
4. Nano-SIM card slot *	8. Volume button

## Notes:

- Items with \* are only available on selected models
- Folio keyboard shown on above image is for demo only. It is available on selected models.



## **PERFORMANCE**

### **Processor**

#### **Processor Family**

Intel® U Series Core Ultra 5 / 7 Processor (Series 1)

#### Processor\*\*

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Processor Graphics	AI Engine
Core Ultra 5 134U	12 (2 P-core + 8 E-core + 2 LPE- core)		P-core 700MHz / E-core 500MHz / LPE-core 400MHz	P-core 4.4GHz / E-core 3.6GHz / LPE-core 2.1GHz	12MB	Intel® Graphics	Intel® AI Boost
Core Ultra 7 164U	12 (2 P-core + 8 E-core + 2 LPE- core)	14	P-core 1.1GHz / E-core 700MHz / LPE-core 400MHz	P-core 4.8GHz / E-core 3.8GHz / LPE-core 2.1GHz	12MB	Intel® Graphics	Intel® AI Boost

# **Operating System**

## Operating System\*\*

- Windows® 11 Pro
- Windows® 11 Home
- No preload operating system

### **NPU**

#### NPU

Intel® AI Boost integrated in Intel® Core™ Ultra processor

## **Graphics**

### **Graphics**

Graphics	Туре	Memory	TGP	Key Features
Intel® Graphics	Integrated	Shared	Share CPU TDP	DirectX® 12.2

## **Monitor Support**

#### Monitor Support[1]

Supports up to 3 independent displays (native display and 2 external monitors via USB-C® and Thunderbolt™)

- USB-C® supports up to 6K@60Hz
- Thunderbolt<sup>™</sup> supports up to 8K@60Hz

#### Notes:

[1] Refresh rates >60hz also supported, however max resolution will be limited. 6K / 8K resolution support needs 2 display pipes. That is, simultaneous display number will "-1" when 6K / 8K resolution displayed.

## Chipset

#### Chipset

Intel® SoC (System on Chip) platform

## **Memory**

### **Max Memory**

- 16GB soldered memory, not upgradable
- 32GB soldered memory, not upgradable

### **Memory Type**

LPDDR5x-6400<sup>[1]</sup>

## Notes:

[1] Installed memory is actually LPDDR5x-7500 but run as LPDDR5x-6400 due to platform limitation.

### **Storage**



### Storage Support[1]

One drive, up to 1TB M.2 2242 SSD

### **Storage Type**

Disk Type	Interface	Offering	Security
M.2 2242 SSD	PCle® NVMe®, PCle® 4.0 x4	256GB / 512GB / 1TB	Opal 2.0

#### Notes:

[1] The storage capacity supported is based on the test results with current Lenovo® storage offerings.

### Multi-Media

#### **Speakers**

Stereo speakers, 1W x2, Dolby Audio™

#### Microphone

Dual-microphone array, Dolby Voice®

#### Camera

Front 5.0MP + IR discrete user-facing camera, privacy shutter, fixed focus Rear 8.0MP, autofocus

#### Sensor

#### **Vibration Motor**

No support

#### Sensors

- · Accelerometer (G) sensor
- Gyroscope sensor
- · Hall sensor
- Inclinometer sensor
- Proximity (P) sensor (WWAN models)

### **Battery**

#### **Battery**

Integrated Li-Polymer 42Wh battery, supports Rapid Charge (charge up to 80% in 1hr) with 65W AC adapter

## Max Battery Life[1]

MobileMark25@250nits: 12.47 hr

Local video (1080p) playback@150nits: 17.52 hr

JEITA-BAT 3.0@200nits (Video/Idle): 9.98 hr / 19.31 hr

### Notes:

[1] All battery life claims are approximate maximum and based on results using the MobileMark® 25, JEITA 3.0, continuous 1080p video playback (with 150nits brightness and default volume level) or Google Power Load Test (PLT) battery-life benchmark tests. Actual battery life will vary depending on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

## **Power Adapter**

### Power Adapter\*\*[1]

- 45W USB-C<sup>®</sup> (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 45W USB-C<sup>®</sup> (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C<sup>®</sup> (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C<sup>®</sup> (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C® slim (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C® slim (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz

## Notes:

[1] AC adapter offerings depend on the country.

## **DESIGN**



## **Display**

### Display<sup>[1]</sup>

Size	Resolution	Touch	Туре	Brightness	Surface	Aspect Ratio	Contrast Ratio	Color Gamut	Viewing Angle (L/R/U/D)	Key Features
12.3"	FHD+ (1920x1280)	Multi- touch	IPS	400nits	Anti- reflection, anti-smudge	3:2	1500:1	100% sRGB	89°/89°/89°/89°	Corning® Gorilla® Glass

#### **Touchscreen**

GMF / GF2 (Metal mesh film sensor) multi-touch, supports 10-point touch

Notes:

[1] IPS (in-plane switching) technology may refer to IPS, PLS, ADS, AHVA, AAS.

## **Input Device**

#### Pen\*\*

- Lenovo® Digital Pen with replaceable AAAA alkaline battery, 4096 levels of pressure sensitivity. For more information, please read <u>Lenovo® Digital Pen Overview</u>
- Lenovo® Digital Pen without replaceable AAAA alkaline battery, 4096 levels of pressure sensitivity. For more
  information, please read <u>Lenovo® Digital Pen Overview</u>
- Lenovo® Precision Pen, 4096 levels of pressure sensitivity, magnetically attached to the system. For more information, please read Lenovo® Precision Pen Overview
- No pen (purchase separately)

#### Mechanical

### Dimensions (WxDxH)[1]

Models	Dimensions
Tablet	283.3 x 203.5 x 8.8 mm (11.15 x 8.01 x 0.34 inches)
Tablet with folio keyboard	Tablet: 283.3 x 203.5 x 8.8 mm (11.15 x 8.01 x 0.35 inches) Folio keyboard: 283.3 x 217.8 x 5.7 mm (11.15 x 8.57 x 0.22 inches) Total: 283.3 x 208.1 x 14.5 mm (11.15 x 8.19 x 0.57 inches)

## Weight<sup>[2]</sup>

Models	Weight
Tablet	around 0.76 kg (1.67 lbs)
Tablet with folio keyboard	Tablet: 0.76 kg (1.67 lbs) Folio keyboard: 0.34 kg (0.75 lbs) Total: 1.1 kg (2.42 lbs)

### **Case Color**

Black

#### **Case Material**

Magnesium-aluminium

### Others

- Hinge open angle: 170°
- Kensington® Nano Security Slot™

#### **Buttons**

- Power button
- Volume button

### Notes:

- [1] The system dimensions may vary depending on configurations.
- [2] The system weight is approximate and based on results in Lenovo® lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

## CONNECTIVITY



#### **Network**

#### WLAN + Bluetooth®[1]

Intel® Wi-Fi® 6E AX211, 802.11ax 2x2 Wi-Fi® + Bluetooth® 5.3

### **WWAN**

- Quectel EM160R-GL Gen 2, 4G LTE CAT16, M.2 card, with embedded eSIM functionality
- No support

#### NFC

- · Near Field Communication
- No support

#### **Location Services**

Models	Location		
WLAN models	No location service		
WWAN models	GPS + GLONASS + Galileo + Beidou + A-GPS		

#### Notes:

[1] Bluetooth® may operate at a lower version than hardware design depending on the factors such as operating system, driver, etc.

## **Ports**

#### Standard Ports[1]

- 1x USB-C® (USB 10Gbps / USB 3.2 Gen 2), with USB PD 3.0 and DisplayPort™ 2.1
- 1x USB-C® (Thunderbolt™ 4 / USB4® 40Gbps), with USB PD 3.0 and DisplayPort™ 2.1
- 1x Headphone / microphone combo jack (3.5mm)
- 1x Pogo pin connector (8-point)

#### **Optional Ports**

1x Nano-SIM card slot (WWAN models)

## Notes:

[1] The transfer speed of the ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes, and other factors related to system configuration and your operating environment, will be slower than the theoretical speed.

### **Docking**

#### **Docking**

Various docking solutions supported via Thunderbolt™ or USB-C®.

For more compatible docking solutions, please visit <u>Docking for ThinkPad® X12 Detachable Gen 2</u>

## **SECURITY & PRIVACY**

## **Security**

## **Security Chip**

Discrete TPM 2.0, TCG certified

#### **Fingerprint Reader**

- · Touch style fingerprint reader on folio keyboard, match-on-chip
- · No fingerprint reader

#### **BIOS Security**

- Supervisor password
- · Power-on password
- System management password
- Hard disk password
- Self-healing BIOS

### MANAGEABILITY



## **System Management**

#### **System Management**

- Intel® vPro® Enterprise
- Non-vPro®

## **SERVICE**

## Warranty

## Base Warranty\*\*

- 1-year courier or carry-in service
- 3-year (1-yr battery) courier or carry-in service
- 3-year (1-yr battery) limited onsite service
- No base warranty

## **ACCESSORIES**

### **Bundled Accessories**

#### **Bundled Accessories**\*\*\*[1]

- Lenovo® USB-C® Port Replicator
- Lenovo® USB-C® to Ethernet Adapter (1Gbps)
- Lenovo® USB-C® to HDMI® Adapter
- Lenovo® USB-C® to VGA Adapter
- ThinkPad® X12 Detachable Gen 2 Folio Keyboard, with touchpad (pogo pin, detachable)
- None

Notes:

[1] For more compatible accessory solutions, please visit Accessories for ThinkPad® X12 Detachable Gen 2.

## **OPERATING REQUIREMENTS**

# **Operating Environment**

### Temperature<sup>[1]</sup>

- Operating: 5°C (41°F) to 35°C (95°F)
- Storage and transportation in original shipping packaging: -20°C (-4°F) to 60°C (140°F)
- Storage without package: 5°C (41°F) to 43°C (109°F)

### **Relative Humidity**

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage and transportation: 5% to 95% at wet-bulb temperature 27°C (81°F)

### **Altitude**

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

[1] When you charge the battery, its temperature must be no lower than 10°C (50°F).

## **ENVIRONMENTAL**

### Sustainability

## Material

90% recycled magnesium on top cover

30% PCC recycled plastic on keyboard cover

30% PCC recycled plastic on bottom cover

30% PCC recycled plastic used in speaker enclosure

50% recycled aluminium used in the kickstand

25% PCC recycled plastic used in the 42Whr battery enclosure



Up to 90% PCC recycled plastic used in standard 45W and 65W USB-C®, and Slim 65W adaptors FSC-certified with 85% recycled plastic and/or sustainable content

## **CERTIFICATIONS**

## Green Certifications<sup>11</sup>

#### Green Certifications[2]

- ENERGY STAR® 8.0
- EPEAT™ Gold Registered[3]
- ErP Lot 6
- ErP Lot 26
- RoHS compliant
- TCO Certified 9.0

#### Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration. For ESG & regulatory compliance documents, please visit <a href="https://compliance.lenovo.com">https://compliance.lenovo.com</a>.

[2] EPEAT™ registration and ENERGY STAR® certification are dependent on system OS. Please visit <u>epeat.net</u> and <u>energystar.gov</u> for more information.

[3] EPEAT™ is registered where applicable, please visit epeat.net for registration status by country.

#### Other Certifications

### Mil-Spec Test

MIL-STD-810H military test passed

- Feature with \*\* means that only one offering listed under the feature is configured on selected models.
- Feature with \*\*\* means that one or more offerings listed under the feature could be configured on selected models.
- Lenovo reserves the right to change specifications or other product information without
  notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES
  THIS PUBLICATION "AS IS," WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING
  THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some
  jurisdictions do not allow disclaimer of express or implied warranties in certain
  transactions, therefore this disclaimer may not apply to you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.











