

Product data sheet

Specifications



Rack PDU, Basic, 1U, 30A, 208V, (10) C13



AP9571A

Overview

Presentation Reliable rack power distribution designed to increase manageability and efficiency in the data center. The output and input connections are (10) C13. Real-time remote monitoring of connected loads. User-defined alarms warn IT and data center managers of potential circuit overloads to prevent accidental power loss to critical equipment.

Lead time Usually in Stock

Main

Color	Black
Product or Component Type	PDU
PDU Type	Basic
Cord length	12 ft (3.7 m)
Number of cables	1
Provided Equipment	Installation guide Rack Mounting brackets User Manual

Complementary

Input Voltage	200 V 208 V 230 V
Height	1.7 in (4.4 cm)
Width	17.5 in (44.5 cm)
Output Voltage	208 V
Depth	3.03 in (7.7 cm)
Net Weight	5.62 lb(US) (2.55 kg)
Mounting Location	Front Rear
Mounting preference	No preference
Input Plug Type	NEMA L6-30P
Mounting Mode	Rack-mounted
Rack units	1U
Mounting position	Horizontal
Line Rated Current	24 A
Acceptable Input Voltage	200...240 V
Max line current	30 A

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Input current limits	30 A
Load Capacity	4992 VA
Input Frequency	50/60 Hz
Outlet type and quantity	10 IEC 60320 C13

Environment

Product Certifications	cUL Listed PSE UL Listed
Standards	UL 60950
Ambient Air Temperature for Operation	23...113 °F (-5...45 °C)
Relative Humidity	5...95 %
Operating altitude	0...15000 ft
Ambient Air Temperature for Storage	-13...149 °F (-25...65 °C)
Storage Relative Humidity	5...95 %
Storage altitude	0...50000 ft (0.0000000000...15240.0000000000 m)

Ordering and shipping details

GTIN	731304272755
-------------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.7 in (17.1 cm)
Package 1 Width	6.9 in (17.4 cm)
Package 1 Length	19.02 in (48.3 cm)
Package 1 Weight	8.02 lb(US) (3.64 kg)

Contractual warranty

Warranty	2 years repair or replace
-----------------	---------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Energy Efficient Take-back Transparency RoHS/REACH


Resource performance

 Energy Efficient Product

 Take-Back Program Available

Well-being performance

 Lead Free

 Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information.

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)