Specifications

Eaton TPC4100-A2

Eaton Basic PDU, 1U - TPC4100-A2

General specifications	
PRODUCT NAME	Eaton basic PDU
CATALOG NUMBER	TPC4100-A2
UPC	786685283920
PRODUCT LENGTH/DEPTH	0.0001 in
PRODUCT HEIGHT	0.0001 in
PRODUCT WIDTH	0.0001 in
PRODUCT WEIGHT	0.0001 lb
COMPLIANCES	TAA Compliant
CERTIFICATIONS	UL Listed

Powering Business Worldwide

Product specifications

FORM FACTOR	1U
OUTLET CONTROL	No
FREQUENCY RATING	50-60 Hz
OPERATING TEMPERATURE	0° to 60°C (32° to 140°F)

Resources

APPLICATION NOTES	Application guide: Small data center power protection solutions
	Eaton maintenance bypass application note
	Eaton network closet solutions brochure
	WUSD: Straight A's for K-12 virtualized environment
BROCHURES	Eaton ePDU G3 one-page overview
	Eaton ePDU G3 brochure
	Eaton Flex and Hotswap MBP ePDU brochure
	Eaton ePDUs for office environments
CASE STUDIES	LACCD: Eaton solution proves knowledge is power for college district
	Shawnigan Lake School: Boarding school protected by Eaton
CERTIFICATION REPORTS	Eaton RoHS declaration of conformity: ePDU G3
DRAWINGS	TPC4100-A2 Technical Drawing
INSTALLATION INSTRUCTIONS	Eaton ePDU G3 troubleshooting guide
MANUALS AND USER GUIDES	Eaton ePDU G3 installation and connectivity quick start
	Eaton ePDU G3 operations manual
	Eaton ePDU G3 replace and configure eNMC module
	Eaton ePDU G3 1U and 2U installation addendum
WHITE PAPERS	Quick guide to power distribution
	Optimizing rack power distribution

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.