



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: B095-004-1E

4 Port IP Serial Console / Terminal Server



Highlights

- 4 - RS-232 Serial Console Ports
- Cisco Compatible Cabling
- Network UPS Tools for UPS Monitoring and management
- Powerman for PDU and RPS management
- Secure Web Management (HTTPS)
- Internal Temperature Sensor
- 2 Gig Internal USB Flash
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases
- Made in the USA

Description

Tripp Lite's B095-004-1E is the perfect solution for In-Band and Out-of-Band management of equipment located in remote branch offices, equipment closets on multiple floors, etc. Remote branch offices typically lack on-site IT staff to handle common IT functions such as server administration, Firewall maintenance, and UPS management. In the event of an outage, expensive third party contractors will need to be outsourced on short notice. Third party support is costly and introduces security issues when allowing contractors access to corporate data and private customer information. Travel to the remote site by corporate personnel is costly and time consuming as well. Tripp Lite Serial Console Servers allow network administrators secure access to all remote devices from anywhere in the world.

In-Band solutions utilize operational network interfaces for communicating to remote sites. When remote sites experience network outages, the only access available is Out-Of-Band solutions. The B095-004-1E allows for an external modem to be connected to one of the four serial ports to allow Out-of-Band access. Tripp Lite branch office solutions provides a single interface to swiftly and efficiently manage your IT infrastructure.

Tripp Lite Serial Console Servers are equipped with the most advanced security features available. Our solution utilizes flexible authentication methods that will query directory servers such as LDAP, Radius, TACACS+ and still retains a local user list for Out-Of-Band channels. We employ advanced encryption modes and detailed device logs to ensure your remote site is protected. Made in the USA. Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.

Applications

Wiring Closet

Actively monitor distributed UPS systems located in a dispersed environment, serial connectivity for routers, switches and wireless access points. Set alarms for temperature fluctuations to locate hotspots. Ideal solution for campus environments, schools and universities.

Branch Office and Remote Site Management

Perfect solution for both SMB and large enterprise customers. One solution for IT management, environmental monitoring and power management. Manage servers, switches, routers, firewalls, SAN with serial console ports. Instantly diagnose remote sites at a glance with our built-in Dashboard feature. Automatic failover to Out-Of-Band including 802.11 wireless, modem or cellular options. Complete remote hands like actually being on-site.

Hospitality

Enable POS and Property Management System connectivity to electronically bill customers from distributed services throughout a resort. Establish receipt printing, PBX connectivity and distributed UPS monitoring from campus style installations.

Medical

Secure remote control over serial ports of critical medical equipment including patient data from blood analyzers, heart monitors, dialysis machines and ventilators. Hospital IT personnel have access to remote clinic hardware, where IT staff would not be typically present. Compliant to HIPAA regulations for security.

Military Industrial

Validated FIPS-140 SSL object module for compliance into DOD regulations on perimeter network edge devices. Now equipped with IP SEC for VPN connectivity to ensure secure connectivity. TAA compliant.

Kiosk and Point of Sale

Small form factor and wireless options make this a perfect fit for kiosks. Connect to receipt printer, scale, door contact sensors and more. Install at point of sale and connect to bar code scanners, printers, credit card readers.

Total Power Management

Manage all UPS systems and RPC connections from one appliance, serial, USB and SNMP connectivity for UPS and RPC devices. Simple Web Interface - Logging, Alerting, Monitoring.

Package Includes

- B095-004-1E Console Server Unit
- 2 - UTP Cat5e Cables
- 2 - DB9F / RJ45 Adapters (1 Straight Through Wired, 1 Crossover)
- Quick Start Guide and CD-ROM
- AC Power Adapter

Features

- 4 - RS-232 Serial Console Ports
- Network UPS Tools for UPS Monitoring and management
- Powerman for PDU and RPS management
- 2 Gig Internal USB Flash
- Attach external modem to Serial ports for out-of-band access
- Secure Shell (SSH V2 and V3)
- IPsec VPN support
- TACACS+ , RADIUS and LDAP authentication
- PAP/CHAP authentication (dial up)
- Local authentication
- System event syslog
- SSH port and IP forwarding support
- IP packet filtering
- Break over SSH support
- Port triggers with SNMP and email alerts
- Offline data logging (Syslog, NFS, CIFS)
- Online data buffering and logging
- Multiple users per port (with port sniffing)
- Telnet/SSH/Raw TCP connect
- RFC 2217 - Port Redirection
- Integrated AJAX serial console and system terminal via web interface
- Native IPMI 1.5 and 2.0 (RMCP/RMCP+) support for BMC and service processor access and control
- Service processor access (IPMI, ILO, LOM and more)
- Access to KVM built in to service processors (DRAC, RSA)
- Secure Telnet access
- Limit user access by LAN device and SDT service for that device

- Port triggers with SMNP and email alerts for all tunnel traffic
- Each gateway can port forward to an unlimited number of locally networked hosts (computers, routers)
- Embedded DHCP server for management LAN devices
- PowerMan for PDU and RPS Management
- Command Line interface (Linux Shell)
- Nagios distributed monitoring
- Internal temperature sensor
- Digital I/O ports for external smoke, fire, vibration, water detection and door contact sensors
- Linux with source code access
- Constructed of heavy-duty steel housing

Specifications

INPUT	
Maximum Input Amps (A)	0.3
PHYSICAL	
Unit Dimensions (HWD/in)	1 1/8" x 3.5" x 4"
Unit Dimensions (HWD/cm)	2.86 x 8.89 x 10.16
Color	Black
ENVIRONMENTAL	
Operating Temperature Range	5C to 50C (41F to 122F)
Relative Humidity	5% to 90%
Storage Temperature	-30C to +60C (-20F to +140F)
BTUs	120V: 21 BTU per hour
Power Consumption (Watts)	120V: 6 Watts
CONNECTIONS	
Local Console Ports	4 x RJ45 Serial Ports
Local Console Ports - Port 1	1 x RJ45 LAN Port
Local Console Ports - Port 2	1 x USB A Port
WARRANTY	
Product Warranty Period (Worldwide)	2-year limited warranty

Related Items

Required Products

Related Model	Description	Qty.
B090-A9F	DB9F - RJ45 Modular Serial Adapter	1
B090-A9F-X	DB9F - RJ45 Modular Serial Adapter	1
B090-A9M	DB9M - RJ45 Modular Serial Adapter	1

Optional Products

Related Model	Description	Qty.
N001-005-BK	5-ft. Cat5e 350MHz Snagless Molded Cable (RJ45 M/M) - Black	1
N001-007-BK	7-ft. Cat5e 350MHz Snagless Molded Cable (RJ45 M/M) - Black	1

N001-010-BK	10-ft. Cat5e 350MHz Snagless Molded Cable (RJ45 M/M) - Black	1
N001-014-BK	14-ft. Cat5e 350MHz Snagless Molded Cable (RJ45 M/M) - Black	1
N001-025-BK	25-ft. Cat5e 350MHz Snagless Molded Cable (RJ45 M/M) - Black	1
N201-005-BK	5-ft. Cat6 Gigabit Snagless Molded Patch Cable (RJ45 M/M) - Black	1
N201-007-BK	7-ft. Cat6 Gigabit Snagless Molded Patch Cable (RJ45 M/M) - Black	1
N201-010-BK	10-ft. Cat6 Gigabit Snagless Molded Patch Cable (RJ45 M/M) - Black	1
N201-014-BK	14-ft. Cat6 Gigabit Snagless Molded Patch Cable (RJ45 M/M) - Black	1
N201-025-BK	25-ft. Cat6 Gigabit Snagless Molded Patch Cable (RJ45 M/M) - Black	1
B092-016	16-Port Serial Console / Terminal Server with Built-in PowerAlert and KVM inputs	1
B095-003-1E-M	3 Port IP Serial Console / Terminal Server Built-in Modem	1
B096-016	16-Port Serial Console / Terminal Server Management Switch	1
B096-048	48-Port Serial Console / Terminal Server Management Switch	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=4496.

Copyright © 2012 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.