

# Product data sheet

Specifications



APC Smart-UPS, Line Interactive, 1000VA, Tower, 230V, 8x IEC C13 outlets, SmartSlot, AVR, LCD

SMT1000I

## Overview

<b>Presentation</b>	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
<b>Lead time</b>	Usually Ships within 2 Weeks

## Main

<b>Main Input Voltage</b>	230 V
<b>Other Input Voltage</b>	220 V 240 V
<b>Main Output Voltage</b>	230 V
<b>Other Output Voltage</b>	220 V 240 V
<b>Kw Rating</b>	700 W
<b>Rated power in VA</b>	1000 VA
<b>Product or Component Type</b>	Uninterruptible power supply (UPS)
<b>Input Connection Type</b>	IEC 320 C14
<b>output connection type</b>	8 IEC 320 C13 2 IEC Jumpers
<b>Battery Type</b>	Lead-Acid battery
<b>Provided equipment</b>	USB cable Documentation CD Installation guide Smart UPS signalling RS-232 cable
<b>Range of Product</b>	Smart-UPS


## Complementary

<b>Communication port type</b>	SmartSlot
--------------------------------	-----------

## Batteries & Runtime

<b>Run Time</b>	<a href="#">View Runtime Graph</a>
<b>Efficiency</b>	<a href="#">View Efficiency Graph</a>
<b>Additional information</b>	Configurable for 220 : 230 or 240 nominal output voltage
<b>Extendable Run Time</b>	0
<b>Included Battery Modules</b>	0
<b>Battery Slots Empty</b>	0
<b>Typical recharge time</b>	3 h

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

RBC Quantity	1
Battery life	3...5 year(s)
Replacement battery	<a href="#">RBC6</a> 
Battery Charge Power (Watts)	88 W rated

## General

Number of power module filled slots	0
Number of power module free slots	0
Redundant	No

## Physical

color	Black
Height	8.6 in (21.9 cm)
Width	6.7 in (17.1 cm)
Depth	17.3 in (43.9 cm)
Net Weight	41.58 lb(US) (18.86 kg)
mounting location	Front
Mounting preference	No preference
Mounting Mode	Not rack-mountable
Two post mountable	0
USB compatible	No

## Input

Efficiency at full load	151...302 V adjustable 160...286 V
Input Frequency	50/60 Hz +/- 3 Hz auto-sensing

## Output

Harmonic distortion	Less than 5 % at full load
Maximum configurable power in VA	1000 VA
Max Configurable Power (Watts)	700 W
Topology	Line Interactive
Waveform Type	Sine wave
Output Frequency (sync to mains)	47...53 Hz for 50 Hz nominal sync to mains 57...63 Hz for 60 Hz nominal sync to mains

## Conformance

Product Certifications	CE EAC RCM VDE
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

## Environmental

acoustic level	41 dBA
Online Thermal Dissipation	100 Btu/h
Operating altitude	0...10000 ft
Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage altitude	0...50000 ft (0.0000000000...15240.0000000000 m)
Relative Humidity	0...95 %
Storage Relative Humidity	0...95 %

## Communications & Management

Control panel	Multi-function LCD status and control console
Emergency Power Off (EPO)	Optional
Free slots	1
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

## Surge Protection and Filtering

Surge energy rating	459 J
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : m

## Ordering and shipping details

GTIN	731304762331
Country of origin	PH

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14.8 in (37.6 cm)
Package 1 Width	12.9 in (32.8 cm)
Package 1 Length	23.4 in (59.5 cm)
Package 1 Weight	50.20 lb(US) (22.77 kg)
Unit Type of Package 2	P12
Number of Units in Package 2	9
Package 2 Height	48.8 in (124 cm)
Package 2 Width	31.5 in (80 cm)
Package 2 Length	47.2 in (120 cm)
Package 2 Weight	924.8 lb(US) (419.5 kg)
SCC14	731304268673

## Contractual warranty

Warranty	3 years repair or replace (excluding battery) and 2 years for battery
----------	---

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Energy Efficient Take-back Transparency RoHS/REACH

## Resource performance

Energy Efficient Product

Take-Back Program Available

## Well-being performance

Mercury Free

Rohs Exemption Information [Yes](#)

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Circularity Profile [End of Life Information](#)