

# Product data sheet

Specifications



## Rack PDU Extender, Basic, 2U, 30A, 100/120/200/208V, (4)L5-30



AP7583

### Overview

**Lead time** Usually in Stock

### Main

**Color** Black

**Product or Component Type** PDU

**PDU Type** Basic

**Cord length** 28 ft (8.5 m)

**Provided Equipment** Installation guide  
Rack Mounting brackets

### Complementary

**Input Voltage** 120 V  
208 V

**Height** 3.5 in (8.9 cm)

**Width** 17.2 in (43.7 cm)

**Output Voltage** 120 V

**Depth** 3.5 in (8.9 cm)

**Net Weight** 14.02 lb(US) (6.36 kg)

**mounting location** Front  
Rear

**Mounting preference** Lower

**Input Plug Type** NEMA L14-30P

**Mounting Mode** Not rack-mountable

**Rack units** 2U

**Mounting position** Horizontal

**Line Rated Current** 24 A

**Input current limits** 30 A

**Load Capacity** 4992 VA

**Input Frequency** 50/60 Hz

**Outlet type and quantity** 4 NEMA L5-30R

### Environment

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

<b>Product Certifications</b>	cUL Listed METI Denan UL Listed
<b>Standards</b>	CSA C22.2 No. 107.1 UL 1778
<b>Ambient Air Temperature for Operation</b>	32.0000000000...113.0000000000 °F (0...45 °C)
<b>Relative Humidity</b>	0...95 %
<b>Operating altitude</b>	0...10000 ft
<b>Ambient Air Temperature for Storage</b>	-13.0000000000...149.0000000000 °F (-25...65 °C)
<b>Storage Relative Humidity</b>	0...95 %
<b>Storage altitude</b>	0...50000 ft (0.0000000000...15240.0000000000 m)

## Ordering and shipping details

<b>GTIN</b>	731304222576
-------------	--------------

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	6.0 in (15.2 cm)
<b>Package 1 Width</b>	20.5 in (52.1 cm)
<b>Package 1 Length</b>	20.5 in (52.1 cm)
<b>Package 1 Weight</b>	16.03 lb(US) (7.27 kg)

## Contractual warranty

<b>Warranty</b>	2 years repair or replace
-----------------	---------------------------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Energy Efficient Take-back Transparency RoHS/REACH

## Resource performance

 Energy Efficient Product

---

 Take-Back Program Available

---

## Well-being performance

 Lead Free

---

## Certifications & Standards

Reach Regulation

[REACH Declaration](#)

---

Eu Rohs Directive

Compliant

[EU RoHS Declaration](#)

---

Environmental Disclosure

[Product Environmental Profile](#)

---

Circularity Profile

[End of Life Information](#)

---