

Cisco Compatible Gigabit Fiber SFP Transceiver Module MM LC – 550m (Mini-GBIC)

StarTech ID: SFPGLCSXMMST



The SFPGLCSXMMST Cisco® Compatible Gigabit Fiber SFP Transceiver Module MM LC – 550m (1804 ft) is built to comply with MSA (Multi-Sourcing Agreement) standards to offer a cost-effective way to add, replace or upgrade a Multimode LC port on your Gigabit fiber networking equipment or fiber media converter.

Supporting data rates up to 1.25 Gbps, this LC Mini-GBIC module can be installed into any fiber networking device with an MSA or Cisco compliant SFP port. Delivering both convenience and scalability, this fiber transceiver is fully hot-pluggable, which enables you to install the module without interrupting network traffic or requiring a device reboot.

This 850nm multi-mode SFP module is compatible with the Cisco GLC-SX-MM transceiver. Also a perfect accessory for the StarTech.com [PCI Express Open SFP NIC](#) (PEX1000SFP), or [Gigabit POE Open SFP Media Converter](#) (ET1110PSE) products.

Backed by a StarTech.com 3-year warranty and free lifetime technical support.

Applications

- Replacing defective or damaged SFPs in MSA compliant or Cisco equipment
- Expand your network to remote segments

Features

- Data rates up to 1.25 Gbps
- Supports distances up to 550m (1804ft)
- Complies with SFP Multi-Source Agreements standards (MSA)
- Compatible with Cisco equipment
- LC Fiber connector
- Fully Hot Pluggable

Technical Specifications

| | |
|-------------------------------|--|
| Warranty | 3 Years |
| WDM | No |
| Industry Standards | IEEE 802.3z 1000BASE-SX |
| Local Unit Connectors | 1 - Fiber Optic LC |
| Compatible Networks | 1000 Mbps (1 Gbps) |
| DDM | No |
| Maximum Data Transfer Rate | 1.25 Gbps |
| Max Transfer Distance | 550 m (1804 ft) |
| Fiber Type | Multi Mode |
| Wavelength | 850nm |
| Fiber Operating Mode | Half/Full-Duplex |
| Product Length | 2.4 in [60 mm] |
| Product Width | 0.5 in [12 mm] |
| Product Height | 0.4 in [10 mm] |
| Product Weight | 0.6 oz [16 g] |
| Operating Temperature | 0°C to 70°C (32°F to 158°F) |
| Storage Temperature | -40°C to 85°C (-40°F to 85°F) |
| Humidity | 30~70% RH |
| System and Cable Requirements | MSA or Cisco compliant SFP port |
| Note | For use in Gigabit fiber networking equipment and media converters |
| Shipping (Package) Weight | 0.1 lb [0 kg] |
| Included in Package | 1 - 1.25 Gbps Multimode LC SFP |

Certifications, Reports and Compatibility

